

**1. Identification**

**Product identifier** **BH5011**  
**Other means of identification** Not available.  
**Recommended use** Not available.  
**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**
**Manufacturer**

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.  
**Address** 2829 Lakeland Drive  
 Jackson, MS 39232  
 USA  
**After hours telephone number** 1-800-222-7122  
**Normal work hours telephone number** 1-877-982-7667  
**Website** www.ergonarmor.com  
**E-mail** sds@ergon.com  
**Emergency 24-hour telephone number** CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887  
**Information on operation hours** 8:00 a.m. to 5:00 p.m.

**2. Hazard(s) identification**

**Physical hazards** Flammable liquids Category 3  
**Health hazards** Acute toxicity, inhalation Category 4  
 Skin corrosion/irritation Category 2  
 Serious eye damage/eye irritation Category 2B  
 Specific target organ toxicity, single exposure Category 3 narcotic effects  
 Specific target organ toxicity, repeated exposure Category 2  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

**Label elements**


**Signal word** Warning  
**Hazard statement** Flammable liquid and vapor. Causes eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure by inhalation. Harmful if inhaled.  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. No smoking. Keep container tightly closed. Do not eat, drink or smoke when using this product. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wear protective gloves/eye protection/face protection. Ground/bond container and receiving equipment. Wash thoroughly after handling. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.  
**Response** In case of fire: Use appropriate media for extinction. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs, seek medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
**Storage** Store in a well-ventilated place. Keep cool. Store locked up.

<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	60 - 80
STODDARD SOLVENT		8052-41-3	20 - 40
1,2,4-TRIMETHYLBENZENE		95-63-6	< 2
Other components below reportable levels			0.04902

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.
<b>Skin contact</b>	For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Not available.
<b>Indication of immediate medical attention and special treatment needed</b>	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.
<b>Unsuitable extinguishing media</b>	Do not use water jet.
<b>Specific hazards arising from the chemical</b>	Fire may produce irritating, corrosive and/or toxic gases.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
<b>Fire-fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.
<b>Specific methods</b>	In the event of fire and/or explosion do not breathe fumes.

### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.
<b>Methods and materials for containment and cleaning up</b>	Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.  Never return spills in original containers for re-use.

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

## 7. Handling and storage

**Precautions for safe handling** Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

**Conditions for safe storage, including any incompatibilities** Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
STODDARD SOLVENT (CAS 8052-41-3)	PEL	2900 mg/m <sup>3</sup> 500 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	TWA	25 ppm	
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m <sup>3</sup>	Inhalable fraction.
STODDARD SOLVENT (CAS 8052-41-3)	TWA	100 ppm	

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)	TWA	125 mg/m <sup>3</sup>	
ASPHALT (CAS 8052-42-4)	Ceiling	25 ppm 5 mg/m <sup>3</sup>	Fume.
STODDARD SOLVENT (CAS 8052-41-3)	Ceiling	1800 mg/m <sup>3</sup>	
	TWA	350 mg/m <sup>3</sup>	

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls** Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses; chemical goggles (if splashing is possible).

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

**Other** It is a good industrial hygiene practice to minimize skin contact. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal hazards** Not available.

**General hygiene considerations** When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

<b>Appearance</b>	Viscous liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Brown - black
<b>Odor</b>	Mild Petroleum Odor
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.

<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	300 °F (148.89 °C)
<b>Flash point</b>	100.0 - 140.0 °F (37.8 - 60.0 °C) Cleveland Open Cup
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	2.04 hPa estimated
<b>Vapor density</b>	> 1
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	7.65 lb/gal estimated
<b>Flammability class</b>	Class II
<b>Molecular weight</b>	250 lb/lb-mole estimated
<b>Percent volatile</b>	<= 35 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Stable at normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Irritants. Carbon oxides. Sulphur oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
<b>Inhalation</b>	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
<b>Skin contact</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	May be irritating to eyes.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Not available.

### Information on toxicological effects

<b>Acute toxicity</b>	Not classified.
-----------------------	-----------------

Product	Species	Test Results
BH5011 (CAS Mixture)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	87755.1016 g/kg estimated
<i>Oral</i>		
LD50	Rat	357.1854 g/kg estimated
<i>Other</i>		
LD50	Rat	7755.1021 mg/kg estimated

Components	Species	Test Results
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 3160 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 2000 ppm, 48 Hours
<i>Oral</i>		
LD50	Rat	6 g/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes eye irritation.

**Respiratory or skin sensitization**

**Respiratory sensitization** Not available.

**Skin sensitization** Not a skin sensitizer.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** None of this product's components are listed by ACGIH, IARC, NIOSH, NTP or OSHA.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

STODDARD SOLVENT (CAS 8052-41-3) 3 Not classifiable as to carcinogenicity to humans.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Reproductive toxicity** Not classified.

**Specific target organ toxicity - single exposure** Central nervous system.

**Specific target organ toxicity - repeated exposure** May cause damage to organs through prolonged or repeated exposure by inhalation.

**Aspiration hazard** Not classified.

**Chronic effects** Prolonged exposure may cause chronic effects.

**12. Ecological information**

**Ecotoxicity** Not expected to be harmful to aquatic organisms.

Product	Species	Test Results
BH5011 (CAS Mixture)		
Fish	LC50	Fish 426.0896 mg/l, 96 hours estimated
Components	Species	Test Results
1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 7.19 - 8.28 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** Not available.

**Bioaccumulative potential** Not available.

**Partition coefficient n-octanol / water (log Kow)**

STODDARD SOLVENT

3.16 - 7.15

**Mobility in soil** Not available.**Other adverse effects** Not available.**13. Disposal considerations****Disposal instructions** Dispose of contents/container in accordance with local/regional/national/international regulations. If discarded, this product is considered a RCRA ignitable waste, D001.**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F**Waste from residues / unused products** Dispose of in accordance with local regulations.**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.**14. Transport information****DOT****UN number** UN1999**UN proper shipping name** Tars, liquid**Transport hazard class(es)****Class** Combustible Liquid**Subsidiary risk** -**Label(s)** 3**Packing group** III**Special precautions for user** If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material.**Special provisions** B1, B52, IB3, T4, TP1, TP29**Packaging exceptions** 150**Packaging non bulk** 203**Packaging bulk** 242**IATA****UN number** UN1999**UN proper shipping name** Tars, liquid**Transport hazard class(es)****Class** 3**Subsidiary risk** -**Packing group** III**Environmental hazards** No.**ERG Code** 3L**Special precautions for user** Not available.**Other information****Passenger and cargo aircraft** Allowed.**Cargo aircraft only** Allowed.**IMDG****UN number** UN1999**UN proper shipping name** Tars, liquid**Transport hazard class(es)****Class** 3**Subsidiary risk** -**Packing group** III**Environmental hazards****Marine pollutant** No.**EmS** F-E, S-E\***Special precautions for user** Not available.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not available.

DOT



IATA; IMDG



**Further information**

If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material. If shipped by vessel in individual containers that are less than 7.9 gallons (30 L) each, then IMDG 2.3.2.5 exception applies: Not regulated as a hazardous material.

**15. Regulatory information**

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
CERCLA/SARA Hazardous Substances - Not applicable.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

ASPHALT (CAS 8052-42-4) Listed.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - Yes  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312**

Yes

**Hazardous chemical**

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
1,2,4-TRIMETHYLBENZENE	95-63-6	< 2

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)**

Not regulated.

**US state regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**US. Massachusetts RTK - Substance List**

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)  
ASPHALT (CAS 8052-42-4)  
STODDARD SOLVENT (CAS 8052-41-3)

**US. New Jersey Worker and Community Right-to-Know Act**

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6) 500 LBS

**US. Pennsylvania RTK - Hazardous Substances**

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)

ASPHALT (CAS 8052-42-4)

STODDARD SOLVENT (CAS 8052-41-3)

**US. Rhode Island RTK**

1,2,4-TRIMETHYLBENZENE (CAS 95-63-6)

**US. California Proposition 65****US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ASPHALT (CAS 8052-42-4)

Listed: January 1, 1990

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision****Issue date** 07-16-2014**Revision date** 02-26-2016**Version #** 02

**References**

ACGIH  
 EPA: AQUIRE database  
 NLM: Hazardous Substances Data Base  
 US. IARC Monographs on Occupational Exposures to Chemical Agents  
 HSDB® - Hazardous Substances Data Bank  
 IARC Monographs. Overall Evaluation of Carcinogenicity  
 National Toxicology Program (NTP) Report on Carcinogens  
 ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Information**

Product and Company Identification: Product and Company Identification  
 Handling and storage: Precautions for safe handling  
 Physical & Chemical Properties: Multiple Properties  
 Toxicological information: Specific target organ toxicity - repeated exposure  
 Transport information: Further information  
 HazReg Data: North America  
 GHS: Classification