SAFETY DATA SHEET



1. Identification

Product identifier Blackhawk Asphalt Coating/Primer

Other means of identification

Synonyms BH5136
Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours telephone number

1-877-982-7667

Website www.ergonarmor.com
E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation 8

hours

ation 8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSkin corrosion/irritationCategory 2Germ cell mutagenicityCategory 1B

Germ cell mutagenicity Category 1B
Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

Environmental hazardsNot classified. **OSHA defined hazards**Combustible dust

Label elements



Signal word Danger

Hazard statement May cause cancer. May be fatal if swallowed and enters airways. Extremely flammable aerosol.

Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects.

Precautionary statement

Prevention Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only

outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use. Wear protective gloves/protective clothing/eye protection/face protection. Do not spray on an open flame or other ignition source. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have

been read and understood.

6369 Version #: 06 Revision date: 09-09-2019 Issue date: 03-21-2018

IF ON SKIN: Wash with plenty of soap and water. Specific treatment see Section 4 of this SDS. Response

Take off contaminated clothing and wash before reuse. If skin irritation occurs, seek medica advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. IF exposed or concerned:

Get medical advice/attention.

Storage Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT, OXIDIZED		64742-93-4	35 - 45
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.		64742-89-8	30 - < 40
DIMETHYL ETHER		115-10-6	20 - 30

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if

victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. For breathing difficulties, oxygen may be necessary. Get medical attention, if needed. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Wash off immediately with plenty of water. Wash

off with soap and water. Rinse skin with water/shower. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin. Take off

contaminated clothing and wash before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Rinse with water. If a contact

> lens is present, DO NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. Get medical attention

if irritation develops and persists.

Ingestion Rinse mouth. Rinse mouth thoroughly. Do not induce vomiting without advice from poison control

center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention if symptoms occur. If ingestion of a large amount does occur, call a poison

control center immediately.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

In case of shortness of breath, give oxygen. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Keep victim under observation. Keep victim warm.

5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

During fire, gases hazardous to health may be formed:

the chemical

and precautions for

Special protective equipment Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

firefighters

Fire fighting equipment/instructions

Specific methods

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Refrigeration recommended.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for A Components	Type	Value	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)	PEL	400 mg/m3	
		100 ppm	
U.S NIOSH			
Components	Туре	Value	
ASPHALT, OXIDIZED (CAS 64742-93-4)	REL	5 mg/m3	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)	TWA	400 mg/m3	
,		100 ppm	
US. Workplace Environmental E	xposure Level (WEEL) Guides		
Components	Туре	Value	
DIMETHYL ETHER (CAS 115-10-6)	TWA	1880 mg/m3	
		1000 ppm	

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

controls occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Material name: Blackhawk Asphalt Coating/Primer

6369 Version #: 06 Revision date: 09-09-2019 Issue date: 03-21-2018 3/9 Skin protection

Hand protection Wear protective gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and considerations before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Liauid. Color Not available. Odor Not available. **Odor threshold** Not available. Нd Not available.

-222.7 °F (-141.5 °C) estimated Melting point/freezing point Initial boiling point and -12.68 °F (-24.82 °C) estimated

boiling range

Flash point -42.0 °F (-41.1 °C) estimated

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower 3.4 % estimated

(%)

Flammability limit -

upper (%)

27 % estimated

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

550 °F (287.78 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Specific gravity 0.68 estimated < 500 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. **Hazardous decomposition**

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components Species Test Results

DIMETHYL ETHER (CAS 115-10-6)

Acute

Inhalation

LC50 Rat 164000 ppm, 4 Hours

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

<u>Acute</u>

Inhalation

LC50 Rat 61 mg/l, 4 Hours

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

6369 Version #: 06 Revision date: 09-09-2019 Issue date: 03-21-2018

^{*} Estimates for product may be based on additional component data not shown.

Product		Species	Test Results
Blackhawk Asphalt Co	ating/Primer		
Aquatic			
Crustacea	EC50	Daphnia	11.1111 mg/l, 48 hours estimated
Fish	LC50	Fish	26.6667 mg/l, 96 hours estimated
Components		Species	Test Results
SOLVENT NAPHTHA (PETROLEUM), LIGH	HT ALIPH. (CAS 64742-89-8)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours
			8.8 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)
DIMETHYL ETHER

Mobility in soil No data available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

0.1

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing groupSpecial precautions for
Not available.
Not available.

user

Special provisionsN82Packaging exceptions306Packaging non bulkNonePackaging bulkNone

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not available.

Environmental hazards No

ERG Code 10L

Special precautions for Not available.

user

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 **Subsidiary risk**

Not available. **Packing group**

Environmental hazards

Marine pollutant No. F-D, S-U Not available. Special precautions for user

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



General information DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

DIMETHYL ETHER (CAS 115-10-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Combustible dust

Skin corrosion or irritation

Serious eye damage or eye irritation

Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

DIMETHYL ETHER (CAS 115-10-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT, OXIDIZED (CAS 64742-93-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH. (CAS 64742-89-8)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 03-21-2018

 Revision date
 09-09-2019

 Version #
 06

NFPA ratings Health: 2
Flammability: 4

Flammability: 4
Instability: 0

Material name: Blackhawk Asphalt Coating/Primer

SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

GHS: Classification **Revision information**

Material name: Blackhawk Asphalt Coating/Primer SDS US 9/9