

**ERGON ARMOR**

**7QD Aerosol Asphalt Primer**

**MSDS No. EA010**

Date of Preparation: **April 3, 2009**

Revision No. 0

**Section 1 – Chemical Product and Company Information**

<b>Product/Chemical Name:</b>	7QD Aerosol Asphalt Primer
<b>Chemical Formula:</b>	Mixture
<b>CAS Number:</b>	Mixture
<b>Other Designations:</b>	None
<b>General Use:</b>	Aerosol asphalt spray primer
<b>Manufacturer:</b>	Ergon Armor, 450 Funston, Kansas City, Kansas 66115, (913) 371-8555; Hours of Operation 8:00 am – 5:00 pm; ERGON 24 Hour Emergency Phone Number 1-800-222-7122; CHEMTREC 1-800-424-9300.

**Section 2 – Composition / Information on Ingredients**

<b>Ingredient Name</b>	<b>CAS Number</b>	<b>% Vol</b>
Asphalt Cement	8052-42-4 (fumes)	24-40
Naphtha, Varnish Makers and Painters (VM&P)	8030-30-6	35-52
<b>Propellant: Liquefied Petroleum Gas Blend</b>		
Propane	74-98-6	11-17
Butane	106-97-8	8-13

<b>INGREDIENT</b>	<b>OSHA PEL</b>		<b>ACGIH TLV</b>		<b>NIOSH REL</b>		<b>NIOSH IDLH</b>
	<b>TWA</b>	<b>STEL</b>	<b>TWA</b>	<b>STEL</b>	<b>TWA</b>	<b>STEL</b>	
Asphalt Cement	None estab.	None estab.	0.5 mg/m <sup>3</sup> (inhalable fraction, as benzene-soluble aerosol)	None estab.	None estab.	5 mg/m <sup>3</sup> (ceiling)	None estab.
Naphtha (VM&P)	100 ppm	None estab.	400 ppm	None estab.	100 ppm	None estab.	1,000 ppm
Propane	1,000 ppm	None estab.	1,000 ppm	None estab.	1,000 ppm	None estab.	2,100 ppm
Butane	None estab.	None estab.	1,000 ppm	None estab.	800 ppm	None estab.	None estab.

**Section 3 – Hazards Information**

**EMERGENCY OVERVIEW**

HMIS H-2 F-4 R-0 PPE* * Sec.8
--

**POTENTIAL HEALTH EFFECTS**

**Primary Entry Routes:** Inhalation, ingestion, and absorption.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nervous system.

**Acute Effects**

**Inhalation:** May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause slight irritation to the respiratory system, moderate central nervous system depression, rapid breathing, low grade fever, and asphyxiation.

**Eye:** Direct contact can cause severe irritation. Direct contact may cause temporary redness and discomfort. Liquefied gas under pressure can cause frostbite and burns.

**Skin:** Prolonged contact may cause moderate irritation. May cause itching, reddening, inflammation. May cause a rash. May cause sensitization. Liquefied gas under pressure can cause frostbite and burns.

**Ingestion:** May cause gastrointestinal irritation, nausea, and vomiting.

**Carcinogenicity:** The International Agency for Research on Cancer (IARC), the National Toxicology Material Program (NTP), and the Occupational Safety and Health Administration (OSHA) do not list asphalt as a carcinogen. However, liquid petroleum asphalt may contain carcinogenic compounds. IARC and NTP have concluded that certain polycyclic aromatic hydrocarbons (i.e., Chrysene, Benz(a)Anthracene and Flouranthene) are probably carcinogenic in humans (Group 2B). The National Institute for Occupational Safety and Health (NIOSH) describes asphalt fumes as a potential occupational carcinogen.

**Medical Conditions Aggravated by Long-Term Exposure:** Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Effects:** Prolonged or repeated skin contact with asphalt may result in skin sensitivity, such as irritation, rashes, and dermatitis. Prolonged or repeated exposure to polycyclic aromatic hydrocarbons and other volatiles which are contained in trace amounts in asphalt have been shown to cause cancer or respiratory damage in animals.

**Section 4 – First Aid Measures**

**Inhalation:** Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Eye Contact:** Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.

**Skin Contact:** Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.

**Ingestion:** Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**After first aid, get appropriate in-plant paramedic or community medical support.**

**Special Precautions/Procedures:** The petroleum hydrocarbons in this product are a complex mixture of paraffinic, naphthenic, and aromatic hydrocarbons. As with other petroleum products, the aromatic compounds are present in varying concentrations and structures. Some of these compounds may be those which have been shown to result in tumor formation in animals under laboratory conditions. The concentrations of aromatic compounds in this product require that the precautions outlined in this MSDS be followed to minimize personnel exposure.

Provide adequate ventilation to keep vapors below allowable exposure levels. Use PPE appropriate for the task.

**Section 5 – Fire Fighting Measures**

**Flash Point:** -101 °F (butane)  
**Flash Point Method:** NA  
**Autoignition Temperature:** 788 °F (butane)  
**LEL:** Propane 2.1%; Butane 1.6%  
**UEL:** Propane 9.5%; Butane 8.4%



**Flammability Classification:** Flammable gas  
**Extinguishing Media:** Use carbon dioxide, dry chemical, or foam.  
**Unusual Fire or Explosion Hazards:** Flammable Gas. Closed containers may explode when heated due to increased pressure. Vapors are heavier than air and may spread long distances and ignite. Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.  
**Hazardous Combustion Products:** Smoke, fumes. Carbon monoxide and carbon dioxide can form. Oxides of sulfur and hydrogen sulfide can form.  
**Fire-Fighting Instructions:** Use accepted fire fighting techniques.  
**Fire-Fighting Equipment:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

**Section 6 – Accidental Release Matters**

**Spill/Leak Procedures:** Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of sewers and waterways. Ventilate area.  
**Small Spills:** Stop spill at source if possible. Isolate and confine by diking, or similar method. Remove discharged material.  
**Large Spills:**  
**Containment:** For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.  
**Cleanup:** Mix with inert absorbent material such as soil, sand, or oil dry, to stabilize.  
**Regulatory Requirements:** Notify local health and pollution control agencies as appropriate. Follow applicable OSHA regulations (29 CFR 1900.120). Subject to hazardous waste treatment, storage, and disposal requirements under RCRA for characteristic of ignitability (D001). For disposal follow all federal, state, and local regulations regarding solid waste.

**Section 7 – Handling and Storage**

**Handling Precautions:** Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Do not use in confined or poorly ventilated areas. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment.  
**Storage Requirements:** Store under dry warehouse conditions away from heat and all ignition sources.  
**Regulatory Requirements:** None known.

**Section 8 – Exposure Controls / Personal Protection**

**Engineering Controls:** Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.  
**Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

*Section 8 continued on next page....*

**Section 8 – Exposure Controls / Personal Protection - Continued**

**Respiratory Protection:** Wear appropriate, properly fitted NIOSH/MSHA-approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134). Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Self-contained, positive-pressure breathing apparatus when used in confined or enclosed space or when exposure limits are exceeded or hydrogen sulfide is unknown or exceeds 20 ppm. Organic vapor respirators can be used with good ventilation when organic vapors are less than 1000 ppm or ten times permissible exposure limit, whichever is less. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear a self-contained breathing apparatus (SCBA). *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes: procedures for selecting respirators; medical evaluation; fit testing; use in routine and emergency situations; cleaning, disinfecting, storing, inspecting, repairing, discarding and maintaining respirators; adequate air quality, quantity and flow; training in respiratory hazards; training in use of respirators; evaluation of effectiveness of respiratory program.

**Protective Clothing/Equipment:** Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure. Wear appropriate eye protection (chemical safety goggles and/or face shield) to prevent eye contact per OSHA eye- and face-protection regulations (29 CFR 1910.133). Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Prevent contact with shoes and clothing.

**Safety Stations:** Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

**Contaminated Equipment:** Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

**Comments:** Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, or smoking.

**Section 9 – Physical and Chemical Properties**

**Physical State:** Black aerosolized liquid

**Water Solubility:** Negligible.

**Appearance and Odor:** Black liquid with a mild solvent odor

**Other Solubilities:** No data.

**Odor Threshold:** Not available.

**Boiling Point:**

**Freezing/Melting Point:** No data.

**Vapor Pressure:** Propane 8.4 atm; Butane 2.05 atm

**Viscosity:** No data.

**Vapor Density (Air = 1):** >1

**Refractive Index:** No data.

**Formula Weight:**

**Surface Tension:** No data.

**Density:**

**% Volatile:** >70%

**Specific Gravity (H<sub>2</sub>O = 1, at 4 °C):**

**Evaporation Rate:** No data.

**pH:** Not available

**Section 10 – Stability and Reactivity**

**Stability:** Stable at room temperature in closed containers under normal storage and handling conditions.

**Polymerization:** Hazardous polymerization will not occur under normal conditions.

**Chemical Incompatibilities:** Strong oxidizing agents.

**Conditions to Avoid:** Keep away from ignition sources, heat and flames.

**Hazardous Decomposition Products:** Primary decomposition products are carbon monoxide, carbon dioxide, and water. Combustion products may include sulfur oxides and hydrogen sulfide.

**Section 11 – Toxicological Information**

**Eye Effects:** Vapors may cause a slight smarting of the eyes or respiratory system if present in high concentrations. The effect is temporary.

**Skin Effects:** May result in skin sensitivity, such as irritation, rashes, and dermatitis.

**Acute Inhalation Effects:** Human, inhalation, TC<sub>10</sub>: No data.

**Acute Oral Effects:** No data.

**Carcinogenicity:** No data.

**Mutagenicity:** No data.

**Teratogenicity:** No data.

**Chronic Effects:** Prolonged and repeated skin contact may cause dermatitis, photosensitization, and melanosis. Evidence from animal studies suggest that asphalt left on the skin for long periods of time may result in local carcinomas, but there have been no reports of such effects on humans skin that can be attributed to asphalt alone.

**Section 12 – Ecological Information**

**Ecotoxicity:** No data.

**Environmental Fate:**

- Environmental Transport:** No data.
- Environmental Degradation:** No data.
- Soil Absorption/Mobility:** No data.

**Section 13 – Disposal Considerations**

**Disposal:** Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

**Disposal Regulatory Requirements:** Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Follow Federal, state, and local regulations for disposal of solid waste.

**Container Cleaning and Disposal:** Recommend using a non-hazardous solvent to remove the product. Follow Federal, state, and local regulations for disposal of the waste material, regardless of its waste classification.

**Section 14 – Transport Information**

<p><b>Shipping Name:</b> Aerosols, <i>flammable</i> (each not exceeding 1L capacity)</p> <p><b>Shipping Symbols:</b> NA</p> <p><b>Hazard Class:</b> 2.1</p> <p><b>ID No.:</b> UN1950</p> <p><b>Packing Group:</b> -</p> <p><b>Label:</b> Flammable Gas</p> <p><b>Special Provisions (172.102):</b> N82</p> <p><b>Shipping Description:</b> "UN1950, Aerosols, flammable (each not exceeding 1L capacity), 2.1"</p>	<p><b>Packaging Authorizations:</b></p> <p><b>a) Exceptions:</b> 173.306</p> <p><b>b) Non-bulk Packaging:</b> none</p> <p><b>c) Bulk Packaging:</b> none</p>	<p><b>Quantity Limitations:</b></p> <p><b>a) Passenger, Aircraft, or Railcar:</b> 25 kg</p> <p><b>b) Cargo Aircraft Only:</b> not allowed</p> <p><b>Vessel Stowage Requirements:</b></p> <p><b>a) Vessel Stowage:</b> For maximum capacity of 1L: Category A, segregation as for class 9 but away from heat sources and separated from class 1 except division 1.4. For capacity above 1L: Category B, segregation as for the appropriate sub-division of class 2.</p> <p><b>b) Other:</b> 47, 87, 126</p>
--	--	--

**Section 15 – Regulatory Information**

**EPA Regulations:**

**RCRA**

RCRA Hazardous Waste Numbers: Not listed

RCRA Hazardous Waste Classification (40 CFR 261): D001 (Characteristic of ignitability): Reportable Quantity = 100 lbs. This classification applies only to the material as it was originally produced.

**CERCLA**

CERCLA: Not listed.

CERCLA Reportable Quantity (RQ): This material is not a listed hazardous substance and does not have a reportable quantity. However, if spilled into waters of the U.S., it may be reportable under the Clean Water Act.

**SARA**

SARA 313 Components: Not Listed

SARA Toxic Chemical: Not listed.

SARA 311/312 Hazards: Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard  
Sudden Release of Pressure Hazard

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed.

**TSCA**

All substances are acceptable for use under TSCA.

**OSHA Regulations**

Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): See Table in Section 2.

OSHA Specifically Regulated Substance: No

**State Regulations:**

Listed in state hazardous substance list for CA and MN as Asphalt (petroleum fumes; FL, MA, NJ, as Asphalt fumes; and PA as Asphalt.

Propane can be found on the following state right to know lists: NJ, PA, MN, and MA.

Butane can be found on the following state right to know lists: CA, NJ, PA, MN, and MA.

Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm: Asphalt (8052-42-4).

**Section 16 – Other Information**

**Revision Notes:**

**Additional Hazard Rating Systems:**

**Disclaimer:** ERGON ARMOR PROVIDES THIS INFORMATION FOR THE USER'S CONSIDERATION. EA BELIEVES THIS INFORMATION IS ACCURATE, BUT NOT ALL INCLUSIVE IN ALL CIRCUMSTANCES. USER SHOULD ENSURE THAT USER HAS CURENT DATA RELEVANT FOR ITS PURPOSES. NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS OR OTHERWISE IS GIVEN.