

1. Identification
Product identifier TUFCHEM II JOINT SEALANT RESIN PART A

Other means of identification None.

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information
Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive
 Jackson, MS 39232
 USA

After hours telephone number 1-800-222-7122

Normal work hours telephone number 1-877-982-7667

Website www.ergonarmor.com

E-mail sds@ergon.com

Emergency 24-hour telephone number CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation hours 8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification
Physical hazards Flammable liquids Category 3

Health hazards Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated exposure Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Signal word Warning

Hazard statement Flammable liquid and vapor. Causes eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure by inhalation. Harmful if inhaled.

Precautionary statement
Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. No smoking. Keep container tightly closed. Do not eat, drink or smoke when using this product. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Wear protective gloves/eye protection/face protection. Ground/bond container and receiving equipment. Wash thoroughly after handling. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Response	In case of fire: Use appropriate media for extinction. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs, seek medical advice/attention. Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	30 - 50
STODDARD SOLVENT		8052-41-3	5 - 20
QUARTZ		14808-60-7	< 1

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.
Skin contact	For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. For minor skin contact, avoid spreading material on unaffected skin. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Not available.
Indication of immediate medical attention and special treatment needed	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.

Specific methods

In the event of fire and/or explosion do not breathe fumes.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Remove sources of ignition. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

Dike far ahead of spill for later disposal. Cover with DRY earth, DRY sand, or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Collect spillage. Prevent product from entering drains.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage**Precautions for safe handling**

Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feedingstuffs. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
STODDARD SOLVENT (CAS 8052-41-3)	PEL	2900 mg/m ³ 500 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.3 mg/m ³ 0.1 mg/m ³ 2.4 mppcf	Total dust. Respirable. Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inhalable fraction.
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
STODDARD SOLVENT (CAS 8052-41-3)	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m ³	Fume.
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.
STODDARD SOLVENT (CAS 8052-41-3)	Ceiling	1800 mg/m ³	
	TWA	350 mg/m ³	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical goggles are recommended.

Skin protection	
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.
Other	Wear appropriate chemical resistant clothing. Chemical resistant gloves.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	Not available.
General hygiene considerations	When using do not smoke. When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance	Black liquid
Physical state	Liquid.
Form	Semi-solid at ambient temperature
Color	Black
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	300 - 360 °F (148.89 - 182.22 °C)
Flash point	100.0 - 140.0 °F (37.8 - 60.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Specific gravity	1 - 1.05
VOC	1.23 lb/gal

10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Stable under normal temperature conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

Conditions to avoid	Heat, flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Irritants. Toxic gas.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis
Eye contact	May be irritating to eyes.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity	Not classified.
Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes eye irritation.

Respiratory or skin sensitization

Respiratory sensitization	Not available.
Skin sensitization	Not a skin sensitizer.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)	2B Possibly carcinogenic to humans.
QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
STODDARD SOLVENT (CAS 8052-41-3)	3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.
-------------------------	-------------------------------

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	Central nervous system.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure by inhalation.
Aspiration hazard	Not classified.
Chronic effects	Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Components of this product are hazardous to aquatic life. Accumulation in aquatic organisms is expected. Not expected to be harmful to aquatic organisms.

Product	Species	Test Results
TUFCHEM II JOINT SEALANT RESIN PART A		
Aquatic		
Fish	LC50	Fish 2441.4763 mg/l, 96 hours estimated

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	Not available.
Bioaccumulative potential	Not available.

Partition coefficient n-octanol / water (log Kow)

STODDARD SOLVENT

3.16 - 7.15

Mobility in soil Not available.**Other adverse effects** Not available.**13. Disposal considerations****Disposal instructions** Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Dispose of this material and its container to hazardous or special waste collection point. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations. Dispose in accordance with all applicable regulations.**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F**Waste from residues / unused products** Dispose of in accordance with local regulations.**Contaminated packaging** Offer rinsed packaging material to local recycling facilities.**14. Transport information****DOT**

UN number UN1999
UN proper shipping name Tars, liquid including road oils and cut back bitumens
Transport hazard class(es)
Class Combustible Liquid
Subsidiary risk -
Label(s) 3
Packing group III
Special precautions for user If shipped by ground in quantities LESS than 119 gallons (450 L): Not regulated as a hazardous material.
Special provisions B1, B13, IB3, T1, TP3
Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1999
UN proper shipping name Tars, liquid including road asphalt and oils, bitumen and cut backs
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards No.
ERG Code 3L
Special precautions for user Not available.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1999
UN proper shipping name TARS, LIQUID including road oils, and cutback bitumens
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No
Hazardous chemical

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)

QUARTZ (CAS 14808-60-7)

STODDARD SOLVENT (CAS 8052-41-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 10-27-2016

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings
Health: 2
Flammability: 3
Instability: 0

References
ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information
Product and Company Identification: Alternate Trade Names
Composition / Information on Ingredients: Disclosure Overrides
GHS: Classification