SAFETY DATA SHEET



1. Identification

Product identifier URETHANE ASPHALT HARDENER - PART B

Other means of identification Not available.

Synonym(s) PENNGUARD ADHESIVE MEMBRANE PART B, TUFCHEM II MEMBRANE PART B, TUFCHEM II SPRAY

GRADE PART B, TUFCHEM II JOINT SEALANT PART B, TUFCHEM II SL MEMBRANE PART B,

PENNCHEM 97 MEMBRANE PART B

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-877-982-7667

1-800-222-7122

Normal work hours telephone number

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

telephone number

Information on operation

8:00 a.m. to 5:00 p.m.

hours

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

exposure

Serious eye damage/eye irritation Category 2A
Sensitization, respiratory Category 1
Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated

Category 2

Environmental hazardsNot classified. **OSHA defined hazards**Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause

allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

Prevention Use only outdoors or in a well-ventilated area. Avoid breathing mist/vapors/spray. Wash hands

thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. Wear eye/face protection. In case of inadequate ventilation

wear respiratory protection.

Response IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. Take off

contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at

rest in a position comfortable for breathing. Specific treatment (see this label).

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Material name: URETHANE ASPHALT HARDENER - PART B 5618 Version #: 01 Issue date: 06-23-2016

Disposal

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with

applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC)

None known.

doctor/physician.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
METHYLENEDIPHENYL DIISOCYANATE		26447-40-5	45 - 55
MDI		101-68-8	< 45

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately. If experiencing respiratory symptoms: Call a POISON CENTER or

Skin contact

Remove contaminated clothing. Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Wash off with soap and plenty of water. Call a physician or poison control center immediately. For minor skin contact, avoid spreading material on unaffected skin. If skin irritation occurs: Get medical advice/attention. Get medical attention if irritation develops and persists. Wash clothing separately before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately. Get medical attention if irritation develops and persists.

Ingestion

Never give anything by mouth to a victim who is unconscious or is having convulsions. Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Most important symptoms/effects, acute and delayed

Irritation of eyes and mucous membranes. Prolonged exposure may cause chronic effects. Irritant effects. May cause allergic respiratory reaction. May cause allergic skin reaction.

Indication of immediate medical attention and special treatment needed

In case of shortness of breath, give oxygen. Oxygen, if needed. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim under observation. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Water spray mist or foam.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Use a water spray to cool fire-exposed containers.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions Move containers from fire area if you can do so without risk. Do not get water inside container.

Material name: URETHANE ASPHALT HARDENER - PART B

5618 Version #: 01 Issue date: 06-23-2016 2/7

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Ventilate closed spaces before entering them. Ensure adequate ventilation. Avoid inhalation of vapors or mists. Avoid skin contact and inhalation of vapors during disposal of spills.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with DRY earth, DRY sand, or other non-combustible material followed with plastic sheet to minimize spreading or contact with rain. Do not get water on spilled substance or inside containers.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. No special environmental precautions required. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

In case of insufficient ventilation, wear suitable respiratory equipment. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Do not get this material on clothing. Use personal protective equipment as required. Wash hands thoroughly after handling. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in a well-ventilated place. Keep container tightly closed.

8. Exposure controls/personal protection

Occupational exposure limits

Components	r Air Contaminants (29 CFR 19: Type	Value	
MDI (CAS 101-68-8)	Ceiling	0.2 mg/m3 0.02 ppm	
US. ACGIH Threshold Limit Va	alues		
Components	Туре	Value	
MDI (CAS 101-68-8)	TWA	0.005 ppm	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
MDI (CAS 101-68-8)	Ceiling	0.2 mg/m3	
	-	0.02 ppm	
	TWA	0.05 mg/m3	
		0.005 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Chemical goggles are recommended. Eye wash fountain is recommended.

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Avoid contact with the skin. Chemical resistant gloves. Wear suitable protective clothing.

Skin protection

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards

Not available.

General hygiene considerations

Do not get in eyes. Do not get this material in contact with skin. Wash hands after handling. Keep away from food and drink. Contaminated work clothing should not be allowed out of the workplace.

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance Brown Liquid

Physical state Liquid. Liquid. **Form** Color Brown. Odor Musty.

Odor threshold Not available. Not available. Not available. Melting point/freezing point

Initial boiling point and

boiling range

> 572 °F (> 300 °C)

> 482.0 °F (> 250.0 °C) Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available

Explosive limit - lower

(%)

Not available.

Not available.

Explosive limit - upper (%)

Vapor pressure 1 hPa @ 20 deg C Vapor density Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature Viscosity** Not available.

Other information

Density 1.24 g/cm3

10. Stability and reactivity

Reactivity Not available.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

This product will autopolymerize at very high temperatures. (>200 deg C)

Conditions to avoid Not available. Alcohols. Amines. **Incompatible materials**

Hazardous decomposition

products

Carbon dioxide. Nitrogen oxides (NOx). Sulfur oxides.

11. Toxicological information

Information on likely routes of exposure

Ingestion Not classified. May cause discomfort if swallowed.

Inhalation May cause sensitization by inhalation. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin contact Irritating to skin.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics Irritating to eyes, respiratory system and skin. Irritating to mouth, throat, and stomach. Irritant

effects.

Material name: URETHANE ASPHALT HARDENER - PART B

SDS US 5618 Version #: 01 Issue date: 06-23-2016

Information on toxicological effects

Acute toxicity Not applicable.

Test Results Product Species

URETHANE ASPHALT HARDENER - PART B (CAS Mixture)

Acute Inhalation

LC50 Rat 1.64 mg/l, 4 Hours estimated

Test Results Components **Species**

MDI (CAS 101-68-8)

Acute

Inhalation

LC50 Rat 0.369 mg/l, 4 Hours

Skin corrosion/irritation Irritating to skin.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization May cause sensitization by inhalation. May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Skin sensitization May cause sensitization by skin contact. May cause an allergic skin reaction. Frequent or prolonged

contact may defat and dry the skin, leading to discomfort and dermatitis.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic. Not available.

Not classifiable as to carcinogenicity to humans. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

MDI (CAS 101-68-8) 3 Not classifiable as to carcinogenicity to humans.

METHYLENEDIPHENYL DIISOCYANATE (CAS 26447-40-5) 3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not available. Not classified. Specific target organ toxicity Respiratory tract irritation.

- single exposure

Specific target organ toxicity

- repeated exposure

Causes damage to organs. Respiratory system.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential Not available. Mobility in soil Not available. Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not discharge into drains, water courses or onto the ground.

Hazardous waste code Not regulated.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

^{*} Estimates for product may be based on additional component data not shown.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

Further information If shipped below RQ, this product is not subject to hazardous materials regulations.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

MDI (CAS 101-68-8) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No

Hazardous chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
MDI	101-68-8	< 45

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

MDI (CAS 101-68-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulationsCalifornia Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is

not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. Massachusetts RTK - Substance List

MDI (CAS 101-68-8)

US. New Jersey Worker and Community Right-to-Know Act

MDI (CAS 101-68-8) 500 LBS

US. Pennsylvania RTK - Hazardous Substances

MDI (CAS 101-68-8) **US. Rhode Island RTK**

MDI (CAS 101-68-8)

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-23-2016

Version # 01

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: URETHANE ASPHALT HARDENER - PART B

5618 Version #: 01 Issue date: 06-23-2016 7 / 7