

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

*** Section 1 - Chemical Product and Company Identification ***

Product Trade Name PENNTROWEL EPOXY HARDENER

Manufacturer Information

Ergon Armor (601) 933-3540
Corrosion Engineering
P.O. Box 1639 (800) 424-9300
Jackson, mS 39215-1639

*** Section 2 - Composition / Information on Ingredients ***

CAS #	Component	Percent	OSHA
111-40-0	Diethylenetriamine	90-100	Yes

The substance(s) marked with a "Y" in the OSHA column, are identified as hazardous chemicals according to the criteria of the OSHA Communication Standard (29 CFR 1910.1200)

The components of this product are all on the TSCA inventory list.

*** Section 3 - Hazards Identification ***

Emergency Overview:

Clear light medium viscosity liquid with slight amine odor

DANGER!

CAUSES EYE AND SKIN BURNS. MAY CAUSE BLINDNESS.

MAY BE HARMFUL IF ABSORBED THROUGH SKIN

MAY CAUSE ALLERGIC RESPIRATORY REACTION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY BE HARMFUL IF SWALLOWED.

Potential Health Effects:

Diethylenetriamine

Inhalation and skin contact are expected to be the primary routes of occupational exposure to this material. Repeated or prolonged skin contact can result in an allergic skin reaction. Overexposure to vapor or mist may be irritating to eyes and respiratory tract and repeated or prolonged exposure can cause an allergic respiratory tract reaction in susceptible individuals. While swallowing of this material is unlikely in the industrial setting, if swallowed this material may cause burns of the mouth, throat and digestive tract. This material is considered, on the basis of single exposure (acute) animal tests, to be slightly toxic if ingested (swallowed), moderately to slightly toxic if absorbed through skin and corrosive to eyes and skin. Due to the potential for this material to cause irritation and an allergic reaction in the respiratory tract, workers with lung disease or diminished respiratory capacity should have limited exposure to this material.

*** Section 4 - First Aid Measures ***

IF IN EYES, immediately flush with plenty of water for at least 15 minutes. Get medical attention immediately.

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

IF ON SKIN, immediately wash with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Destroy contaminated shoes.

IF SWALLOWED, do NOT induce vomiting. Give water to drink. Get medical attention immediately. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

*** Section 5 - Fire Fighting Measures ***

Flash Point:	>212 deg F (100 deg C)	Method Used:	TCC	Flammability Classification:
Upper Flammable Limit (UFL):	9.2%	Lower Flammable Limit (LFL):	1.4%	

Fire & Explosion Hazards:

Closed containers of this material may explode when subjected to heat from surrounding fire. Cool exposed containers with water. Avoid breathing fumes from fire exposed material.

Extinguishing Media:

Use water spray, carbon dioxide, foam or dry chemical.

Fire-Fighting Instructions:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

*** Section 6 - Accidental Release Measures ***

Spill or Leak

Isolate hazard area and deny entry to unnecessary or unprotected personnel. Contain spilled liquid with sand or earth. Clean up spill immediately, observing precautions in the Personal Protection section of MSDS. Avoid runoff into storm sewers and ditches which lead to waterways.

*** Section 7 - Handling and Storage ***

Handling Procedures:

Do not get in eyes, on skin or clothing. Avoid breathing vapor or mist. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Empty container may contain hazardous residues.

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

Storage Procedures:

Avoid excessive heat. Store out of direct sunlight in a cool, well-ventilated place.

* * * Section 8 - Exposure Controls / Personal Protection * * *

Component Exposure Limits

-Only those components with exposure limits are printed in this section.

Diethylenetriamine

ACGIH:	TLV-TWA 4.2 mg/m ³ , 1 ppm
ACGIH (SKIN DESIGNATOR):	Y
OSHA:	PEL-TWA 4.2 mg/m ³ , 1 ppm
OSHA (SKIN DESIGNATOR):	Y

-Skin contact limits designated with a "Y" above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required.

-ACGIH Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic reactions.

Engineering Controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits. Provide ventilation if necessary to control exposure levels below airborne exposure limits (see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment. Consult ACGIH ventilation manual or NFPA Standard 91 for design of exhaust systems.

PERSONAL PROTECTIVE EQUIPMENT

As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1910.132), employers must perform a Hazard Assessment of all workplaces to determine the need for, and selection of, proper protective equipment for each task performed.

Eyes/Face Protective Equipment:

Where there is potential for eye contact, wear chemical goggles and have eye flushing equipment available.

Skin Protection:

Neoprene or Polyvinyl chloride gloves should be worn when handling this material. Wear face shield and chemical resistant clothing such as a rubber apron when splashing may occur. Wash contaminated clothing and clean protective equipment before reuse. Rinse contaminated skin promptly. Wash skin thoroughly after handling.

Respiratory Protection:

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

Avoid breathing vapor or mist. When airborne exposure limits are exceeded (see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Consult respirator manufacturer to determine appropriate type equipment for given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

*** Section 9 - Physical & Chemical Properties ***

Physical State:	Liquid	Appearance:	Clear to yellow, amber liquid
Odor:	Amine	Vapor Pressure:	<1 mg/Hg @ 20 deg C
Vapor Density:	3.5	Boiling Point:	>400 deg F
Melting Point:	N/E	Specific Gravity:	1.03 @ 25/25 Deg C
pH:	N/A	Viscosity:	NE
VOC:	<1%	Solubility Water:	Partially soluble

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability:

This material is chemically stable under normal and anticipated storage and handling conditions.

Incompatibility:

Avoid contact with strong acids, alkalis, oxidizers, copper, copper alloys, chlorinated compounds and epoxy resins (in uncontrolled conditions).

Decomposition Products:

Oxides of carbon and nitrogen.

Hazardous Polymerization:

Hazardous polymerization is not known to occur.

*** Section 11 - Toxicological Information ***

Acute Toxicity:

A: General Product Information

No information available for the product.

B: Component Analysis –

Data on this material and/or its components are summarized below.

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

Diethylenetriamine

Single exposure (acute) studies indicate that this material is slightly toxic to rats if swallowed (LD50 1,080-2,330 mg/kg), moderately to slightly toxic to rabbits if absorbed through skin (LD50 670-1,090 mg/kg), and corrosive to rabbit eyes and skin. No deaths were observed in rats exposed to saturated vapor for 8-hours. Allergic skin and respiratory tract reactions have been observed in humans following repeated exposure to this material. Rats orally administered up to 50,000 ppm for 14-days showed decreased body weight, food consumption and spleen weights. Decreased body weight and increased liver, kidney and brain weights were seen in rats administered up to 1060 mg/kg/day by gavage or 15,000 ppm in the diet daily for 90-days. Lifetime dermal exposure to rats produced effects on the liver, lungs, kidneys, spleen and adrenal glands. No tumors were seen in mice after lifetime dermal application. No adverse effects were observed in the offspring of rats exposed subcutaneously (10 or 50 mg/kg/day) or dermally (0.4 ml) for life. This material has generally produced no genetic changes in standard tests using bacterial and animal cells and animals, although a few positive results have been observed in standard tests using bacterial and animal cells.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Chronic Toxicity

No information available for the product.

Epidemiology:

No information available for the product.

Neurotoxicity:

No information available for the product.

Mutagenicity:

No information available for the product.

Teratogenicity:

No information available for the product.

*** Section 12 - Ecological Information ***
--

Ecotoxicity:

A: General Product Information

No information available for the product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Data on this material and/or its components are summarized below.

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

Diethylenetriamine

24-hr TLm Brine shrimp: 710 mg/l
24-hr TLm Himehada: 1,000 mg/l
48-hr LC50 Daphnia magna: 11.5-17.0 mg/l, Slightly Toxic
48-hr LC50 Golden orfe (static): 100-500 mg/l, Practically Non-toxic
96-hr LC50 Fathead minnow: 258-332 mg/l, Practically Non-toxic
Bacterial Inhibition (IC50): >5,000 mg/l

Environmental Fate:

Data on this material and/or its components are summarized below.

Diethylenetriamine

This material has a theoretical oxygen demand (ThOD) of 1.55 mg/mg and a chemical oxygen demand (COD) of 1.57 mg/mg. Its 20-day biochemical oxygen demand (BOD) is 0% (non-acclimated) and 70% (acclimated). Due to its high water solubility and low octanol/water partition coefficient ($K_{ow} = 0.11$), this material is not expected to bioconcentrate.

*** Section 13 - Disposal Considerations ***

US EPA Waste Numbers & Descriptions:

A: General Product Information

Recover, reclaim or recycle when practical.

Disposal via incineration is recommended. Appropriate pretreatment and disposal in an authorized landfill is acceptable. In all cases, dispose of material in accordance with all applicable federal, state, and local laws and regulations. Consult appropriate regulatory officials or your attorney for information on such disposal.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

*** Section 14 - Transportation Information ***

US DOT Information

DOT Name: Diethylenetriamine, Mixture
DOT Technical Name:
DOT Hazard Class: 8
UN Number: 2079
DOT Packing Group: PG II

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

*** Section 15 - Regulatory Information ***
--

US Federal Regulations

A: General Product Information

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

B: Component Analysis

SARA Title III, Section 313

This product does not contain chemical(s) which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 986 and 40 CFR Part 372. See Section 2

This product does not contain chemical(s) which are defined as toxic chemicals under and subject to the reporting requirements of SARA Section 302 (40 CFR 355 Appendix A or CERCLA (40 CFR 302.4).

SARA 311/312: Acute: Y Chronic: Y Fire: N Pressure: N Reactive: N

CERCLA Reportable Quantities (40 CFR 302.4):

NE

State Regulations

A: General Product Information

No additional information available.

B: Component Analysis – State

The following components appear on one or more of the following state hazardous substances lists:

Massachusetts Right to Know

This product does contain the following chemical(s), as indicated below, currently on the Massachusetts Right to Know Substance List.

Diethylenetriamine

New Jersey Right to Know

This product does contain the following chemical(s), as indicated below, currently on the New Jersey Right-to-Know Substances List.

Diethylenetriamine

Pennsylvania Right to Know

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Hazardous Substance List.

Material Safety Data Sheet

Material Name: PENNTROWEL® EPOXY HARDENER

IDs:

Diethylenetriamine

Other Regulations

A: General Product Information

All components are on the U.S. EPA TSCA Inventory List.

B: Component Analysis – Inventory Component Analysis - Inventory

CAS #	Component	TSCA	DSL	EINECS
111-40-0	Diethylenetriamine	Yes	Yes	Yes

C: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Disclosure / Classifications
Diethylenetriamine	111-40-0	0.1% / D2B, E

*** Section 16 - Other Information ***

Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; NFPA = National Fire Protection Association; HMIS = Hazardous Material Identification System; CERCLA = Comprehensive Environmental Response, Compensation and Liability Act; SARA = Superfund Amendments and Reauthorization Act

The information presented herein is believed to be factual as it has been derived from the works and opinions of persons believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which Ergon Armor bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.