

Ergon Asphalt & Emulsions, Inc.

COHEREX

January 6, 2010

MSDS No. AE075

Revision No. 1

Section 1 – Chemical Product and Company Information

Product/Chemical Name:	Coherex
Chemical Formula:	Mixture
CAS Number:	Mixture
Other Designations:	Petroleum Emulsion
General Use:	Dust Control
Manufacturer:	Ergon Asphalt & Emulsions, Inc.; P O Box 1639; Jackson MS 39215-1639; Phone 601-933-3000; Hours of Operation 8:00 am – 5:00 pm; ERGON 24 Hour Emergency Phone Number 1-800-222-7122; CHEMTREC 1-800-424-9300.

Section 2 – Composition / Information on Ingredients

Ingredient Name	CAS Number	% Vol
Heavy Naphthenic extract (petroleum)	64742-11-6	50-70%
Water	7732-18-5	25-45%
Cationic Emulsifier	Listed in TSCA Inventory	<1%
Saponifier	7647-01-0	<2%

INGREDIENT	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH IDLH
	TWA	STEL	TWA	STEL	TWA	STEL	
Heavy Naphthenic extract (petroleum)	100 mg/m ³ as total particulate	None estab.	None estab.	None estab.	100 mg/m ³ as total particulate	None estab.	None estab.
Water	None estab.	None estab.	None estab.	None estab.	None estab.	None estab.	None estab.
Cationic Emulsifier	400 ppm	500 ppm	400 ppm	500 ppm	None estab.	None estab.	None estab.
Saponifier	None estab.	5 ppm (ceiling)	None estab.	2 ppm (ceiling)	None estab.	5 ppm (ceiling)	50 ppm

Section 3 – Hazards Information

EMERGENCY OVERVIEW

HMIS H-1 F-0 R-0 PPE* * Sec.8
--

POTENTIAL HEALTH EFFECTS

Primary Entry Routes: Inhalation and absorption.

Target Organs: Mucous membranes, skin, and digestive tract.

Acute Effects

Inhalation: Irritating to mucous membranes and respiratory tract. May produce symptoms such as headache, dizziness, nausea, vomiting, and loss of coordination.

Eye: May cause slight irritation if directly in contact with eye

Skin: Prolonged skin contact may cause irritation

Ingestion: This product is not expected to be acutely toxic by ingestion. If swallowed, do not induce vomiting. Contact Poison Control Center.

Carcinogenicity: NTP and OSHA do not list this product as carcinogen. This product contains petroleum oils similar to ones categorize by IARC as causing skin cancer on laboratory animals when the oil was repeatedly applied and not removed between applications.

Medical Conditions Aggravated by Long-Term Exposure: Dermatitis.

Chronic Effects: Prolonged and repeated skin contact may cause dermatitis, photosensitization, and melanosis.

Section 4 – First Aid Measures

Inhalation: Remove to fresh air. Apply artificial respiration if needed. Seek medical attention.

Eye Contact: Flush thoroughly with water for at least 15 minutes. If burning persists seek medical attention.

Skin Contact: If in contact with skin, wash thoroughly with soap and water. Seek medical attention if irritation persists.

Ingestion: Do not induce vomiting and seek medical help.

After first aid, get appropriate in-plant paramedic or community medical support.

Special Precautions/Procedures: The petroleum hydrocarbons in this product are a complex mixture of paraffinic, naphthenic, and aromatic hydrocarbons. As with other petroleum products, the aromatic compounds are present in varying concentrations and structures. Some of these compounds may be those which have been shown to result in tumor formation in animals under laboratory conditions. The concentrations of aromatic compounds in this product require that the precautions outlined in this MSDS be followed to minimize personnel exposure.

Provide adequate ventilation to keep vapors below allowable exposure levels. Use PPE appropriate for the task.

Section 5 – Fire Fighting Measures

Flash Point: 400°F (204°C)

Flash Point Method: COC

Auto Ignition Temperature: >700°F (>370°C)

LEL: NA

UEL: NA

Flammability Classification: Class IIIB

Extinguishing Media: Dry chemical, foam and carbon dioxide.

Unusual Fire or Explosion Hazards: NA

Hazardous Combustion Products: Carbon monoxide, carbon dioxide, and sulfur dioxide.

Fire-Fighting Instructions: Use of foam or water may cause frothing. Do not release runoff from fire control methods to sewers or waterways. Use a water supply to cool fire-exposed containers.

Fire-Fighting Equipment: Use self-contained breathing apparatus in enclosed areas where heavy smoke may occur.



Section 6 – Accidental Release Matters

Spill/Leak Procedures: Stop spill at source. Confine spill by diking or impoundment. Remove sources of heat or ignition. Clean-up spill but do not flush to sewer or surface water. Ventilate area and avoid breathing vapors or mists.

Small Spills: Stop spill at source if possible. Isolate and confine by diking, or similar method. Remove discharged material.

Large Spills:

Containment: For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Cleanup: Allow material to cool. Mix with inert absorbent material such as soil, sand, or oil dry, to stabilize.

Regulatory Requirements: Notify local health and pollution control agencies as appropriate. Follow applicable OSHA regulations (29 CFR 1900.120). This material is not a hazardous waste as defined in RCRA. For disposal follow all federal, state, and local regulations regarding solid waste.

Section 7 – Handling and Storage

Handling Precautions: This product is a mixture of water and petroleum oil. Heating this mixture above 190°F can cause the water portion to boil. This may result in frothing of the mixture causing hot product to overflow the container.

Storage Requirements: Ground and bond all transfer and storage equipment. Ventilation is required only in enclosed areas where the emulsion is subjected to severe conditions of heat or agitation.

Regulatory Requirements: None known.

Section 8 – Exposure Controls / Personal Protection

Engineering Controls: Not applicable.

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA

respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Self-contained, positive-pressure breathing apparatus when used in confined or enclosed space or when exposure limits are exceeded or hydrogen sulfide is unknown or exceeds 20 ppm. Organic vapor respirators can be used with good ventilation when organic vapors are less than 1000 ppm or ten times permissible exposure limit, whichever is less. For emergency or nonroutine operations (cleaning spills, reactor vessels, or storage tanks), wear an SCBA. *Warning! Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.* If respirators are used, OSHA requires a written respiratory protection program that includes: procedures for selecting respirators; medical evaluation; fit testing; use in routine and emergency situations; cleaning, disinfecting, storing, inspecting, repairing, discarding and maintaining respirators; adequate air quality, quantity and flow; training in respiratory hazards; training in use of respirators; evaluation of effectiveness of respiratory program.

Protective Clothing/Equipment: Wear protective gloves, boots, aprons, and gauntlets as need to prevent prolonged or repeated skin contact. Goggles and face shields should be used in areas where splashing may occur. Wear protective eyeglasses or safety goggles per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, or smoking.

Section 9 – Physical and Chemical Properties

Physical State: Liquid	Water Solubility: Slightly soluble.
Appearance and Odor: Yellow liquid; mild odor	Other Solubilities: No data.
Odor Threshold: Petroleum odor	Boiling Point: 212°F
Vapor Pressure: <1 mm Hg at 70°F (20°C)	Freezing/Melting Point: No data.
Vapor Density (Air = 1): >1	Viscosity: No data.
Formula Weight: Est. 250 lb/lb-mole	Refractive Index: No data.
Density: 8.42 lb/gal	Surface Tension: No data.
Specific Gravity (H₂O = 1, at 4°C): 1.01	% Volatile: <2%
pH: 4.5-5.4	Evaporation Rate: <1

Section 10 – Stability and Reactivity

Stability: Stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizing agents.

Conditions to Avoid: DO NOT HEAT PRODUCT

Hazardous Decomposition Products: Primary decomposition products are carbon monoxide, carbon dioxide, and water. Combustion products may include sulfur oxides and hydrogen sulfide.

Section 11 – Toxicological Information

Eye Effects: Vapors may cause a slight smarting of the eyes or respiratory system if present in high concentrations. The effect is temporary.

Acute Inhalation Effects: Human, inhalation, TC_{LO}: No data.

Carcinogenicity: Not a known human carcinogen.

Teratogenicity: No data.

Chronic Effects: Prolonged and repeated skin contact may cause dermatitis, photosensitization, and melanosis.

Skin Effects: Slightly irritating to the skin.

Acute Oral Effects: Rat, oral, LD₅₀: 5 to 15 g/kg

Mutagenicity: No data.

Section 12 – Ecological Information

Ecotoxicity: No data.

Environmental Fate:

Environmental Transport: No data.

Environmental Degradation: No data.

Soil Absorption/Mobility: No data.

Section 13 – Disposal Considerations

Disposal: Contact your supplier or a licensed contractor for detailed recommendations. Follow applicable Federal, state, and local regulations.

Disposal Regulatory Requirements: Solidified waste material should not be a hazardous waste under RCRA guidelines. Follow Federal, state, and local regulations for disposal of solid waste.

Container Cleaning and Disposal: Recommend using a non-hazardous solvent to remove the product. Follow Federal, state, and local regulations for disposal of the waste material, regardless of its waste classification.

Section 14 – Transport Information

Shipping Name: Not Regulated	Packaging Authorizations: a) Exceptions: NA b) Non-bulk Packaging: NA c) Bulk Packaging: NA	Quantity Limitations: a) Passenger, Aircraft, or Railcar: NA b) Cargo Aircraft Only: NA
Shipping Symbols: NA		Vessel Stowage Requirements: a) Vessel Stowage: NA b) Other: NA
Hazard Class: NA		
ID No.: NA		
Packing Group: NA		
Label: NA		
Special Provisions (172.102): NA		

Section 15 – Regulatory Information

EPA Regulations:

RCRA
RCRA Hazardous Waste Number: Not listed.
RCRA Hazardous Waste Classification (40 CFR 261): This material should not be hazardous due to characteristics.

CERCLA
CERCLA: Not listed.
CERCLA Reportable Quantity (RQ): This material is not a listed hazardous substance and does not have a reportable quantity. However, if spilled into waters of the U.S., it may be reportable under the Clean Water Act.

SARA
SARA 311/312 Codes: Not Listed
SARA Toxic Chemical: Not listed.

OSHA Regulations
Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-1-A): See Table in Section 2.

OSHA Specifically Regulated Substance: No

State Regulations: Listed as a hazardous substance by the state: MA

Section 16 – Other Information

Revision Notes:

Additional Hazard Rating Systems:

Disclaimer: ERGON ASPHALT & EMULSIONS, INC. (EAE) PROVIDES THIS INFORMATION FOR THE USER'S CONSIDERATION. EAP BELIEVES THIS INFORMATION IS ACCURATE, BUT NOT ALL INCLUSIVE IN ALL CIRCUMSTANCES. USER SHOULD ENSURE THAT USER HAS CURENT DATA RELEVANT FOR ITS PURPOSES. NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING MERCHANTABILITY, FITNESS OR OTHERWISE IS GIVEN.