

1. Product and Company Identification

Material name 13% CONCENTRATE
Version # 01
Revision date 09-07-2011
CAS # Mixture
Manufacturer: Ergon Asphalt & Emulsions, Inc.
Address: P O Box 1639
Jackson MS 39215-1639
Contact Name: Mary Ellen Snow
Telephone: 601-933-3540; 24-hour Customer Service 1-800-222-7122
E-mail: mary.snow@ergon.com
CHEMTREC: 1-800-424-9300

2. Hazards Identification

Emergency overview May cause irritation of respiratory tract. Material may be hot.

Potential health effects

Routes of exposure

Inhalation.

Eyes

Severely irritating to eyes. A significant thermal hazard under normal usage due to high temperatures required for application.

Skin

Moderately irritating. Hot asphalt will cause severe burns. May lead to photosensitization and drying of the skin.

Inhalation

Vapors may irritate throat and respiratory system and cause coughing. Prolonged inhalation may be harmful. Prolonged exposure may result in dizziness or nausea

Ingestion

Irritating to mucous membranes and gastrointestinal tract. May cause thermal burns.

Potential environmental effects

Ecological injuries are not known or expected under normal use.

3. Composition / Information on Ingredients

Components	CAS #	Percent
ASPHALT	8052-42-4	85 - 90
Other components below reportable levels		10 - 25

4. First Aid Measures

First aid procedures

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact

If molten asphalt strikes exposed skin, cool immediately by quenching with cold water. Lotion or hand cream may aid in the removal of asphalt. If clothing sticks to the skin, do not remove. Wash contact areas with soap and water. If needed, seek medical attention.

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.

5. Fire Fighting Measures

Flammable properties

This product may ignite when sufficient heat is applied. Check for combustible vapors prior to and during welding or torch cutting on vessels or tank. It has been found that in hot storage tanks low flash substances may accumulate in the vapor space. Keep ignition sources away from tank vents and prevent accumulation or pyrophoric iron sulfide.

Extinguishing media

Suitable extinguishing media Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific methods In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

Hazardous combustion products Decomposition of this product may yield oxides of sulfur and nitrogen. Hydrogen sulfide Carbon monoxide and carbon dioxide.

6. Accidental Release Measures

Personal precautions Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods for containment Ventilate area and avoid breathing vapors or mist. Prevent entry into waterways, sewer, basements or confined areas. Remove sources of ignition. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Methods for cleaning up Dike far ahead of spill for later disposal. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal. Absorb spill with vermiculite or other inert material.

7. Handling and Storage

Handling Avoid contact with molten material. Trace amounts of hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.

Storage Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place.

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH

Components	Type	Value	Form
ASPHALT (8052-42-4)	TWA	0.5000 mg/m ³	Inhalable fraction.

Engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Eye / face protection Chemical goggles and face shield are recommended.

Skin protection Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance Brown to black in color.

Color Brown.

Odor Tar-like Sulphurous.

Odor threshold Not available.

Physical state Liquid.

Form Liquid.

pH Not available.

Melting point	Not available.
Freezing point	Not available.
Boiling point	> 700 °F (> 371.1 °C)
Flash point	> 450 °F (> 232.2 °C)
Evaporation rate	Not available.
Flammability limits in air, upper, % by volume	Not available.
Flammability limits in air, lower, % by volume	Not available.
Vapor pressure	< 1 mm Hg @ 20 C
Vapor density	> 5
Specific gravity	0.98 - 1.04
Relative density	Not available.
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	> 700 °F (> 371.1 °C)
Decomposition temperature	Not available.
VOC	Not available.

10. Chemical Stability & Reactivity Information

Chemical stability	Stable under normal temperature conditions.
Conditions to avoid	Do not overheat product.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Chronic effects	Prolonged inhalation may be harmful.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

ACGIH Carcinogens

ASPHALT (CAS 8052-42-4) A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.
3 Not classifiable as to carcinogenicity to humans.

12. Ecological Information

Ecotoxicity	This product has no known eco-toxicological effects.
Persistence and degradability	Not available.

13. Disposal Considerations

Waste codes	Not applicable.
Disposal instructions	Allow molten resin to solidify before disposal. Dispose in accordance with all applicable regulations.

14. Transport Information

DOT

Basic shipping requirements:

UN number	3257
Proper shipping name	Elevated temperature liquid, n.o.s. (ASPHALT)
Hazard class	9
Packing group	III

Additional information:

ERG number 128

**15. Regulatory Information****CERCLA (Superfund) reportable quantity**

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - No
 Delayed Hazard - Yes
 Fire Hazard - No
 Pressure Hazard - No
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

Section 311 hazardous chemical No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCs)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

ASPHALT (CAS 8052-42-4) Listed.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990 Carcinogenic.

US - Pennsylvania RTK - Hazardous Substances: Listed substance

ASPHALT (CAS 8052-42-4) Listed.

US - Pennsylvania RTK - Hazardous Substances: Special hazard

ASPHALT (CAS 8052-42-4) Special hazard.

16. Other Information

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 2
Flammability: 1
Physical hazard: 1

NFPA ratings

Health: 2
Flammability: 1
Instability: 0

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Issue date

09-07-2011