

## 1. Product and Company Identification

**Material name** CSS-1HPM  
**Version #** 01  
**Revision date** 10-11-2011  
**CAS #** Mixture  
**Manufacturer:** Ergon Asphalt & Emulsions, Inc.  
**Address:** P O Box 1639  
Jackson MS 39215-1639  
**Contact Name:** Mary Ellen Snow  
**Telephone:** 601-933-3540; 24-hour Customer Service 1-800-222-7122  
**E-mail:** mary.snow@ergon.com  
**CHEMTREC:** 1-800-424-9300

## 2. Hazards Identification

**Emergency overview** May cause irritation of respiratory tract. Material may be hot.

### Potential health effects

#### Routes of exposure

Inhalation. Ingestion. Skin contact. Eye contact.

#### Eyes

Severely irritating to eyes. A significant thermal hazard under normal usage due to high temperatures required for application.

#### Skin

Moderately irritating. Hot asphalt will cause severe burns. May lead to photosensitization and drying of the skin.

#### Inhalation

Vapors may irritate throat and respiratory system and cause coughing. Prolonged inhalation may be harmful. Prolonged exposure may result in dizziness or nausea

#### Ingestion

Irritating to mucous membranes and gastrointestinal tract. May cause thermal burns.

### Potential environmental effects

Ecological injuries are not known or expected under normal use.

## 3. Composition / Information on Ingredients

Hazardous components	CAS #	Percent
HYDROCHLORIC ACID	7647-01-0	0 - 1
ASPHALT	8052-42-4	62 - 65
Non-hazardous components	CAS #	Percent
WATER	7732-18-5	30 - 32
Other components below reportable levels		0.0001 - 20

## 4. First Aid Measures

### First aid procedures

#### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

#### Skin contact

If molten asphalt strikes exposed skin, cool immediately by quenching with cold water. Lotion or hand cream may aid in the removal of asphalt. If clothing sticks to the skin, do not remove. Wash contact areas with soap and water. If needed, seek medical attention.

#### Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

#### Ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.

## 5. Fire Fighting Measures

<b>Flammable properties</b>	This product may ignite when sufficient heat is applied. Check for combustible vapors prior to and during welding or torch cutting on vessels or tank. It has been found that in hot storage tanks low flash substances may accumulate in the vapor space. Keep ignition sources away from tank vents and prevent accumulation or pyrophoric iron sulfide.
<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use a solid water stream as it may scatter and spread fire.
<b>Specific methods</b>	In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.
<b>Hazardous combustion products</b>	Decomposition of this product may yield oxides of sulfur and nitrogen. Hydrogen sulfide Carbon monoxide and carbon dioxide.

## 6. Accidental Release Measures

<b>Personal precautions</b>	Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
<b>Methods for containment</b>	Ventilate area and avoid breathing vapors or mist. Prevent entry into waterways, sewer, basements or confined areas. Remove sources of ignition. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.
<b>Methods for cleaning up</b>	Dike far ahead of spill for later disposal. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal. Absorb spill with vermiculite or other inert material.

## 7. Handling and Storage

<b>Handling</b>	Avoid contact with molten material. Trace amounts of hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.
<b>Storage</b>	Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place.

## 8. Exposure Controls / Personal Protection

### Occupational exposure limits

#### ACGIH

Components	Type	Value	Form
ASPHALT (8052-42-4)	TWA	0.5000 mg/m3	Inhalable fraction.
HYDROCHLORIC ACID (7647-01-0)	Ceiling	2.0000 ppm	

#### U.S. - OSHA

Components	Type	Value
HYDROCHLORIC ACID (7647-01-0)	Ceiling	5.0000 ppm 7.0000 mg/m3

<b>Engineering controls</b>	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
<b>Personal protective equipment</b>	
<b>Eye / face protection</b>	Do not get in eyes. Chemical goggles are recommended.
<b>Skin protection</b>	Wear chemical protective equipment that is specifically recommended by the manufacturer. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact. Plastic or rubber gloves, apron and boots.

**General hygiene considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical & Chemical Properties**

<b>Appearance</b>	Brown to black in color.
<b>Color</b>	Black
<b>Odor</b>	Tar-like
<b>Odor threshold</b>	Not available.
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>pH</b>	2 - 4
<b>Melting point</b>	Not available.
<b>Freezing point</b>	Not available.
<b>Boiling point</b>	212 °F (100 °C)
<b>Flash point</b>	400 °F (204.4 °C) Cleveland Open Cup
<b>Evaporation rate</b>	< 1
<b>Flammability limits in air, upper, % by volume</b>	Not available.
<b>Flammability limits in air, lower, % by volume</b>	Not available.
<b>Vapor pressure</b>	< 1 mm Hg @20 C
<b>Vapor density</b>	> 1
<b>Specific gravity</b>	1.01
<b>Relative density</b>	Not available.
<b>Solubility (water)</b>	Slightly soluble
<b>Partition coefficient (n-octanol/water)</b>	Not available
<b>Auto-ignition temperature</b>	> 700 °F (> 371.1 °C)
<b>Decomposition temperature</b>	Not available.
<b>VOC</b>	Not available.
<b>Percent volatile</b>	< 2 %

**10. Chemical Stability & Reactivity Information**

<b>Chemical stability</b>	Stable under normal temperature conditions.
<b>Conditions to avoid</b>	Do not overheat product.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.

**11. Toxicological Information****Toxicological data****Product**

CSS-1HPM (Mixture)

**Test Results**

Acute Dermal LD50 Mouse: 79180 mg/kg estimated  
Acute Inhalation LC50 Mouse: 60546 mg/l estimated  
Acute Oral LD50 Rabbit: 49180 mg/kg estimated

**Components**

HYDROCHLORIC ACID (7647-01-0)

**Test Results**

Acute Dermal LD50 Mouse: 1449 mg/kg  
Acute Inhalation LC50 Mouse: 1108 mg/l 1.00 Hours  
Acute Inhalation LC50 Rat: 3124 mg/l 1.00 Hours

## Components

HYDROCHLORIC ACID (7647-01-0)

## Test Results

Acute Oral LD50 Rabbit: 900 mg/kg

Acute Other LD50 Mouse: 1449 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Acute effects** Causes burns.

**Local effects** Irritating to respiratory system.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

### ACGIH Carcinogens

ASPHALT (CAS 8052-42-4)

A4 Not classifiable as a human carcinogen.

HYDROCHLORIC ACID (CAS 7647-01-0)

A4 Not classifiable as a human carcinogen.

### IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)

2B Possibly carcinogenic to humans.

HYDROCHLORIC ACID (CAS 7647-01-0)

3 Not classifiable as to carcinogenicity to humans.

3 Not classifiable as to carcinogenicity to humans.

**Skin corrosion/irritation** Hazardous by OSHA criteria.

## 12. Ecological Information

### Ecotoxicological data

#### Product

CSS-1HPM (Mixture)

#### Test Results

LC50 Fish: 15410 mg/l 96.00 Hours estimated

#### Components

HYDROCHLORIC ACID (7647-01-0)

#### Test Results

LC50 Western mosquitofish (*Gambusia affinis*): 282 mg/l 96.00 Hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** Not available.

## 13. Disposal Considerations

**Disposal instructions** Dispose in accordance with all applicable regulations.

## 14. Transport Information

### DOT

Not regulated as dangerous goods.

## 15. Regulatory Information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Spill: Reportable quantity

HYDROCHLORIC ACID (CAS 7647-01-0)

5000 LBS

### US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Substance: Threshold Planning Quantity

HYDROCHLORIC ACID (CAS 7647-01-0)

500 LBS

### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

HYDROCHLORIC ACID (CAS 7647-01-0)

1.0 %

### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

HYDROCHLORIC ACID (CAS 7647-01-0)

Listed.

### CERCLA (Superfund) reportable quantity

HYDROCHLORIC ACID: 5000.0000

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories**  
Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

**Section 302 extremely hazardous substance**  
No

**Section 311 hazardous chemical**  
Yes

**Clean Water Act (CWA)**  
Hazardous substance

### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCs)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

ASPHALT (CAS 8052-42-4) Listed.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990 Carcinogenic.

#### US - New Jersey Community RTK (EHS Survey): Reportable threshold

HYDROCHLORIC ACID (CAS 7647-01-0) 500 LBS

#### US - Pennsylvania RTK - Hazardous Substances: Listed substance

ASPHALT (CAS 8052-42-4) Listed.

HYDROCHLORIC ACID (CAS 7647-01-0) Listed.

#### US - Pennsylvania RTK - Hazardous Substances: Special hazard

ASPHALT (CAS 8052-42-4) Special hazard.

## 16. Other Information

**Further information** HMIS® is a registered trade and service mark of the NPCA.

**HMIS® ratings**  
Health: 2  
Flammability: 1  
Physical hazard: 0

**NFPA ratings**  
Health: 2  
Flammability: 1  
Instability: 0

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Issue date** 10-11-2011