

1. Identification

| | |
|---|--|
| Product identifier | Coating Asphalt |
| Other means of identification | Not available. |
| Recommended use | Not available. |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Manufacturer | |
| Manufacturer: | Ergon Asphalt & Emulsions, Inc. |
| Address: | P. O. Box 1639 Jackson, MS 39215-1639 |
| Website: | www.ergonasphalt.com |
| Telephone: | 1-800-222-7122 (Customer Service) |
| E-mail: | sds@ergon.com |
| 24 hour Emergency (CHEMTREC): | North America 1-800-424-9300; International 1-703-527-3887 |

2. Hazard(s) identification

| | |
|------------------------------|-----------------|
| Physical hazards | Not classified. |
| Health hazards | Not classified. |
| Environmental hazards | Not classified. |
| OSHA defined hazards | Not classified. |

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

| | |
|--|--|
| Hazard symbol | None. |
| Signal word | Not available. |
| Hazard statement | Not available. |
| Prevention | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/eye protection/face protection. |
| Response | If exposed or concerned: Get medical advice/attention. |
| Storage | Store locked up. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | Molten asphalt presents a thermal hazard. |
| Supplemental information | Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H ₂ S) can be harmful or fatal if inhaled. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|-------------------|--------------------------|------------|-----|
| ASPHALT, OXIDIZED | | 64742-93-4 | 100 |

4. First-aid measures

| | |
|---------------------|--|
| Inhalation | If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist. |
| Skin contact | Immediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY. Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of the asphalt due to the risk of adhesion. Get immediate medical attention. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention or advice. |
| Ingestion | Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately. |

Most important symptoms/effects, acute and delayed Potential for severe thermal burns.

5. Fire-fighting measures

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical Irritating and toxic gases or fumes may be released during a fire.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use of foam or water may cause frothing.

Specific methods In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up Dike far ahead of spill for later disposal. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal.

7. Handling and storage

Precautions for safe handling Avoid contact with molten material. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.

Conditions for safe storage, including any incompatibilities Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - NIOSH Components

ASPHALT, OXIDIZED (CAS 64742-93-4)

Type

REL

Value

5 mg/m³

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses. Wear face shield if there is risk of splashes.

Hand protection

Thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

Other

Normal work clothing (long sleeved shirts and long pants) is recommended. Wear 100% cotton clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

During product use, there is a risk of thermal burns.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Solid.

Physical state Solid.

Form Solid.

| | |
|---|--|
| Color | Dark brown to. Black |
| Odor | Hydrocarbon-like. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | > 650 °F (> 343.33 °C) |
| Flash point | > 450.0 °F (> 232.2 °C) Cleveland Open Cup |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 3 mm Hg @ 20°C 4 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Insoluble |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 650 °F (343.33 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Flammability class | Combustible IIIB estimated |

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Stable under normal temperature conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Do not overheat product. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|---|
| Ingestion | Causes digestive tract burns. |
| Inhalation | May cause irritation to the respiratory system. |
| Skin contact | Molten material will produce thermal burns. |
| Eye contact | Molten material will produce thermal burns. |

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

| | |
|--|----------------|
| Acute toxicity | Not available. |
| Skin corrosion/irritation | Not available. |
| Serious eye damage/eye irritation | Not available. |

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Not available.

Germ cell mutagenicity Not available.

Carcinogenicity IARC: occupational exposures to oxidized bitumens and their emissions during roofing are "probably carcinogenic to humans" (Group 2A) Contains polycyclic aromatic compounds (PACs). Prolonged and/or repeated skin contact with certain PACs has been shown to cause skin cancer. Prolonged and/or repeated exposures by inhalation of certain PACs may also cause cancer of the lung and of other sites of the body.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT, OXIDIZED (CAS 64742-93-4)

2A Probably carcinogenic to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not available.

Specific target organ toxicity - single exposure Not available.

Specific target organ toxicity - repeated exposure Not available.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity This product has no known eco-toxicological effects.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Allow molten resin to solidify before disposal. Dispose in accordance with all applicable regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Hazardous waste code Not applicable.

Waste from residues / unused products Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging No special precautions.

14. Transport information

DOT

UN number UN3257

UN proper shipping name Elevated temperature liquid, n.o.s. (ASPHALT)

Transport hazard class(es)

Class 9

Subsidiary risk -

Packing group III

Special precautions for user Not available.

IATA

UN number Not available.

UN proper shipping name Forbidden

Transport hazard class(es)

Class Forbidden

Subsidiary risk -

Packing group Not applicable.

Environmental hazards No.

Special precautions for user Not available.

Other information

Passenger and cargo aircraft Forbidden.

Cargo aircraft only Forbidden.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

DOT**Further information**

Shipping Marking: HOT. Transport by air is forbidden when shipped above 212°F (100°C).

15. Regulatory information**US federal regulations****TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Yes

Hazardous chemical**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

Not regulated.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-20-2015

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.