

1. Identification

Product identifier CQS-1HB
Other means of identification Not available.
Recommended use Not available.
Recommended restrictions None known.
Manufacturer/Importer/Supplier/Distributor information
Manufacturer
Manufacturer: Ergon Asphalt & Emulsions, Inc.
Address: P. O. Box 1639
Jackson, MS 39215-1639
Website: www.ergonasphalt.com
Telephone: 1-800-222-7122 (Customer Service)
E-mail: sds@ergon.com
24 hour Emergency (CHEMTREC): North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.
Hazard statement The mixture does not meet the criteria for classification.
Prevention Observe good industrial hygiene practices.
Response Wash hands after handling.
Storage Store away from incompatible materials.
Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H₂S) can be harmful or fatal if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	60 - < 70
WATER		7732-18-5	30 - < 40
HYDROCHLORIC ACID		7647-01-0	1 - < 3
Other components below reportable levels			1 - < 3

Composition comments Components not listed are either non-hazardous or below the required disclosure threshold.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of asphalt. Wash contact areas with soap and water. If needed, seek medical attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire-fighting equipment/instructions	ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.
Specific methods	In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.
Conditions for safe storage, including any incompatibilities	Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	7 mg/m ³
		5 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inhalable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	2 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	7 mg/m3	
		5 ppm	

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses; chemical goggles (if splashing is possible).
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.
Other	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact. Plastic or rubber gloves, apron and boots.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Brown to black in color.
Physical state	Liquid.
Form	Liquid.
Color	Black
Odor	Tar-like
Odor threshold	Not available.
pH	2 - 4
Melting point/freezing point	-173.6 °F (-114.22 °C) estimated
Initial boiling point and boiling range	212 °F (100 °C)
Flash point	400.0 °F (204.4 °C) Cleveland Open Cup
Evaporation rate	< 1
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 1 mm Hg @ 70C
Vapor density	> 1
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 700 °F (> 371.11 °C)

Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Flammability class	Flammable III B
Percent volatile	< 2 %
Specific gravity	1.02

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable under normal temperature conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat product.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Harmful in contact with eyes.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
CQS-1HB (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Mouse	78324.3281 mg/kg estimated
<i>Inhalation</i>		
LC50	Mouse	59891.8906 ppm, 1 Hours estimated
<i>Oral</i>		
LD50	Rabbit	48648.6484 mg/kg estimated
<i>Other</i>		
LD50	Mouse	78324.3281 mg/kg estimated

Components	Species	Test Results
HYDROCHLORIC ACID (CAS 7647-01-0)		
Acute		
<i>Dermal</i>		
LD50	Mouse	1449 mg/kg
<i>Inhalation</i>		
LC50	Mouse	1108 ppm, 1 Hours
	Rat	3124 ppm, 1 Hours
<i>Oral</i>		
LD50	Rabbit	900 mg/kg
<i>Other</i>		
LD50	Mouse	1449 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation	Harmful in contact with eyes. None known.
Respiratory or skin sensitization	
Respiratory sensitization	Not available.
Skin sensitization	May cause skin disorders if contact is repeated or prolonged.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure. IARC: occupational exposures to straight-run bitumens and their emissions during road paving are "possibly carcinogenic to humans" (Group 2B)

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)	2B Possibly carcinogenic to humans.
HYDROCHLORIC ACID (CAS 7647-01-0)	3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged exposure may cause chronic effects.
Further information	This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product	Species	Test Results
CQS-1HB (CAS Mixture)		
Fish	LC50	Fish 15243.2432 mg/l, 96 hours estimated
Components	Species	Test Results
HYDROCHLORIC ACID (CAS 7647-01-0)		
Aquatic		
Fish	LC50	Western mosquitofish (Gambusia affinis) 282 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. No components are identified as hazardous wastes. Disposal recommendations are based on uncontaminated material.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Not applicable.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	Not regulated as dangerous goods.
------------	-----------------------------------

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.**Further information** If shipped above 212 deg F: "UN3257, Elevated Temperature Liquid, n.o.s. (Asphalt mixture), 9, PG III"**15. Regulatory information****US federal regulations** All components are on the U.S. EPA TSCA Inventory List.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

HYDROCHLORIC ACID (CAS 7647-01-0) Listed.

US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity

HYDROCHLORIC ACID (CAS 7647-01-0) 5000 LBS

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories** Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No**SARA 302 Extremely hazardous substance**

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
HYDROCHLORIC ACID	7647-01-0	5000	500 lbs		

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
HYDROCHLORIC ACID	7647-01-0	1 - < 3

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

HYDROCHLORIC ACID (CAS 7647-01-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

HYDROCHLORIC ACID (CAS 7647-01-0)

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2))**

HYDROCHLORIC ACID (CAS 7647-01-0)

DEA Essential Chemical Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

HYDROCHLORIC ACID (CAS 7647-01-0) 20 %WV

DEA Exempt Chemical Mixtures Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.**US. Massachusetts RTK - Substance List**

ASPHALT (CAS 8052-42-4)

HYDROCHLORIC ACID (CAS 7647-01-0)

US. New Jersey Worker and Community Right-to-Know Act

HYDROCHLORIC ACID (CAS 7647-01-0) 500 LBS

US. Pennsylvania RTK - Hazardous SubstancesASPHALT (CAS 8052-42-4)
HYDROCHLORIC ACID (CAS 7647-01-0)**US. Rhode Island RTK**

HYDROCHLORIC ACID (CAS 7647-01-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 05-05-2015**Version #** 01**Further information** HMIS® is a registered trade and service mark of the NPCA.**References**ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.