

1. Identification

Product identifier CSS-1EP (R)
Other means of identification Not available.
Recommended use Not available.
Recommended restrictions None known.
Manufacturer/Importer/Supplier/Distributor information
Manufacturer
Manufacturer: Ergon Asphalt & Emulsions, Inc.
Address: 2829 Lakeland Drive
 Jackson, MS 39232
Website: www.ergonasphalt.com
Telephone: 1-800-222-7122 (Customer Service)
E-mail: sds@ergon.com
24 hour Emergency (CHEMTREC): North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Carcinogenicity Category 1B
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement May cause cancer by skin contact.
Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.
Response If exposed or concerned: Get medical advice/attention.
Storage Store locked up.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H2S) can be harmful or fatal if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	50 - 70
WATER		7732-18-5	20 - 40
EXTRACTS (PETROLEUM), HEAVY NAPHTHENIC DISTILLATE SOLVENT		64742-11-6	< 10
HYDROCHLORIC ACID		7647-01-0	< 3

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.
Skin contact If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of asphalt. Wash contact areas with soap and water. If needed, seek medical attention.

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire-fighting equipment/instructions	ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.
Specific methods	In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.
Conditions for safe storage, including any incompatibilities	Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
EXTRACTS (PETROLEUM), HEAVY NAPHTHENIC DISTILLATE SOLVENT (CAS 64742-11-6)	PEL	5 mg/m ³	Mist.
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	7 mg/m ³ 5 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inhalable fraction.
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	2 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m ³	Fume.
EXTRACTS (PETROLEUM), HEAVY NAPHTHENIC DISTILLATE SOLVENT (CAS 64742-11-6)	STEL	10 mg/m ³	Mist.
HYDROCHLORIC ACID (CAS 7647-01-0)	TWA Ceiling	5 mg/m ³ 7 mg/m ³ 5 ppm	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses. If risk of splashing, wear safety goggles or face shield.

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Wash hands after handling.

Other

Chemical/solvent resistant gloves are recommended. If contact with forearms is likely, use gauntlet-style gloves. Wear suitable protective clothing as protection against splashing or contamination.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Brown to black in color.

Physical state

Liquid.

Form

Liquid.

Color

Black

Odor

Tar-like

Odor threshold

Not available.

pH

2 - 4

Melting point/freezing point

Not available.

Initial boiling point and boiling range

212 °F (100 °C)

Flash point

> 212.0 °F (> 100.0 °C) Cleveland Open Cup

Evaporation rate

< 1

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits**Flammability limit - lower (%)** Not available.**Flammability limit - upper (%)** Not available.**Explosive limit - lower (%)** Not available.**Explosive limit - upper (%)** Not available.**Vapor pressure** < 1 mm Hg @20 C**Vapor density** > 1**Relative density** Not available.**Solubility(ies)****Solubility (water)** Slightly soluble**Partition coefficient (n-octanol/water)** Not available.**Auto-ignition temperature** > 700 °F (> 371.11 °C)**Decomposition temperature** Not available.**Viscosity** Not available.**Other information****Density** 8.30 - 8.50 lb/gal**Specific gravity** 1.01**10. Stability and reactivity****Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.**Chemical stability** Material is stable under normal conditions.**Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.**Conditions to avoid** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.**Incompatible materials** Strong oxidizing agents.**Hazardous decomposition products** No hazardous decomposition products are known.**11. Toxicological information****Information on likely routes of exposure****Ingestion** Expected to be a low ingestion hazard.**Inhalation** Prolonged inhalation may be harmful.**Skin contact** Causes mild skin irritation. May cause cancer by skin contact.**Eye contact** Harmful in contact with eyes.**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.**Information on toxicological effects****Acute toxicity**

Product	Species	Test Results
CSS-1EP (R) (CAS Mixture)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	85230.7656 ppm, 1 Hours estimated
<i>Oral</i>		
LD50	Mouse	1352.8302 g/kg estimated
	Rabbit	69230.7656 mg/kg estimated
	Rat	1211.3208 g/kg estimated

Components	Species	Test Results
HYDROCHLORIC ACID (CAS 7647-01-0)		
Acute		
<i>Dermal</i>		
LD50	Mouse	1449 mg/kg
<i>Inhalation</i>		
LC50	Mouse	1108 ppm, 1 Hours
	Rat	3124 ppm, 1 Hours
<i>Oral</i>		
LD50	Rabbit	900 mg/kg
<i>Other</i>		
LD50	Mouse	1449 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Harmful in contact with eyes. None known.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause skin disorders if contact is repeated or prolonged.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Contains polycyclic aromatic compounds (PACs). Prolonged and/or repeated skin contact with certain PACs has been shown to cause skin cancer. Prolonged and/or repeated exposures by inhalation of certain PACs may also cause cancer of the lung and of other sites of the body. NTP Carcinogens (DHHS).

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.
 HYDROCHLORIC ACID (CAS 7647-01-0) 3 Not classifiable as to carcinogenicity to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema/chapping and oil acne.

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
HYDROCHLORIC ACID (CAS 7647-01-0)		
Aquatic		
Fish	LC50	Western mosquitofish (Gambusia affinis) 282 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

15. Regulatory information

US federal regulations	All components are on the U.S. EPA TSCA Inventory List.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	
ASPHALT (CAS 8052-42-4)	Listed.
HYDROCHLORIC ACID (CAS 7647-01-0)	Listed.
US EPCRA Section 304 Extremely Haz. Subs. & CERCLA Haz. Subs.: Section 304 EHS reportable quantity	
HYDROCHLORIC ACID (CAS 7647-01-0)	5000 LBS
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
--------------------------	--

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value
---------------	------------	---------------------	-----------------------------	--	--

HYDROCHLORIC ACID	7647-01-0	5000	500 lbs		
-------------------	-----------	------	---------	--	--

SARA 311/312 Hazardous chemical
No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
HYDROCHLORIC ACID	7647-01-0	< 3

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

HYDROCHLORIC ACID (CAS 7647-01-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

HYDROCHLORIC ACID (CAS 7647-01-0)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2))

HYDROCHLORIC ACID (CAS 7647-01-0)

DEA Essential Chemical Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

HYDROCHLORIC ACID (CAS 7647-01-0) 20 %WV

DEA Exempt Chemical Mixtures Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

ASPHALT (CAS 8052-42-4)

EXTRACTS (PETROLEUM), HEAVY NAPHTHENIC DISTILLATE SOLVENT (CAS 64742-11-6)

HYDROCHLORIC ACID (CAS 7647-01-0)

US. New Jersey Worker and Community Right-to-Know Act

HYDROCHLORIC ACID (CAS 7647-01-0) 500 LBS

US. Pennsylvania RTK - Hazardous Substances

ASPHALT (CAS 8052-42-4)

EXTRACTS (PETROLEUM), HEAVY NAPHTHENIC DISTILLATE SOLVENT (CAS 64742-11-6)

HYDROCHLORIC ACID (CAS 7647-01-0)

US. Rhode Island RTK

HYDROCHLORIC ACID (CAS 7647-01-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-06-2016

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.