

1. Identification

Product identifier **SPG 73-25**
Other means of identification None.
Recommended use Not available.
Recommended restrictions None known.
Manufacturer/Importer/Supplier/Distributor information
Manufacturer: Ergon Asphalt & Emulsions, Inc.
Address: 2829 Lakeland Drive
Jackson, MS 39232
Website: www.ergonasphalt.com
Telephone: 1-800-222-7122 (Customer Service)
E-mail: sds@ergon.com
24 hour Emergency (CHEMTREC): North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

Label elements

Hazard symbol None.

Signal word None.

Hazard statement Not available.

Precautionary statement

Prevention Wear protective gloves/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) Molten asphalt presents a thermal hazard.

Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H₂S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	<100

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact Immediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY. Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of the asphalt due to the risk of adhesion. Get immediate medical attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention or advice.

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed Potential for severe thermal burns.

5. Fire-fighting measures

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical Irritating and toxic gases or fumes may be released during a fire.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use of foam or water may cause frothing.

Specific methods In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and materials for containment and cleaning up Dike far ahead of spill for later disposal. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal.

Environmental precautions Not available.

7. Handling and storage

Precautions for safe handling Avoid contact with molten material. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container.

Conditions for safe storage, including any incompatibilities Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. It is recommended that the storage temperature never exceed 375°F.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
HYDROGEN SULFIDE (CAS 7783-06-4)	Ceiling	20 ppm

US. ACGIH Threshold Limit Values

Material	Type	Value	Form
SPG 73-25	TWA	0.5 mg/m3	Inhalable fraction.
Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.
HYDROGEN SULFIDE (CAS 7783-06-4)	STEL	5 ppm	
	TWA	1 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Material	Type	Value	Form
SPG 73-25	Ceiling	5 mg/m3	Fume.
Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.

US. NIOSH: Pocket Guide to Chemical Hazards Components

Type	Value	Form
HYDROGEN SULFIDE (CAS 7783-06-4)	Ceiling 15 mg/m3 10 ppm	
Biological limit values	No biological exposure limits noted for the ingredient(s).	
Appropriate engineering controls	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.	
Individual protection measures, such as personal protective equipment		
Eye/face protection	Safety glasses. Wear face shield if there is risk of splashes.	
Skin protection		
Hand protection	Thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.	
Other	Normal work clothing (long sleeved shirts and long pants) is recommended. Wear 100% cotton clothing.	
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.	
Thermal hazards	During product use, there is a risk of thermal burns.	
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	
9. Physical and chemical properties		
Appearance	Brown to black in color.	
Physical state	Liquid.	
Form	Semi-solid at ambient temperature	
Color	Black.	
Odor	Tar-like	
Odor threshold	Not available.	
pH	Not available.	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	> 700 °F (> 371.11 °C)	
Flash point	> 446.0 °F (> 230.0 °C) Open Cup	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	< 1 mm Hg at 70°F	
Vapor density	> 5	
Relative density	0.96 - 1.06	
Solubility(ies)		
Solubility (water)	Insoluble	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	> 700 °F (> 371.11 °C)	
Decomposition temperature	Not available.	

Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable under normal temperature conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Do not overheat product.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Molten material will produce thermal burns.

Eye contact Molten material will produce thermal burns.

Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Not available.

Serious eye damage/eye irritation Not available.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Not available.

Germ cell mutagenicity Not available.

Carcinogenicity IARC: occupational exposures to straight-run bitumens and their emissions during road paving are "possibly carcinogenic to humans" (Group 2B). Contains polycyclic aromatic compounds (PACs). Prolonged and/or repeated skin contact with certain PACs has been shown to cause skin cancer. Prolonged and/or repeated exposures by inhalation of certain PACs may also cause cancer of the lung and of other sites of the body.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity Not available.

Specific target organ toxicity - single exposure Not available.

Specific target organ toxicity - repeated exposure Not available.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity This product has no known eco-toxicological effects.

Product	Species		Test Results
SPG 73-25			
Aquatic			
Fish	LC50	Fish	58.589 mg/l, 96 hours estimated
Components	Species		Test Results
HYDROGEN SULFIDE (CAS 7783-06-4)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	0.009 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Allow molten resin to solidify before disposal. Dispose in accordance with all applicable regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Hazardous waste code Not applicable.

Waste from residues / unused products Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging No special precautions.

14. Transport information

DOT

UN number	UN3257
UN proper shipping name	Elevated temperature liquid, n.o.s., at or above 100 C and below its flash point (including molten metals, molten salts, etc.)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Special precautions for user	Not available.
Special provisions	IB1, T3, TP3, TP29
Packaging exceptions	None
Packaging non bulk	None
Packaging bulk	247

IATA

UN number	UN3257
UN proper shipping name	Elevated temperature liquid, n.o.s. at or above 100°C and below its flash point (including molten metals, molten salts, etc.)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	9L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Forbidden
Cargo aircraft only	Forbidden

IMDG

UN number	UN3257
------------------	--------

UN proper shipping name ELEVATED TEMPERATURE LIQUID, N.O.S. at or above 100°C and below its flashpoint (including molten metals, molten salts, etc.)

Transport hazard class(es)

Class 9

Subsidiary risk -

Packing group III

Environmental hazards


Marine pollutant No.

EmS F-A, S-P

Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

DOT; IATA; IMDG



15. Regulatory information

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
HYDROGEN SULFIDE	7783-06-4	100	500		

SARA 311/312 No

Hazardous chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-03-2018
Version #	01
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 2 Flammability: 1 Instability: 0 Special hazards: -W-

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.