SAFETY DATA SHEET



1. Identification

Product identifier LMCQS-1H (C-450)

Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information
Manufacturer: Ergon Asphalt & Emulsions, Ir

Manufacturer:Ergon Asphalt & Emulsions, Inc.Address:2829 Lakeland Drive

Jackson, MS 39232

Website: www.ergonasphalt.com

Telephone: 1-800-222-7122 (Customer Service)

E-mail: sds@ergon.com

24 hour Emergency

(CHEMTREC):

North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

Molten asphalt presents a thermal hazard.

Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN

SULFIDE (H2S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	50 - 70
HYDROCHLORIC ACID		7647-01-0	< 2

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of

asphalt. Wash contact areas with soap and water. If needed, seek medical attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Material name: LMCQS-1H (C-450)

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately.

Most important

symptoms/effects, acute and delaved

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed:

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

water spray.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze.

SDS US 6759 Version #: 01 Issue date: 10-23-2019

Material name: LMCQS-1H (C-450)

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	7 mg/m3

5 ppm

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
HYDROCHLORIC ACID (CAS	Ceiling	2 ppm	

7647-01-0)

US. NIOSH: Pocket Guide to Chemical Hazards Form Components **Type** Value ASPHALT (CAS 8052-42-4) 5 mg/m3 Ceiling Fume. HYDROCHLORIC ACID (CAS 7 mg/m3 Ceiling 7647-01-0) 5 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined Appropriate engineering occupational exposure limit is not exceeded. controls

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged

vapor contact. Plastic or rubber gloves, apron and boots.

When workers are facing concentrations above the exposure limit they must use appropriate Respiratory protection

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and considerations before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Not available. Not available. Color Odor Not available. **Odor threshold** Not available. Not available.

Melting point/freezing point -173.6 °F (-114.22 °C) estimated

Initial boiling point and

boiling range

>= 212 °F (>= 100 °C)

Flash point > 212.0 °F (> 100.0 °C)

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Material name: LMCQS-1H (C-450) SDS US 6759 Version #: 01 Issue date: 10-23-2019

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure 0.00001 hPa estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water)Not available.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature 905 °F (485 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Specific gravity 1.02

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable under normal temperature conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat

product.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or

products low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact May be irritating to eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components Species Test Results

HYDROCHLORIC ACID (CAS 7647-01-0)

Acute Dermal

LD50 Mouse 1449 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

May be irritating to eyes.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization Prolonged skin contact may cause temporary irritation.

Germ cell mutagenicity Not available.

Material name: LMCQS-1H (C-450)

6759 Version #: 01 Issue date: 10-23-2019

4 / 7

Carcinogenicity

Risk of cancer cannot be excluded with prolonged exposure. IARC: occupational exposures to straight-run bitumens and their emissions during road paving are "possibly carcinogenic to

humans" (Group 2B).

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

HYDROCHLORIC ACID (CAS 7647-01-0) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Not available. Reproductive toxicity Specific target organ toxicity Not available.

single exposure

Not available.

Specific target organ toxicity - repeated exposure

Aspiration hazard Not available.

Chronic effects Prolonged exposure may cause chronic effects.

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity

Product		Species	Test Results
LMCQS-1H (C-450)			
Aquatic			
Fish	LC50	Fish	25538.125 mg/l, 96 hours estimated
Components		Species	Test Results

HYDROCHLORIC ACID (CAS 7647-01-0)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 282 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential Not available. Mobility in soil Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations. No components are identified as hazardous wastes.

Disposal recommendations are based on uncontaminated material.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company. Not applicable.

Waste from residues /

unused products residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions). Avoid discharge into water courses or onto the ground.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

Material name: LMCQS-1H (C-450) 5/7

6759 Version #: 01 Issue date: 10-23-2019

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US federal regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed. HYDROCHLORIC ACID (CAS 7647-01-0) Listed.

SARA 304 Emergency release notification

HYDROCHLORIC ACID (CAS 7647-01-0) 5000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
--------------------------	------------------------------	--------------------------------------	--	--

500

HYDROCHLORIC ACID 7647-01-0 5000

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
HYDROCHLORIC ACID	7647-01-0	< 2	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

HYDROCHLORIC ACID (CAS 7647-01-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

HYDROCHLORIC ACID (CAS 7647-01-0)

Safe Drinking Water Act Not regulated. (SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

HYDROCHLORIC ACID (CAS 7647-01-0) 20 %WV

DEA Exempt Chemical Mixtures Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

US state regulations

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)

HYDROCHLORIC ACID (CAS 7647-01-0)

Material name: LMCQS-1H (C-450)

International Inventories

Philippines

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

On inventory (yes/no)*

Yes

(PICCS)

Inventory name

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes

Philippine Inventory of Chemicals and Chemical Substances

16. Other information, including date of preparation or last revision

Issue date 10-23-2019

Version # 01

NFPA ratings Health: 2

Flammability: 1 Instability: 0

Disclaimer Not available.

Material name: LMCQS-1H (C-450) SDS US 7/7

6759 Version #: 01 Issue date: 10-23-2019

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).