SAFETY DATA SHEET



1. Identification

Product identifier MC-800 Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information Manufacturer: Ergon Asphalt & Emulsions, Inc.

Address: 2829 Lakeland Drive

Jackson, MS 39232

Website: www.ergonasphalt.com

Telephone: 1-800-222-7122 (Customer Service)

E-mail: sds@ergon.com

24 hour Emergency

(CHEMTREC):

North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Category 1B Carcinogenicity

> Reproductive toxicity Category 2 Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word

Hazard statement May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to

organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective

gloves/protective clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention. Response

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Heated product will cause thermal burns.

Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN

SULFIDE (H2S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	70 - 90
FUEL OIL, NO. 6		68553-00-4	1 - 20

Material name: MC-800 SDS US 1/8 5267 Version #: 03 Revision date: 02-05-2024 Issue date: 08-05-2014

Chemical nameCommon name and synonymsCAS number%Petroleum Distilled Fuel68476-34-61 - 20Other components below reportable levels0.14

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. Get medical attention, if needed. Call a physician if symptoms develop or persist.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes

before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present,

DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops

and persists

Ingestion Rinse mouth. Do not induce vomiting. Do not use mouth-to-mouth method if victim ingested the

substance. Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms/effects, acute and delayed

not available.

Indication of immediate medical attention and special treatment needed

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the

fire may cause frothing.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Fire or high temperatures create: Development of hazardous combustion gases or vapours possible in the event of fire.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear full protective clothing including self contained breathing apparatus. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and water sources. Dike for water control.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. Do not touch or walk through spilled material.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far ahead of spill for later disposal. Following product recovery, flush area with water.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Runoff or release to sewer, waterway or ground is forbidden.

7. Handling and storage

Precautions for safe handling [

Do not use in areas without adequate ventilation. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Material name: MC-800 SDS US 2024 January date: 00.05.2014 2024 January date: 00.05.2014

5267 Version #: 03 Revision date: 02-05-2024 Issue date: 08-05-2014

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep the container tightly closed and dry. Store in a closed container away from incompatible materials. Keep out of the reach of children.

8. Exposure controls/personal protection

Occupational exposure limits

116	ACCTU	Throch	ald Limi	t Values	/TI \/\
us.	ALGIN	111111111111111111111111111111111111111)ICI EIIIII	ı vanues	

Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
Petroleum Distilled Fuel (CAS 68476-34-6)	TWA	100 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to Che Components	emical Hazards Recommende Type	ed Exposure Limits (REL) Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.

Biological limit values

ACGTH	Riological	Exposure	Indicas	(RFT)
ACGIN	DIOIOUICAI	EXDOSUFE	muices	(DEI)

Components	Value (222)	Determinant	Specimen	Sampling Time	
ASPHALT (CAS 8052-42-4)	2.5 μg/l	1-Hydroxypyren e, with hydrolysis (1-HP)	Urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

Petroleum Distilled Fuel (CAS 68476-34-6) Danger of cutaneous absorption

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eve/face protection Safety glasses. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand protection Use gloves with long sleeves. When handling hot material, use heat resistant gloves.

Other Thermally protective apron and long sleeves are recommended when volume of hot material is

significant.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards During product use, there is a risk of thermal burns. Wear appropriate thermal protective clothing,

when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment

to remove contaminants.

9. Physical and chemical properties

Appearance Brown to black in color.

Physical state Liquid. **Form** Liquid. Color Brown - black

Odor Aromatic Mild Petroleum Odor

Odor threshold Not available. pН Not available. Melting point/freezing point Not available.

Initial boiling point and

boiling range

> 320 - < 550 °F (> 160 - < 287.78 °C)

Flash point >150.0 °F (>65.6 °C)

Evaporation rate

Flammability (solid, gas) Not available.

Material name: MC-800 SDS US 3/8 5267 Version #: 03 Revision date: 02-05-2024 Issue date: 08-05-2014

Upper/lower flammability or explosive limits

0.3 %

Explosive limit - lower

(%)

Explosive limit - upper 5 %

(%)

Vapor pressure <50 psi Vapor density >4.5

Not available. Relative density

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

490 °F (254.44 °C) Auto-ignition temperature

Decomposition temperature Not available. Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Risk of ignition. Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or

low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact May be irritating to the skin. Eye contact May be irritating to eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Not available.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
------------	---------	--------------

ASPHALT (CAS 8052-42-4)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not available. Skin sensitization Irritating to skin.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Material name: MC-800 SDS US 4/8

5267 Version #: 03 Revision date: 02-05-2024 Issue date: 08-05-2014

^{*} Estimates for product may be based on additional component data not shown.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans. FUEL OIL, NO. 6 (CAS 68553-00-4) 2B Possibly carcinogenic to humans.

Petroleum Distilled Fuel (CAS 68476-34-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

ASPHALT (CAS 8052-42-4) Known To Be Human Carcinogen.

Suspected of damaging fertility or the unborn child. Reproductive toxicity

Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

- repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. May cause eczema-like skin disorders (dermatitis).

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product			Species	Test Results	
ſ	MC-800				
	Aquatic				
	Fish	LC50	Fish	41.8493 mg/l, 96 hours	
	Acute				
	Fish	LC50	Fish	41.8493 mg/l, 96 hours estimated	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this substance.

Bioaccumulative potential Not available. Mobility in soil Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Disposal recommendations are based on material as supplied. Disposal must be in accordance

with current applicable laws and regulations, and material characteristics at time of disposal.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

14. Transport information

DOT

UN1999 **UN number UN proper shipping name** Tars, liquid

Transport hazard class(es) Class

3 **Subsidiary hazard** Packing group IIII

Environmental hazards

Marine pollutant No.

Special precautions for Not assigned.

user

IATA

UN1999 **UN number UN proper shipping name** Tars, liquid

Material name: MC-800 SDS US 5267 Version #: 03 Revision date: 02-05-2024 Issue date: 08-05-2014

5/8

Transport hazard class(es)

Class 3 **Subsidiary hazard Packing group** III **Environmental hazards** No. **ERG Code** 3L

Special precautions for

user

Not assigned.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN1999 **UN** number **UN proper shipping name** Tars, liquid Transport hazard class(es)

Class 3 **Subsidiary hazard Packing group** III**Environmental hazards**

Marine pollutant No. F-E, S-E **EmS Special precautions for** Not assigned.

Transport in bulk according to Not available. Annex II of MARPOL 73/78

and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

One or more components are not listed on TSCA.

CERCLA/SARA Hazardous Substances - Not applicable.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

Material name: MC-800 SDS US 6/8

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Carcinogenicity categories Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ASPHALT (CAS 8052-42-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)

FUEL OIL, NO. 6 (CAS 68553-00-4)

Petroleum Distilled Fuel (CAS 68476-34-6)

California Proposition 65

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Listed: October 1, 1990 FUEL OIL, NO. 6 (CAS 68553-00-4)

International Inventories

Country(s) or region	Inventory name O	n inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
SEA HAZ HET DE LE LE LE HE		

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 08-05-2014 **Revision date** 02-05-2024

Version # 03

Further information HMIS® is a registered trade and service mark of the NPCA.

Material name: MC-800 SDS US 7/8

5267 Version #: 03 Revision date: 02-05-2024 Issue date: 08-05-2014

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings Health: 2

Flammability: 1 Instability: 0

References ACGIH

EPA: AOUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic

Materials)

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any

other materials or in any process, unless specified in the text.

Revision information Hazard(s) identification: Response

Physical & Chemical Properties: Multiple Properties Regulatory information: US federal regulations

GHS: Classification

 Material name: MC-800
 SDS US

 5267
 Version #: 03
 Revision date: 02-05-2024
 Issue date: 08-05-2014
 8 / 8