

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name or designation of the mixture	HyVolt NG
Registration number	01-2119480375-34
Synonyms	HyVolt I NG HP SA
Issue date	12-April-2013
Version number	04
Revision date	08-March-2016
Supersedes date	03-February-2016

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Transformer Oil
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Manufacturer:	Ergon Refining, Inc. 2611 Haining Rd Vicksburg, Mississippi 39181
EU Contact:	sds@ergon.com Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone Numbers:

Ergon Refining, Inc.:	+ 1.601.638.4960 Normal Business Hours
Chemtrec:	+ 1.800.424.9300 After Business Hours (North America) + 1.703.527.3887 (International)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This substance does not meet the criteria for classification according to Directive 67/548/EEC as amended.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards	Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.
-----------------------	-------------------	------------	--

Hazard summary

Physical hazards	Not classified for physical hazards.
Health hazards	Occupational exposure to the substance or mixture may cause adverse health effects.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	Harmful by inhalation. Do not breathe dust/fume/gas/mist/vapors/spray.
Main symptoms	Respiratory disorder.

2.2. Label elements**Label according to Regulation (EC) No. 1272/2008 as amended**

Contains:	Distillates (petroleum), hydrotreated light naphthenic, Distillates (petroleum), hydrotreated light paraffinic, DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC, DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC, Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based, Solvent naphtha (petroleum), heavy arom.
------------------	--

Hazard pictograms

Signal word	Danger
--------------------	--------

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements**Prevention**

Do not breathe gas/mist/vapours/spray.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P331 Do NOT induce vomiting.

Storage

P405 Store locked up.

Disposal

P501 See section 13 of this SDS for disposal instructions.
Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Supplemental label information

None.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Distillates (petroleum), hydrotreated light naphthenic Classification: DSD: - CLP: Asp. Tox. 1;H304	50 - 100	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	L
Distillates (petroleum), hydrotreated light paraffinic Classification: DSD: - CLP: -	0 - 50	64742-55-8 265-158-7	-	649-468-00-3	L
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based Classification: DSD: - CLP: -	0 - 50	72623-86-0 276-737-9	-	649-482-00-X	L
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC Classification: DSD: - CLP: -	0 - 10	64741-96-4 265-097-6	01-2119483621-38	649-457-00-3	L
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC Classification: DSD: - CLP: -	0 - 10	64741-89-5 265-091-3	-	649-455-00-2	L
Solvent naphtha (petroleum), heavy arom. Classification: DSD: Xn;R65 CLP: Asp. Tox. 1;H304	0 - 5	64742-94-5 265-198-5	-	649-424-00-3	

67/548: Directive 67/548/EEC.
CLP: Regulation No. 1272/2008.
#: This substance has workplace exposure limit(s).
PBT: persistent, bioaccumulative and toxic substance.
vPvB: very persistent and very bioaccumulative substance.

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both acute and delayed Defatting of the skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media Halon. Dry chemicals. Foam. Carbon dioxide (CO₂). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting procedures Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Material	Type	Value
HyVolt NG (CAS Mixture)	TWA	5 mg/m3
Components	Type	Value
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	5 mg/m3
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3

Czech Republic. OELs. Government Decree 361

Material	Type	Value	
HyVolt NG (CAS Mixture)	Ceiling	1000 mg/m3	
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1000 mg/m3	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA Ceiling	200 mg/m3 10 mg/m3	Aerosol
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA Ceiling	5 mg/m3 10 mg/m3	Aerosol Aerosol
Solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA Ceiling	5 mg/m3 1000 mg/m3	Aerosol
	TWA	200 mg/m3	

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TLV	1 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TLV	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TLV	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TLV	1 mg/m3	Mist.

Finland. Workplace Exposure Limits

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Solvent naphtha (petroleum), heavy arom. (CAS 64742-94-5)	TWA	100 mg/m3	

Greece. OELs (Decree No. 90/1999, as amended)

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TWA	5 mg/m3	Mist.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Mist.

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	Ceiling	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Ceiling	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	Ceiling	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	Ceiling	5 mg/m3	Mist.

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TWA	1 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	1 mg/m3	Mist.

Ireland. Occupational Exposure Limits

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TWA	0,2 mg/m3	Inhalable fraction.

Ireland. Occupational Exposure Limits

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Inhalable fraction.

Italy. Occupational Exposure Limits

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TWA	5 mg/m3	Inhalable fraction.
Components	Type	Value	Form
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Inhalable fraction.

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	STEL	3 mg/m3	Fume and mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	1 mg/m3	Fume and mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	3 mg/m3	Fume and mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	1 mg/m3	Fume and mist.
	STEL	3 mg/m3	Fume and mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	1 mg/m3	Fume and mist.
	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.

Netherlands. OELs (binding)

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.

Netherlands. OELs (binding)

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Mist.

Norway. Administrative Norms for Contaminants in the Workplace

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	TLV	1 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TLV	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TLV	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TLV	1 mg/m3	Mist.

Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	STEL	10 mg/m3	Aerosol
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Aerosol
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Aerosol
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	TWA	5 mg/m3	Aerosol
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Material	Type	Value	
HyVolt NG (CAS Mixture)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Components	Type	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	
	TWA	5 mg/m3	
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	STEL	10 mg/m3	
	TWA	5 mg/m3	
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	3 mg/m3	Fume and mist.
	TWA	15 ppm	Fume and mist.
		1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.

Spain. Occupational Exposure Limits

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Sweden. Occupational Exposure Limit Values

Material	Type	Value	Form
HyVolt NG (CAS Mixture)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Not available.

Derived no-effect level (DNEL)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information	Wear suitable protective equipment.
Eye/face protection	Goggles/face shield are recommended.
Skin protection	
- Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.
- Other	Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.
Respiratory protection	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN14387.
Thermal hazards	Not available.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental exposure controls	Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear & bright
Physical state	Liquid.
Form	Liquid.
Colour	Water White
Odour	Mild Petroleum Odor
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	<= -20 °C (<= -4 °F) ASTM D5950
Initial boiling point and boiling range	>= 232 °C (>= 449,6 °F)
Flash point	>= 140,0 °C (>= 284,0 °F) Pensky-Martens Closed Cup ASTM D93
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0,88 ASTM D1298
Relative density temperature	20 °C (68 °F)
Solubility(ies)	
Solubility (water)	Not available.
Solubility (other)	Not available.
Partition coefficient (n-octanol/water)	Not established.
Auto-ignition temperature	>= 315 °C (>= 599 °F)
Decomposition temperature	Not available.
Viscosity	<= 11 mm ² /s (40 °C (104 °F) ASTM D445)
Explosive properties	Not available.
Oxidizing properties	Not available.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidising agents.
10.2. Chemical stability Stable.
10.3. Possibility of hazardous reactions Hazardous polymerisation does not occur.
10.4. Conditions to avoid Avoid temperatures exceeding the flash point.
10.5. Incompatible materials Strong oxidising agents.
10.6. Hazardous decomposition products Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available.

Information on likely routes of exposure

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration. May be fatal if swallowed and enters airways.
Inhalation May be fatal if swallowed and enters airways.
Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact May be irritating to eyes.

Symptoms Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest.

11.1. Information on toxicological effects

Acute toxicity Not applicable.
Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.
Serious eye damage/eye irritation Not classified. May cause minor irritation on eye contact.
Respiratory sensitisation Not classified.
Skin sensitisation Not classified. May cause defatting of the skin, but is not an irritant.
Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Nota L - Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.
Reproductive toxicity Contains no ingredient listed as toxic to reproduction
Specific target organ toxicity - single exposure Not classified.
Specific target organ toxicity - repeated exposure Not classified.
Aspiration hazard May be fatal if swallowed and enters airways.
Mixture versus substance information Not available.
Other information Risk of chemical pneumonia after aspiration.

SECTION 12: Ecological information

12.1. Toxicity Not expected to be harmful to aquatic organisms.
12.2. Persistence and degradability Not inherently biodegradable.
12.3. Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
Partition coefficient n-octanol/water (log Kow) Not established.
Bioconcentration factor (BCF) Not available.
12.4. Mobility in soil Not available.
12.5. Results of PBT and vPvB assessment Not applicable.
12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.
EU waste code	Not applicable. Waste codes should be assigned by the user based on the application for which the product was used.
Disposal methods/information	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

General Not regulated as dangerous goods.

ADR

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

ADN

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex II

Not listed.

Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, Article 59(1). Candidate List

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use

Not regulated.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Not listed.

Other EU regulations**Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances**

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Not listed.

Directive 94/33/EC on the protection of young people at work

Not listed.

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

National regulations

Germany: WGK 1

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

List of abbreviations

Not available.

References

ACGIH
 IARC Monographs. Overall Evaluation of Carcinogenicity
 ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
 Chemical Abstracts Service Registry Handbook
 CRC; Handbook of Chemistry and Physics
 ILO Safety Cards
 International Labour Organization
 International Maritime Organization Marine Pollutants List
 NFPA Hazardous Chemical Data Sheets
 NIOSH Pocket Guide
 Registry of Toxic Effects of Chemical Substances (RTECS)
 US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15

H304 May be fatal if swallowed and enters airways.

Revision information

Training information

Disclaimer

Physical & Chemical Properties: Multiple Properties

Not available.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.