ERGONE

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyGold 60

Identification number 649-466-00-2 (Index number)

Registration number 01-2119480375-34

Synonyms None.

Issue date 18-July-2018

Version number 02

Revision date 27-March-2019 Supersedes date 18-July-2018

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Metalworking Fluids, Industrial Lubricants, Grease Manufacturing, Hydraulic Oils, Gear Oils, Heavy

Duty Engine Oil, Bar & Chain, Carriers & Diluents, Engine Oil.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

> Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

Chemtrec: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International)

See Section 15 for additional CHEMTREC Hotline Numbers

E-mail: sds@ergon.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Aspiration hazard H304 - May be fatal if swallowed Category 1

and enters airways.

Hazard summary May be fatal if swallowed and enters airways.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Distillates (petroleum), hydrotreated light naphthenic

Hazard pictograms

Signal word Danger

Hazard statements

May be fatal if swallowed and enters airways. H304

Precautionary statements

Prevention

Material name: HyGold 60 - Ergon International

Do not breathe gas/fumes/vapour/spray. P260

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

Do NOT induce vomiting. P331

Storage

Store locked up. P405

Disposal

See section 13 of this SDS for disposal instructions.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

Supplemental label

information

None.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated light naphthenic	100	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	
Classification: Asp. Tox. 1;	H304				

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Flush thoroughly with water. If irritation occurs, get medical assistance. **Eye contact**

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any immediate medical attention and special treatment

needed

Treat symptomatically.

Defatting of the skin.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting

procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a

fire.

SDS FU 4728 Version #: 02 Revision date: 27-March-2019 Issue date: 18-July-2018

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch

damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

64742-53-6)

Occupational exposure limits

Belgium. Exposure Limit Values.

Material	Туре	Value	Form	
HyGold 60	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Material	туре	value	
HyGold 60	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS	TWA	5 mg/m3	

Czech Republic. OELs. Government Decree 361

Material	Туре	Value
HyGold 60	Ceiling	1000 mg/m3
	TWA	200 mg/m3

4728 Version #: 02 Revision date: 27-March-2019 Issue date: 18-July-2018

Material name: HyGold 60 - Ergon International

Components	Туре	Value	
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
Denmark. Exposure Limit Value			_
Material	Туре	Value	Form
HyGold 60	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TLV	1 mg/m3	Mist.
Finland. Workplace Exposure Li Material	mits Type	Value	Form
HyGold 60	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum),	TWA	5 mg/m3	Mist.
hydrotreated light naphthenic (CAS 64742-53-6)	TWA	3 mg/m3	Plist.
Germany. DFG MAK List (adviso Compounds in the Work Area (l		Investigation of Health H	azards of Chemical
Material	Туре	Value	Form
HyGold 60	TWA	5 mg/m3	Respirable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/1 Material	999, as amended) Type	Value	Form
HyGold 60	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree on Material	Chemical Safety of Workplac Type	ces Value	Form
HyGold 60	Ceiling	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	5 mg/m3	Mist.
Iceland. OELs. Regulation 154/ Material	1999 on occupational exposu Type	re limits Value	Form
HyGold 60	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS	TWA	1 mg/m3	Mist.

Material name: HyGold 60 - Ergon International

SDS EU 4728 Version #: 02 Revision date: 27-March-2019 Issue date: 18-July-2018

Material	Туре	Value	Form
HyGold 60	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Italy. Occupational Exposure Limit Material	s Type	Value	Form
HyGold 60	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Latvia. OELs. Occupational exposu Material	re limit values of chemica Type	l substances in work enviro Value	onment
HyGold 60	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	
Lithuania. OELs. Limit Values for C Material	Chemical Substances, Gen Type	eral Requirements Value	Form
HyGold 60	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding) Material	Туре	Value	Form
HyGold 60	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms for Material	Contaminants in the Wor Type	kplace Value	Form
HyGold 60	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.

Material name: HyGold 60 - Ergon International

4728 Version #: 02 Revision date: 27-March-2019 Issue date: 18-July-2018 5 /

and intensities of harmful health facto Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Portugal. VLEs. Norm on occupational o Material	exposure to chemical a Type	gents (NP 1796) Value	Form
HyGold 60	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Romania. OELs. Protection of workers Material	from exposure to chem Type	ical agents at the workpl Value	ace
HyGold 60	STEL	10 mg/m3	
	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Slovakia. OELs. Regulation No. 300/20 Material	07 concerning protecti Type	on of health in work with Value	chemical agents Form
HyGold 60	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
Spain. Occupational Exposure Limits			
Material	Туре	Value	Form
HyGold 60	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
•	TWA	5 mg/m3	Mist.
Sweden. OELs. Work Environment Autl	hority (AV), Occupation	al Exposure Limit Values	(AFS 2015:7)
Material	Туре	Value	Form
HyGold 60	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Mist.
,	TWA	1 mg/m3	Mist.

Material name: HyGold 60 - Ergon International

SDS EU 6 / 11 Switzerland. SUVA Grenzwerte am Arbeitsplatz **Material Value** Form Inhalable fraction. HyGold 60 TWA 5 ma/m3 **Value Form** Components **Type** Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. hydrotreated light naphthenic (CAS 64742-53-6)

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Not available.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information Not available.

Eye/face protection

Goggles/face shield are recommended.

Skin protection
- Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

gloves may be suitable.

- **Other** Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection

Under normal conditions, respirator is not normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)]

meeting EN14387.

Thermal hazards Not available.

Hygiene measuresAlways observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear & bright

Physical stateLiquid.FormLiquid.

Colour colorless to slight yellow tint

Odour Mild Petroleum Odor

Odour threshold Not available.

pH Not applicable

Melting point/freezing point
Initial boiling point and

Initial boiling point and boiling range

-63 °C (-81,4 °F) ASTM D5950/ISO 3016 284 °C (543,2 °F) ASTM D86/ ISO 3294

Flash point 143,0 °C (289,4 °F) Pensky-Martens Closed Cup ASTM D93/ ISO 2719

153,0 °C (307,4 °F) Cleveland open cup ASTM D92/ ISO 2592

Evaporation rate Not available.

Material name: HyGold 60 - Ergon International

4728 Version #: 02 Revision date: 27-March-2019 Issue date: 18-July-2018 7 / 1

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Not available. Vapour pressure

Vapour density > 5

Relative density 0,885 (15,56 °C (60 °F) ASTM D4052/ ISO 12185)

Solubility(ies)

Solubility (water) Insoluble

Not established. **Partition coefficient**

(n-octanol/water)

> 315,56 °C (> 600 °F) ASTM E659 **Auto-ignition temperature**

Decomposition temperature Not available.

Viscosity 9,34 cSt (40 °C (104 °F) ASTM D445/ISO 3104)

Explosive properties Not available. **Oxidising properties** Not available.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

Strong oxidising agents. 10.1. Reactivity

10.2. Chemical stability Stable.

10.3. Possibility of hazardous Hazardous polymerisation does not occur.

reactions

10.4. Conditions to avoid Avoid temperatures exceeding the flash point.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

decomposition products weight hydrocarbons.

SECTION 11: Toxicological information

Not available. **General information**

Information on likely routes of exposure Inhalation May be fatal if swallowed and enters airways.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration. May be fatal if swallowed and enters airways.

Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest. Symptoms

11.1. Information on toxicological effects

Acute toxicity Not applicable.

May cause defatting of the skin, but is neither an irritant nor a sensitizer. Skin corrosion/irritation

Serious eye damage/eye

irritation

Not classified. May cause minor irritation on eye contact.

Respiratory sensitisation Not classified.

Skin sensitisation Not classified. May cause defatting of the skin, but is not an irritant.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Nota L - Meets

EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Contains no ingredient listed as toxic to reproduction Reproductive toxicity

Specific target organ toxicity

- single exposure

Not classified.

4728 Version #: 02 Revision date: 27-March-2019 Issue date: 18-July-2018

Specific target organ toxicity

- repeated exposure

Aspiration hazard

May be fatal if swallowed and enters airways.

Mixture versus substance

information

Not available.

Not classified.

Other information Risk of chemical pneumonia after aspiration.

SECTION 12: Ecological information

Not expected to be harmful to aquatic organisms. 12.1. Toxicity

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient

n-octanol/water (log Kow)

Not established.

Bioconcentration factor (BCF) Not available 12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

Not applicable. Waste codes should be assigned by the user based on the application for which the EU waste code

product was used.

Disposal recommendations are based on material as supplied. Disposal must be in accordance with Disposal

methods/information current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

according to Annex II of MARPOL 73/78 and the IBC

14.7. Transport in bulk

Code

General information Not regulated as dangerous goods.

Not available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Material name: HyGold 60 - Ergon International SDS FU Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Germany: WGK 1

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

International Inventories Country(c) or region

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

SECTION 16: Other information

List of abbreviations Not available.

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

References ACGIH

IARC Monographs. Overall Evaluation of Carcinogenicity

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements

not written out in full under Sections 2 to 15

H304 May be fatal if swallowed and enters airways.

Sections 2 to 15
Revision information

SECTION 2: Hazards identification: Hazard statements Physical & Chemical Properties: Multiple Properties

HazReg Data: International Inventories

Training information

Disclaimer

Not available.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Further information

Local CHEMTREC Numbers: CHEMTREC China: 4001-204937

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349

Material name: HyGold 60 - Ergon International

4728 Version #: 02 Revision date: 27-March-2019 Issue date: 18-July-2018 11 / 3