ERGONE

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyPrint 500

Identification number 649-465-00-7 (Index number)

Registration number 01-2119467170-45

Synonyms None.

Issue date 19-April-2018

Version number 02

Revision date 05-April-2019 Supersedes date 19-April-2018

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pigments; Printing Inks

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

> Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

Chemtrec: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International)

See Section 15 for additional CHEMTREC Hotline Numbers

E-mail: sds@ergon.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary Not available.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.

Signal word Not applicable. **Hazard statements** Not applicable.

Precautionary statements

Prevention Not applicable. Response Not applicable. Storage Not applicable. Not applicable. Disposal

Supplemental label

information

None.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

Material name: HyPrint 500 - Ergon International

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), heavy naphthenic	nydrotreated	100	64742-52-5 265-155-0	01-2119467170-45	649-465-00-7	
Classification:	Carc. 1B;H350					L

List of abbreviations and symbols that may be used above

67/548: Directive 67/548/EEC. CLP: Regulation No. 1272/2008.

#: This substance has workplace exposure limit(s). PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

Composition comments

A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces finished oil with a viscosity near 500 SUS at 100°F.

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Defatting of the skin.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

5.1. Extinguishing media

Suitable extinguishing

media

extinguisher, as this will spread the fire.

Unsuitable extinguishing

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or

mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an

Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Material name: HyPrint 500 - Ergon International

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

5 mg/m3

Mist.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.					
Material	Туре	Value	Form		
HyPrint 500	STEL	10 mg/m3	Mist.		
	TWA	5 mg/m3	Mist.		
Components	Туре	Value	Form		
Distillates (petroleum), hydrotreated heavy naphthenic (CAS	STEL	10 mg/m3	Mist.		

Bulgaria. OELs. Regulation	No 13 on protection of work	ers against risks of exposure to chemical agents at work
Material	Tyne	Value

TWA

масела	туре	value	
HyPrint 500	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	

Denmark. Exposure Limit Values

Material	Туре	Value	Form	
HyPrint 500	TLV	1 mg/m3	Mist.	
Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy	TLV	1 mg/m3	Mist.	

Finland, Workplace Exposure Limits

64742-52-5)

Components	Type	Value	Form	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.	

Material name: HyPrint 500 - Ergon International

Material	Туре	Value	Form
HyPrint 500	TWA	5 mg/m3	Respirable fraction
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Respirable fraction
Greece. OELs (Decree No. 90/1999, as a Material	amended) Type	Value	Form
HyPrint 500	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree on Chemic Material	al Safety of Workplaces Type	Value	Form
HyPrint 500	Ceiling	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	5 mg/m3	Mist.
Iceland. OELs. Regulation 154/1999 on Material	occupational exposure limits Type	Value	Form
HyPrint 500	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	1 mg/m3	Mist.
Ireland. Occupational Exposure Limits Material	Туре	Value	Form
HyPrint 500	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Italy. Occupational Exposure Limits Material	Туре	Value	Form
HyPrint 500	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
	ical Substances General Poquir	ements	
Lithuania. OELs. Limit Values for Chem Material	Type	Value	Form
			Form Fume and mist.

Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding)	_		_
Material	Туре	Value	Form
HyPrint 500	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms Material	for Contaminants in the Wor Type	kplace Value	Form
HyPrint 500	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
Ordinance of the Minister of Lal and intensities of harmful healt Material			
HyPrint 500	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Components			
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa	TWA ational exposure to chemical	5 mg/m3 agents (NP 1796)	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA ational exposure to chemical Type	5 mg/m3 agents (NP 1796) Value	Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa	TWA ational exposure to chemical Type TWA	5 mg/m3 agents (NP 1796) Value 5 mg/m3	Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material	TWA ational exposure to chemical Type	5 mg/m3 agents (NP 1796) Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA Pational exposure to chemical Type TWA Type TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w	TWA Pational exposure to chemical Type TWA Type TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA ational exposure to chemical Type TWA Type TWA TWA TWA TWA TWA TWA	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w Material	TWA Pational exposure to chemical Type TWA Type TWA TYPE TWA TWA TWA TWA TYPE TWA	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w Material	TWA ational exposure to chemical Type TWA Type TWA TWA TWA TWA TWA Sorkers from exposure to che Type STEL	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 **mical agents at the workplayed value 10 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w Material HyPrint 500	TWA Pational exposure to chemical Type TWA Type TWA Type TWA Orkers from exposure to che Type STEL TWA	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 smical agents at the workpl Value 10 mg/m3 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA Type TWA Type TWA Type TWA Type TWA Sorkers from exposure to che Type STEL TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 mical agents at the workplants Value 10 mg/m3 5 mg/m3 Value	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA ational exposure to chemical Type TWA Type TWA Type TWA Orkers from exposure to che Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 mical agents at the workple Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 Value 10 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Slovakia. OELs. Regulation No. Material	TWA Pational exposure to chemical Type TWA Type TWA Type TWA Orkers from exposure to che Type STEL TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 value 5 mg/m3 value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 value 10 mg/m3 **Transport of the selection of the selecti	Form Inhalable fraction. Form Inhalable fraction. ace chemical agents
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupa Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of w Material HyPrint 500 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Slovakia. OELs. Regulation No.	TWA ational exposure to chemical Type TWA Type TWA Type TWA orkers from exposure to che Type STEL TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 mical agents at the workpl Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 Value 10 mg/m3	Form Inhalable fraction. Form Inhalable fraction. ace chemical agents Form

Material name: HyPrint 500 - Ergon International

Material	Туре	Value	Form
		5 ppm	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.
Spain. Occupational Expo Material	sure Limits Type	Value	Form
HyPrint 500	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Sweden. OELs. Work Envi Material	ronment Authority (AV), Occupation	onal Exposure Limit Values Value	(AFS 2015:7) Form
HyPrint 500	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Switzerland. SUVA Grenz			_
Material	Туре	Value	Form
HyPrint 500	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
ogical limit values ommended monitoring cedures	No biological exposure limits noted f Not available.	or the ingredient(s).	
ved no effect levels ELs)	Not available.		
dicted no effect centrations (PNECs)	Not available.		
Exposure controls			
ropriate engineering trols	Adequate ventilation should be prov Provide adequate ventilation, includi occupational exposure limit is not ex	ng appropriate local extraction,	

Material name: HyPrint 500 - Ergon International

General information Eye/face protection

Skin protection

Not available.

Goggles/face shield are recommended.

- Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

gloves may be suitable.

- Other Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection Under normal conditions, respirator is not normally required. No respiratory protection is ordinarily

required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined

particulate/organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN14387.

Thermal hazards Not available.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear & bright

Physical stateLiquid.FormLiquid.

ColourLight Amber to GoldenOdourMild Petroleum Odor

Odour threshold Not available.

pH Not applicable

Melting point/freezing point -31 °C (-23,8 °F) ASTM D5950/ISO 3016

Initial boiling point and 323 °C (613,4 °F) ASTM D2887/ ISO 3294

boiling range

Flash point > 200,0 °C (> 392,0 °F) Cleveland open cup ASTM D92/ ISO 2592

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit -

Not available.

upper (%)

Vapour pressure Not available.

Vapour density > 5

Relative density 0,92 (15,56 °C (60 °F) ASTM D4052/ ISO 12185)

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not established.

(n-octanol/water)

Auto-ignition temperature > 315,56 °C (> 600 °F) ASTM E659

Decomposition temperature Not available.

Viscosity 101 cSt (40 °C (104 °F) ASTM D445/ ISO 3104)

Explosive propertiesNot available. **Oxidising properties**Not available.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidising agents.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Material name: HyPrint 500 - Ergon International

10.4. Conditions to avoid Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

decomposition products

weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available. Information on likely routes of exposure

Inhalation May be harmful if inhaled. However, this product does not currently meet the criteria for

classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May be irritating to eyes.

May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may Ingestion

increase risk of product aspiration.

Symptoms Not available.

11.1. Information on toxicological effects

Not classified. **Acute toxicity**

Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer. Skin corrosion/irritation

Serious eye damage/eye

irritation

Not classified.

Respiratory sensitisation Not classified Skin sensitisation Not classified.

Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU Carcinogenicity

requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified

Aspiration hazard

Mixture versus substance

Not classified. Not available.

information

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity 12.2. Persistence and

degradability

Not expected to be harmful to aquatic organisms. Not inherently biodegradable.

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow) Not established.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation 12.6. Other adverse effects potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

Material name: HyPrint 500 - Ergon International

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

EU waste codeNot applicable. Waste codes should be assigned by the user based on the application for which the

product was used.

Disposal Disposal recommendations are based on material as supplied. Disposal must be in accordance with

current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk

methods/information

Not available.

according to Annex II of MARPOL 73/78 and the IBC

Code

General information Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed

 $\label{eq:Regulation} \textbf{(EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended}$

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Material name: HyPrint 500 - Ergon International

SDS FU

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Germany: WGK 1

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: Other information

List of abbreviations Not available. References **ACGIH**

IARC Monographs, Overall Evaluation of Carcinogenicity

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under Sections 2 to 15

H350 May cause cancer.

Physical & Chemical Properties: Multiple Properties **Revision information**

Regulatory Information: United States

Training information Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: HyPrint 500 - Ergon International