ERGON E

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyPrene L750

Identification number 649-465-00-7 (Index number)

Registration number 01-2119467170-45

Synonyms None.

Issue date 26-July-2018

Version number 03

Revision date 07-May-2019 **Supersedes date** 16-October-2018

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified usesTire Oils, Rubber Compounding, Automotive & Industrial Hoses, Dedusting, Plasticizer, Titanium Dioxide Wash, Compressor Wash Oils, Hydraulic Fracturing Oil, Adhesives, Carnet Backing, Feed

Dioxide Wash, Compressor Wash Oils, Hydraulic Fracturing Oil, Adhesives, Carpet Backing, Feed Stock for White Oil, Refrigeration Oil, Diluents and Carriers, Carbon Black, Banbury Dust Stop,

Defoamers, Sealants, Belts & Hoses, Coatings, Leather Tanning, Agriculture Oils.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

Chemtrec: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International)

See Section 15 for additional CHEMTREC Hotline Numbers

E-mail: sds@ergon.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary Not available.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.

Signal wordNot applicable. **Hazard statements**Not applicable.

Precautionary statements

PreventionNot available.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Supplemental label

information

None.

2.3. Other hazards None known.

Material name: HyPrene L750 - Ergon International
5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), h heavy naphthenic	nydrotreated	100	64742-52-5 265-155-0	01-2119467170-45	649-465-00-7	
Classification:	Carc. 1B;H350					L

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Defatting of the skin.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

5.1. Extinguishing media

Suitable extinguishing

media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand

breathing apparatus, protective clothing and face mask.

Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

Material name: HyPrene L750 - Ergon International 2 / 10 5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium.	Exposure	Limit	Values.
----------	-----------------	-------	---------

Material	Туре	Value	Form
HyPrene L750	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work Material **Type** Value

	· ·		
HyPrene L750	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum),	TWA	5 mg/m3	

naphthenic (CAS 64742-52-5)

Denmark. Exposure Limit Values

Material	Туре	Value	Form	
HyPrene L750	TLV	1 mg/m3	Mist.	
Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy	TLV	1 mg/m3	Mist.	

naphthenic (CAS 64742-52-5)

Finland, Workplace Exposure Limits

Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.	

5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018

Material	Туре	Value	Form
HyPrene L750	TWA	5 mg/m3	Respirable fraction
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Respirable fraction
Greece. OELs (Decree No. 90/1999, as a Material	amended) Type	Value	Form
HyPrene L750	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree on Chemic Material	al Safety of Workplaces Type	Value	Form
HyPrene L750	Ceiling	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	5 mg/m3	Mist.
Iceland. OELs. Regulation 154/1999 on	-	Walana	Fa
Material	Туре	Value	Form
	TWA	1 mg/m3	Mist.
Material HyPrene L750 Components			
HyPrene L750	TWA	1 mg/m3	Mist.
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS	TWA Type	1 mg/m3 Value	Mist. Form
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits	TWA Type TWA	1 mg/m3 Value 1 mg/m3	Mist. Form Mist.
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits Material	TWA Type TWA Type	1 mg/m3 Value 1 mg/m3 Value	Mist. Form Mist. Form
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits Material HyPrene L750	TWA Type TWA Type TWA	1 mg/m3 Value 1 mg/m3 Value 5 mg/m3	Mist. Form Mist. Form Inhalable fraction.
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS	TWA Type TWA Type TWA Type	1 mg/m3 Value 1 mg/m3 Value 5 mg/m3 Value	Mist. Form Mist. Form Inhalable fraction. Form
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Italy. Occupational Exposure Limits Material	TWA Type TWA Type TWA Type TWA Type	1 mg/m3 Value 1 mg/m3 Value 5 mg/m3 Value 5 mg/m3	Mist. Form Mist. Form Inhalable fraction. Form Inhalable fraction.
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Italy. Occupational Exposure Limits Material HyPrene L750	TWA Type TWA Type TWA Type TWA Type TWA	1 mg/m3 Value 1 mg/m3 Value 5 mg/m3 Value 5 mg/m3 Value	Mist. Form Mist. Form Inhalable fraction. Form Inhalable fraction.
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 54742-52-5) Ireland. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 54742-52-5) Italy. Occupational Exposure Limits	TWA Type TWA Type TWA Type TWA Type TWA Type TWA	1 mg/m3 Value 1 mg/m3 Value 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3	Mist. Form Mist. Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Italy. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS Distillates (petroleum), hydrotreated heavy haphthenic (CAS	TWA Type	1 mg/m3 Value 1 mg/m3 Value 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3	Mist. Form Mist. Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. Form
HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Ireland. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Italy. Occupational Exposure Limits Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem	TWA Type	1 mg/m3 Value 1 mg/m3 Value 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3	Mist. Form Mist. Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.

Material name: HyPrene L750 - Ergon International

SDS EU 5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018

Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding)	_		F
Material	Туре	Value	Form
HyPrene L750	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms fo Material	r Contaminants in the Wor Type	kplace Value	Form
HyPrene L750	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
Ordinance of the Minister of Labo and intensities of harmful health Material			
HyPrene L750	TWA	5 mg/m3	Inhalable fraction.
•		5 ,	_
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati	TWA onal exposure to chemical	5 mg/m3 agents (NP 1796)	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material	TWA Tonal exposure to chemical Type	5 mg/m3 agents (NP 1796) Value	Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750	TWA onal exposure to chemical Type TWA	5 mg/m3 agents (NP 1796) Value 5 mg/m3	Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components	TWA Tonal exposure to chemical Type TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value	Inhalable fraction. Form Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750	TWA onal exposure to chemical Type TWA	5 mg/m3 agents (NP 1796) Value 5 mg/m3	Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor	TWA fonal exposure to chemical Type TWA Type TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor	TWA fonal exposure to chemical Type TWA Type TWA Type TWA	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor	TWA Tonal exposure to chemical Type TWA Type TWA Type TWA Twa Twa Twa Twa Twa Twa Twa Tw	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA fonal exposure to chemical Type TWA Type TWA TWA TWA TWA TWA TWA TWA TW	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 **mical agents at the workplayed value 10 mg/m3	Form Inhalable fraction. Form Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor Material HyPrene L750	TWA Tonal exposure to chemical Type TWA Type TWA Type TWA Twa Twa Twa Twa Twa Twa Type Twa Twa Twa Type Twa Twa	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 smical agents at the workpl Value 10 mg/m3 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA fonal exposure to chemical Type TWA Type TWA TYPE TWA TWA TYPE STEL TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 *mical agents at the workplay Value 10 mg/m3 5 mg/m3 Value	Form Inhalable fraction. Form Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA fonal exposure to chemical Type TWA Type TWA Type TWA Twa Twa Type STEL TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 mical agents at the workple Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 Value 10 mg/m3	Form Inhalable fraction. Form Inhalable fraction. ace
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Slovakia. OELs. Regulation No. 30	TWA Tonal exposure to chemical Type TWA Type TWA Type TWA Type STEL TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 mical agents at the workpl Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 Value 10 mg/m3	Form Inhalable fraction. Form Inhalable fraction. ace
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupati Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wor Material HyPrene L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Slovakia. OELs. Regulation No. 30 Material	TWA fonal exposure to chemical Type TWA Type TWA Type TWA Twa Type STEL TWA Type	agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 value 5 mg/m3 value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 value 10 mg/m3 **Transport of the selection of the selecti	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. ace chemical agents Form

Material name: HyPrene L750 - Ergon International

5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018 5 /

		5 ppm	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.
Spain. Occupational Expos Material	ure Limits Type	Value	Form
HyPrene L750	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Sweden. OELs. Work Envir Material	onment Authority (AV), Occupatio Type	nal Exposure Limit Values (Value	(AFS 2015:7) Form
HyPrene L750	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Switzerland. SUVA Grenzw Material	rerte am Arbeitsplatz Type	Value	Form
HyPrene L750	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
ogical limit values ommended monitoring cedures	No biological exposure limits noted for Not available.	or the ingredient(s).	
ved no effect levels ELs)	Not available.		
licted no effect centrations (PNECs)	Not available.		
Exposure controls			
ropriate engineering	Provide adequate ventilation, includir	ng appropriate local extraction,	to ensure that the defin

Material name: HyPrene L750 - Ergon International

Eye/face protection

Skin protection

5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018 6 / 10

Goggles/face shield are recommended.

- Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

gloves may be suitable.

- **Other** Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection Under normal conditions, respirator is not normally required. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Not available.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear & bright

Physical stateLiquid.FormLiquid.ColourAmber.

Odour Mild Petroleum Odor

Odour threshold Not available. pH Not available.

Melting point/freezing point -27 °C (-16,6 °F) ASTM D5949/ ISO 3016

Initial boiling point and

boiling range

320 °C (608 °F) ASTM D2887

Flash point 217,0 °C (422,6 °F) Pensky-Martens Closed Cup ASTM D93/ ISO 2592

228,0 °C (442,4 °F) Cleveland open cup ASTM D92/ ISO 2719

Evaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit -

upper (%)

Not available.

Vapour pressure Not available.

Vapour density > 5

Relative density 0,92 (15,56 °C (60 °F) ASTM D4052/ ISO 12185)

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not established.

(n-octanol/water)

Auto-ignition temperature

> 315,56 °C (> 600 °F) ASTM E659

Decomposition temperature Not available.

Viscosity 144 cSt (40 °C (104 °F) ASTM D445/ ISO 3014)

Explosive propertiesNot available. **Oxidising properties**Not available.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidising agents.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous Hazardous polymerisation does not occur.

reactions

decomposition products

10.4. Conditions to avoid Avoid temperatures exceeding the flash point.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available. Information on likely routes of exposure

Inhalation May be harmful if inhaled. However, this product does not currently meet the criteria for

classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May be irritating to eyes.

May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may Ingestion

increase risk of product aspiration.

Symptoms Not available.

11.1. Information on toxicological effects

Acute toxicity Not classified.

Skin corrosion/irritation

Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified.

Respiratory sensitisation Skin sensitisation

Not classified. Not classified.

Germ cell mutagenicity

Non-mutagenic based on Modified Ames Assay.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

Not classified.

- single exposure

Specific target organ toxicity

Not classified.

- repeated exposure

Aspiration hazard Mixture versus substance

information

Not classified. Not available.

Other information Not available.

SECTION 12: Ecological information

Not expected to be harmful to aquatic organisms. 12.1. Toxicity

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient

n-octanol/water (log Kow)

Not established.

Bioconcentration factor (BCF) Not available. Not available. 12.4. Mobility in soil

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

EU waste code Not applicable. Waste codes should be assigned by the user based on the application for which the

product was used.

Material name: HyPrene L750 - Ergon International 5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018 **Disposal** methods/information No components are identified as hazardous wastes. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC

Code

General information Not regulated as dangerous goods.

Not available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Germany: WGK 1

SDS FU 5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

SECTION 16: Other information

List of abbreviations Not available.

References Chemical Abstracts Service Registry Handbook

CRC: Handbook of Chemistry and Physics

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

IARC Monographs. Overall Evaluation of Carcinogenicity

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under

Sections 2 to 15

H350 May cause cancer.

Revision information

Physical & Chemical Properties: Multiple Properties **Training information** Not available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Local CHEMTREC Numbers: **Further information**

CHEMTREC China: 4001-204937

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349

5609 Version #: 03 Revision date: 07-May-2019 Issue date: 26-July-2018

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).