# ERGONE

## SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyPrint L151

**Identification number** 649-465-00-7 (Index number)

**Registration number** 01-2119467170-45

**Synonyms** None.

22-May-2019 **Issue date** 

**Version number** 02

**Revision date** 23-May-2019 Supersedes date 22-May-2019

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Pigments; Printing Inks

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

**MANUFACTURER:** Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

**EU Contact:** Ergon International, Inc.

> Drève Richelle 161 Building C B-1410 Waterloo, Belgium

**Emergency Phone** 

**Numbers:** 

**US Customer Service:** + 1-800-222-7122

**Chemtrec:** + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International)

See Section 15 for additional CHEMTREC Hotline Numbers

E-mail: sds@ergon.com

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008 as amended

This substance does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended

**Hazard summary** Not available.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

**Hazard pictograms** None.

Signal word Not applicable. **Hazard statements** Not applicable.

**Precautionary statements** 

**Prevention** Not available. Response Not applicable. **Storage** Not applicable. **Disposal** Not applicable.

Supplemental label

information

None.

2.3. Other hazards None known.

## **SECTION 3: Composition/information on ingredients**

3.1. Substances

Material name: HyPrint L151 - Ergon International SDS EU 5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019 1 / 10 **General information** 

| Chemical name                                    | %           | CAS-No. / EC<br>No.     | REACH Registration No. | Index No.    | Notes |
|--|-------------|-------------------------|------------------------|--------------|-------|
| Distillates (petroleum), hydrot heavy naphthenic | treated 100 | 64742-52-5<br>265-155-0 | 01-2119467170-45       | 649-465-00-7 |       |
| Classification: Car                              | c. 1B;H350  |                         |                        |              | L     |

#### **SECTION 4: First aid measures**

**General information** Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

**Eye contact** Flush thoroughly with water. If irritation occurs, get medical assistance.

**Ingestion** Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any immediate medical attention and special treatment

Treat symptomatically.

Defatting of the skin.

needed

## **SECTION 5: Firefighting measures**

**General fire hazards** No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

5.1. Extinguishing media

Suitable extinguishing

media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an

extinguisher, as this will spread the fire.

**Unsuitable extinguishing** 

media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or

mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

**Special protective** equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

SDS EU 5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019

## 6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

## **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

Value

7.2. Conditions for safe storage, including any incompatibilities

Use care in handling/storage. Keep away from heat, sparks and open flame. Store in a well-ventilated place.

**7.3. Specific end use(s)** Not available.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### Occupational exposure limits

| Belgium. | Exposure | Limit | Values. |
|----------|----------|-------|---------|
|----------|----------|-------|---------|

| Material   | Туре | Value    | Form  |
|--|------|----------|-------|
| HyPrint L151   | STEL | 10 mg/m3 | Mist. |
|  | TWA  | 5 mg/m3  | Mist. |
| Components   | Туре | Value    | Form  |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | STEL | 10 mg/m3 | Mist. |
|  | TWA  | 5 mg/m3  | Mist. |

# Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work Material Type Value

| HyPrint L151             | TWA  | 5 mg/m3 |  |
|--------------------------|------|---------|--|
| Components               | Туре | Value   |  |
| Distillates (petroleum), | TWA  | 5 mg/m3 |  |

hydrotreated heavy naphthenic (CAS 64742-52-5)

Material

64742-52-5)

#### **Czech Republic. OELs. Government Decree 361**

| riatei iai   | туре    | Value      |
|--------------|---------|------------|
| HyPrint L151 | Ceiling | 1000 mg/m3 |
|              | TWA     | 200 ma/m3  |

## **Denmark. Exposure Limit Values**

| Material  | Туре | Value   | Form  |
|---|------|---------|-------|
| HyPrint L151  | TLV  | 1 mg/m3 | Mist. |
| Components  | Туре | Value   | Form  |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS | TLV  | 1 mg/m3 | Mist. |

Material name: HyPrint L151 - Ergon International

5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019 3 /

| Finland. Workplace Exposure I Components                          | Limits<br>Type | Value   | Form  |  |
|---|----------------|---------|-------|--|
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS | TWA            | 5 mg/m3 | Mist. |  |
| 64742-52-5)   |                |         |       |  |

| Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemica | ı |
|--|---|
| Compounds in the Work Area (DFG)   |   |

| Components   | Туре | Value   | Form                 |
|--|------|---------|----------------------|
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | TWA  | 5 mg/m3 | Respirable fraction. |

## Greece. OELs (Decree No. 90/1999, as amended)

| Material   | Туре | Value   | Form  |  |
|--|------|---------|-------|--|
| HyPrint L151   | TWA  | 5 mg/m3 | Mist. |  |
| Components   | Туре | Value   | Form  |  |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | TWA  | 5 mg/m3 | Mist. |  |

## Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

| Material  | Туре    | Value   | Form  |  |
|---|---------|---------|-------|--|
| HyPrint L151  | Ceiling | 5 mg/m3 | Mist. |  |
| Components  | Туре    | Value   | Form  |  |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS | Ceiling | 5 mg/m3 | Mist. |  |

## Iceland. OELs. Regulation 154/1999 on occupational exposure limits

| Material   | Туре | Value   | Form  |  |
|--|------|---------|-------|--|
| HyPrint L151   | TWA  | 1 mg/m3 | Mist. |  |
| Components   | Туре | Value   | Form  |  |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | TWA  | 1 mg/m3 | Mist. |  |

#### **Ireland. Occupational Exposure Limits**

64742-52-5)

64742-52-5)

| Components   | Туре | Value   | Form                |
|--|------|---------|---------------------|
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | TWA  | 5 mg/m3 | Inhalable fraction. |

#### **Italy. Occupational Exposure Limits**

| Components  | Туре | Value   | Form                |
|---|------|---------|---------------------|
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS | TWA  | 5 mg/m3 | Inhalable fraction. |

## Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

| Material     | Type | Value   | Form           |  |
|--------------|------|---------|----------------|--|
| HyPrint L151 | STEL | 3 mg/m3 | Fume and mist. |  |
|              | TWA  | 1 mg/m3 | Fume and mist. |  |

5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019

| Interpretated heavy reported from the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Material Type Value Form 14 Material Type Value Form 15 Material Type Value Form 16 Material Type Value Form 16 Material Type Value Form 17 Material Type Value Form 18 Material Type Val | Lithuania. OELs. Limit Values fo<br>Components                    | Туре                          | Value                     | Form                |
|--|---|-------------------------------|---------------------------|---------------------|
| Netherlands. OELs (binding) Material Type Value Form HyPrint L151 TWA 5 mg/m3 Mist. Components Type Value Form Distillates (petroleum), HyPrint L151 TLV 1 mg/m3 Mist. Components Type Value Form Distillates (petroleum), TLV 1 mg/m3 Mist. Components Type Value Form Distillates (petroleum), TLV 1 mg/m3 Mist. Components Type Value Form Distillates (petroleum), TLV 1 mg/m3 Mist. Distillates (petroleum), Type Value Form Distillates (petroleum) Type Value Form Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form Typ | nydrotreated heavy<br>naphthenic (CAS                             | STEL                          | 3 mg/m3                   | Fume and mist.      |
| HyPrint L151 TWA 5 mg/m3 Mist.  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Mist.  Walve Form  TWA 5 mg/m3 Mist.  TWA 5 mg/m3 Mist.  TWA 5 mg/m3 Mist.  Mist.  TWA 5 mg/m3 Mist.  Mist.  Form  TWA 5 mg/m3 Mist.  Mist.  Form  Type Value Form  Mist.  Mist.  Form  Type Value Form  Type Type Form  Type Value Form |   | TWA                           | 1 mg/m3                   | Fume and mist.      |
| HyPrint L151 TWA 5 mg/m3 Mist.  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Mist. aphthenic (CAS 64742-52-5)  Norway. Administrative Norms for Contaminants in the Workplace Material Type Value Form  HyPrint L151 TLV 1 mg/m3 Mist.  Components Type Value Form  Distillates (petroleum), TLV 1 mg/m3 Mist.  Components Type Value Form  Distillates (petroleum), TLV 1 mg/m3 Mist.  Components Type Value Form  Distillates (petroleum), TLV 1 mg/m3 Mist.  Advirous aphthenic (CAS 64742-52-5)  Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Form Type Value Form  Distillates (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  HyPrint L151 STEL 10 mg/m3 Aerosc 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  HyPrint L151 STEL 10 mg/m3 Form  TWA 5 mg/m3 Inhala form Material Type Value  Distillates (petroleum), TWA 5 mg/m3 Form  TWA 5 mg/m3 Form  Distillates (petroleum), TWA 5 mg/m3 Form  Distillates (petroleum), TWA 5 mg/m3 Form  Type Value Form  Distillates (petroleum), Type Value  Distillates (petroleum), Type Value  Distillates (petroleum), Type Value   |   | _                             |                           | _                   |
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Norway. Administrative Norms for Contaminants in the Workplace Material Type Value Form  Distillates (petroleum), TLV 1 mg/m3 Mist. Type Value Form  Distillates (petroleum), TLV 1 mg/m3 Mist. Type  Distillates (petroleum), Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc Type  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)  Material Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc Type  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)  Material Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)  Material Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Components  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Components  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Components  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Components  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Form  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Form  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Form  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Form  Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Form  Type Value Form  Distillates (petroleum), Type Value Form  | Material<br>————————————————————————————————————                  |                               |                           |                     |
| Distiliates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Norway- Administrative Norms for Contaminants in the Workplace Type Value Form  Norway- Administrative Norms for Contaminants in the Workplace Type Value Form  TLV 1 mg/m3 Mist. Nyroreated heavy naphthenic (CAS 64742-52-5)  Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Nyrorteated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Nyrorteated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value HyPrint L151 STEL 10 mg/m3 Form  TWA 5 mg/m3 ThAla 5 mg/m3 TWA 5 mg/m3  Components Type Value  Distillates (petroleum), TWA 5 mg/m3  Components Type Value  Distillates (petroleum), STEL 10 mg/m3 Aerosc Type Value  | •   |                               | <u>-</u> -                |                     |
| Norway. Administrative Norms for Contaminants in the Workplace Material Type Value Form HyPrint L151 TLV 1 mg/m3 Mist. Components Type Value Form Distillates (petroleum), Norway. Administrative Norms for Contaminants in the Workplace Type Value Form Distillates (petroleum), TLV 1 mg/m3 Mist.  Norway. Administrative Norms for Contaminants in the Workplace Type Value Form Distillates (petroleum), TLV 1 mg/m3 Mist.  Nordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Type Value Form HyPrint L151 STEL 10 mg/m3 Aerosc Components Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhala naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form HyPrint L151 STEL 10 mg/m3 Aerosc 64742-52-5) Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form Distillates (petroleum), TWA 5 mg/m3 Form Distillates (petroleum), TWA 5 mg/m3 Form TWA 5 mg/m3 Form Distillates (petroleum), TWA 5 mg/m3 Form Distillates (petroleum), TWA 5 mg/m3 Form TWA 5 mg/m3 Form Form Form Form Form Form Form Form   | Components  | Туре                          | Value                     | Form                |
| HyPrint L151 TLV 1 mg/m3 Mist.  Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc TyWA 5 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala maphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc GA742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value HyPrint L151 STEL 10 mg/m3 Aerosc Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala TWA 5 mg/m3 Form  Distillates (petroleum), TWA 5 mg/m3 Inhala  | nydrotreated heavy<br>naphthenic (CAS                             | TWA                           | 5 mg/m3                   | Mist.               |
| HyPrint L151 TLV 1 mg/m3 Mist.  Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc TWA 5 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala nydrotreated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc 7 mg/m3 Mg/m3 Aerosc 7 mg/m3 Aerosc 7 mg/m3 Aerosc 7 mg/m3 Mg/m3 Mg/m3 Mg/m3 Aerosc  | <del>-</del>  |                               | -                         | Form                |
| Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc TWA 5 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala Type Value  HyPrint L151 STEL 10 mg/m3 TWA 5 mg/m3  Components Type Value  Distillates (petroleum), TWA 5 mg/m3  Components Type Value   | HyPrint L151  |                               | 1 ma/m3                   | Mist.               |
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissib and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Material  Type Value Form  HyPrint L151  STEL 10 mg/m3 Aerosc  TWA 5 mg/m3 Aerosc  Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)  Material Type Value Form  HyPrint L151  STEL 10 mg/m3 Aerosc  Components Type Value Form  TWA 5 mg/m3 Aerosc  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  HyPrint L151  STEL 10 mg/m3  TWA 5 mg/m3  Inhala hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  Distillates (petroleum), TWA 5 mg/m3  Components Type Value  Distillates (petroleum), STEL 10 mg/m3  TWA 5 mg/m3  Components Type Value  | •   |                               | <u>-</u> -                |                     |
| And intensities of harmful health factors in the work environment, Journal of Laws 2014, item 81 Material Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc  TWA 5 mg/m3 Aerosc  Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Aerosc  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  HyPrint L151 STEL 10 mg/m3  TWA 5 mg/m3  Inhala 5 mg/m3  TWA 5 mg/m3  Components Type Value  Distillates (petroleum), TWA 5 mg/m3  TWA 5 mg/m3  TWA 10 mg/m3  Type Value   | Distillates (petroleum), nydrotreated heavy naphthenic (CAS       |                               |                           | Mist.               |
| HyPrint L151  STEL  TWA  5 mg/m3  Aerosc  Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material  Type  Value  Form  HyPrint L151  STEL  10 mg/m3  Aerosc  TWA  5 mg/m3  Aerosc  TWA  5 mg/m3  Aerosc  Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material  Type  Value  HyPrint L151  STEL  10 mg/m3  Inhala  Inhala  Type  Value  Form  TWA  5 mg/m3  Inhala  Type  Value  HyPrint L151  STEL  10 mg/m3  TWA  5 mg/m3  Components  Type  Value  HyPrint L151  STEL  10 mg/m3  TWA  5 mg/m3  Components  Type  Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS  Form  STEL  10 mg/m3  TWA  5 mg/m3  Components  Type  Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS  | and intensities of harmful health                                 | n factors in the work enviror | ment, Journal of Laws 201 | L4, item 817        |
| TWA 5 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc TWA 5 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  HyPrint L151 STEL 10 mg/m3 Inhala for the components Type Value  HyPrint L151 STEL 10 mg/m3  TWA 5 mg/m3  Components Type Value  HyPrint L151 STEL 10 mg/m3  TWA 5 mg/m3  Components Type Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  STEL 10 mg/m3  Components Type Value  |   |                               | 10 mg/m3                  | Aerosol             |
| Components  Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc Components Type Value Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value  HyPrint L151 STEL 10 mg/m3 Inhala  TWA 5 mg/m3 Inhala  TWA 5 mg/m3  Inhala  Type Value  HyPrint L151 STEL 10 mg/m3 TWA 5 mg/m3  Components Type Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value  HyPrint L151 STEL 10 mg/m3 TWA 5 mg/m3  Components Type Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS   | ., 2131   |                               | <u>-</u> -                | Aerosol             |
| Distillates (petroleum), TWA 5 mg/m3 Inhala Inhala hydrotreated heavy naphthenic (CAS 64742-52-5)  Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form  HyPrint L151 STEL 10 mg/m3 Aerosc TWA 5 mg/m3 Aerosc TWA 5 mg/m3 Inhala Properties (CAS 64742-52-5)  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value  HyPrint L151 STEL 10 mg/m3  TWA 5 mg/m3  Components Type Value  Distillates (petroleum), STEL 10 mg/m3  Components Type Value  Distillates (petroleum), STEL 10 mg/m3  hydrotreated heavy naphthenic (CAS   | Components  |                               | <u>-</u> -                |                     |
| Material  Type  Value  Form  HyPrint L151  STEL  TWA  5 mg/m3  Aerosc  Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS  64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material  Type  HyPrint L151  STEL  10 mg/m3  TWA  5 mg/m3  Components  Type  Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS  | Distillates (petroleum),<br>nydrotreated heavy<br>naphthenic (CAS |                               | 5 mg/m3                   | Inhalable fraction. |
| TWA 5 mg/m3 Aeroso  Components Type Value Form  Distillates (petroleum), TWA 5 mg/m3 Inhala hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  HyPrint L151 STEL 10 mg/m3  TWA 5 mg/m3  Components Type Value  Distillates (petroleum), STEL 10 mg/m3 hydrotreated heavy naphthenic (CAS  |   | -                             | _ ` `                     | Form                |
| Components  Type  Value  Form  Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material  HyPrint L151  STEL  TWA  5 mg/m3  Inhala  10 mg/m3  TWA  5 mg/m3  Components  Type  Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS  | HyPrint L151  | STEL                          | 10 mg/m3                  | Aerosol             |
| Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material  HyPrint L151  STEL  10 mg/m3  TWA  5 mg/m3  Inhala  10 mg/m3  TWA  5 mg/m3  Type  Distillates (petroleum), hydrotreated heavy naphthenic (CAS  |   | TWA                           | 5 mg/m3                   | Aerosol             |
| hydrotreated heavy naphthenic (CAS 64742-52-5)  Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value  HyPrint L151 STEL 10 mg/m3 TWA 5 mg/m3  Components Type Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS   | Components  | Туре                          | Value                     | Form                |
| Material     Type     Value       HyPrint L151     STEL     10 mg/m3       TWA     5 mg/m3       Components     Type     Value       Distillates (petroleum), hydrotreated heavy naphthenic (CAS     STEL     10 mg/m3   | nydrotreated heavy<br>naphthenic (CAS                             | TWA                           | 5 mg/m3                   | Inhalable fraction. |
| HyPrint L151         STEL         10 mg/m3           TWA         5 mg/m3           Components         Type         Value   |   | <del>-</del>                  | <del>-</del>              | ace                 |
| TWA 5 mg/m3  Components Type Value  Distillates (petroleum), STEL 10 mg/m3 hydrotreated heavy naphthenic (CAS  | HyPrint L151  |                               | 10 mg/m3                  |                     |
| Components Type Value  Distillates (petroleum), hydrotreated heavy naphthenic (CAS   | •   |                               | <u>-</u> -                |                     |
| Distillates (petroleum), STEL 10 mg/m3 hydrotreated heavy naphthenic (CAS  | Components  |                               | <u>-</u> -                |                     |
| UT/TC-JC-J)  | Distillates (petroleum), nydrotreated heavy naphthenic (CAS       |                               | 10 mg/m3                  |                     |
| TWA 5 mg/m3  | (כ-22-3 <i>ן</i> +/דע   | TWΔ                           | 5 ma/m3                   |                     |

Material name: HyPrint L151 - Ergon International

5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019 5

| Components   | Туре  | Value                              |                              |
|--|---|------------------------------------|------------------------------|
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | STEL  | 3 mg/m3                            | Fume and mist.               |
|  |   | 15 ppm                             | Fume and mist.               |
|  | TWA   | 1 mg/m3                            | Fume and mist.               |
|  |   | 5 ppm                              | Fume and mist.               |
| Spain. Occupational Expo<br>Material   | sure Limits<br>Type   | Value                              | Form                         |
| HyPrint L151   | STEL  | 10 mg/m3                           | Mist.                        |
|  | TWA   | 5 mg/m3                            | Mist.                        |
| Components   | Туре  | Value                              | Form                         |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | STEL  | 10 mg/m3                           | Mist.                        |
|  | TWA   | 5 mg/m3                            | Mist.                        |
| Sweden. OELs. Work Env<br>Material   | ironment Authority (AV), Occupation<br>Type                                   | nal Exposure Limit Values<br>Value | (AFS 2015:7)<br>Form         |
| HyPrint L151   | STEL  | 3 mg/m3                            | Mist.                        |
| 119111111111111111111111111111111111111  | TWA   | 1 mg/m3                            | Mist.                        |
| Components   | Туре  | Value                              | Form                         |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | STEL  | 3 mg/m3                            | Mist.                        |
|  | TWA   | 1 mg/m3                            | Mist.                        |
| Switzerland. SUVA Grenz  | werte am Arbeitsplatz   |                                    |                              |
| Components   | Туре  | Value                              | Form                         |
| Distillates (petroleum),<br>hydrotreated heavy<br>naphthenic (CAS<br>64742-52-5) | TWA   | 5 mg/m3                            | Inhalable fraction.          |
| ogical limit values  | No biological exposure limits noted fo  | r the ingredient(s).               |                              |
| ommended monitoring<br>cedures   | Not available.  |                                    |                              |
| ived no effect levels<br>IELs)   | Not available.  |                                    |                              |
| dicted no effect<br>centrations (PNECs)  | Not available.  |                                    |                              |
| <b>Exposure controls</b>   |   |                                    |                              |
| ropriate engineering<br>trols  | Provide adequate ventilation, includin occupational exposure limit is not exc |                                    | , to ensure that the defined |
| =  | es, such as personal protective equi  | pment                              |                              |
| General information  | Not available.  |                                    |                              |
| Eye/face protection Skin protection  | Goggles/face shield are recommended   | 1.                                 |                              |
| - Hand protection  | Chemical resistant gloves are recomm gloves. When prolonged or frequent r     |                                    |                              |

Material name: HyPrint L151 - Ergon International

- Other

5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019 6 / 10

gloves may be suitable.

(Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Under normal conditions, respirator is not normally required. When workers are facing Respiratory protection

concentrations above the exposure limit they must use appropriate certified respirators. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)]

Thermal hazards Not available.

**Hygiene measures** Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

**Environmental exposure** 

controls

Not available.

meeting EN14387.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Clear & bright **Appearance** Physical state Liquid. **Form** Liquid.

Colour Light Amber to Golden Odour Mild Petroleum Odor

**Odour threshold** Not available. Not applicable

-41 °C (-41,8 °F) ASTM D5949 Melting point/freezing point

Initial boiling point and

boiling range Flash point

> 371,11 °C (> 700 °F) ASTM D2887/ ISO 3294

161,0 °C (321,8 °F) Pensky-Martens Closed Cup

172.0 °C (341.6 °F) Cleveland open cup ASTM D92/ ISO 2592

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Not available. Vapour pressure

> 5 Vapour density

Relative density 0,902 (15,56 °C (60 °F) ASTM D4052/ ISO 12185)

Solubility(ies)

Insoluble Solubility (water)

**Partition coefficient** 

Not established.

(n-octanol/water)

**Auto-ignition temperature** > 315,56 °C (> 600 °F) ASTM E659

**Decomposition temperature** Not available.

28,8 cSt (40 °C (104 °F) ASTM D445/ ISO 3104) **Viscosity** 

**Explosive properties** Not available. **Oxidising properties** Not available.

9.2. Other information No relevant additional information available.

## **SECTION 10: Stability and reactivity**

10.1. Reactivity Strong oxidising agents.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous Hazardous polymerisation does not occur.

reactions

10.4. Conditions to avoid Avoid temperatures exceeding the flash point.

10.5. Incompatible materials Strong oxidising agents.

Material name: HyPrint L151 - Ergon International 5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019 10.6. Hazardous decomposition products Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

weight hydrocarbons.

## **SECTION 11: Toxicological information**

**General information** Not available. Information on likely routes of exposure

Inhalation May be harmful if inhaled. However, this product does not currently meet the criteria for

classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis

**Eve contact** May be irritating to eyes.

May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may Ingestion

increase risk of product aspiration.

**Symptoms** Not available. 11.1. Information on toxicological effects

**Acute toxicity** Not classified.

Skin corrosion/irritation Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified.

Respiratory sensitisation Not classified. Skin sensitisation Not classified.

Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Nota L - Meets

EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

**Aspiration hazard** Not classified. Mixture versus substance

information

Not available.

Other information Not available.

## **SECTION 12: Ecological information**

12.1. Toxicity Not expected to be harmful to aquatic organisms.

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

**Partition coefficient** 

n-octanol/water (log Kow)

Not established.

Not available. **Bioconcentration factor (BCF)** 12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**Residual waste** Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

SDS EU

emptied. Offer rinsed packaging material to local recycling facilities.

Material name: HyPrint L151 - Ergon International

8 / 10 5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019

**EU** waste code Not applicable. Waste codes should be assigned by the user based on the application for which the

product was used.

Disposal recommendations are based on material as supplied. Disposal must be in accordance with Disposal

methods/information current applicable laws and regulations, and material characteristics at time of disposal.

#### **SECTION 14: Transport information**

**ADR** 

14.1. - 14.6.: Not regulated as dangerous goods.

**RID** 

14.1. - 14.6.: Not regulated as dangerous goods.

**ADN** 

14.1. - 14.6.: Not regulated as dangerous goods.

**IATA** 

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG** 

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk

Not available.

according to Annex II of MARPOL 73/78 and the IBC

Code

**General information** Not regulated as dangerous goods.

#### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

#### Other EU regulations

#### Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006

**National regulations** Germany: WGK 1

Material name: HyPrint L151 - Ergon International SDS EU

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

#### **International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | Yes                    |
| Canada               | Domestic Substances List (DSL)   | Yes                    |
| Canada               | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | Yes                    |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes                    |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | Yes                    |
| Korea                | Existing Chemicals List (ECL)  | Yes                    |
| New Zealand          | New Zealand Inventory  | Yes                    |
| Philippines          | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes                    |
| Taiwan               | Taiwan Chemical Substance Inventory (TCSI)                             | Yes                    |

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### **SECTION 16: Other information**

United States & Puerto Rico

List of abbreviations Not available.

References **ACGIH** 

IARC Monographs. Overall Evaluation of Carcinogenicity

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

Toxic Substances Control Act (TSCA) Inventory

**ILO Safety Cards** 

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

**Information on evaluation** method leading to the classification of mixture

Not available.

**Full text of any H-statements** not written out in full under

Sections 2 to 15

H350 May cause cancer.

**Revision information** Physical & Chemical Properties: Multiple Properties

**Training information** Not available.

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

> information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Further information** Local CHEMTREC Numbers:

CHEMTREC China: 4001-204937

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349

Material name: HyPrint L151 - Ergon International SDS EU 5495 Version #: 02 Revision date: 23-May-2019 Issue date: 22-May-2019

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).