ERGONE

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance Hyprint L201

Identification number 649-465-00-7 (Index number)

Registration number

Synonyms None. 23-May-2019 **Issue date**

Version number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pigments; Printing Inks

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

> Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

Chemtrec: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International)

See Section 15 for additional CHEMTREC Hotline Numbers

E-mail: sds@ergon.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended

Not available. **Hazard summary**

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Distillates (petroleum), hydrotreated light naphthenic

Hazard pictograms None.

Signal word Not applicable. **Hazard statements** Not applicable.

Precautionary statements

Prevention Not available. Response Not applicable. Not applicable. **Storage Disposal** Not applicable.

Supplemental label None.

information

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated heavy naphthenic	55 - 75	64742-52-5 265-155-0	01-2119467170-45	649-465-00-7	
Classification: Carc. 1B;H3	50				L
Distillates (petroleum), hydrotreated light naphthenic	25 - 45	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	
Classification: Asp. Tox. 1	H304				

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any

immediate medical attention and special treatment

needed

Treat symptomatically.

Defatting of the skin.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an

Do not use water jet as an extinguisher, as this will spread the fire.

extinguisher, as this will spread the fire.

5.2. Special hazards arising

from the substance or

mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

Material name: Hyprint L201 - Ergon International 5506 Version #: 01 Issue date: 23-May-2019

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Use care in handling/storage. Keep away from heat, sparks and open flame. Store in a well-ventilated place.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Material	Туре	Value	Form	
Hyprint L201	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work **Material** Value

i iacciiai	.,,,	Value	
Hyprint L201	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	

Czech Republic. OELs. Government Decree 361

Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	

Material	Туре	Value	Form
Hyprint L201	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
Finland. Workplace Exposure Components	Limits Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
	sory OELs). Commission for the	e Investigation of Health H	azards of Chemical
Compounds in the Work Area Components	(DFG) Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Respirable fraction
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Respirable fraction
Greece. OELs (Decree No. 90/ Material	1999, as amended) Type	Value	Form
Hyprint L201	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree o Material	n Chemical Safety of Workpla Type	ces Value	Form
Hyprint L201	Ceiling	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS	Ceiling	5 mg/m3	Mist.

Material	Туре	Value	Form
Hyprint L201	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	1 mg/m3	Mist.
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA	1 mg/m3	Mist.
reland. Occupational Exposure Limits Material	Туре	Value	Form
Hyprint L201	TWA	0,2 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Italy. Occupational Exposure Limits Material	Туре	Value	Form
Hyprint L201	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), ydrotreated heavy aphthenic (CAS 4742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Latvia. OELs. Occupational exposure lir Components	nit values of chemical Type	substances in work enviro Value	nment
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA	5 mg/m3	
Lithuania. OELs. Limit Values for Chem Material	nical Substances, Gene Type	eral Requirements Value	Form
Hyprint L201	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum),	STEL	3 mg/m3	Fume and mist.
naphthenic (CAS			
naphthenic (CAS	TWA	1 mg/m3	Fume and mist.
nydrotreated heavy naphthenic (CAS 54742-52-5) Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA STEL	1 mg/m3 3 mg/m3	Fume and mist. Fume and mist.

Material	Туре	Value	Form
Hyprint L201	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms Material	s for Contaminants in the Wor Type	rkplace Value	Form
Hyprint L201	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
Ordinance of the Minister of La and intensities of harmful hea Material			
Hyprint L201	STEL	10 mg/m3	Aerosol
	T\A/A	Γ ma σ /ma 2	AI
	TWA	5 mg/m3	Aerosol
Components	Туре	Value	Form
Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		5.	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS	Type TWA TWA	Value 5 mg/m3 5 mg/m3	Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occup	Type TWA TWA pational exposure to chemical	Value 5 mg/m3 5 mg/m3	Form Inhalable fraction. Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occup	Type TWA TWA pational exposure to chemical Type	Value 5 mg/m3 5 mg/m3 agents (NP 1796) Value	Form Inhalable fraction. Inhalable fraction. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occup	Type TWA TWA pational exposure to chemical Type STEL	Value 5 mg/m3 5 mg/m3 4 agents (NP 1796) Value 10 mg/m3	Form Inhalable fraction. Inhalable fraction. Form Aerosol
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occup Material Hyprint L201 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	Type TWA TWA Pational exposure to chemical Type STEL TWA	Value 5 mg/m3 5 mg/m3 1 agents (NP 1796) Value 10 mg/m3 5 mg/m3	Form Inhalable fraction. Inhalable fraction. Form Aerosol Aerosol
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occup Material Hyprint L201	Type TWA TWA pational exposure to chemical Type STEL TWA Type	Value 5 mg/m3 5 mg/m3 agents (NP 1796) Value 10 mg/m3 5 mg/m3 Value	Form Inhalable fraction. Inhalable fraction. Form Aerosol Aerosol Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occup Material Hyprint L201 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS	Type TWA TWA Pational exposure to chemical Type STEL TWA Type TWA TWA TWA TWA	Value 5 mg/m3 5 mg/m3 4 agents (NP 1796) Value 10 mg/m3 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Inhalable fraction. Form Aerosol Aerosol Form Inhalable fraction. Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occup Material Hyprint L201 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Romania. OELs. Protection of N	Type TWA TWA Pational exposure to chemical Type STEL TWA Type TWA Type TWA	Value 5 mg/m3 5 mg/m3 10 mg/m3 5 mg/m3 Value 5 mg/m3 Value 5 mg/m3 emical agents at the workplease	Form Inhalable fraction. Inhalable fraction. Form Aerosol Aerosol Form Inhalable fraction. Inhalable fraction.

Romania. OELs. Protection of v Components	Туре	Value	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Distillates (petroleum), nydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Slovakia. OELs. Regulation No Material	. 300/2007 concerning proted Type	tion of health in work with Value	chemical agents Form
Hyprint L201	TWA	1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist
	TWA	1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	STEL	3 mg/m3	Fume and mist.
,		15 ppm	Fume and mist
Spain. Occupational Exposure Material	Limits Type	Value	Form
Hyprint L201	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Sweden. OELs. Work Environn Material	nent Authority (AV), Occupation	onal Exposure Limit Values Value	(AFS 2015:7) Form
Hyprint L201	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Mist.
JT/TZ"JZ"J)			
,	TWA	1 mg/m3	Mist.

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)
Components Type Value Form

STEL

TWA

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) 3 mg/m3

1 mg/m3

Mist.

Mist.

Switzerland. SUVA Grenzwerte am Arbeitsplatz

ComponentsTypeValueFormDistillates (petroleum),TWA5 mg/m3Inhalable fraction.

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction.

hydrotreated light naphthenic (CAS 64742-53-6)

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Not available.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information Not available.

Eye/face protection Goggles/face shield are recommended.

Skin protection
- Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

gloves may be suitable.

- Other Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection Under normal conditions, respirator is not normally required. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)]

meeting EN14387.

Thermal hazards Not available.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear & bright Physical state Liquid.

Form Liquid.

Colour Light yellow. to Light Amber

Odour Mild Petroleum Odor

Material name: Hyprint L201 - Ergon International 5506 Version #: 01 Issue date: 23-May-2019

Odour thresholdNot available.pHNot applicable.Melting point/freezing point-38 °C (-36,4 °F)

Initial boiling point and

boiling range

> 253,89 °C (> 489 °F) ASTM D2887

Flash point 168,0 °C (334,4 °F) Pensky-Martens Closed Cup estimated

180,0 °C (356,0 °F) Cleveland open cup ASTM D92

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

Vapour pressureNot available.Vapour densityNot available.

Relative density 0,906 (15,56 °C (60 °F) ASTM D4052)

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not established.

(n-octanol/water)

Auto-ignition temperature > 315,56 °C (> 600 °F) ASTM E659

Decomposition temperature Not available.

Viscosity 39,7 cSt (40 °C (104 °F) ASTM D445)

Explosive propertiesNot available. **Oxidising properties**Not available.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidising agents.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous

Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous decomposition products

reactions

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

ucts weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available. **Information on likely routes of exposure**

Inhalation May be harmful if swallowed and enters airways. However, this product does not currently meet

the criteria for classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration.

Symptoms Not available.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

Not classified. May be irritating to eyes.

Respiratory sensitisation Not classified.

Skin sensitisation Not classified. Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.

Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Nota L - Meet: EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity

Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

Not classified. May cause irritation to the respiratory system.

- single exposure

Specific target organ toxicity

- repeated exposure

Not available.

Aspiration hazard

Mixture versus substance

information

Not applicable. Not applicable.

Other information Not assigned.

SECTION 12: Ecological information

12.1. Toxicity Not expected to be harmful to aquatic organisms.

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient Not established.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

EU waste code Not applicable. Waste codes should be assigned by the user based on the application for which the

product was used.

Disposal methods/information Disposal recommendations are based on material as supplied. Disposal must be in accordance with

current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of Not available.

MARPOL 73/78 and the IBC

Code

General information Not regulated as dangerous goods.

Material name: Hyprint L201 - Ergon International 5506 Version #: 01 Issue date: 23-May-2019

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulationsThe product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006

National regulations Germany: WGK 1

15.2. Chemical safety No Chemical Safet

assessment

No Chemical Safety Assessment has been carried out.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: Hyprint L201 - Ergon International 5506 Version #: 01 Issue date: 23-May-2019

Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: Other information

List of abbreviations Not available. **ACGIH** References

IARC Monographs. Overall Evaluation of Carcinogenicity

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under Sections 2 to 15

H304 May be fatal if swallowed and enters airways.

H350 May cause cancer.

Revision information Product and Company Identification: Alternate Trade Names

Physical & Chemical Properties: Multiple Properties

Regulatory Information: United States

GHS: Classification

Training information

Not available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Further information Local CHEMTREC Numbers:

CHEMTREC China: 4001-204937

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349

Material name: Hyprint L201 - Ergon International 5506 Version #: 01 Issue date: 23-May-2019