

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	HyVolt III
Registration number	01-2119480375-34
Synonyms	None.
Issue date	25-January-2011
Version number	30
Revision date	30-April-2021
Supersedes date	21-January-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Transformer Oil
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company:	Ergon, Inc.
Address:	P.O. Box 1639 Jackson, MS 39215
E-mail:	sds@ergon.com
Emergency Contacts	
Customer service:	1-800-222-7122
Chemtrec:	1-800-424-9300 After Business Hours (North America Only) 1-703-527-3887 After Business Hours (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.
-------------------	------------	--

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

Hazard summary May be harmful by inhalation.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Distillates (petroleum), hydrotreated light naphthenic, Distillates (petroleum), hydrotreated light paraffinic, LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED

Hazard pictograms



Signal word Danger

Hazard statements

H412	Harmful to aquatic life with long lasting effects.
H304	May be fatal if swallowed and enters airways.

Precautionary statements

Prevention

P260	Do not breathe gas/mist/vapours/spray.
P273	Avoid release to the environment.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P331 Do NOT induce vomiting.

Storage

P405 Store locked up.

Disposal

P501 See section 13 of this SDS for disposal instructions.
Dispose of contents/container in accordance with local/regional/national/international regulations

Supplemental label information

None.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated light naphthenic Classification: Asp. Tox. 1;H304	30 - 99,6	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	
Distillates (petroleum), hydrotreated light paraffinic Classification: Carc. 1B;H350	0 - 50	64742-55-8 265-158-7	01-2119487077-29	649-468-00-3	L
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED Classification: Carc. 1B;H350	0 - 20	72623-87-1 276-738-4	01-2119474889-13	649-483-00-5	L
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] Classification: Aquatic Chronic 1;H410	< 0,4	128-37-0 204-881-4	01-2119565113-46	-	

Composition comments

Note L - Not classified as a carcinogen. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

SECTION 4: First aid measures

General information

Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.

Skin contact

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact

Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion

Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both acute and delayed

Defatting of the skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards

No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media

Halon. Dry chemicals. Foam. Carbon dioxide (CO₂). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

For personal protection, see section 8. For waste disposal, see section 13.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	MAK	10 mg/m ³

Belgium. Exposure Limit Values.

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	2 mg/m ³	Vapour and aerosol.

Belgium. Exposure Limit Values.

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Material	Type	Value
HyVolt III	TWA	5 mg/m3
Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	STEL	50 mg/m3
	TWA	10 mg/m3
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3
	TWA	5 mg/m3
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	MAC	10 mg/m3

Czech Republic. OELs. Government Decree 361

Material	Type	Value	
HyVolt III	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Ceiling	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

Denmark. Exposure Limit Values

Material	Type	Value	Form
HyVolt III	TLV	1 mg/m3	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TLV	10 mg/m3	

Denmark. Exposure Limit Values Components

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TLV	1 mg/m3	Mist.

Finland. Workplace Exposure Limits Material

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	STEL	20 mg/m3	
	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	VME	10 mg/m3

Regulatory status: Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m3	Vapor and aerosol, inhalable fraction.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Respirable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Respirable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m3	Respirable fraction.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	AGW	10 mg/m3	Inhalable fraction.

Greece. OELs (Decree No. 90/1999, as amended)

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m3	Mist.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Mist.

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Material	Type	Value	Form
HyVolt III	Ceiling	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	Ceiling	5 mg/m3	Mist.

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Material	Type	Value	Form
HyVolt III	TWA	1 mg/m3	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	1 mg/m3	Mist.

Ireland. Occupational Exposure Limits

Material	Type	Value	Form
HyVolt III	TWA	0,2 mg/m3	Inhalable fraction.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.

Italy. Occupational Exposure Limits

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m3	Inhalable fraction.

Italy. Occupational Exposure Limits Components

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment Components

Components	Type	Value
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Material	Type	Value	Form
HyVolt III	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.

Netherlands. OELs (binding)

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Mist.

Norway. Administrative Norms for Contaminants in the Workplace

Material	Type	Value	Form
HyVolt III	TLV	1 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TLV	1 mg/m ³	Mist.

Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Aerosol
	TWA	5 mg/m ³	Aerosol
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m ³	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m ³	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m ³	Inhalable fraction.

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Aerosol
	TWA	5 mg/m ³	Aerosol
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	2 mg/m ³	Inhalable fraction and vapor.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m ³	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m ³	Inhalable fraction.

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Material	Type	Value
HyVolt III	STEL	10 mg/m ³
	TWA	5 mg/m ³
Components	Type	Value
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m ³
	TWA	5 mg/m ³
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m ³
	TWA	5 mg/m ³

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m ³	Fume and mist.

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	15 ppm 3 mg/m ³	Fume and mist. Fume and mist.
	TWA	15 ppm 1 mg/m ³	Fume and mist. Fume and mist.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	STEL	5 ppm 3 mg/m ³	Fume and mist. Fume and mist.
	TWA	15 ppm 1 mg/m ³	Fume and mist. Fume and mist.
		5 ppm	Fume and mist.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m ³	Inhalable fraction.

**Spain. Occupational Exposure Limits
Material**

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m ³	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Material	Type	Value	Form
HyVolt III	STEL	3 mg/m ³	Mist.
	TWA	1 mg/m ³	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m ³	Mist.
	TWA	1 mg/m ³	Mist.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	STEL	3 mg/m ³	Mist.
	TWA	1 mg/m ³	Mist.

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	STEL	40 mg/m3	Vapor and aerosol, inhalable.
	TWA	10 mg/m3	Vapor and aerosol, inhalable.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated light paraffinic (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Not available.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information Wear suitable protective equipment.

Eye/face protection Goggles/face shield are recommended.

Skin protection

- Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.

- Other Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN14387.

Thermal hazards Not available.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental exposure controls Not available.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Material name: HyVolt III

4710 Version #: 30 Revision date: 30-April-2021 Issue date: 25-January-2011

SDS EU

10 / 14

Appearance	Clear & bright
Physical state	Liquid.
Form	Liquid.
Colour	Water White
Odour	Mild Petroleum Odor
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	-63 °C (-81,4 °F) ASTM D5950/ISO 3016
Initial boiling point and boiling range	287 °C (548,6 °F) ASTM D2887/ ISO 3294
Flash point	>= 135,0 °C (>= 275,0 °F) Pensky-Martens Closed Cup ASTM D93
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0,88 (20 °C (68 °F) ASTM D4052/ ISO 12185)
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not established.
Auto-ignition temperature	>= 315 °C (>= 599 °F) ASTM E659
Decomposition temperature	Not available.
Viscosity	9,4 cSt (40 °C (104 °F) ISO 3104)
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	Strong oxidising agents.
10.2. Chemical stability	Stable.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

SECTION 11: Toxicological information

General information	Not available.
Information on likely routes of exposure	
Inhalation	May be fatal if swallowed and enters airways.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis
Eye contact	May be irritating to eyes.
Ingestion	May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration. May be fatal if swallowed and enters airways.
Symptoms	Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest
11.1. Information on toxicological effects	
Acute toxicity	Not applicable.
Skin corrosion/irritation	May cause defatting of the skin, but is neither an irritant nor a sensitizer.
Serious eye damage/eye irritation	Not classified. May cause minor irritation on eye contact.

Respiratory sensitisation	Not classified.
Skin sensitisation	Not classified. May cause defatting of the skin, but is not an irritant.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Note L - Meet: EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity	Contains no ingredient listed as toxic to reproduction
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways.
Mixture versus substance information	Not available.
Other information	Risk of chemical pneumonia after aspiration.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects.

Product	Species	Test Results
HyVolt III		
Aquatic		
Crustacea	EC50 Daphnia	800 mg/l, 48 hours estimated
Components	Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)		
Aquatic		
Crustacea	EC50 Water flea (Daphnia pulex)	1,44 mg/l, 48 hours

Not available. * Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability	Not inherently biodegradable.
12.3. Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
Partition coefficient n-octanol/water (log Kow)	Not established.
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	Not available.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.
EU waste code	Not applicable. Waste codes should be assigned by the user based on the application for which the product was used.
Disposal methods/information	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk Not available.

**according to Annex II of
MARPOL 73/78 and the IBC**

Code

General information Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws
This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

National regulations

Germany: WGK 1

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: Other information

List of abbreviations

Not available.

References

ACGIH
IARC Monographs. Overall Evaluation of Carcinogenicity
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Chemical Abstracts Service Registry Handbook
CRC: Handbook of Chemistry and Physics
ILO Safety Cards
International Labour Organization
International Maritime Organization Marine Pollutants List
NFPA Hazardous Chemical Data Sheets
NIOSH Pocket Guide
Registry of Toxic Effects of Chemical Substances (RTECS)
US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under Sections 2 to 15

H304 May be fatal if swallowed and enters airways.
H350 May cause cancer.
H410 Very toxic to aquatic life with long lasting effects.

Revision information

Product and Company Identification: Alternate Trade Names
Physical & Chemical Properties: Multiple Properties
GHS: Classification

Training information

Not available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Further information

Local CHEMTREC Numbers:
CHEMTREC China: 4001-204937
CHEMTREC EU (Brussels): +(32)-28083237
CHEMTREC Indonesia: 001-803-017-9114
CHEMTREC Malaysia: +(60)-327884561
CHEMTREC Mexico: 1-800-681-9531
CHEMTREC Singapore: +(65)-31581349