

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture HyVolt III

Registration number -

UFI: EU: C500-C029-G00D-DQUF

Synonyms None.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Transformer Oil

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.
P.O. Box 1639
Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.
Drève Richelle 161 Building C
B-1410 Waterloo, Belgium

Emergency Phone Numbers:

US Customer Service: + 1-800-222-7122

CHEMTREC: + 1-800-424-9300 After Business Hours (North America)
+ 1-703-527-3887 (International),
+32-28083237 (Belgium)
+33-975181407 (France)
+49-69643508409 (Germany)
+39-0245557031 (Italy)
+34-931768545 (Spain)

E-mail: sds@ergon.com

Poison Centre (Centre Antipoisons - Belgium): +32022649636

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

UFI: EU: C500-C029-G00D-DQUF

Contains: Distillates (petroleum), Hydrotreated Light, Distillates (petroleum), hydrotreated light naphthenic, Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang

Hazard pictograms



Signal word

Danger

Hazard statements

H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P273 Avoid release to the environment.
P260 Do not breathe gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P280 Wear protective gloves.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor/.
P331 Do NOT induce vomiting.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P321 Specific treatment see Section 4 of this SDS.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

None.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated light naphthenic	30 - 99,6	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	Classification: Asp. Tox. 1;H304
Distillates (petroleum), Hydrotreated Light	0 - 55	64742-47-8 265-149-8	-	649-422-00-2	Classification: Flam. Liq. 3;H226, Acute Tox. 3;H331;(ATE: 5,2 mg/l), Asp. Tox. 1;H304, Aquatic Chronic 2;H411
Distillates (petroleum), hydrotreated light paraffinic	0 - 50	64742-55-8 265-158-7	-	649-468-00-3	Classification: -
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang	0 - 50	848301-69-9 232-443-2	-	649-262-00-3	Classification: Flam. Liq. 1;H224, Muta. 1B;H340, Carc. 1B;H350, Asp. Tox. 1;H304, Aquatic Chronic 2;H411

P

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED	0 - 20	72623-87-1 276-738-4	-	649-483-00-5	
Classification: Asp. Tox. 1;H304					
2,6-DI-TERT-BUTYL-P-CRESOL	< 0,4	128-37-0 204-881-4	01-2119565113-46	-	
Classification: Aquatic Chronic 1;H410					

List of abbreviations and symbols that may be used above

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16. Note P - The harmonized classification as a carcinogen or mutagen does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS No 200-753-7).

SECTION 4: First aid measures

General information Contact physician if discomfort continues. Keep victim under observation.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or poison control centre immediately.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth thoroughly. Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both acute and delayed Defatting of the skin. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media Halon. Dry chemicals. Foam. Carbon dioxide (CO₂). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting procedures Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Do not get this material on clothing. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Use care in handling/storage.

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	MAK	10 mg/m ³

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	2 mg/m ³	Vapour and aerosol.
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m ³	Vapour.

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

Material	Type	Value
HyVolt III	TWA	5 mg/m ³
Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	50 mg/m ³
	TWA	10 mg/m ³
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	300 mg/m ³

Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	MAC	10 mg/m ³

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)

Material	Type	Value
HyVolt III	Ceiling	1000 mg/m ³
	TWA	200 mg/m ³
Components	Type	Value
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	Ceiling	1000 mg/m ³
	TWA	200 mg/m ³

Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2

Material	Type	Value	Form
HyVolt III	TLV	1 mg/m ³	Mist.
Components	Type	Value	
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	20 mg/m ³	
	TLV	10 mg/m ³	
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	TLV	25 ppm	

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	STEL	300 mg/m ³
		50 ppm

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m ³	Mist.
Components	Type	Value	
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	20 mg/m ³	
	TWA	10 mg/m ³	

Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health

Components	Type	Value
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	500 mg/m ³

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	VME	10 mg/m ³

Regulatory status: Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m ³	Vapor and aerosol, inhalable fraction.
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m ³	Respirable aerosol fraction
		350 mg/m ³	Vapour.
		50 ppm	Vapour.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m ³	Respirable fraction.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	AGW	10 mg/m ³	Inhalable fraction.
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	AGW	300 mg/m ³	

Greece. OELs, Presidential Decree No. 307/1986, as amended

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m ³	Mist.

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m ³

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Material	Type	Value	Form
HyVolt III	Ceiling	5 mg/m ³	Mist.

Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended

Material	Type	Value	Form
HyVolt III	TWA	1 mg/m ³	Mist.

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m ³

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

Material	Type	Value	Form
HyVolt III	TWA	0,2 mg/m ³	Inhalable fraction.

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	2 mg/m ³

Ireland. OELVs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations

Components	Type	Value	Form
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m ³	Inhalable fraction.

Italy. OELs (Legislative Decree n.81, 9 April 2008), as amended

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m ³	Inhalable fraction.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)	TWA	2 mg/m ³	Inhalable fraction and vapour.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m ³	Inhalable fraction.

Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended

Components	Type	Value
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	TWA	10 mg/m ³

Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended

Material	Type	Value	Form
HyVolt III	STEL	3 mg/m ³	Fume and mist.
	TWA	1 mg/m ³	Fume and mist.
Components	Type	Value	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	500 mg/m ³	
	TWA	350 mg/m ³	

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m ³	Mist.

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

Material	Type	Value	Form
HyVolt III	TLV	1 mg/m ³	Mist.
Components	Type	Value	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TLV	275 mg/m ³	
		40 ppm	

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Aerosol

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

Material	Type	Value	Form
	TWA	5 mg/m ³	Aerosol
Components	Type	Value	Form
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	300 mg/m ³	
	TWA	100 mg/m ³	
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m ³	Inhalable fraction.

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Aerosol
	TWA	5 mg/m ³	Aerosol
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	2 mg/m ³	Inhalable fraction and vapour.

Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)

Material	Type	Value
HyVolt III	STEL	10 mg/m ³
	TWA	5 mg/m ³
Components	Type	Value
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	STEL	200 mg/m ³
	TWA	100 mg/m ³

Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)

Components	Type	Value	Form
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	STEL	3 mg/m ³	Fume and mist.
		15 ppm	Fume and mist.
	TWA	1 mg/m ³	Fume and mist.
		5 ppm	Fume and mist.

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Ann. I 100/2001), as amended

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	KTV	40 mg/m ³	Inhalable fraction.

Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3	Inhalable fraction.

Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Type	Value	
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	TWA	200 mg/m3	

Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended

Material	Type	Value	Form
HyVolt III	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Type	Value	
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	500 mg/m3	
	TWA	350 mg/m3	
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	STEL	300 mg/m3	
		50 ppm	
	TWA	150 mg/m3 25 ppm	

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	40 mg/m3	Vapor and aerosol, inhalable.
	TWA	10 mg/m3	Vapor and aerosol, inhalable.
Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)	STEL	700 mg/m3	Vapour.
		100 ppm	Vapour.
	TWA	5 mg/m3	Aerosol
		350 mg/m3	Vapour.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	50 ppm	Vapour.
		5 mg/m3	Inhalable fraction.

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value	Form
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	TWA	1100 mg/m3	
		300 ppm	

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)	TWA	10 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines**Belgium OELs: Skin designation**

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) Can be absorbed through the skin.

Romania OELs: Skin designation

Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9) Can be absorbed through the skin.

Spain OELs: Skin designation

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information Wear suitable protective equipment. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Goggles/face shield are recommended.

Skin protection

- Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Wear suitable gloves tested to EN374. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.

- Other Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection Not available.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	L0.5
Odour	Mild Petroleum Odor
Melting point/freezing point	-63 °C (-81,4 °F) ASTM D5950/ISO 3016
Boiling point or initial boiling point and boiling range	287 °C (548,6 °F) ASTM D2887/ ISO 3294
Flammability	Will burn if involved in a fire.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Flash point	156,0 °C (312,8 °F)
Auto-ignition temperature	≥315 °C (≥599 °F) ASTM E659
Decomposition temperature	Not determined.
pH	Not determined.
Kinematic viscosity	9,4 mm ² /s ISO 3104 (40 °C (104 °F))
Solubility	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water) (log value)	Not established. Not applicable.
Vapour pressure	Not determined.
Density and/or relative density	
Relative density	0,88 (20 °C (68 °F) ASTM D4052/ ISO 12185)
Vapour density	Not determined.
Particle characteristics	Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes No relevant additional information available.

9.2.2. Other safety characteristics No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	Strong oxidising agents.
10.2. Chemical stability	Stable.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration. May be fatal if swallowed and enters airways.

Symptoms Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
	Rat	> 2000 mg/kg
Oral		
LD50	Rat	> 6000 mg/kg > 2930 mg/kg

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Acute

Dermal

LD50 Rat > 2000 mg/kg

Inhalation

LC50 Rat > 5200 mg/m³, 4 Hours

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Acute

Dermal

LD50 Rat > 2000 mg/kg

Inhalation

LC50 Rat > 5000 mg/m³

Oral

LD50 Rat > 5000 mg/kg

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Prolonged exposure may cause irritation to eyes.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation Not classified. May cause defatting of the skin, but is not an irritant.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Poland. Order concerning carcinogenic and mutagenic substances in the workplace, as amended

Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9) Mutagenic, Category 1B.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Note L - Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

Hungary. 26/2000 Eüm Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

Mixture versus substance information No information available.

11.2. Information on other hazards

Endocrine disrupting properties This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

Other information Risk of chemical pneumonia after aspiration.

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Product		Species	Test Results
HyVolt III			
Aquatic			
Crustacea	EC50	Daphnia	24,3982 mg/l, 48 hours estimated
Fish	LC50	Fish	58,5556 mg/l, 96 hours estimated
<i>Acute</i>			
Crustacea	EC50	Daphnia	16,8277 mg/l, 48 hours estimated
Fish	LC50	Fish	13,0178 mg/l, 4 days estimated

Components		Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)			
Aquatic			
<i>Acute</i>			
Algae	EC10	Freshwater algae	0,24 mg/l, 72 hours
Crustacea	EC50	Daphnia magna	0,48 mg/l, 48 hours
Fish	LC50	Fish	0,199 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	0,069 mg/l, 21 days
Fish	NOEC	Fish	0,053 mg/l, 30 days

Distillates (petroleum), Hydrotreated Light (CAS 64742-47-8)

Aquatic

Acute

Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	2,2 mg/l, 4 days
------	------	---	------------------

Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)

Aquatic

Crustacea	EC50	Water flea (<i>Daphnia pulex</i>)	>= 2,7 - <= 5,1 mg/l, 48 hours
-----------	------	-------------------------------------	--------------------------------

Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>)	8,8 mg/l, 96 hours
------	------	--	--------------------

8,8 mg/l, 96 hours

Acute

Crustacea	EC50	Water flea (<i>Daphnia pulex</i>)	>= 2,7 - <= 5,1 mg/l, 48 hours
-----------	------	-------------------------------------	--------------------------------

Fish	LC50	Rainbow trout,donaldson trout (<i>Oncorhynchus mykiss</i>)	8,8 mg/l, 96 hours
------	------	--	--------------------

8,8 mg/l, 96 hours

Not available. * Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability Expected to be inherently biodegradable.

12.3. Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient n-octanol/water (log Kow) Not established.

2,6-DI-TERT-BUTYL-P-CRESOL 5,1

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Expected to be slightly to moderately mobile in soil.

- 12.5. Results of PBT and vPvB assessment** This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
- 12.6. Endocrine disrupting properties** This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
- 12.7. Other adverse effects** Oil spills are generally hazardous to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Residual waste** Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
- Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.
- EU waste code** Waste codes should be assigned by the user based on the application for which the product was used.
- Disposal methods/information** Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

- 14.1. UN number** UN1993
- 14.2. UN proper shipping name** FLAMMABLE LIQUID, N.O.S. (Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang, Distillates (petroleum), Hydrotreated Light)
- 14.3. Transport hazard class(es)**
- Class** 3
 - Subsidiary hazard** -
 - Label(s)** 3
 - Hazard No. (ADR)** 30
 - Tunnel restriction code** D/E
- 14.4. Packing group** III
- 14.5. Environmental hazards** No.
- 14.6. Special precautions for user** Not assigned.

RID

- 14.1. UN number** UN1993
- 14.2. UN proper shipping name** FLAMMABLE LIQUID, N.O.S. (Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang, Distillates (petroleum), Hydrotreated Light)
- 14.3. Transport hazard class(es)**
- Class** 3
 - Subsidiary hazard** -
 - Label(s)** 3
- 14.4. Packing group** III
- 14.5. Environmental hazards** No.
- 14.6. Special precautions for user** Not assigned.

ADN

- 14.1. UN number** UN1993
- 14.2. UN proper shipping name** FLAMMABLE LIQUID, N.O.S. (Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang, Distillates (petroleum), Hydrotreated Light)
- 14.3. Transport hazard class(es)**
- Class** 3
 - Subsidiary hazard** -
 - Label(s)** 3
- 14.4. Packing group** III
- 14.5. Environmental hazards** No.

14.6. Special precautions for user Not assigned.

IATA

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping name Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary hazard -

14.4. Packing group -

14.5. Environmental hazards No.

14.6. Special precautions for user Not assigned.

IMDG

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping name Not regulated as dangerous goods.

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary hazard -

14.4. Packing group -

14.5. Environmental hazards

Marine pollutant No.

EmS Not assigned.

14.6. Special precautions for user Not assigned.

14.7. Maritime transport in bulk according to IMO instruments This product is a liquid. Therefore, bulk transport is governed by MARPOL 73/78, Annex I.

ADN; ADR; RID



General information Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

UFI:

EU: C500-C029-G00D-DQUF

Authorisations**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

Restrictions on use**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered**Distillates (petroleum), Hydrotreated Light 3
(CAS 64742-47-8)

Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended

Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended

Not listed.

Other EU regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EU) 2020/878."

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EU) 2020/878.

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

National regulationsFollow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.
Germany: WGK 1**France regulations****France INRS Table of Occupational Diseases**

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse 36
Naphtha; Low boiling point naphtha [Refined, partly refined, or unrefined petroleum products produced by the distillation of natural gas. It consists of hydrocarbons having carbon numbers predominantly in the range of C5 through C6 and boiling in the rang (CAS 848301-69-9)	Affections cutanées ou affections des muqueuses provoquées par les goudrons de houille, les huiles de houille (comprenant les fractions de distillation dites phénoliques, naphthaléniques, acénaphténiques, anthracéniques et chryséniques), les brais de houil 16

15.2. Chemical safety assessment

The chemical safety assessment has been carried out for the components of the mixture listed in section 3 of the SDS. Exposure scenarios relevant for these substances are annexed to this eSDS.

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: Other information

List of abbreviations

vPvB: very Persistent, very Bioaccumulative.
PBT: Persistent, bioaccumulative, toxic.
CEN: European Committee for Standardization (Comité Européen de Normalisation).
TWA: Time Weighted Average.
STEL: Short-term Exposure Limit.
TLV: Threshold Limit Value.

References

ACGIH
IARC Monographs. Overall Evaluation of Carcinogenicity
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Chemical Abstracts Service Registry Handbook
CRC: Handbook of Chemistry and Physics
ILO Safety Cards
International Labour Organization
International Maritime Organization Marine Pollutants List
NFPA Hazardous Chemical Data Sheets
NIOSH Pocket Guide
Registry of Toxic Effects of Chemical Substances (RTECS)
US DOT Hazardous Materials Regulations
Chemical safety report. Korea. Dangerous Substances Threshold Quantity (Presidential Decree of Dangerous Substances Safety Management Act No. 18406, Schedule 1)
Korea. Regulated volatile organic compounds (VOCs) (MOE Notice No. 2001-36, March 8, 2001, as amended)

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any statements, which are not written out in full under sections 2 to 15

H224 Extremely flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H331 Toxic if inhaled.
H340 May cause genetic defects.
H350 May cause cancer.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

Training information

Follow training instructions when handling this material.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.