

1. Identification

Product identifier	HyPrint MVI 150BS
Other means of identification	Not available.
Recommended use	Pigments; Printing Inks
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer:	Ergon Refining
Address:	2611 Haining Rd Vicksburg, Mississippi 39183
Contact Name:	Will Poe
Telephone:	1.601.630.8319
E-mail:	will.poe@ergon.com
Emergency Contacts	
Ergon Refining:	1.601.638.4960 Normal Business Hours
Chemtrec:	1.800.424.9300 After Business Hours (North America Only) 1.703.527.3887 After Business Hours (International)

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Not classified.
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.

Label elements

Hazard symbol	None.
Signal word	Not applicable.
Hazard statement	Not applicable.
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.

Hazard(s) not otherwise classified (HNOC) See section 11 of the SDS for additional information on health hazards.

Supplemental information None.

3. Composition/information on ingredients
Mixtures

Chemical name	Common name and synonyms	CAS number	%
RESIDUAL OILS (PETROLEUM), HYDROTREATED		64742-57-0	75 - 95
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC		64742-52-5	5 - 25

Composition comments A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly greater than C20 through C50 and boiling above 400 °C and produces a finished oil with viscosity near 3500 SUS at 100°F.

4. First-aid measures

Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.
Skin contact	Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact	Flush thoroughly with water. If irritation occurs, get medical assistance.
Ingestion	Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Defatting of the skin.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Contact physician if discomfort continues.

5. Fire-fighting measures

Suitable extinguishing media	Halon. Dry chemicals. Foam. Carbon dioxide (CO ₂). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Specific hazards arising from the chemical	No unusual fire or explosion hazards noted.
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire-fighting equipment/instructions	Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurized air mask if product is involved in a fire.
General fire hazards	No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.
Methods and materials for containment and cleaning up	Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling	Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.
Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Material	Type	Value	Form
HyPrint MVI 150BS	PEL	5 mg/m ³	Mist.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
RESIDUAL OILS (PETROLEUM), HYDROTREATED (CAS 64742-57-0)	PEL	5 mg/m3	Mist.

US. ACGIH Threshold Limit Values

Material	Type	Value	Form
HyPrint MVI 150BS	TWA	5 mg/m3	Inhalable fraction.
Components	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
RESIDUAL OILS (PETROLEUM), HYDROTREATED (CAS 64742-57-0)	TWA	5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Material	Type	Value	Form
HyPrint MVI 150BS	STEL	10 mg/m3	Mist.
Components	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
RESIDUAL OILS (PETROLEUM), HYDROTREATED (CAS 64742-57-0)	TWA	5 mg/m3	Mist.
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Adequate ventilation should be provided whenever the material is heated or mists are generated. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Goggles/face shield are recommended.

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection

Under normal conditions, respirator is not normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Not available.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance	Clear & bright
Physical state	Liquid.
Form	Liquid.
Color	Yellow to Amber.
Odor	Mild Petroleum Odor
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	< 45 °F (< 7.22 °C) ASTM D 5949/ ISO 3016
Initial boiling point and boiling range	> 700 °F (> 371.11 °C) ASTM D 2887/ ISO 3294
Flash point	>= 510.0 °F (>= 265.6 °C) Cleveland Open Cup ASTM D 92/ ISO 2592
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	1
Relative density	0.91 (60 °F (15.56 °C) ASTM D 4052/ ISO 12185)
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not established.
Auto-ignition temperature	> 599 °F (> 315 °C) ASTM E 659
Decomposition temperature	Not available.
Viscosity	640 cSt (104 °F (40 °C) ASTM D 445/ ISO 3104)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Ingestion	May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration.
Inhalation	May be harmful if inhaled. However, this product does not currently meet the criteria for classification.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	May be irritating to eyes.
Symptoms related to the physical, chemical and toxicological characteristics	Not available.

Information on toxicological effects

Acute toxicity	Not classified.
Skin corrosion/irritation	Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.
Serious eye damage/eye irritation	Not classified.
Respiratory or skin sensitization	
Respiratory sensitization	Not classified.
Skin sensitization	Not classified.
Germ cell mutagenicity	Non-mutagenic based on Modified Ames Assay.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	Contains no ingredient listed as toxic to reproduction
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	Prolonged or repeated contact may cause drying, cracking, or irritation of the skin.

12. Ecological information

Ecotoxicity	Not expected to be harmful to aquatic organisms.
Persistence and degradability	Not inherently biodegradable.
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
Mobility in soil	Not available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
Hazardous waste code	Not applicable.
Waste from residues / unused products	Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not available.

15. Regulatory information

US federal regulations	This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List. CERCLA/SARA Hazardous Substances - Not applicable.
-------------------------------	---

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

References

ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Chemical Abstracts Service Registry Handbook
CRC: Handbook of Chemistry and Physics
ILO Safety Cards
International Labour Organization
International Maritime Organization Marine Pollutants List
NFPA Hazardous Chemical Data Sheets
NIOSH Pocket Guide
US DOT Hazardous Materials Regulations

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.