

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Trade name or designation of the mixture** HyVolt GO  
**Registration number** 01-2119480375-34  
**Synonyms** None.  
**Issue date** 10-October-2017  
**Version number** 01

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Not available.  
**Uses advised against** None known.

**1.3. Details of the supplier of the safety data sheet**

**MANUFACTURER:** Ergon Refining, Inc.  
2611 Haining Rd  
Vicksburg, Mississippi 39181  
**EU Contact:** sds@ergon.com  
Drève Richelle 161 Building C  
B-1410 Waterloo, Belgium

**Emergency Phone Numbers:**

**Ergon Refining, Inc.:** + 1.601.638.4960 Normal Business Hours  
**Chemtrec:** + 1.800.424.9300 After Business Hours (North America)  
+ 1.703.527.3887 (International)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

**Classification according to Regulation (EC) No 1272/2008 as amended****Health hazards**

Aspiration hazard Category 1

H304 - May be fatal if swallowed and enters airways.

**Hazard summary** Harmful by inhalation.

**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended**

**Contains:** Distillates (petroleum), hydrotreated light naphthenic

**Hazard pictograms**

**Signal word** Danger

**Hazard statements**

H304 May be fatal if swallowed and enters airways.

**Precautionary statements****Prevention**

P260 Do not breathe gas/mist/vapours/spray.

**Response**

P331  
P301 + P310

Do NOT induce vomiting.  
IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

#### Storage

P405

Store locked up.

#### Disposal

P501

See section 13 of this SDS for disposal instructions.  
Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

#### Supplemental label information

None.

#### 2.3. Other hazards

None known.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Distillates (petroleum), hydrotreated light naphthenic	67-99,5%	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	
<b>Classification:</b>	Asp. Tox. 1;H304				
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based	0-30%	72623-86-0 276-737-9	-	649-482-00-X	
<b>Classification:</b>	-				L
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC	0-3%	64741-89-5 265-091-3	-	649-455-00-2	
<b>Classification:</b>	-				L

## SECTION 4: First aid measures

#### General information

Contact physician if discomfort continues.

#### 4.1. Description of first aid measures

##### Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.

##### Skin contact

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

##### Eye contact

Flush thoroughly with water. If irritation occurs, get medical assistance.

##### Ingestion

Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control centre immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Defatting of the skin.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

#### General fire hazards

No unusual fire or explosion hazards noted.

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Halon. Dry chemicals. Foam. Carbon dioxide (CO<sub>2</sub>). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

##### Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

No unusual fire or explosion hazards noted.

### 5.3. Advice for firefighters

#### Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

#### Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

#### For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

### 6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

### 6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Belgium. Exposure Limit Values.

Material	Type	Value	Form
HyVolt GO	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

##### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Material	Type	Value
HyVolt GO	TWA	5 mg/m3

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3

**Czech Republic. OELs. Government Decree 361**

<b>Material</b>	<b>Type</b>	<b>Value</b>	
HyVolt GO	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	Ceiling	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

**Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, An. 2 & 3**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO	TLV	1 mg/m3	Mist.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TLV	1 mg/m3	Mist.

**Finland. Workplace Exposure Limits**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO	TWA	5 mg/m3	Mist.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.

**Greece. OELs (Decree No. 90/1999, as amended)**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO	TWA	5 mg/m3	Mist.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Mist.

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO <b>Components</b>	Ceiling <b>Type</b>	5 mg/m3 <b>Value</b>	Mist. <b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	Ceiling	5 mg/m3	Mist.

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO <b>Components</b>	TWA <b>Type</b>	1 mg/m3 <b>Value</b>	Mist. <b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	1 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	1 mg/m3	Mist.

**Ireland. Occupational Exposure Limits**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO <b>Components</b>	TWA <b>Type</b>	0,2 mg/m3 <b>Value</b>	Inhalable fraction. <b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Inhalable fraction.

**Italy. Occupational Exposure Limits**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO <b>Components</b>	TWA <b>Type</b>	5 mg/m3 <b>Value</b>	Inhalable fraction. <b>Form</b>
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Inhalable fraction.

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO	STEL	3 mg/m3	Fume and mist.
<b>Components</b>	TWA <b>Type</b>	1 mg/m3 <b>Value</b>	Fume and mist. <b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.

**Netherlands. OELs (binding)**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
-----------------	-------------	--------------	-------------

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
-------------------	-------------	--------------	-------------

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TWA	5 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Norway. Administrative Norms for Contaminants in the Workplace**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
-----------------	-------------	--------------	-------------

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
-------------------	-------------	--------------	-------------

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
	TLV	1 mg/m3	Mist.

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	TLV	1 mg/m3	Mist.
	TLV	1 mg/m3	Mist.

**Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
-----------------	-------------	--------------	-------------

HyVolt GO	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
-----------------	-------------	--------------	-------------

HyVolt GO	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

<b>Material</b>	<b>Type</b>	<b>Value</b>	
HyVolt GO	STEL	10 mg/m3	
	TWA	5 mg/m3	
<b>Components</b>	<b>Type</b>	<b>Value</b>	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	
	TWA	5 mg/m3	
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	3 mg/m3	Fume and mist.
	TWA	15 ppm 1 mg/m3 5 ppm	Fume and mist. Fume and mist. Fume and mist.

**Spain. Occupational Exposure Limits**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Sweden. Occupational Exposure Limit Values**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt GO	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.

**Sweden. Occupational Exposure Limit Values**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)	STEL	3 mg/m <sup>3</sup>	Mist.
	TWA	1 mg/m <sup>3</sup>	Mist.
<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).		
<b>Recommended monitoring procedures</b>	Not available.		
<b>Derived no effect levels (DNELs)</b>	Not available.		
<b>Predicted no effect concentrations (PNECs)</b>	Not available.		
<b>8.2. Exposure controls</b>			
<b>Appropriate engineering controls</b>	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.		
<b>Individual protection measures, such as personal protective equipment</b>			
<b>General information</b>	Wear suitable protective equipment.		
<b>Eye/face protection</b>	Goggles/face shield are recommended.		
<b>Skin protection</b>			
<b>- Hand protection</b>	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.		
<b>- Other</b>	Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.		
<b>Respiratory protection</b>	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN14387.		
<b>Thermal hazards</b>	Not available.		
<b>Hygiene measures</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.		
<b>Environmental exposure controls</b>	Not available.		

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Appearance</b>	Clear & bright
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	Water White
<b>Odour</b>	Mild Petroleum Odor
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	<= -40 °C (<= -40 °F) ASTM D5950 estimated / <= -40 °C (<= -40 °F) ASTM D5950
<b>Initial boiling point and boiling range</b>	>= 285 °C (>= 545 °F) ASTM D86 estimated
<b>Flash point</b>	>= 140,0 °C (>= 284,0 °F) Pensky-Martens Closed Cup ASTM D93
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.



<b>Flammability limit - upper (%)</b>	Not available.
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Relative density</b>	0,89 ASTM D1298
<b>Relative density temperature</b>	20 °C (68 °F)
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Solubility (other)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not established.
<b>Auto-ignition temperature</b>	>= 315 °C (>= 599 °F)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	<= 11 mm <sup>2</sup> /s (40 °C (104 °F) ASTM D445)
<b>Explosive properties</b>	Not available.
<b>Oxidising properties</b>	Not available.

## 9.2. Other information

**VOC** 0,75 % estimated

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	Strong oxidising agents.
<b>10.2. Chemical stability</b>	Stable.
<b>10.3. Possibility of hazardous reactions</b>	Hazardous polymerisation does not occur.
<b>10.4. Conditions to avoid</b>	Avoid temperatures exceeding the flash point.
<b>10.5. Incompatible materials</b>	Strong oxidising agents.
<b>10.6. Hazardous decomposition products</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

## SECTION 11: Toxicological information

<b>General information</b>	Not available.
<b>Information on likely routes of exposure</b>	
<b>Inhalation</b>	May be fatal if swallowed and enters airways.
<b>Skin contact</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	May be irritating to eyes.
<b>Ingestion</b>	May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration. May be fatal if swallowed and enters airways.
<b>Symptoms</b>	Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest.
<b>11.1. Information on toxicological effects</b>	
<b>Acute toxicity</b>	Not applicable.
<b>Skin corrosion/irritation</b>	May cause defatting of the skin, but is neither an irritant nor a sensitizer.
<b>Serious eye damage/eye irritation</b>	Not classified. May cause minor irritation on eye contact.
<b>Respiratory sensitisation</b>	Not classified.
<b>Skin sensitisation</b>	Not classified. May cause defatting of the skin, but is not an irritant.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Nota L - Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.
<b>Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)</b>	
Not listed.	
<b>Reproductive toxicity</b>	Contains no ingredient listed as toxic to reproduction
<b>Specific target organ toxicity - single exposure</b>	Not classified.

<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Mixture versus substance information</b>	Not available.
<b>Other information</b>	Risk of chemical pneumonia after aspiration.

## SECTION 12: Ecological information

<b>12.1. Toxicity</b>	Not expected to be harmful to aquatic organisms.
<b>12.2. Persistence and degradability</b>	Not inherently biodegradable.
<b>12.3. Bioaccumulative potential</b>	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
<b>Partition coefficient n-octanol/water (log Kow)</b>	Not established.
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	Not available.
<b>12.5. Results of PBT and vPvB assessment</b>	Not applicable.
<b>12.6. Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.
<b>EU waste code</b>	Not applicable. Waste codes should be assigned by the user based on the application for which the product was used.
<b>Disposal methods/information</b>	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

## SECTION 14: Transport information

### ADR

14.1. - 14.6.: Not regulated as dangerous goods.

### RID

14.1. - 14.6.: Not regulated as dangerous goods.

### ADN

14.1. - 14.6.: Not regulated as dangerous goods.

### IATA

14.1. - 14.6.: Not regulated as dangerous goods.

### IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code** Not available.

**General information** Not regulated as dangerous goods.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex I**

Not listed.

**Regulation (EC) No. 2037/2000 on substances that deplete the ozone layer, Annex II**

Not listed.

**Regulation (EC) No. 850/2004 on persistent organic pollutants, Annex I**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry**

Not listed.

**Regulation (EC) No. 1907/2006, Article 59(1). Candidate List**

Not listed.

**Authorisations****Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use****Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)  
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)  
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)  
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)  
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)  
DISTILLATES (PETROLEUM), SOLVENT-REFINED LIGHT PARAFFINIC (CAS 64741-89-5)  
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)

**Other EU regulations****Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Not listed.

**Other regulations**

The product is classified and labelled in accordance with EC directives or respective national laws  
This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

**National regulations**

Germany: WGK 1

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information****List of abbreviations**

Not available.

**References**

ACGIH  
IARC Monographs. Overall Evaluation of Carcinogenicity  
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices  
Chemical Abstracts Service Registry Handbook  
CRC: Handbook of Chemistry and Physics  
ILO Safety Cards  
International Labour Organization  
International Maritime Organization Marine Pollutants List  
NFPA Hazardous Chemical Data Sheets  
NIOSH Pocket Guide  
Registry of Toxic Effects of Chemical Substances (RTECS)  
US DOT Hazardous Materials Regulations

**Information on evaluation method leading to the classification of mixture**

Not available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H304 May be fatal if swallowed and enters airways.

**Revision information**

None.

**Training information**

Not available.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.