

SAFETY DATA SHEET

Ergon-West Virginia, Inc.

1. Identification

Product identifier	Ultra Low Sulfur Diesel, Dyed
Other means of identification	Not available.
Recommended use	Fuels
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer:	Ergon - West Virginia, Inc.
Address:	9995 Ohio River Blvd. Newell, WV 26050
E-mail:	sds@ergon.com
Emergency Contacts	
Ergon - West Virginia, Inc. :	1-304-387-4343 Normal Business Hours
Chemtrec:	1-800-424-9300 After Business Hours (North America Only) 1-703-527-3887 After Business Hours (International)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Acute toxicity, oral	Category 4
	Skin corrosion/irritation	Category 2
	Carcinogenicity	Category 2
	Specific target organ toxicity, repeated exposure	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning
Hazard statement	Combustible liquid. Harmful if swallowed. Causes skin irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or vapor. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. Rinse mouth. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DIESEL FUEL		68476-34-6	80 - 100

Chemical name	Common name and synonyms	CAS number	%
Biodiesel (Canola derived)		129828-16-6	0 - 20
Biodiesel (Fatty Acid, Methyl Ester)		68937-84-8	0 - 20
Biodiesel (Rapeseed derived)		73891-99-3	0 - 20
Biodiesel (Soybean derived)		67784-80-9	0 - 20
Biodiesel (Tallow derived)		61788-61-2	0 - 20
XYLENE		1330-20-7	0.25
ETHYLBENZENE		100-41-4	< 0.1
TOLUENE		108-88-3	< 0.1

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.

Skin contact

Remove and isolate contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Rinse skin with water/shower. For minor skin contact, avoid spreading material on unaffected skin. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Irritation of eyes and mucous membranes. Irritant effects.

Indication of immediate medical attention and special treatment needed

In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water spray. Water fog. Dry powder. Carbon dioxide (CO₂). Alcohol resistant foam. Halon.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

By heating and fire, harmful vapors/gases may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.

Specific methods

In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers.

General fire hazards

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Remove sources of ignition. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb spillage with non-combustible, absorbent material. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Following product recovery, flush area with water. Prevent product from entering drains

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Use personal protective equipment as required. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. Wash hands thoroughly after handling. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Store in a well-ventilated place. Store in a closed container away from incompatible materials. Use care in handling/storage. Store in accordance with local/regional/national/international regulation.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m3
XYLENE (CAS 1330-20-7)	PEL	100 ppm
		435 mg/m3
		100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
TOLUENE (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Material	Type	Value	Form
Ultra Low Sulfur Diesel, Dyed (CAS Mixture)	TWA	100 mg/m3	Inhalable fraction and vapor.
Components	Type	Value	Form
DIESEL FUEL (CAS 68476-34-6)	TWA	100 mg/m3	Inhalable fraction and vapor.
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm	
TOLUENE (CAS 108-88-3)	TWA	20 ppm	
XYLENE (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards Components

Components	Type	Value
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3
	TWA	125 ppm 435 mg/m3
TOLUENE (CAS 108-88-3)	STEL	100 ppm 560 mg/m3
	TWA	150 ppm 375 mg/m3 100 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
TOLUENE (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
XYLENE (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

TOLUENE (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

TOLUENE (CAS 108-88-3) Skin designation applies.

US ACGIH Threshold Limit Values: Skin designation

DIESEL FUEL (CAS 68476-34-6) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

Wear suitable protective clothing. Wear protective gloves. Normal work clothing (long sleeved shirts and long pants) is recommended.

Skin protection**Respiratory protection**

Use personal protective equipment as required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. No personal respiratory protective equipment normally required.

Thermal hazards

Not available.

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance	Liquid.
Physical state	Liquid.
Form	Liquid.
Color	Light yellow or Straw
Odor	Mild Petroleum Odor

Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	> -20 °F (> -28.89 °C) ASTM D 5949
Initial boiling point and boiling range	340 - 640 °F (171.11 - 337.78 °C) ASTM D 86
Flash point	>= 130.0 °F (>= 54.4 °C) Pensky-Martens Closed Cup ASTM D 93
Evaporation rate	< 0.1
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 1 mm Hg at 20°C
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	2.2 cSt (100 °F (37.78 °C) ASTM D 445)

10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Risk of ignition. Stable under normal temperature conditions.
Possibility of hazardous reactions	Will not occur.
Conditions to avoid	Heat, flames and sparks. High temperatures.
Incompatible materials	Strong acids, alkalies and oxidizing agents.
Hazardous decomposition products	Combustion products may include sulfur oxides and hydrogen sulfide. Upon decomposition, this product emits carbon monoxide, carbon dioxide, and water.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Harmful if swallowed.
Inhalation	Prolonged inhalation may be harmful. May cause damage to organs by inhalation.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if swallowed. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Product	Species	Test Results
Ultra Low Sulfur Diesel, Dyed (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	17200 g/kg estimated

Product	Species	Test Results
<i>Other</i> LD50	Rat	1520.0052 mg/kg estimated
Components	Species	Test Results
ETHYLBENZENE (CAS 100-41-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	17800 mg/kg
<i>Oral</i>		
LD50	Rat	3500 mg/kg
<i>Other</i>		
LD50	Mouse	2272 mg/kg
TOLUENE (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
<i>Inhalation</i>		
LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	2.6 g/kg
<i>Other</i>		
LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg
XYLENE (CAS 1330-20-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 43 g/kg
<i>Inhalation</i>		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
<i>Oral</i>		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg
<i>Other</i>		
LD50	Rat	3.8 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cancer.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
DIESEL FUEL (CAS 68476-34-6)	3 Not classifiable as to carcinogenicity to humans.	
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
TOLUENE (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Based on available data, the classification criteria are not met.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Contains a substance which causes risk of hazardous effects to the environment.

Product	Species	Test Results
Ultra Low Sulfur Diesel, Dyed (CAS Mixture)		
Fish	LC50	18474.9707 mg/l, 96 hours estimated
Components	Species	Test Results
ETHYLBENZENE (CAS 100-41-4)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 7.5 - 11 mg/l, 96 hours
TOLUENE (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours
XYLENE (CAS 1330-20-7)		
Aquatic		
Fish	LC50	Bluegill (Lepomis macrochirus) 7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

ETHYLBENZENE	3.15
TOLUENE	2.73
XYLENE	3.12 - 3.2

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. Do not discharge into drains, water courses or onto the ground.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

TOLUENE (CAS 108-88-3)	U220
XYLENE (CAS 1330-20-7)	U239

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number NA1993
UN proper shipping name Combustible Liquid, n.o.s.
Transport hazard class(es)
Class Combustible Liquid
Subsidiary risk -
Packing group III
Special precautions for user Not available.

IATA

UN number UN1202
UN proper shipping name Diesel Fuel
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards No.
ERG Code 3L
Special precautions for user Not available.
Other information
Passenger and cargo aircraft Allowed.
Cargo aircraft only Allowed.

IMDG

UN number UN1202
UN proper shipping name DIESEL FUEL
Transport hazard class(es)
Class 3
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant No.
EmS F-E, S-E
Special precautions for user Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ETHYLBENZENE (CAS 100-41-4)	Listed.
TOLUENE (CAS 108-88-3)	Listed.
XYLENE (CAS 1330-20-7)	Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No

Hazardous chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLBENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2))

TOLUENE (CAS 108-88-3)

DEA Essential Chemical Code Number

TOLUENE (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

TOLUENE (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

TOLUENE (CAS 108-88-3) 594

US state regulations Product may be subject to reporting in states other than those listed for individual components.

US. Massachusetts RTK - Substance List

ETHYLBENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

DIESEL FUEL (CAS 68476-34-6)	10000 LBS
ETHYLBENZENE (CAS 100-41-4)	500 LBS
TOLUENE (CAS 108-88-3)	500 LBS
XYLENE (CAS 1330-20-7)	500 LBS

US. Pennsylvania RTK - Hazardous Substances

DIESEL FUEL (CAS 68476-34-6)
ETHYLBENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. Rhode Island RTK

ETHYLBENZENE (CAS 100-41-4)
TOLUENE (CAS 108-88-3)
XYLENE (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 05-07-2014

Revision date 05-21-2015

Version # 02

References

ACGIH
EPA: AQUIRE database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Product and Company Identification: Product and Company Identification
Hazard(s) identification: Supplemental information
Toxicological information: Acute toxicity
Disposal considerations: Hazardous waste code
Regulatory information: <INDENT>
GHS: Classification