

SAFETY DATA SHEET

Ergon-West Virginia, Inc.

1. Identification

Product identifier	Unleaded Mid-Grade with 10% Ethanol
Other means of identification	Not available.
Recommended use	Not available.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer:	Ergon - West Virginia, Inc.
Address:	9995 Ohio River Blvd. Newell, WV 26050
E-mail:	sds@ergon.com
Emergency Contacts	
Ergon - West Virginia, Inc. :	1-304-387-4343 Normal Business Hours
Chemtrec:	1-800-424-9300 After Business Hours (North America Only) 1-703-527-3887 After Business Hours (International)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 1
Health hazards	Acute toxicity, oral	Category 3
	Acute toxicity, inhalation	Category 4
	Carcinogenicity	Category 1A
	Reproductive toxicity (fertility, the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Not available.
Hazard statement	Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Harmful if inhaled. Extremely flammable liquid and vapor. May cause cancer. Toxic if swallowed.
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or vapor. Do not eat, drink or smoke when using this product. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Ground/bond container and receiving equipment. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Keep container tightly closed.
Response	In case of fire: Use CO2 for extinction. Wash hands after handling. Specific treatment see Section 4 of this SDS. IF exposed or concerned: Get medical advice/attention. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
Storage	Store away from incompatible materials. Store locked up. Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions.

Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
GASOLINE		86290-81-5	< 93
ETHANOL		64-17-5	5 - 10
BENZENE, DIMETHYL		1330-20-7	1 - 10
BENZENE, METHYL-		108-88-3	1 - 10
HEXANE		110-54-3	< 5
BENZENE		71-43-2	< 2
ETHYLBENZENE		100-41-4	< 2
NAPHTHALENE		91-20-3	< 1

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Remove and isolate contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash clothing separately before reuse. For minor skin contact, avoid spreading material on unaffected skin.
Eye contact	Get medical attention if irritation develops and persists. Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Remove contact lenses, if present and easy to do. Continue rinsing.
Ingestion	If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Persons with pre-existing respiratory tract, skin, lung (such as asthma), and kidney disorders may be aggravated by exposure to this product. Light hydrocarbons like this one have been associated with cardiac sensitization in abuse situations. Hypoxia or the injection of adrenaline-like substances enhances these effects.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Water Spray or Fog. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may travel considerable distance to a source of ignition and flash back.
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage**Precautions for safe handling**

Observe good industrial hygiene practices. Avoid prolonged and repeated contact. Wear appropriate personal protective equipment. Do not use in areas without adequate ventilation. Do not empty into drains. Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place with adequate ventilation. Keep away from incompatible materials, open flames, and high temperatures.

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
BENZENE, DIMETHYL (CAS 1330-20-7)	PEL	435 mg/m ³
		100 ppm
ETHANOL (CAS 64-17-5)	PEL	1900 mg/m ³
		1000 ppm
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m ³
		100 ppm
HEXANE (CAS 110-54-3)	PEL	1800 mg/m ³
		500 ppm
NAPHTHALENE (CAS 91-20-3)	PEL	50 mg/m ³
		10 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
BENZENE (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
BENZENE, METHYL- (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
BENZENE, DIMETHYL (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm
BENZENE, METHYL- (CAS 108-88-3)	TWA	20 ppm
ETHANOL (CAS 64-17-5)	STEL	1000 ppm
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm
GASOLINE (CAS 86290-81-5)	STEL	500 ppm
	TWA	300 ppm
HEXANE (CAS 110-54-3)	TWA	50 ppm

US. ACGIH Threshold Limit Values Components

Components	Type	Value
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm

US. NIOSH: Pocket Guide to Chemical Hazards Components

Components	Type	Value
BENZENE (CAS 71-43-2)	STEL	1 ppm
	TWA	0.1 ppm
BENZENE, METHYL- (CAS 108-88-3)	STEL	560 mg/m3
	TWA	150 ppm 375 mg/m3
ETHANOL (CAS 64-17-5)	TWA	100 ppm 1900 mg/m3
	TWA	1000 ppm
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3
	TWA	125 ppm 435 mg/m3
HEXANE (CAS 110-54-3)	TWA	100 ppm 180 mg/m3
	TWA	50 ppm
NAPHTHALENE (CAS 91-20-3)	STEL	75 mg/m3
	TWA	15 ppm 50 mg/m3 10 ppm

Biological limit values**ACGIH Biological Exposure Indices Components**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE (CAS 71-43-2)	25 µg/g	S-Phenylmercapturic acid	Creatinine in urine	*
BENZENE, DIMETHYL (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, METHYL- (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
		Toluene	Urine	*
		Toluene	Blood	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
		2,5-Hexanedion, without hydrolysis	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

BENZENE (CAS 71-43-2)	Can be absorbed through the skin.
BENZENE, METHYL- (CAS 108-88-3)	Can be absorbed through the skin.
HEXANE (CAS 110-54-3)	Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BENZENE, METHYL- (CAS 108-88-3)	Skin designation applies.
---------------------------------	---------------------------

US ACGIH Threshold Limit Values: Skin designation

BENZENE (CAS 71-43-2)	Can be absorbed through the skin.
HEXANE (CAS 110-54-3)	Can be absorbed through the skin.
NAPHTHALENE (CAS 91-20-3)	Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Hand protection	When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Color	Light orange.
Odor	Characteristic.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-173.38 °F (-114.1 °C) estimated
Initial boiling point and boiling range	85 °F (29.44 °C) IBP
Flash point	-45.0 °F (-42.8 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.1 % estimated
Flammability limit - upper (%)	8 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	< 0.8
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	437 °F (225 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions. Instability caused by elevated temperatures.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide, and water.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Harmful if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
------------------	--

Inhalation Prolonged inhalation may be harmful.
Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results
Unleaded Mid-Grade with 10% Ethanol (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	1566.6666 ml/kg estimated 577.1815 g/kg estimated
	Rat	6666.667 g/kg estimated
<i>Inhalation</i>		
LC50	Mouse	44444.4453 ppm, 24 Hours estimated 781.2344 mg/l, 4 Hours estimated
	LD	Mouse
<i>Oral</i>		
LD50	Dog	110.1741 g/kg estimated
	Guinea pig	112.1772 g/kg estimated
	Mouse	36856.6563 mg/kg estimated
	Rat	1093.1799 mg/kg estimated
	Wistar rat	2450 mg/kg estimated
<i>Other</i>		
LD50	Mouse	3066.2998 mg/kg estimated 9.348 ml/kg estimated
	Rat	76.7026 mg/kg estimated

Components	Species	Test Results
BENZENE (CAS 71-43-2)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	9980 ppm
	Rat	10000 ppm, 7 Hours
<i>Oral</i>		
LD50	Mouse	4700 mg/kg
	Rat	3306 mg/kg
<i>Other</i>		
LD50	Mouse	340 mg/kg 0.28 ml/kg
	Rat	2.89 mg/kg
BENZENE, DIMETHYL (CAS 1330-20-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 43 g/kg
<i>Inhalation</i>		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
<i>Oral</i>		
LD50	Mouse	1590 mg/kg
	Rat	3523 - 8600 mg/kg

Components	Species	Test Results
<i>Other</i> LD50	Rat	3.8 mg/kg
BENZENE, METHYL- (CAS 108-88-3)		
Acute		
<i>Dermal</i> LD50	Rabbit	12124 mg/kg 14.1 ml/kg
<i>Inhalation</i> LC50	Mouse	5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours
<i>Oral</i> LD50	Rat	2.6 g/kg
<i>Other</i> LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg
ETHANOL (CAS 64-17-5)		
Acute		
<i>Inhalation</i> LC50	Mouse	39 mg/l, 4 Hours
	Rat	20000 ppm, 10 Hours
<i>Oral</i> LD50	Dog	5.5 g/kg
	Guinea pig	5.6 g/kg
	Mouse	3450 mg/kg
	Rat	6.2 g/kg
<i>Other</i> LD50	Mouse	933 mg/kg
	Rat	1440 mg/kg
ETHYLBENZENE (CAS 100-41-4)		
Acute		
<i>Dermal</i> LD50	Rabbit	17800 mg/kg
<i>Oral</i> LD50	Rat	3500 mg/kg
<i>Other</i> LD50	Mouse	2272 mg/kg
HEXANE (CAS 110-54-3)		
Acute		
<i>Inhalation</i> LC50	Mouse	48000 ppm, 4 Hours
<i>Oral</i> LD50	Rat	24 mg/kg
	Wistar rat	49 mg/kg
NAPHTHALENE (CAS 91-20-3)		
Acute		
<i>Dermal</i> LD50	Rabbit	> 2 g/kg
	Rat	> 20 g/kg

Components	Species	Test Results
<i>Oral</i>		
LD50	Guinea pig	1200 mg/kg
	Rat	490 mg/kg
<i>Other</i>		
LD50	Mouse	100 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Contains material which may cause cancer. Hazardous by OSHA criteria.

IARC Monographs. Overall Evaluation of Carcinogenicity

BENZENE (CAS 71-43-2)	1 Carcinogenic to humans.
BENZENE, DIMETHYL (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.
BENZENE, METHYL- (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.
GASOLINE (CAS 86290-81-5)	2B Possibly carcinogenic to humans.
NAPHTHALENE (CAS 91-20-3)	2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

BENZENE (CAS 71-43-2)	Known To Be Human Carcinogen.
NAPHTHALENE (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)	Cancer
-----------------------	--------

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results	
Unleaded Mid-Grade with 10% Ethanol (CAS Mixture)			
Crustacea	EC50	Daphnia	241.4691 mg/l, 48 hours estimated
Fish	LC50	Fish	797.5594 mg/l, 96 hours estimated
Components	Species	Test Results	
BENZENE (CAS 71-43-2)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/l, 96 hours
BENZENE, DIMETHYL (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours
BENZENE, METHYL- (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours

Components		Species	Test Results
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
ETHANOL (CAS 64-17-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7.7 - 11.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
ETHYLBENZENE (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
HEXANE (CAS 110-54-3)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours
NAPHTHALENE (CAS 91-20-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.09 - 3.4 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha)	1.11 - 1.68 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

BENZENE	2.13
BENZENE, DIMETHYL	3.12 - 3.2
BENZENE, METHYL-	2.73
ETHANOL	-0.31
ETHYLBENZENE	3.15
HEXANE	3.9
NAPHTHALENE	3.3

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1203
UN proper shipping name	Gasoline includes gasoline mixed with ethyl alcohol, with not more than 10 percent alcohol
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	144, 177, B1, B33, IB2, T4, TP1
Packaging exceptions	150
Packaging non bulk	202

Packaging bulk 242

IATA

UN number UN1203

UN proper shipping name Petrol

Transport hazard class(es)

Class 3

Subsidiary risk -

Packing group II

Environmental hazards No.

ERG Code 3H

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft Allowed.

Cargo aircraft only Allowed.

IMDG

UN number UN1203

UN proper shipping name MOTOR SPIRIT or GASOLINE or PETROL

Transport hazard class(es)

Class 3

Subsidiary risk -

Packing group II

Environmental hazards

Marine pollutant No.

EmS F-E, S-E

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BENZENE (CAS 71-43-2)	Listed.
BENZENE, DIMETHYL (CAS 1330-20-7)	Listed.
BENZENE, METHYL- (CAS 108-88-3)	Listed.
ETHANOL (CAS 64-17-5)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.

GASOLINE (CAS 86290-81-5)
HEXANE (CAS 110-54-3)
NAPHTHALENE (CAS 91-20-3)

Listed.
Listed.
Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

BENZENE (CAS 71-43-2)

Cancer
Central nervous system
Blood
Aspiration
Skin
Eye
respiratory tract irritation
Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 No

Hazardous chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
BENZENE, DIMETHYL	1330-20-7	1 - 10
HEXANE	110-54-3	< 5
BENZENE	71-43-2	< 2
ETHYLBENZENE	100-41-4	< 2
NAPHTHALENE	91-20-3	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2))

BENZENE, METHYL- (CAS 108-88-3)

DEA Essential Chemical Code Number

BENZENE, METHYL- (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

BENZENE, METHYL- (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

BENZENE, METHYL- (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

BENZENE (CAS 71-43-2)
BENZENE, DIMETHYL (CAS 1330-20-7)
BENZENE, METHYL- (CAS 108-88-3)
ETHANOL (CAS 64-17-5)
ETHYLBENZENE (CAS 100-41-4)
HEXANE (CAS 110-54-3)
NAPHTHALENE (CAS 91-20-3)

US. New Jersey Worker and Community Right-to-Know Act

BENZENE (CAS 71-43-2) 500 LBS
BENZENE, DIMETHYL (CAS 1330-20-7) 500 LBS
BENZENE, METHYL- (CAS 108-88-3) 500 LBS

ETHYLBENZENE (CAS 100-41-4)	500 LBS
HEXANE (CAS 110-54-3)	500 LBS
NAPHTHALENE (CAS 91-20-3)	500 LBS

US. Pennsylvania RTK - Hazardous Substances

BENZENE (CAS 71-43-2)
 BENZENE, DIMETHYL (CAS 1330-20-7)
 BENZENE, METHYL- (CAS 108-88-3)
 ETHANOL (CAS 64-17-5)
 ETHYLBENZENE (CAS 100-41-4)
 GASOLINE (CAS 86290-81-5)
 HEXANE (CAS 110-54-3)
 NAPHTHALENE (CAS 91-20-3)

US. Rhode Island RTK

BENZENE (CAS 71-43-2)
 BENZENE, DIMETHYL (CAS 1330-20-7)
 BENZENE, METHYL- (CAS 108-88-3)
 ETHYLBENZENE (CAS 100-41-4)
 HEXANE (CAS 110-54-3)
 NAPHTHALENE (CAS 91-20-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

BENZENE (CAS 71-43-2)	Listed: February 27, 1987
ETHANOL (CAS 64-17-5)	Listed: April 29, 2011
	Listed: July 1, 1988
ETHYLBENZENE (CAS 100-41-4)	Listed: June 11, 2004
NAPHTHALENE (CAS 91-20-3)	Listed: April 19, 2002

US - California Proposition 65 - CRT: Listed date/Developmental toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
BENZENE, METHYL- (CAS 108-88-3)	Listed: January 1, 1991
ETHANOL (CAS 64-17-5)	Listed: October 1, 1987

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

BENZENE, METHYL- (CAS 108-88-3)	Listed: August 7, 2009
---------------------------------	------------------------

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

BENZENE (CAS 71-43-2)	Listed: December 26, 1997
-----------------------	---------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-22-2015
Version #	01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.