

1. Identification

Product identifier ERTECH 2120
Other means of identification None.
Recommended use Not available.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.
Address 2829 Lakeland Drive
 Jackson, MS 39232
 USA
After hours telephone number 1-800-222-7122
Normal work hours telephone number 1-877-982-7667
Website www.ergonarmor.com
E-mail sds@ergon.com
Emergency 24-hour telephone number CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887
Information on operation hours 8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.
Hazard statement The mixture does not meet the criteria for classification.
Precautionary statement
Prevention Observe good industrial hygiene practices.
Response Wash hands after handling.
Storage Store away from incompatible materials.
Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Not applicable.

3. Composition/information on ingredients
Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	40 - 50
QUARTZ		14808-60-7	1 - 5
Other components below reportable levels			55.7139

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact	If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of asphalt. Wash contact areas with soap and water. If needed, seek medical attention.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed:
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire fighting equipment/instructions	ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.
Specific methods	In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.
Conditions for safe storage, including any incompatibilities	Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
CELLULOSE (CAS 9004-34-6)	PEL	5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m ³	Respirable dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inhalable fume.
CELLULOSE (CAS 9004-34-6)	TWA	10 mg/m ³	
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m ³	Fume.
CELLULOSE (CAS 9004-34-6)	TWA	5 mg/m ³	Respirable.
		10 mg/m ³	Total
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical goggles and face shield are recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

Other

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact. Plastic or rubber gloves, apron and boots.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Heavy-consistency emulsion.

Physical state

Liquid.

Form

Liquid.

Color

Brown

Odor

Mild Petroleum Odor

Odor threshold

n/a

pH

5 - 7

Melting point/freezing point	n/a
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	> 212.0 °F (> 100.0 °C) Cleveland Open Cup
Evaporation rate	n/a
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	n/a
Flammability limit - upper (%)	n/a
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	60 mm Hg at 100°F, approx.
Vapor density	n/a
Relative density	0.9 - 1.1
Solubility(ies)	
Solubility (water)	Slightly
Partition coefficient (n-octanol/water)	n/a
Auto-ignition temperature	> 400 °F (> 204.44 °C)
Decomposition temperature	Not available.
Viscosity	100000 cP
Viscosity temperature	77 °F (25 °C)
Other information	
VOC	0.2 lb/gal maximum

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport
Chemical stability	Stable under normal temperature conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat product.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	May be irritating to eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	May be irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause skin disorders if contact is repeated or prolonged.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity Not available.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Chronic effects Not expected to be hazardous by OSHA criteria.

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product	Species	Test Results
ERTECH 2120		
Aquatic		
Crustacea	EC50 Daphnia	44642.8555 mg/l, 48 hours estimated

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. No components are identified as hazardous wastes. Disposal recommendations are based on uncontaminated material.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Not applicable.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer
lung effects
immune system effects
kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

Classified hazard categories Respiratory or skin sensitization
Reproductive toxicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65

WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)

QUARTZ (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	06-09-2015
Revision date	11-27-2018
Version #	05
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
References	ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Hazard(s) identification: Storage Hazard(s) identification: Hazard statement Hazard(s) identification: GHS Symbols Composition / Information on Ingredients: Disclosure Overrides Physical & Chemical Properties: Multiple Properties Toxicological information: Chronic effects Toxicological information: Reproductivity GHS: Classification