SAFETY DATA SHEET



1. Identification

Product identifier EP57XX Series Part A Coating and Lining (All Colors)

Other means of identification

Synonyms EP5720

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

1-800-222-7122

Normal work hours telephone number

1-877-982-7667

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation 8:00 a.m. to 5:00 p.m.

hours

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Germ cell mutagenicity Category 2
Carcinogenicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic

defects. Suspected of causing cancer. Causes skin irritation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective

gloves/protective clothing/eye protection/face protection.

Response Specific treatment see Section 4 of this SDS. IF ON SKIN: Wash with plenty of soap and water. IF

IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage Store locked up.

Material name: EP57XX Series Part A Coating and Lining (All Colors)

4893 Version #: 08 Revision date: 12-10-2019 Issue date: 04-06-2015

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
PHENOL-FORMALDEHYDE POLYME GLYCIDYL ETHER	R	28064-14-4	20 - 30
QUARTZ		14808-60-7	10 - 20
1,3-DIGLYCIDYLOXYBENZENE		101-90-6	1 - 10
2-METHOXY-1-METHYLETHYL ACETATE		108-65-6	<1
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.	,	64742-95-6	<1
Other components below reportable	e levels		50.665

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

> Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve

or other proper respiratory medical device. Get medical attention, if needed.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a POISON

> CENTER or doctor/physician if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. For minor skin contact, avoid spreading

material on unaffected skin. Take off contaminated clothing and wash before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention

immediately.

Ingestion Call a physician or poison control center immediately. Rinse mouth thoroughly. Never give anything

redness and pain. Prolonged exposure may cause chronic effects.

by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash. Irritant effects. May cause

General information

Take off contaminated clothing and shoes immediately. In case of shortness of breath, give oxygen IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with

water until well after the fire is out. Water runoff can cause environmental damage.

Water fog. Foam. Dry chemical powder. Alcohol foam. Carbon dioxide (CO2).

Specific methods In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

Material name: EP57XX Series Part A Coating and Lining (All Colors)

SDS US

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid skin contact and inhalation of vapors during disposal of spills. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with skin. Avoid prolonged exposure. Avoid contact with clothing. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

CAUTION Store locked up. Keep away from heat, sparks and open flame. Store in a closed container away from incompatible materials. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Store in accordance with local/regional/international regulation.

8. Exposure controls/personal protection

Occupational exposure limits

Components	r Contaminants (29 CFR 1910.1000) Type	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 191	- <u>-</u>		F
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Туре	Value	
2-METHOXY-1-METHYLETH YL ACETATE (CAS 108-65-6)	TWA	50 ppm	

Material name: EP57XX Series Part A Coating and Lining (All Colors)

SDS US

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

2-METHOXY-1-METHYLETHYL ACETATE (CAS 108-65-6) Can be absorbed through the skin.

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. Form Liquid.

Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.

Melting point/freezing point
Initial boiling point and

boiling range

89.6 °F (32 °C) estimated 4046 °F (2230 °C) estimated

Flash point 350.0 °F (176.7 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure 240.97 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 8.69 lb/gal estimated **Flammability class** Combustible IIIB estimated

Specific gravity 1.04 estimated **VOC** 0.13 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

materials.

Incompatible materials Peroxides. Chlorine. Strong acids, alkalies and oxidizing agents.

Hazardous decomposition

If product is burned hazardous gases such as oxides of carbon and nitrogen and various

products hydrocarbons may be produced.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected

Skin contactCauses skin irritation.Eye contactCauses eye irritation.

Ingestion Suspected of causing cancer by ingestion.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritationCauses skin irritation. **Serious eye damage/eye**Causes eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause sensitization by skin contact. **Germ cell mutagenicity** Suspected of causing genetic defects.

Carcinogenicity Possible cancer hazard based on tests with laboratory animals. This product contains crystalline

silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of

exposure are unavailable. Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) 2B Possibly carcinogenic to humans. QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) Reasonably Anticipated to be a Human Carcinogen.

QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does no exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Test Results Product Species EP57XX Series Part A Coating and Lining (All Colors) **Aquatic** Crustacea EC50 Daphnia 21219.168 mg/l, 48 hours estimated Fish LC50 Fish 20816.7891 mg/l, 96 hours estimated Components **Species Test Results**

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER (CAS 28064-14-4)

Aquatic

Acute

Fish LC50 Fish 1 - 10 mg/l

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

EP57XX Series Part A Coating and Lining (All Colors) > 3

Mobility in soil No data available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsDispose in accordance with all applicable regulations. When this product as supplied is to be

discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

UN number UN3077

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL-FORMALDEHYDE

POLYMER GLYCIDYL ETHER), MARINE POLLUTANT

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards

Marine pollutantYesEmSF-A, S-FSpecial precautions forNot available.

user

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

IMDG



Marine pollutant



General information

DOT Regulated Marine Pollutant. IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

QUARTZ (CAS 14808-60-7)

Cancer lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312

Yes

Hazardous chemical

Classified hazard

Acute toxicity (any route of exposure)

categories Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,3-DIGLYCIDYLOXYBENZENE	101-90-6	1 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) Listed: July 1, 1989 QUARTZ (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)

QUARTZ (CAS 14808-60-7)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 04-06-2015 **Revision date** 12-10-2019

Version # 80

NFPA ratings Health: 3

> Flammability: 0 Instability: 0

References EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

> information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Material name: EP57XX Series Part A Coating and Lining (All Colors)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

Revision information

Product and Company Identification: Physical States

Hazard(s) identification: Response

Hazard(s) identification: Supplemental information

Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

Transport Information: Proper Shipping Name/Packing Group

HazReg Data: International Inventories

GHS: Classification

Material name: EP57XX Series Part A Coating and Lining (All Colors)
4893 Version #: 08 Revision date: 12-10-2019 Issue date: 04-06-2015