## SAFETY DATA SHEET



## 1. Identification

Product identifier SC54XX Series Part A Coating and Lining (All Colors)

Other means of identification

**Synonyms** SC5410, SC5420, SC5440

**Recommended use**Not available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.

Address 2829 Lakeland Drive Jackson, MS 39232

**USA** 

After hours telephone

number

1-800-222-7122

Normal work hours telephone number

1-877-982-7667

Website www.ergonarmor.com
E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

**Information on operation** 8:00 a.m. to 5:00 p.m.

hours

## 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1
Germ cell mutagenicity Category 2
Carcinogenicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

**Label elements** 



Signal word Warning

**Hazard statement** Suspected of causing cancer by ingestion. Causes skin irritation. Causes serious eye irritation. May

cause an allergic skin reaction. Suspected of causing genetic defects.

**Precautionary statement** 

**Prevention** Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wear

protective gloves/protective clothing/eye protection/face protection.

**Response** Specific treatment see Section 4 of this SDS. Wash contaminated clothing before reuse. IF exposed

or concerned: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye

irritation persists: Get medical advice/attention.

**Storage** Store locked up.

Material name: SC54XX Series Part A Coating and Lining (All Colors)

**Disposal** 

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

**Supplemental information** 

Not applicable.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER		28064-14-4	25-35
1,3-DIGLYCIDYLOXYBENZENE		101-90-6	10-20
POLYETHYLENE		9002-88-4	1-10
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.		64742-95-6	<1
BENZENE,1-METHYLETHYL-		98-82-8	< 0.1

#### 4. First-aid measures

**Inhalation** If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

> Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve

or other proper respiratory medical device. Get medical attention, if needed.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a POISON

> CENTER or doctor/physician if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. For minor skin contact, avoid spreading

material on unaffected skin. Take off contaminated clothing and wash before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO Eye contact

NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention

immediately.

Ingestion Call a physician or poison control center immediately. Rinse mouth thoroughly. Never give anything

> by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

**Most important** 

symptoms/effects, acute and delayed

**Indication of immediate** medical attention and special

treatment needed **General information**  Skin irritation. May cause an allergic skin reaction. Dermatitis. Rash. Irritant effects. May cause

redness and pain. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off contaminated clothing and shoes immediately. In case of shortness of breath, give oxygen IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in

attendance. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Alcohol foam. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Fire may produce irritating, corrosive and/or toxic gases.

**Special protective equipment** and precautions for

firefighters

Wear suitable protective equipment. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers. Cool containers exposed to flames with

water until well after the fire is out. Water runoff can cause environmental damage.

Specific methods In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

**General fire hazards** No unusual fire or explosion hazards noted.

Material name: SC54XX Series Part A Coating and Lining (All Colors) 4848 Version #: 04 Revision date: 12-10-2019 Issue date: 04-07-2015

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid skin contact and inhalation of vapors during disposal of spills. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

#### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

## Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with skin. Avoid prolonged exposure. Avoid contact with clothing. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash thoroughly after handling. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

CAUTION Store locked up. Keep away from heat, sparks and open flame. Store in a closed container away from incompatible materials. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Store in accordance with local/regional/national/international regulation.

## 8. Exposure controls/personal protection

## **Occupational exposure limits**

Components	Contaminants (29 CFR 1910.1000 Type	Value	
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	PEL	245 mg/m3	
		50 ppm	
US. OSHA Table Z-3 (29 CFR 1910	.1000)		
Components	Туре	Value	Form
POLYETHYLENE (CAS 9002-88-4)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Values	<b>3</b>		
Components	Туре	Value	
BENZENE,1-METHYLETHYL- (CAS 98-82-8)	TWA	50 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards
Components Type

BENZENE,1-METHYLETHYL- TWA 245 mg/m3

(CAS 98-82-8)

50 ppm

**Value** 

**Biological limit values**No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

**US - California OELs: Skin designation** 

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies** 

BENZENE,1-METHYLETHYL- (CAS 98-82-8) Skin designation applies.

**US - Tennessee OELs: Skin designation** 

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation** 

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Safety glasses. If risk of splashing, wear safety goggles or face shield.

Skin protection

**Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear quantilet style

gloves.

**Other** Wear appropriate clothing to prevent any possibility of skin contact.

**Respiratory protection** When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical stateLiquid.FormLiquid.ColorNot available.OdorNot available.

Odor thresholdNot available.pH7 estimatedMelting point/freezing pointNot available.

Initial boiling point and

> 392 °F (> 200 °C)

boiling range

**Flash point** > 302.0 °F (> 150.0 °C)

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits
Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

**Explosive limit - lower** 

Not available.

(%)

**Explosive limit - upper** 

(%)

Not available.

Vapor pressure 82 Pa at 20°C Not available. Vapor density **Relative density** Not available.

Solubility(ies)

Solubility (water) Not available.

**Partition coefficient** > 3

(n-octanol/water)

**Auto-ignition temperature** 572 °F (300 °C) **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

**Density** 13.90 lb/gal 0.01 % estimated Percent volatile Specific gravity 1.67 estimated

## 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

**Chemical stability** 

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible

**Incompatible materials** Peroxides. Chlorine. Strong acids, alkalies and oxidizing agents.

If product is burned hazardous gases such as oxides of carbon and nitrogen and various **Hazardous decomposition** 

products hydrocarbons may be produced.

## 11. Toxicological information

Information on likely routes of exposure

Inhalation May be harmful if inhaled. Skin contact Causes skin irritation.

**Eye contact** Causes serious eye irritation.

Ingestion Suspected of causing cancer by ingestion. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

**Acute toxicity** 

**Test Results** Components **Species** 

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Acute **Inhalation** 

LC50 Mouse 24.7 mg/l, 2 Hours

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause sensitization by skin contact. Germ cell mutagenicity Suspected of causing genetic defects.

4848 Version #: 04 Revision date: 12-10-2019 Issue date: 04-07-2015

Material name: SC54XX Series Part A Coating and Lining (All Colors)

SDS US

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Carcinogenicity** Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6)

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

2B Possibly carcinogenic to humans.

2B Possibly carcinogenic to humans.

POLYETHYLENE (CAS 9002-88-4) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

. . . . . .

**Aspiration hazard** Not available.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, this does not

exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

**Product Test Results Species** SC54XX Series Part A Coating and Lining (All Colors) **Aquatic** EC50 16405.707 mg/l, 48 hours estimated Crustacea Daphnia Fish LC50 Fish 15929.5781 mg/l, 96 hours estimated Components **Species Test Results** BENZENE,1-METHYLETHYL- (CAS 98-82-8) Aquatic EC50 Crustacea Brine shrimp (Artemia sp.) 3.55 - 11.29 mg/l, 48 hours

Crustacea EC50 Brine shrimp (Artemia sp.) 3.55 - 11.29 mg/l, 48 hours
Fish LC50 Rainbow trout,donaldson trout 2.7 mg/l, 96 hours

(Oncorhynchus mykiss)

PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER (CAS 28064-14-4)

**Aquatic** 

Acute

Fish LC50 Fish 1 - 10 mg/l

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** Not available.

Partition coefficient n-octanol / water (log Kow)

SC54XX Series Part A Coating and Lining (All Colors) > 3 BENZENE,1-METHYLETHYL- 3.66

**Mobility in soil** No data available.

**Other adverse effects**No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Dispose in accordance with all applicable regulations. When this product as supplied is to be

discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.

## 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

**Transport in bulk according to** Not available.

Annex II of MARPOL 73/78

and the IBC Code

## 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

## SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312** 

**Hazardous chemical** 

**Classified hazard** categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,3-DIGLYCIDYLOXYBENZENE	101-90-6	10-20	

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

BENZENE,1-METHYLETHYL- (CAS 98-82-8)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA) **US state regulations** 

## California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) Listed: July 1, 1989 BENZENE,1-METHYLETHYL- (CAS 98-82-8) Listed: April 6, 2010

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,3-DIGLYCIDYLOXYBENZENE (CAS 101-90-6) BENZENE,1-METHYLETHYL- (CAS 98-82-8)

SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM. (CAS 64742-95-6)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 04-07-2015

 Revision date
 12-10-2019

Version # 04

NFPA ratings Health: 2

Flammability: 0 Instability: 0

**References** EPA: AQUIRE database

US. IARC Monographs on Occupational Exposures to Chemical Agents

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information** Hazard(s) identification: Hazard statement

Material name: SC54XX Series Part A Coating and Lining (All Colors)