SAFETY DATA SHEET



1. Identification

Product identifier MC-250 Tricor

Other means of identification

Product Code 1693

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer:Tricor Refining, LLC.Address:P.O. Box 5877

Bakersfield, CA 93388

24-hour Telephone

Number:

(661) 393-7110

CHEMTREC: 1-800-424-9300 (North America) 1-703-527-3887 (International)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Warning

Hazard statement Combustible liquid. May cause drowsiness or dizziness.

Precautionary statement

Prevention Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from

heat/sparks/open flames/hot surfaces. - No smoking. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection.

Ground/bond container and receiving equipment. Keep container tightly closed.

Response IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a poison center/doctor if you feel unwell. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	60 - 80
Petroleum Distillate		8008-20-6	20 - 40

Material name: MC-250 Tricor

SDS US

1 (93 - Namina # + 93 - Parising data 10 17 2010 - Laws data 10 31 2014

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Immediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY.

Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of

the asphalt due to the risk of adhesion. Get immediate medical attention.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention or advice.

Ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed Not available.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

- ...

Specific hazards arising from the chemical

Special protective equipment

and precautions for

firefighters

Fire fighting equipment/instructions

Specific methods

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Environmental precautions

Foam. Dry powder. Carbon dioxide (CO2).

Water. Do not use a solid water stream as it may scatter and spread fire. Do not use water jet as

an extinguisher, as this will spread the fire.

Fire may produce irritating, corrosive and/or toxic gases.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers.

6. Accidental release measures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them.

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Prevent further leakage or spillage if safe to do so. Do not contaminate water. No special environmental precautions required. Contact local authorities in case of spillage to drain/aguatic

environment. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling May be ignited by open flame. Keep away from sources of ignition - No smoking. DO NOT handle,

store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid contact with skin. Do not get this material on clothing. Wear personal protective equipment. Do not use in areas without adequate ventilation.

person

Conditions for safe storage,

including any incompatibilities

CAUTION The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Store in a well-ventilated place. Keep container tightly closed. Store in a closed container away from incompatible materials. Keep in an area equipped with sprinklers. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

This mixture has no ingredients that have PEL, TLV, or other recommended exposure limit

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand protection Use gloves with long sleeves. When handling hot material, use heat resistant gloves.

Other Thermally protective apron and long sleeves are recommended when volume of hot material is

significant.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards During product use, there is a risk of thermal burns. Wear appropriate thermal protective clothing,

when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance Brown to black in color.

Physical state Liquid. Form Liquid.

Color Brown - black

Odor Aromatic Mild Petroleum Odor

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.

Initial boiling point and

boiling range

320 - 550 °F (160 - 287.78 °C)

Flash point > 150.0 °F (> 65.6 °C)

Evaporation rate < 1

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 0.3 %

(%)

Flammability limit -

upper (%)

5 %

Explosive limit - lower

Not available.

(%)

Material name: MC-250 Tricor

Explosive limit - upper

(%)

Not available.

Vapor pressure < 50 psi Vapor density > 4.5

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature490 °F (254.44 °C)Decomposition temperatureNot available.ViscosityNot available.

Other information

Density8.13 lb/galFlammability classCombustible IIIA

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Risk of ignition. Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or

low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea

Skin contact Molten material will produce thermal burns.

Eye contact Molten material will produce thermal burns. Harmful in contact with eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Not available.

Information on toxicological effects

Acute toxicity

Product Species Test Results

MC-250 Tricor

Acute Inhalation Vapor

ATEmix 3 mg/l

Skin corrosion/irritation Not available. **Serious eye damage/eye** None known.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available. **Skin sensitization** None known.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not classified. Specific target organ toxicity

Not available.

- single exposure

Specific target organ toxicity

Not available.

- repeated exposure

Aspiration hazard Not available.

Chronic effects Hazardous by OSHA criteria. Prolonged inhalation may be harmful. Repeated absorption may cause

disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause

chronic effects. Not expected to be hazardous by WHMIS criteria.

Further information Symptoms may be delayed. This product has no known adverse effect on human health

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Persistence and degradability Not available. **Bioaccumulative potential** Not available Mobility in soil Not available. Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Disposal recommendations are based on material as supplied. Disposal must be in accordance with

current applicable laws and regulations, and material characteristics at time of disposal.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues /

unused products

Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

14. Transport information

DOT

UN number UN1999 UN proper shipping name Tars, liquid

Transport hazard class(es)

Class 3 **Subsidiary risk** Packing group III

Not available. Special precautions for

user

IATA

UN number UN1999 UN proper shipping name Tars, liquid

Transport hazard class(es)

Class 3 **Subsidiary risk Packing group** III**Environmental hazards** No. **ERG Code** 3L

Special precautions for

user

Not available.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)
Class 3
Subsidiary risk Packing group III

Environmental hazards

Marine pollutantNo.EmSF-E, S-ESpecial precautions forNot available.

user

Transport in bulk according to Not available. **Annex II of MARPOL 73/78**

and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

10-31-2014 **Issue date Revision date** 10-17-2018

Version # 02

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2 Flammability: 2 Instability: 0

References **ACGIH**

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic

Materials)

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits

The information in the sheet was written based on the best knowledge and experience currently **Disclaimer**

available.

Material name: MC-250 Tricor SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision information

Product and Company Identification: Product and Company Identification

Hazard(s) identification: Response Hazard(s) identification: Prevention Hazard(s) identification: Storage

Hazard(s) identification: Hazard statement

Hazard(s) identification: GHS Signal Words Hazard(s) identification: Supplemental information Physical & Chemical Properties: Multiple Properties

Transport Information: Material Transportation Information

Regulatory Information: United States HazReg Data: International Inventories

GHS: Classification