

SAFETY DATA SHEET

1. Identification

Product identifier MC-30
Other means of identification None.
Recommended use Not available.
Recommended restrictions None known.
Manufacturer/Importer/Supplier/Distributor information
Company name Bryan & Bryan Asphalt, L.L.C.
Address P.O. Box 636
Henderson, TX 75653

Telephone number 1-800-222-7122 (Customer Service)
E-mail sds@ergon.com
Emergency telephone number 1-800-424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4
Health hazards Acute toxicity, oral Category 4
Skin corrosion/irritation Category 2
Carcinogenicity Category 2
Specific target organ toxicity, repeated exposure Category 2
Environmental hazards Not classified.
OSHA defined hazards Not classified.
Label elements



Signal word Warning

Hazard statement Combustible liquid. Harmful if swallowed. Causes skin irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or vapor. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	50 - 70
FUELS, DIESEL, NO. 2		68476-34-6	30 - 50

4. First-aid measures

Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Skin contact	Remove and isolate contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Rinse skin with water/shower. For minor skin contact, avoid spreading material on unaffected skin. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Irritant effects.
Indication of immediate medical attention and special treatment needed	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Water. Do not use a solid water stream as it may scatter and spread fire. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Specific methods	In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them.

Methods and materials for containment and cleaning up

Extinguish all flames in the vicinity.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. No special environmental precautions required. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

May be ignited by open flame. Keep away from sources of ignition - No smoking. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid contact with skin. Do not get this material on clothing. Wear personal protective equipment. Do not use in areas without adequate ventilation.

Conditions for safe storage, including any incompatibilities

CAUTION The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Keep away from heat and sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Store in a well-ventilated place. Keep container tightly closed. Store in a closed container away from incompatible materials. Keep in an area equipped with sprinklers. Keep away from food, drink and animal feedingstuffs. Keep out of the reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m ³	Inhalable fraction.
FUELS, DIESEL, NO. 2 (CAS 68476-34-6)	TWA	100 mg/m ³	Inhalable fraction and vapor.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m ³	Fume.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

FUELS, DIESEL, NO. 2 (CAS 68476-34-6)

Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety glasses. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand protection

Use gloves with long sleeves. When handling hot material, use heat resistant gloves.

Other

Thermally protective apron and long sleeves are recommended when volume of hot material is significant.

Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Thermal hazards	During product use, there is a risk of thermal burns. Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Brown to black in color.
Physical state	Liquid.
Form	Liquid.
Color	Brown - black
Odor	Aromatic Mild Petroleum Odor
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	320 - 550 °F (160 - 287.78 °C)
Flash point	> 150.0 °F (> 65.6 °C)
Evaporation rate	< 1
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	0.3 %
Flammability limit - upper (%)	5 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 50 psi
Vapor density	> 4.5
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	490 °F (254.44 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.60 lb/gal
Flammability class	Combustible IIIA

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Risk of ignition. Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful. May cause damage to organs by inhalation.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Harmful if swallowed. Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4)

2B Possibly carcinogenic to humans.

FUELS, DIESEL, NO. 2 (CAS 68476-34-6)

3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Persistence and degradability Not available.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Other adverse effects Not available.

13. Disposal considerations

Disposal instructions Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.

Contaminated packaging Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

14. Transport information

DOT

UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Not available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

DOT





15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4)
FUELS, DIESEL, NO. 2 (CAS 68476-34-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	08-05-2014
Revision date	11-29-2017
Version #	02
Further information	HMIS® is a registered trade and service mark of the NPCA.
NFPA ratings	Health: 2 Flammability: 2 Instability: 0
References	ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic Materials) HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.