

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** AC-0.6  
**Other means of identification** None.  
**Recommended use** Not available.  
**Recommended restrictions** None known.  
**Manufacturer/Importer/Supplier/Distributor information**  
**Company name** Bryan & Bryan Asphalt, L.L.C.  
**Address** P.O. Box 636  
Henderson, TX 75653  
  
**Telephone number** 1-800-222-7122 (Customer Service)  
**E-mail** sds@ergon.com  
**Emergency telephone number** 1-800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Not classified.  
**Health hazards** Acute toxicity, inhalation Category 4  
Carcinogenicity Category 1B  
Reproductive toxicity Category 1  
Specific target organ toxicity, repeated exposure Category 2  
**Environmental hazards** Hazardous to the aquatic environment, long-term hazard Category 1  
**OSHA defined hazards** Not classified.  
**Label elements**



**Signal word** Danger

**Hazard statement** Harmful if inhaled. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects. May cause cancer.

### Precautionary statement

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

**Response** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention. Collect spillage.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. Breathing of high vapor concentrations may cause dizziness, light-headedness, headache, nausea, and loss of coordination. Continued inhalation may result in unconsciousness. Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema/chapping and oil acne. Components of the product may be absorbed into the body through the skin.

**Supplemental information** 100% of the mixture consists of component(s) of unknown acute oral toxicity. 100% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 100% of the mixture consists of component(s) of unknown acute dermal toxicity.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	60 - 80
CLARIFIED OILS (PETROLEUM), CATALYTIC CRACKED		64741-62-4	20 - 40

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell. Apply artificial respiration if needed. Get medical attention.
<b>Skin contact</b>	For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Wash off with soap and water. Get medical attention if irritation develops and persists. Do not use solvents to remove product residues from skin. Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists. Flush thoroughly with water for at least 15 minutes. Get medical assistance.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately. Get medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Addition of water or foam to the fire may cause frothing. Water may be ineffective. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Use water fog, alcohol-resistant foam, dry chemical or carbon dioxide (CO <sub>2</sub> ) to extinguish flames. Water spray should be used to cool containers.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Material will float and may ignite on surface of water. Do not release runoff from fire control measures to sewers or waterways. Use self-contained breathing apparatus in enclosed areas where heavy smoke may occur. Irritating and/or toxic gases may be emitted upon the products decomposition.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Cool containers / tanks with water spray. Use supplied air respirator if product is involved in a fire.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Do not breathe the mist or vapor. Ensure adequate ventilation. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. For Small Spills: Absorb with sand or other non-combustible absorbent material and place into containers for later disposal. Avoid runoff into storm sewers and ditches which lead to waterways.

### Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid heat, sparks, open flames and other ignition sources. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Avoid contact with oxidizing agents. Protect from contamination.

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m <sup>3</sup>	Inhalable fraction.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m <sup>3</sup>	Fume.

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Chemical goggles and face shield are recommended. Chemical respirator with organic vapor cartridge and full facepiece.

#### Skin protection

##### Hand protection

Wear appropriate chemical resistant gloves. Thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves. Chemical resistant gloves required for prolonged or repeated contact.

<b>Other</b>	Do not get this material in contact with skin. Where contact is likely, wear chemical-resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield. Use of an impervious apron is recommended. For molten product, use any type rubber thermal insulating gloves and other clothing as necessary to protect from thermal burns. Wear full protective clothing. Use appropriate hand protection. Use arm protection.
<b>Respiratory protection</b>	If ventilation is not sufficient to effectively prevent buildup of aerosols or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

<b>Appearance</b>	Brown Liquid
<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Brown.
<b>Odor</b>	Aromatic.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	500 - 1150 °F (260 - 621.11 °C) estimated
<b>Flash point</b>	300.0 °F (148.9 °C) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	0.3
<b>Explosive limit - upper (%)</b>	5
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	> 4 estimated
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IIIB estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Specific gravity</b>	1 - 1.1 estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Stable.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur. Will not occur.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials. Flammable/combustible - Keep away from oxidizers, heat and flames.

<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Hydrogen sulfide. Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

**Acute toxicity** Harmful if inhaled.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Direct contact with eyes may cause temporary irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** May cause cancer. Contains polycyclic aromatic compounds (PACs). Prolonged and/or repeated skin contact with certain PACs has been shown to cause skin cancer. Prolonged and/or repeated exposures by inhalation of certain PACs may also cause cancer of the lung and of other sites of the body. Prolonged and repeated contact with the product may cause skin cancer.

### IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

CLARIFIED OILS (PETROLEUM), CATALYTIC CRACKED (CAS 64741-62-4) 2B Possibly carcinogenic to humans.

### US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**Reproductive toxicity** May damage fertility or the unborn child.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. Prolonged and repeated contact with the product may cause skin cancer.

## 12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects. Keep out of sewers and waterways.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations


<b>Disposal instructions</b>	No components are identified as hazardous wastes. Dispose of contents/container in accordance with local/regional/national/international regulations. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

<b>DOT</b>	
<b>UN number</b>	UN3257
<b>UN proper shipping name</b>	Elevated temperature liquid, n.o.s., at or above 100 C and below its flash point (including molten metals, molten salts, etc.) (ASPHALT RQ = 143 LBS)
<b>Transport hazard class(es)</b>	
<b>Class</b>	9
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	9
<b>Packing group</b>	III
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	IB1, T3, TP3, TP29
<b>Packaging exceptions</b>	None
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	247
<b>IATA</b>	
<b>UN number</b>	UN3257
<b>UN proper shipping name</b>	Elevated temperature liquid, n.o.s. at or above 100°C and below its flash point (including molten metals, molten salts, etc.)
<b>Transport hazard class(es)</b>	
<b>Class</b>	9
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	9L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Forbidden
<b>Cargo aircraft only</b>	Forbidden
<b>IMDG</b>	
<b>UN number</b>	UN3257
<b>UN proper shipping name</b>	ELEVATED TEMPERATURE LIQUID, N.O.S. at or above 100°C and below its flashpoint (including molten metals, molten salts, etc.)
<b>Transport hazard class(es)</b>	
<b>Class</b>	9
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-A, <u>S</u> -P
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT; IATA; IMDG



## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

ASPHALT (CAS 8052-42-4) Listed.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

CLARIFIED OILS (PETROLEUM), CATALYTIC Listed: October 1, 1990

CRACKED (CAS 64741-62-4)

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

ASPHALT (CAS 8052-42-4)

CLARIFIED OILS (PETROLEUM), CATALYTIC CRACKED (CAS 64741-62-4)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 04-03-2018

**Version #** 01

**NFPA ratings**  
Health: 2  
Flammability: 1  
Instability: 0

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Bryan & Bryan Asphalt, L.L.C. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.