SAFETY DATA SHEET



1. Identification

Product identifier HFE-60P
Other means of identification None.
Recommended use Paving.
Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer:Ergon Asphalt & Emulsions, Inc.Address:2829 Lakeland Drive

Jackson, MS 39232

Website: www.ergonasphalt.com

Telephone: 1-800-222-7122 (Customer Service)

E-mail: sds@ergon.com

24 hour Emergency

(CHEMTREC):

North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention
Response
Not applicable.
Storage
Not applicable.
Not applicable.
Not available.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN

SULFIDE (H2S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	55 - 75
WATER		7732-18-5	25 - 45
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC		64741-96-4	1 - 10

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of

asphalt. Wash contact areas with soap and water. If needed, seek medical attention.

Material name: HFE-60P SDS US

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately. Direct contact with eyes may cause temporary irritation.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

Treat symptomatically.

treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed:

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

water spray.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze.

Material name: HFE-60P SDS US

6861 Version #: 01 Issue date: 09-03-2019

8. Exposure controls/personal protection

Occupational exposure limits

NAPHTHENIC (CAS 64741-96-4)

Components	Туре	Value	Form	
DISTILLATES (PETROLEUM),	PEL	5 mg/m3	Mist.	
COLVENT-DEFINED HEAVY				

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form	
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.	_
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY	TWA	5 mg/m3	Inhalable fraction.	

NAPHTHENIC (CAS 64741-96-4)

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form	
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.	-
DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)	Ceiling	1800 mg/m3		
	STEL	10 mg/m3	Mist.	
	TWA	350 mg/m3		

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged

vapor contact. Plastic or rubber gloves, apron and boots.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

9. Physical and chemical properties

Appearance Brown to black in color.

Liquid. Physical state Liquid. **Form** Color Black. Odor Tar-like **Odor threshold** Not available. рH Not available. Melting point/freezing point Not available.

Material name: HFE-60P SDS US

6861 Version #: 01 Issue date: 09-03-2019

Initial boiling point and

boiling range

212 °F (100 °C)

50....g . u...ge

Flash point > 212.0 °F (> 100.0 °C) Cleveland Open Cup

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 0.3 %

(%)

Flammability limit - 10 %

upper (%)

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure < 1 mm Hg @ 20 C

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Not miscible
Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature500 °F (260 °C)Decomposition temperatureNot available.Viscosity1500 cP

Other information

Density 8.45 lb/gal **Specific gravity** 1.01

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable under normal temperature conditions. **Possibility of hazardous** Hazardous polymerization does not occur.

reactions

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials. Do not overheat

product.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or

low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactNo adverse effects due to skin contact are expected.

Eye contact Harmful in contact with eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Harmful in contact with eyes. None known.

Material name: HFE-60P SDS US

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause skin disorders if contact is repeated or prolonged.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY 3 Not classifiable as to carcinogenicity to humans.

NAPHTHENIC (CAS 64741-96-4)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not classified. Specific target organ toxicity Not classified. - single exposure

Specific target organ toxicity

- repeated exposure

Not classified.

Not available. **Aspiration hazard**

Chronic effects Prolonged exposure may cause chronic effects.

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product	t Species		Test Results	
HFE-60P				
Aquatic				
Crustacea	EC50	Daphnia	21567.9531 mg/l, 48 hours estimated	
Fish	LC50	Fish	78054.1406 mg/l, 96 hours estimated	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations. No components are identified as hazardous wastes.

Disposal recommendations are based on uncontaminated material.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company. Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

Material name: HFE-60P SDS US

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard categories

Respiratory or skin sensitization

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY NAPHTHENIC (CAS 64741-96-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Material name: HFE-60P SDS US

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 09-03-2019

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2

Flammability: 1 Instability: 0

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written

based on the best knowledge and experience currently available

Material name: HFE-60P SDS US

6861 Version #: 01 Issue date: 09-03-2019