

**1. Identification**

**Product identifier** **ONYX R1P**  
**Other means of identification** None.  
**Recommended use** Not available.  
**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Company Name** ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc.  
**Address** 2829 Lakeland Drive  
 Jackson, MS 39232  
 USA  
**After hours telephone number** 1-800-222-7122  
**Normal work hours telephone number** 1-877-982-7667  
**Website** www.ergonarmor.com  
**E-mail** sds@ergon.com  
**Emergency 24-hour telephone number** CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887  
**Information on operation hours** 8:00 a.m. to 5:00 p.m.

**2. Hazard(s) identification**

**Physical hazards** Not classified.  
**Health hazards** Not classified.  
**Environmental hazards** Not classified.  
**OSHA defined hazards** Not classified.

**Label elements**

**Hazard symbol** None.  
**Signal word** None.  
**Hazard statement** The mixture does not meet the criteria for classification.  
**Precautionary statement**  
**Prevention** Observe good industrial hygiene practices.  
**Response** Wash hands after handling.  
**Storage** Store away from incompatible materials.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)** Molten asphalt presents a thermal hazard.

**Supplemental information** Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN SULFIDE (H<sub>2</sub>S) can be harmful if inhaled.

**3. Composition/information on ingredients**
**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	1 - 20
QUARTZ		14808-60-7	1 - 10
TITANIUM DIOXIDE		13463-67-7	< 1

## 4. First-aid measures

### Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

### Skin contact

Immediately place the affected skin under running water for at least 20 minutes - DO NOT DELAY. Prolonged flushing/cooling is necessary. Ice (or "cold packs") may be used in the event that water is unavailable. Do not attempt to remove the asphalt. Do not place any sheets or towels on top of the asphalt due to the risk of adhesion. Get immediate medical attention.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention or advice.

### Ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large amount does occur, call a poison control center immediately.

### Most important symptoms/effects, acute and delayed

Potential for severe thermal burns.

## 5. Fire-fighting measures

### Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

### Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### Specific hazards arising from the chemical

Irritating and toxic gases or fumes may be released during a fire.

### Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

### Fire fighting equipment/instructions

ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray. Use of foam or water may cause frothing.

### Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

### Methods and materials for containment and cleaning up

Dike far ahead of spill for later disposal. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal.

### Environmental precautions

Not available.

## 7. Handling and storage

### Precautions for safe handling

Avoid contact with molten material. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Do not add water to hot product. This may result in frothing of the mixture causing hot asphalt to overflow the container

### Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. It is recommended that the storage temperature never exceed 350°F.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
TITANIUM DIOXIDE (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	2.4 mppcf	Respirable.
		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

**US. ACGIH Threshold Limit Values**

Material	Type	Value	Form
ONYX R1P	TWA	0.5 mg/m3	Inhalable fraction.

  

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
TITANIUM DIOXIDE (CAS 13463-67-7)	TWA	10 mg/m3	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Material	Type	Value	Form
ONYX R1P	Ceiling	5 mg/m3	Fume.

  

Components	Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
QUARTZ (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Safety glasses. Wear face shield if there is risk of splashes.

**Skin protection****Hand protection**

Thermally protective, chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.

**Other**

Normal work clothing (long sleeved shirts and long pants) is recommended. Wear 100% cotton clothing.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal hazards**

During product use, there is a risk of thermal burns.

**General hygiene considerations**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance**

Brown to black in color.

**Physical state**

Liquid.

**Form**

Not available.

**Color**

Black.

**Odor**

Tar-like

**Odor threshold**

Not available.

**pH**

6 - 7

**Melting point/freezing point**

Not available.

<b>Initial boiling point and boiling range</b>	>= 212 °F (>= 100 °C)
<b>Flash point</b>	> 212.0 °F (> 100.0 °C) Pensky-Martens Closed Cup
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available. estimated
<b>Flammability limit - upper (%)</b>	Not available. estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	1.2
<b>Relative density temperature</b>	77 °F (25 °C)
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Insoluble
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	> 700 °F (> 371.11 °C)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Specific gravity</b>	1

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport
<b>Chemical stability</b>	Stable under normal temperature conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Do not overheat product.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen sulfide.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause irritation to the respiratory system.
<b>Skin contact</b>	May be irritating to the skin.
<b>Eye contact</b>	May be irritating to eyes.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Not available.

### Information on toxicological effects

<b>Acute toxicity</b>	Not available.
<b>Skin corrosion/irritation</b>	Not available.
<b>Serious eye damage/eye irritation</b>	Not available.

### Respiratory or skin sensitization

<b>Respiratory sensitization</b>	Not available.
----------------------------------	----------------

<b>Skin sensitization</b>	Not available.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product contains crystalline silica. Silica is a known carcinogen; however in this encapsulated form the normal routes of exposure are unavailable.

#### **IARC Monographs. Overall Evaluation of Carcinogenicity**

ASPHALT (CAS 8052-42-4)	2B Possibly carcinogenic to humans.
QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
TITANIUM DIOXIDE (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

#### **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

QUARTZ (CAS 14808-60-7)	Cancer
-------------------------	--------

#### **US. National Toxicology Program (NTP) Report on Carcinogens**

QUARTZ (CAS 14808-60-7)	Known To Be Human Carcinogen.
-------------------------	-------------------------------

<b>Reproductive toxicity</b>	Not available.
<b>Specific target organ toxicity - single exposure</b>	Not available.
<b>Specific target organ toxicity - repeated exposure</b>	Not available.
<b>Aspiration hazard</b>	Not available.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.

## **12. Ecological information**

<b>Ecotoxicity</b>	This product has no known eco-toxicological effects.
<b>Persistence and degradability</b>	Not available.
<b>Bioaccumulative potential</b>	Not available.
<b>Mobility in soil</b>	Not available.
<b>Other adverse effects</b>	Not available.

## **13. Disposal considerations**

<b>Disposal instructions</b>	Allow molten resin to solidify before disposal. Dispose in accordance with all applicable regulations. When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261.
<b>Hazardous waste code</b>	Not applicable.
<b>Waste from residues / unused products</b>	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	No special precautions.

## **14. Transport information**

<b>DOT</b>	Not regulated as dangerous goods.
<b>IATA</b>	Not regulated as dangerous goods.
<b>IMDG</b>	Not regulated as dangerous goods.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not available.

## **15. Regulatory information**

<b>US federal regulations</b>	
<b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>	Not regulated.
<b>CERCLA Hazardous Substance List (40 CFR 302.4)</b>	
ASPHALT (CAS 8052-42-4)	Listed.
<b>SARA 304 Emergency release notification</b>	Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

QUARTZ (CAS 14808-60-7)

Cancer  
lung effects  
immune system effects  
kidney effects**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Not listed.

**Classified hazard categories**Skin corrosion or irritation  
Serious eye damage or eye irritation  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)  
Hazard not otherwise classified (HNOC)**SARA 313 (TRI reporting)**

Not regulated.

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)**

Not regulated.

**US state regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer.

**California Proposition 65****California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ASPHALT (CAS 8052-42-4)

Listed: January 1, 1990

QUARTZ (CAS 14808-60-7)

Listed: October 1, 1988

TITANIUM DIOXIDE (CAS 13463-67-7)

Listed: September 2, 2011

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

ASPHALT (CAS 8052-42-4)

QUARTZ (CAS 14808-60-7)

TITANIUM DIOXIDE (CAS 13463-67-7)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 10-24-2019

**Version #** 01

**Further information** HMIS® is a registered trade and service mark of the NPCA.

**NFPA ratings**  
Health: 2  
Flammability: 1  
Instability: 0

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.