SAFETY DATA SHEET



1. Identification

Product identifier CPB
Other means of identification None.

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Ergon Asphalt & Emulsions, Inc.

Address: 2829 Lakeland Drive

Jackson, MS 39232 www.ergonasphalt.com

Telephone: 1-800-222-7122 (Customer Service)

E-mail: sds@ergon.com

24 hour Emergency

(CHEMTREC):

Website:

North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsCarcinogenicityCategory 2Specific target organ toxicity, repeatedCategory 2

exposure

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Warning

Hazard statement Combustible liquid. Suspected of causing cancer. May cause damage to organs through prolonged

or repeated exposure.

Precautionary statement

Prevention Observe good industrial hygiene practices. Obtain special instructions before use. Do not handle

until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Keep

away from flames and hot surfaces-No smoking.

Response If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to

extinguish.

Storage Store locked up. Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Heated product will cause thermal burns.

Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN

SULFIDE (H2S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	60 - 80

Chemical nameCommon name and synonymsCAS number%DIESEL, NO.268476-34-620 - 40Other components below reportable levels6.16

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Skin contact

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve

or other proper respiratory medical device. Call a physician if symptoms develop or persist.

Wash off with soap and plenty of water. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse. Get medical attention if irritation develops

unaffected skin. Wash clothing separately before reuse. Get medical attention if irritation develop and persists.

and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO

NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if

irritation develops and persists.

Ingestion Rinse mouth thoroughly. Do not induce vomiting without advice from poison control center. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If

ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

Treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

treatment needed
General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Addition of water or foam to the fire

may cause frothing.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

Fire may produce irritating, corrosive and/or toxic gases. Development of hazardous combustion gases or vapours possible in the event of fire.

the chemical
Special protective equipment

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective

and precautions for firefighters

clothing will only provide limited protection.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. Move containers from fire area if you can do so without risk. By fire, toxic gases may be formed (COx, NOx). Keep run-off water out of sewers and water sources. Dike for water control.

Specific methods

Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch or walk through spilled material. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Runoff or release to sewer, waterway or ground is forbidden.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid prolonged exposure. Should be handled in closed systems, if possible. Do not use in areas without adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash hands after handling. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Keep the container tightly closed and dry. Store in tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit At this time, the other constituents have no known exposure limits.

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
DIESEL, NO.2 (CAS 68476-34-6)	TWA	100 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to Che Components	emical Hazards Type	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

DIESEL, NO.2 (CAS 68476-34-6) Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. When handling hot material, use heat resistant gloves.

Use gloves with long sleeves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended. Thermally

protective apron and long sleeves are recommended when volume of hot material is significant.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards During product use, there is a risk of thermal burns. Wear appropriate thermal protective clothing,

when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants. When using do not smoke.

9. Physical and chemical properties

Appearance Brown to black in color.

Physical stateLiquid.FormLiquid.ColorBrown - black

Odor Aromatic Mild Petroleum Odor

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.

Initial boiling point and

boiling range

320 - 550 °F (160 - 287.78 °C)

Flash point 185.0 °F (85.0 °C) Pensky-Martens Closed Cup

Evaporation rate < 1

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower 0.3 %

(%)

Flammability limit -

upper (%)

5 %

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure< 50 psi</th>Vapor density> 4.5

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature490 °F (254.44 °C)Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

Specific gravity 0.98

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Risk of ignition. Material is stable under normal conditions.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or

low molecular weight hydrocarbons.

Material name: CPB sps us

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact May be irritating to the skin. Eye contact May be irritating to eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

Not known. **Acute toxicity**

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Germ cell mutagenicity

Direct contact with eyes may cause temporary irritation.

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

DIESEL, NO.2 (CAS 68476-34-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Product		Species	Test Results	
СРВ				
Aquatic				
Crustacea	EC50	Daphnia	2073.2051 mg/l, 48 hours estimated	
Fish	LC50	Fish	7063.1528 mg/l, 96 hours estimated	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this substance.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component. The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Disposal recommendations are based on material as supplied. Disposal must be in accordance with

current applicable laws and regulations, and material characteristics at time of disposal.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this

container.

14. Transport information

DOT

UN number UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)

3 Class **Subsidiary risk** IIII Packing group

Special precautions for

Read safety instructions, SDS and emergency procedures before handling.

user ΤΔΤΔ

> **UN number UN proper shipping name**

UN1999 Tars, liquid

Transport hazard class(es)

Class 3 **Subsidiary risk** Packing group III **Environmental hazards** No. **ERG Code** 3L

Special precautions for

Other information

user

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

Allowed with restrictions.

aircraft Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1999 **UN proper shipping name** Tars, liquid

Transport hazard class(es)

Class 3 **Subsidiary risk Packing group** III **Environmental hazards**

Marine pollutant No. F-E, S-E

Special precautions for

Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established. Annex II of MARPOL 73/78

and the IBC Code



IATA; IMDG



Further information

If shipped above the flash point, must be classified as follows: UN3256, Elevated temperature

liquid, flammable, n.o.s. (contains fuel oil), 3, PG III.

15. Regulatory information

US federal regulations

One or more components are not listed on TSCA.

CERCLA/SARA Hazardous Substances - Not applicable.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

ASPHALT (CAS 8052-42-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes

Hazardous chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: CPB SDS US

6109 Version #: 05 Revision date: 02-25-2021 Issue date: 01-12-2017

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including ASPHALT, which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

ASPHALT (CAS 8052-42-4) DIESEL, NO.2 (CAS 68476-34-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 01-12-2017

 Revision date
 02-25-2021

Version # 05

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2 Flammability: 1 Instability: 0

References ACGIH

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

EPA: AQUIRE database

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

Taiwan. Toxic Materials (Rules on Hazard Communication of Dangerous Materials and Toxic

Materials)

Japan Society for Occupational Health, Recommendation of Occupational Exposure Limits

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety