SAFETY DATA SHEET



1. Identification

Product identifier Polarbond
Other means of identification None.

Recommended useAnti-stripping additive

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer: Ergon Asphalt & Emulsions, Inc.

Address: 2829 Lakeland Drive

Jackson, MS 39232

Website: www.ergonasphalt.com

Telephone: 1-800-222-7122 (Customer Service)

E-mail: sds@ergon.com

24 hour Emergency

(CHEMTREC):

North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazardsCorrosive to metalsCategory 1Health hazardsAcute toxicity, oralCategory 4Acute toxicity, dermalCategory 4Skin corrosion/irritationCategory 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be corrosive to metals. Harmful if swallowed. Harmful in contact with skin. Causes severe

skin burns and eye damage.

Precautionary statement

Prevention Keep only in original container. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat,

drink or smoke when using this product. Wear protective gloves/protective clothing/eye

protection/face protection. Wash hands thoroughly after handling.

Response IF ON SKIN: Wash with plenty of water. IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Take off contaminated clothing and wash before reuse. Specific treatment see Section 4 of this SDS.

Absorb spillage to prevent material damage.

Storage Store locked up. Store in corrosive resistant container with a resistant inner liner.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Material name: Polarbond SDS US

Chemical name	Common name and synonyms	CAS number	%
POLYPHOSPHORIC ACIDS		8017-16-1/7664-38-2	90 - 99
PROPRIETARY INGREDIENTS		N/A	0 - 10
HEXAFLUOROSILICIC ACID		16961-83-4	<=1
HYDROGEN FLUORIDE, ANHYDROUS		7664-39-3	<=1

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a physician or poison control center immediately.

Skin contact Wash the skin immediately with soap and water. Immediately remove contaminated clothing.

> Wash contaminated clothing before reuse. Contaminated leather articles, including shoes, that cannot be decontaminated should be discarded. DO NOT rub or scratch affected area. Call a

physician or poison control center immediately.

Immediately flush eyes with plenty of water for at least 20 minutes. Take care not to rinse Eve contact

contaminated water into the unaffected eye or onto the face. Remove contact lenses, if present

and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to a victim who is

unconscious or is having convulsions. If vomiting occurs, keep head low so that stomach content

doesn't get into the lungs. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

May cause severe irritation or burns to the eyes, skin, gastrointestinal tract, and respiratory system. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Choking.

Wheezing. Shortness of breath. Corrosive effects. Nausea, vomiting.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water spray. Dry chemicals. Carbon dioxide (CO2). Dry sand. Foam. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Irritating and toxic gases or fumes may be released during a fire.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Particular/heightened danger of slipping on leaked/spilled product. Do not inhale explosion gases or combustion gases. Water spray should be used to cool containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Keep upwind of the spilled material and isolate exposure. Particular danger of slipping on leaked/spilled product.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Large Spills: Dike the spilled material, where this is possible. Stop leak if you can do so without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground.

Material name: Polarbond SDS US 2/8

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from metals and other incompatibles Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not taste or swallow. Avoid contact with skin. Avoid contact with clothing. Wear personal protective equipment. Avoid contact during pregnancy/while nursing. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Avoid release to the environment.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store in corrosive resistant container with a resistant inner liner. Unsuitable containers: metals. Store in a cool, dry place out of direct sunlight. Store locked up. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store in a closed container away from incompatible materials. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
HEXAFLUOROSILICIC ACID (CAS 16961-83-4)	PEL	2.5 mg/m3	
HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3)	PEL	2.5 mg/m3	
US. OSHA Table Z-2 (29 CFR 191	.0.1000)		
Components	Туре	Value	Form
HEXAFLUOROSILICIC ACID (CAS 16961-83-4)	TWA	2.5 mg/m3	Dust.
Hydrogen fluoride, Anhydrous (CAS 7664-39-3)	TWA	3 ppm	
JS. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
HEXAFLUOROSILICIC ACID (CAS 16961-83-4)	TWA	2.5 mg/m3	
HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3)	Ceiling	2 ppm	
	TWA	0.5 ppm	
JS. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
HEXAFLUOROSILICIC ACID (CAS 16961-83-4)	TWA	2.5 mg/m3	
Hydrogen fluoride, Anhydrous (CAS 7664-39-3)	Ceiling	5 mg/m3	
		6 ppm	
	TWA	2.5 mg/m3	
		3 ppm	

Biological limit values

ACGIH Biological Expos	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
HEXAFLUOROSILICIC ACID (CAS 16961-83-4)	3 mg/l	Fluoride	Urine	*	
	2 mg/l	Fluoride	Urine	*	
HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3)	3 mg/l	Fluoride	Urine	*	

Material name: Polarbond SDS US

ACGIH Biological Exposure Indices

Value Determinant Specimen Sampling Time Components

Fluoride

* - For sampling details, please see the source document.

2 ma/l

Exposure guidelines

US - California OELs: Skin designation

HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3) Danger of cutaneous absorption

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

Urine

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical goggles and face shield are recommended.

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Avoid contact with clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not get in eyes. Avoid contact with skin. When using, do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Green liquid. Viscous. **Appearance**

Liquid. Physical state **Form** Liquid. Color Green Odor Odorless. Not available. Odor threshold

0 - 1 pН

Melting point/freezing point Not available. Initial boiling point and

boiling range

269.6 °F (132 °C)

Flash point Not available. **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits **Explosive limit - lower** Not available.

(%)

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Not available. Auto-ignition temperature

Material name: Polarbond SDS US **Decomposition temperature** Not available. Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Possibility of hazardous

reactions

Hazardous polymerization will not occur.

Stable under normal temperature conditions.

Conditions to avoid Strong alkalis. Metals other than stainless steel. Contact with incompatible materials. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. Protect against direct

sunlight.

Incompatible materials Reacts violently with alkalis producing heat. This material is corrosive to common metals such as

mild steel, copper, brass and bronze and may generate hydrogen gas as a result of reaction.

Metals. Strong bases. Strong acids.

Hazardous decomposition

Skin contact

products

Oxides of phosphorus. Carbon dioxide. Carbon monoxide. Thermal decomposition can lead to

release of irritating gases and vapors. Corrosive vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Eve contact Causes serious eye damage.

Ingestion Harmful if swallowed. Swallowing will lead to a strong caustic effect on mouth and throat and to

the danger of perforation of esophagus and stomach.

Causes severe skin burns and eye damage.

Symptoms related to the physical, chemical and toxicological characteristics May cause severe irritation or burns to the eyes, skin, gastrointestinal tract, and respiratory system. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause

redness and pain. Nausea, vomiting. Shortness of breath.

Information on toxicological effects

Acute toxicity

Test Results Components **Species**

HEXAFLUOROSILICIC ACID (CAS 16961-83-4)

<u>Acute</u> Oral

LD50

Rat 430 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not available. Not available. Skin sensitization Germ cell mutagenicity Not available.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not available. Specific target organ toxicity Not available.

- single exposure

Not available.

Specific target organ toxicity - repeated exposure

Aspiration hazard Not available.

Material name: Polarbond SDS US 5/8 7075 Version #: 02 Revision date: 07-11-2022 Issue date: 11-16-2020

12. Ecological information

Ecotoxicity The product components are not classified as environmentally hazardous. However, this does not

exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

Not available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Collect and reclaim or dispose in sealed containers at licensed

waste disposal site. Dispose of contents/container in accordance with

local/regional/national/international regulations. Do not contaminate ponds, waterways or ditches

with chemical or used container.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN1805

UN proper shipping name

Phosphoric acid solution

Transport hazard class(es)

Class 8 **Subsidiary risk** 8 Label(s) **Packing group** III

Special precautions for

user

Not available.

Special provisions A7, IB3, N34, T4, TP1 **Packaging exceptions** 154

Packaging non bulk 203 Packaging bulk 241

IATA

UN number UN1805

UN proper shipping name Phosphoric acid, solution

Transport hazard class(es) Class 8 Subsidiary risk Packing group III

Environmental hazards No. **ERG Code** 81

Special precautions for

user

Not available.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1805

UN proper shipping name PHOSPHORIC ACID SOLUTION

Transport hazard class(es) Class 8 **Subsidiary risk**

Material name: Polarbond SDS US 6/8

7075 Version #: 02 Revision date: 07-11-2022 Issue date: 11-16-2020

III Packing group **Environmental hazards**

Marine pollutant No. **EmS** F-A, S-B

Special precautions for

Not available.

Transport in bulk according to Not available. Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3) Listed.

SARA 304 Emergency release notification

Hydrofluoric acid (CAS 7664-39-3) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
HYDROGEN	7664-39-3	100	100	. ,	., ,

FLUORIDE, **ANHYDROUS**

SARA 311/312 Hazardous Yes

chemical

Classified hazard Corrosive to metal

categories Acute toxicity (any route of exposure)

Skin corrosion or irritation

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
HYDROGEN FLUORIDE, ANHYDROUS	7664-39-3	<=1	

Material name: Polarbond SDS US 7/8

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

HEXAFLUOROSILICIC ACID (CAS 16961-83-4)

HYDROGEN FLUORIDE, ANHYDROUS (CAS 7664-39-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 11-16-2020

 Revision date
 07-11-2022

Version # 02

NFPA ratings Health: 3

Flammability: 1 Instability: 0

Disclaimer Not available.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: Polarbond SDS US

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).