SAFETY DATA SHEET



1. Identification

Product identifier ePrime Other means of identification None.

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information Manufacturer: Ergon Asphalt & Emulsions, Inc.

Address: 2829 Lakeland Drive

Jackson, MS 39232

Website: www.ergonasphalt.com

Telephone: 1-800-222-7122 (Customer Service)

E-mail: sds@ergon.com

24 hour Emergency

(CHEMTREC):

North America 1-800-424-9300; International 1-703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2 Category 2

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer. May cause damage to organs through prolonged or repeated

exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not breathe dust/fume/gas/mist/vapors/spray. Observe

good industrial hygiene practices. Wear protective gloves/protective clothing/eye protection/face

protection. Do not handle until all safety precautions have been read and understood.

Response If exposed or concerned: Call a poison center/doctor. Wash hands after handling. Get medical

advice/attention if you feel unwell.

Storage Store locked up.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

Molten asphalt presents a thermal hazard.

Supplemental information Vapors containing hydrogen sulfide may accumulate during storage or transport. HYDROGEN

SULFIDE (H2S) can be harmful if inhaled.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
ASPHALT		8052-42-4	15 - 30
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		64742-47-8	0 - 20

Material name: ePrime SDS US 1/9

Chemical name	Common name and synonyms	CAS number	%
KEROSINE (PETROLEUM), HYDRODESULFURIZED		64742-81-0	0 - 20
HYDROCHLORIC ACID		7647-01-0	< 1
NAPHTHALENE		91-20-3	< 1

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. Call a physician if symptoms develop or persist.

If clothing sticks to the skin, do not remove. Lotion or hand cream may aid in the removal of Skin contact

asphalt. Wash contact areas with soap and water. If needed, seek medical attention.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately. If ingestion of a large

amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed

Ingestion

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

Fire fighting equipment/instructions ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Move containers from fire area if you can do so without risk. In the event of fire, cool tanks with water spray.

Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with

water spray.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Ventilate area and avoid breathing vapors or mist. For large spills, dike far ahead of liquid spill for later disposal. Do not release into sewers or waterways.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Material name: ePrime SDS US 2/9

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Use only in well-ventilated areas. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site.

Conditions for safe storage, including any incompatibilities

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in original tightly closed container. Store in a well-ventilated place. Do not allow material to freeze.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	ir Contaminants (29 CFR 19) Value	10.1000)
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	7 mg/m3	
		5 ppm	
NAPHTHALENE (CAS 91-20-3)	PEL	50 mg/m3	
		10 ppm	
US. ACGIH Threshold Limit Value			_
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
HYDROCHLORIC ACID (CAS 7647-01-0)	Ceiling	2 ppm	
KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)	TWA	200 mg/m3	Non-aerosol.
NAPHTHALENE (CAS 91-20-3)	TWA	10 ppm	
NIOSH. Immediately Dangerous	to Life or Health (IDLH) Val	ues, as amended	
Components	Туре	Value	
IADHTHAI ENE (CAS	IDLH	0.9 %	
	IDLII	0.9 %	
	IDLII	250 ppm	
91-20-3) US. NIOSH: Pocket Guide to Che		250 ppm	Form
91-20-3) JS. NIOSH: Pocket Guide to Cher Components	mical Hazards Recommende	250 ppm ed Exposure Limits (REL)	Form Fume.
NAPHTHALENE (CAS 91-20-3) US. NIOSH: Pocket Guide to Cher Components ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	mical Hazards Recommende Type	250 ppm ed Exposure Limits (REL) Value	
US. NIOSH: Pocket Guide to Cher Components ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8) HYDROCHLORIC ACID (CAS	mical Hazards Recommende Type Ceiling	250 ppm ed Exposure Limits (REL) Value 5 mg/m3	
DI-20-3) JS. NIOSH: Pocket Guide to Chercomponents ASPHALT (CAS 8052-42-4) DISTILLATES PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8) HYDROCHLORIC ACID (CAS	mical Hazards Recommende Type Ceiling TWA	250 ppm ed Exposure Limits (REL) Value 5 mg/m3 100 mg/m3	
US. NIOSH: Pocket Guide to Cher Components ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8) HYDROCHLORIC ACID (CAS 7647-01-0) KEROSINE (PETROLEUM), HYDRODESULFURIZED	mical Hazards Recommende Type Ceiling TWA	250 ppm ed Exposure Limits (REL) Value 5 mg/m3 100 mg/m3 7 mg/m3	
US. NIOSH: Pocket Guide to Cher Components ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	mical Hazards Recommende Type Ceiling TWA Ceiling	250 ppm ed Exposure Limits (REL) Value 5 mg/m3 100 mg/m3 7 mg/m3 5 ppm	
US. NIOSH: Pocket Guide to Cher Components ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8) HYDROCHLORIC ACID (CAS 7647-01-0) KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0) NAPHTHALENE (CAS	mical Hazards Recommende Type Ceiling TWA Ceiling TWA	250 ppm ed Exposure Limits (REL) Value 5 mg/m3 100 mg/m3 7 mg/m3 5 ppm 100 mg/m3	
JS. NIOSH: Pocket Guide to Cher Components ASPHALT (CAS 8052-42-4) DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8) HYDROCHLORIC ACID (CAS 7647-01-0) KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0) NAPHTHALENE (CAS	mical Hazards Recommende Type Ceiling TWA Ceiling TWA	250 ppm ed Exposure Limits (REL) Value 5 mg/m3 100 mg/m3 7 mg/m3 5 ppm 100 mg/m3 75 mg/m3	

Material name: ePrime SDS US

Biological limit values

Components	Value	Determinant	Specimen	Sampling Time
ASPHALT (CAS 8052-42-4)	2.5 μg/l	1-Hydroxypyren e, with hydrolysis (1-HP)	Urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

NAPHTHALENE (CAS 91-20-3) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

KEROSINE (PETROLEUM), HYDRODESULFURIZED

(CAS 64742-81-0)

NAPHTHALENE (CAS 91-20-3) Danger of cutaneous absorption

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

Danger of cutaneous absorption

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged

vapor contact. Plastic or rubber gloves, apron and boots.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment

to remove contaminants.

9. Physical and chemical properties

Appearance Brown to black in color.

Physical state Liquid.
Form Liquid.
Color Brown
Odor Mild. Tar-like
Odor threshold Not available.

Initial boiling point and

boiling range

≥212 °F (≥100 °C)

Flash point >212.0 °F (>100.0 °C)

Evaporation rate <1

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower 0.7 % estimated

Explosive limit - upper

(%)

(%)

5 % estimated

Vapor pressure <1 mm Hg @ 70 F

Vapor density >1

Relative density Not available.

Solubility(ies)

Solubility (water) Soluble

Material name: ePrime SDS US

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

>700 °F (>371.11 °C)

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Specific gravity 1.01

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable under normal temperature conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

products

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Do not

overheat product.

Incompatible materials Strong oxidizing agents.

Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide Hazardous decomposition

and/or low molecular weight hydrocarbons. Hydrogen sulfide.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact May be irritating to eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components **Species Test Results**

ASPHALT (CAS 8052-42-4)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 > 5000 mg/kg Rat

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)

Acute **Dermal**

LD50 Rat > 2000 mg/kg

Inhalation

LC50 Rat > 5200 mg/m3, 4 Hours

HYDROCHLORIC ACID (CAS 7647-01-0)

Acute

Dermal

1449 mg/kg LD50 Mouse

KEROSINE (PETROLEUM), HYDRODESULFURIZED (CAS 64742-81-0)

Acute

Inhalation

LC50 > 5200 mg/m3, 4 Hours

Material name: ePrime SDS US 5/9

5862 Version #: 01 Issue date: 11-04-2024

Components **Species Test Results**

NAPHTHALENE (CAS 91-20-3)

Acute Oral

LD50 Rat 490 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

May be irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization May cause skin disorders if contact is repeated or prolonged.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

ASPHALT (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

HYDROCHLORIC ACID (CAS 7647-01-0) 3 Not classifiable as to carcinogenicity to humans.

NAPHTHALENE (CAS 91-20-3) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

ASPHALT (CAS 8052-42-4) Known To Be Human Carcinogen. NAPHTHALENE (CAS 91-20-3) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Test Results

Reproductive toxicity Not classified. Specific target organ toxicity Not classified.

- single exposure

Specific target organ toxicity

- repeated exposure

Product

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged exposure may cause chronic effects.

Further information This product has no known adverse effect on human health.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

ePrime **Aquatic** Crustacea EC50 Daphnia 1122.9861 mg/l, 48 hours Fish LC50 Fish 39.9203 mg/l, 96 hours Acute Crustacea EC50 Daphnia 454.1667 mg/l, 48 hours estimated LC50 30.5556 mg/l, 4 days estimated Fish Fish **Test Results**

Components Species

Species

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)

Aquatic

Acute

LC50 Fish Bluegill (Lepomis macrochirus) 2.2 mg/l, 4 days

Material name: ePrime SDS US 6/9 Components **Species Test Results**

HYDROCHLORIC ACID (CAS 7647-01-0)

Aquatic

Acute

Fish LC50 Western mosquitofish (Gambusia affinis) 282 mg/l, 96 hours

NAPHTHALENE (CAS 91-20-3)

Aquatic

Acute

Crustacea EC50 Water flea (Daphnia magna) 1.09 - 3.4 mg/l, 48 hours LC50 Fish Pink salmon (Oncorhynchus gorbuscha) 0.95 - 1.62 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

NAPHTHALENE 3.3

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in

accordance with all applicable regulations. No components are identified as hazardous wastes.

Disposal recommendations are based on uncontaminated material.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company. Not applicable.

Waste from residues / unused products

Contaminated packaging

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions). Avoid discharge into water courses or onto the ground.

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT Listed.

(CAS 64742-47-8)

HYDROCHLORIC ACID (CAS 7647-01-0) Listed. KEROSINE (PETROLEUM), HYDRODESULFURIZED Listed.

(CAS 64742-81-0)

NAPHTHALENE (CAS 91-20-3) Listed.

Material name: ePrime SDS US 7/9

^{*} Estimates for product may be based on additional component data not shown.

SARA 304 Emergency release notification

HYDROCHLORIC ACID (CAS 7647-01-0)

5000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Chemical name CAS number Reportable **Threshold Threshold Threshold** planning planning quantity planning quantity (pounds) (pounds) quantity, lower quantity, upper value (pounds) value (pounds)

HYDROCHLORIC 7647-01-0 5000 500

ACID

SARA 311/312 Hazardous Yes

chemical

Classified hazard Carcinogenicity

categories Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.NAPHTHALENE91-20-3< 1</td>

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ASPHALT (CAS 8052-42-4)

HYDROCHLORIC ACID (CAS 7647-01-0)

NAPHTHALENE (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

HYDROCHLORIC ACID (CAS 7647-01-0)

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

HYDROCHLORIC ACID (CAS 7647-01-0) 20 %WV

DEA Exempt Chemical Mixtures Code Number

HYDROCHLORIC ACID (CAS 7647-01-0) 6545

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

NAPHTHALENE (CAS 91-20-3) Listed: April 19, 2002

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Material name: ePrime SDS US

Country(s) or region Inventory name On inventory (yes/no)*

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-04-2024

Version # 01

Further information HMIS® is a registered trade and service mark of the NPCA.

NFPA ratings Health: 2

Flammability: 1 Instability: 0

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge.

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was

written based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Alternate Trade Names

Hazard(s) identification: Response Hazard(s) identification: Prevention Hazard(s) identification: Hazard statement

Composition / Information on Ingredients: Disclosure Overrides Fire-fighting measures: Specific hazards arising from the chemical

Physical & Chemical Properties: Multiple Properties

GHS: Classification

Material name: ePrime SDS US

5862 Version #: 01 Issue date: 11-04-2024

Yes