ERGONE

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or HyPrene BO150

designation of the mixture

Registration number 01-2119467170-45

Synonyms None.

Issue date 25-April-2016

Version number 03

Revision date 01-July-2019 Supersedes date 29-March-2018

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Tire Oils, Rubber Compounding, Automotive & Industrial Hoses, Adhesives, Carpet Backing, Carbor

Black, Banbury Dust Stop, Defoamers, Sealants, Belts & Hoses.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

> Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

Chemtrec: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International)

See Section 15 for additional CHEMTREC Hotline Numbers

E-mail: sds@ergon.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended

Hazard summary Not available.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Asphalt, Distillates (petroleum), hydrotreated heavy naphthenic

Hazard pictograms None.

Signal word Not applicable. **Hazard statements** Not applicable.

Precautionary statements

Prevention Not applicable. Response Not applicable. Not applicable. Storage **Disposal** Not applicable.

Supplemental label

information

None.

2.3. Other hazards None known.

Material name: HyPrene BO150 SDS EU

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), heavy naphthenic	hydrotreated	60 - 95	64742-52-5 265-155-0	01-2119467170-45	649-465-00-7	
Classification:	Carc. 1B;H3	50				L
Asphalt		5 - 40	8052-42-4 232-490-9	01-2119480172-44	-	
Classification:	Flam. Liq. 2;	:H225				

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any immediate medical attention and special treatment

Treat symptomatically.

Defatting of the skin.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

5.1. Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

extinguisher, as this will spread the fire.

Do not use a solid water stream as it may scatter and spread fire.

No unusual fire or explosion hazards noted.

5.2. Special hazards arising from the substance or

mixture

needed

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an

breathing apparatus, protective clothing and face mask.

Special fire fighting

procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a

fire

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch

damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the

ground.

Material name: HyPrene BO150 SDS EU

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Use care in handling/storage. Keep away from heat, sparks and open flame. Store in a

well-ventilated place.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Material	Туре	Value	Form	
HyPrene BO150	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Components	Туре	Value	Form	
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work Material Value

Material	Туре	value	
HyPrene BO150	TWA	5 mg/m3	
Components	Туре	Value	
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Туре	Value	
Asphalt (CAS 8052-42-4)	MAC	5 mg/m3	
	STEL	10 mg/m3	

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.
Denmark. Exposure Limit Values Material	Туре	Value	Form
- 1446.141	-,,,,		
HyPrene BO150	TLV	1 mg/m3	Mist.

Material name: HyPrene BO150 SDS EU

Denmark. Exposure Limit Value Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TLV	1 mg/m3	Dust.
Distillates (petroleum), hydrotreated heavy haphthenic (CAS h4742-52-5)	TLV	1 mg/m3	Mist.
Estonia. OELs. Occupational Exp September 2001)	osure Limits of Hazardous Su	ıbstances. (Annex of Regu	lation No. 293 of 18
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Vapour.
Finland. Workplace Exposure Li Components	mits Type	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Mist.
Germany. DFG MAK List (adviso Compounds in the Work Area (L		Investigation of Health H	azards of Chemical
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	1,5 mg/m3	Vapour and aerosol
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/19 Material	999, as amended) Type	Value	Form
HyPrene BO150	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree on Material	Chemical Safety of Workplac Type	es Value	Form
HyPrene BO150	Ceiling	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	5 mg/m3	Mist.
Iceland. OELs. Regulation 154/ Material	1999 on occupational exposu Type	re limits Value	Form
HyPrene BO150	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	1 mg/m3	Mist.
Ireland. Occupational Exposure Components	Limits Type	Value	Form
components		· -	
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Fume.

Material name: HyPrene BO150

Ireland. Occupational Exposure Limits Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Italy. Occupational Exposure Limits Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Inhalable fume.
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Lithuania. OELs. Limit Values for Chem Material	ical Substances, General Re Type	equirements Value	Form
HyPrene BO150	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding) Material	Туре	Value	Form
HyPrene BO150	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms for Cont Material	aminants in the Workplace Type	Value	Form
HyPrene BO150	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TLV	5 mg/m3	Fume.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
Ordinance of the Minister of Labour and and intensities of harmful health factor Material			
HyPrene BO150	STEL	10 mg/m3	Aerosol
iyi iciic botoo	TWA	5 mg/m3	Aerosol
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	STEL	10 mg/m3	Inhalable fraction.
ophali (Cro 0002-72-7)	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	TWA	5 mg/m3	Inhalable fraction.
	xposure to chemical agents	- (ND 1706)	

Material name: HyPrene BO150

HyPrene BO150

10 mg/m3

Aerosol

5634 Version #: 03 Revision date: 01-July-2019 Issue date: 25-April-2016

STEL

	Туре		Form
	TWA	5 mg/m3	Aerosol
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0,5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Romania. OELs. Protection of w Material	orkers from exposure to che Type	mical agents at the workpla Value	ace
HyPrene BO150	STEL	10 mg/m3	
	TWA	5 mg/m3	
Components	Туре	Value	Form
Asphalt (CAS 8052-42-4)	TWA	5 mg/m3	Fume.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Slovakia. OELs. Regulation No. Components	300/2007 concerning protec Type	tion of health in work with Value	chemical agents Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
		Г	Fume and mist.
		5 ppm	rame and mist.
Slovenia. OELs. Regulations co working (Official Gazette of the	Republic of Slovenia)	rs against risks due to expo	sure to chemicals whi
working (Official Gazette of the Components	e Republic of Slovenia) Type	rs against risks due to expo Value	sure to chemicals whi
working (Official Gazette of the Components	Republic of Slovenia)	rs against risks due to expo	sure to chemicals whi
working (Official Gazette of the	Republic of Slovenia) Type TWA	rs against risks due to expo Value	sure to chemicals whi
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure L	Republic of Slovenia) Type TWA .imits	value 10 ppm	Form Vapour and aerosol.
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure L Material	E Republic of Slovenia) Type TWA Limits Type	Value Value Value Value	Form Vapour and aerosol. Form
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure L Material	TWA imits Type STEL	Value 10 ppm Value 10 mg/m3	Form Vapour and aerosol. Form Mist.
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure L Material HyPrene BO150	TWA Type TWA Type STEL TWA	Value 10 ppm Value 10 mg/m3 5 mg/m3	Form Vapour and aerosol. Form Mist. Mist.
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure L Material HyPrene BO150 Components	TWA Limits Type STEL TWA Type	Value 10 ppm Value 10 mg/m3 5 mg/m3 Value	Form Vapour and aerosol. Form Mist. Mist. Form
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure Legal Material HyPrene BO150 Components Asphalt (CAS 8052-42-4) Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA Type TWA STEL TWA Type TWA Type STEL TWA Type TWA Type	Value 10 ppm Value 10 mg/m3 5 mg/m3 Value 0,5 mg/m3	Form Vapour and aerosol. Form Mist. Mist. Form Aerosol
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure Legal Material HyPrene BO150 Components Asphalt (CAS 8052-42-4) Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA Type TWA STEL TWA Type TWA Type STEL TWA Type TWA Type TWA STEL TWA TYPE TWA TYPE	Value 10 ppm Value 10 mg/m3 5 mg/m3 Value 0,5 mg/m3 10 mg/m3 5 mg/m3	Form Vapour and aerosol. Form Mist. Mist. Form Aerosol Mist. Mist.
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure Legal Material HyPrene BO150 Components Asphalt (CAS 8052-42-4) Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Sweden. OELs. Work Environme Material	TWA Type TWA STEL TWA Type TWA Type TWA Type TWA Type TWA STEL TWA STEL TWA STEL TWA STEL	Value 10 ppm Value 10 mg/m3 5 mg/m3 Value 0,5 mg/m3 10 mg/m3 5 mg/m3	Form Vapour and aerosol. Form Mist. Mist. Form Aerosol Mist. Mist. (AFS 2015:7)
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure Legal Material HyPrene BO150 Components Asphalt (CAS 8052-42-4) Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Sweden. OELs. Work Environments	E Republic of Slovenia) Type TWA Limits Type STEL TWA Type TWA STEL TWA STEL TWA STEL TWA STEL	Value 10 ppm Value 10 mg/m3 5 mg/m3 Value 0,5 mg/m3 10 mg/m3 5 mg/m3 Long/m3	Form Vapour and aerosol. Form Mist. Mist. Form Aerosol Mist. Mist. Form Aerosol Mist. Mist. Mist. Form
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure Legal Material HyPrene BO150 Components Asphalt (CAS 8052-42-4) Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Sweden. OELs. Work Environme Material	TWA Type TWA Type STEL TWA Type TWA Type TWA STEL TWA STEL TWA STEL TWA STEL TWA STEL STEL STEL STEL STEL TWA STEL STEL STEL STEL STEL STEL STEL	Value 10 ppm Value 10 mg/m3 5 mg/m3 Value 0,5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 3 mg/m3	Form Vapour and aerosol. Form Mist. Mist. Form Aerosol Mist. Mist. (AFS 2015:7) Form Mist.
working (Official Gazette of the Components Asphalt (CAS 8052-42-4) Spain. Occupational Exposure Lest Material HyPrene BO150 Components Asphalt (CAS 8052-42-4) Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Sweden. OELs. Work Environmental HyPrene BO150	TWA Imits Type STEL TWA Type TWA Type TWA Type TWA STEL TWA TYPE STEL TWA TWA TYPE TWA STEL TWA	Value 10 ppm Value 10 mg/m3 5 mg/m3 Value 0,5 mg/m3 10 mg/m3 5 mg/m3 10 mg/m3 10 mg/m3 1 mg/m3	Form Vapour and aerosol. Form Mist. Mist. Form Aerosol Mist. Mist.

Material name: HyPrene BO150

Switzerland. SUVA Grenzwerte am Arbeitsplatz Form Components Value Asphalt (CAS 8052-42-4) TWA 10 mg/m3 Vapour and aerosol. Distillates (petroleum), **TWA** 5 mg/m3 Inhalable fraction. hydrotreated heavy naphthenic (CAS 64742-52-5) **UK. EH40 Workplace Exposure Limits (WELs)**

Form Value Components Type Fume. Asphalt (CAS 8052-42-4) **STEL** 10 mg/m3 TWA 5 mg/m3 Fume.

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Not available.

Not available.

Derived no effect levels (DNELs)

Predicted no effect

concentrations (PNECs)

Not available.

Exposure guidelines

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Asphalt (CAS 8052-42-4) Can be absorbed through the skin.

8.2. Exposure controls

controls

Appropriate engineering

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information Not available.

Eye/face protection Goggles/face shield are recommended.

Skin protection

- Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

> gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

gloves may be suitable.

- Other Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Under normal conditions, respirator is not normally required. When workers are facing Respiratory protection

> concentrations above the exposure limit they must use appropriate certified respirators. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)]

meeting EN14387.

Thermal hazards Not available.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Heavy Black Oil

Physical state Liquid. **Form** Liquid.

Colour Dark brown to Black Mild Petroleum Odor Odour

Odour threshold Not available.

Material name: HyPrene BO150

pH Not available.

Melting point/freezing point -8 °C (17,6 °F) ASTM D5949/ ISO 3016 Initial boiling point and > 343,33 °C (> 650 °F) ASTM D7169

boiling range Flash point

243,0 °C (469,4 °F) Cleveland open cup ASTM D92/ ISO 2592

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits
Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Vapour pressure Not available.

Vapour density > 5

Relative density 0,942 (15,56 °C (60 °F) ASTM D4052/ ISO 12185)

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not established.

(n-octanol/water)

Auto-ignition temperature > 315,56 °C (> 600 °F) ASTM E659

Decomposition temperature Not available.

Viscosity 682 cSt (40 °C (104 °F) ASTM D445/ ISO 3104)

Explosive propertiesNot available. **Oxidising properties**Not available.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidising agents.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous Hazardous polymerisation does not occur.

reactions

10.4. Conditions to avoid Avoid temperatures exceeding the flash point.

10.5. Incompatible materials Strong oxidising agents.

10.6. HazardousUpon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

decomposition products weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available. **Information on likely routes of exposure**

Inhalation May be harmful if swallowed and enters airways. However, this product does not currently meet

the criteria for classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration.

Symptoms Not available.

11.1. Information on toxicological effects

Acute toxicity Not classified.

Skin corrosion/irritation Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified.

Respiratory sensitisationNot classified. **Skin sensitisation**Not classified.

Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EL

requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

Material name: HyPrene BO150

SDS EU

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Mixture versus substance

Not classified.

information

Not available.

Other information Not available.

SECTION 12: Ecological information

Not expected to be harmful to aquatic organisms. 12.1. Toxicity

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient Not established.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

around.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

EU waste code Not applicable. Waste codes should be assigned by the user based on the application for which the

product was used.

Disposal

methods/information

When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material

characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

General information Not regulated as dangerous goods.

Not available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Material name: HyPrene BO150 SDS EU 9 / 11

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulationsThe product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006

National regulations Germany: WGK 1

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	\	Yes
Canada	Domestic Substances List (DSL)	`	Yes
Canada	Non-Domestic Substances List (NDSL)		No
China	Inventory of Existing Chemical Substances in China (IECSC)	•	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	`	Yes
Europe	European List of Notified Chemical Substances (ELINCS)		No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	•	Yes
Korea	Existing Chemicals List (ECL)	`	Yes
New Zealand	New Zealand Inventory	•	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	`	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	•	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	•	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Material name: HyPrene BO150 SDS EU

SECTION 16: Other information

List of abbreviationsNot available. **References**ACGIH

IARC Monographs. Overall Evaluation of Carcinogenicity

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under

Sections 2 to 15

H225 Highly flammable liquid and vapour.

H350 May cause cancer.

Revision information Product and Company Identification: Product and Company Identification

SECTION 7: Handling and storage: 7,2. Conditions for safe storage, including any incompatibilities

SECTION 8: Exposure controls/personal protection: Appropriate engineering controls

SECTION 8: Exposure controls/personal protection: Respiratory protection

Physical & Chemical Properties: Multiple Properties SECTION 11: Toxicological information: Inhalation

Regulatory Information: United States

SECTION 16: Other information: Further information

Training information

Disclaimer

Not available.

The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Further information

Local CHEMTREC Numbers: CHEMTREC China: 4001-204937

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349

Material name: HyPrene BO150