

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name or designation of the mixture	HyGold 41
Registration number	-
Synonyms	None.
Issue date	05-August-2021
Version number	01
1.2. Relevant identified uses o	f the substance or mixture and uses advised against
Identified uses	Metalworking Fluids, Industrial Lubricants, Grease Manufacturing, Hydraulic Oils, Gear Oils, Heavy Duty Engine Oil, Bar & Chain, Carriers & Diluents, Engine Oil.
Uses advised against	None known.
1.3. Details of the supplier of t	he safety data sheet
MANUFACTURER:	Ergon, Inc.
	P.O. Box 1639
	Jackson, MS 39181 USA
EU Contact:	Ergon International, Inc.
	Drève Richelle 161 Building C
	B-1410 Waterloo, Belgium
Emergency Phone Numbers:	
US Customer Service:	+ 1-800-222-7122
Chemtrec:	+ 1-800-424-9300 After Business Hours (North America)
	+ 1-703-5273887 (International)
	See Section 15 for additional CHEMTREC Hotline Numbers
E-mail:	sds@ergon.com

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classificatio applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Specific target organ toxi	city - single exposureCategory 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.
Hazard summary	May be fatal if swallowed and enters airways. Causes skin system effects.	irritation. May cause central nervous

Distillates (petroleum), hydrotreated light, Distillates (petroleum), hydrotreated light naphthenic

#### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

Danger

Contains:

Hazard pictograms

Signal word Hazard statements H304 H315

May be fatal if swallowed and enters airways. Causes skin irritation.

H336	May cause drowsiness or dizziness.
Precautionary statements	
Prevention	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe gas/fumes/vapour/spray.
P102	Keep out of reach of children.
P280	Wear protective gloves/protective clothing/eye protection/face protection
Response	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician
P302 + P352	IF ON SKIN: Wash with plenty of water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312	Call a POISON CENTRE/doctor if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
Storage	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed
P405	Store locked up.
Disposal	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations
Supplemental label information	None.
2.3. Other hazards	None known.

## **SECTION 3: Composition/information on ingredients**

3.2. Mixtures

#### **General information**

Chemical name	%	CAS-No. / EC No.	<b>REACH Registration No.</b>	Index No.	Notes
Distillates (petroleum), hydrotreated light	40 - 100	64742-47-8 265-149-8	01-2119484819-18	649-422-00-2	
Classification: Asp. Tox. 1;	H304, Aqua	tic Chronic 2;H411			
Distillates (petroleum), hydrotreated light naphthenic	35 - 50	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	
Classification: Asp. Tox. 1;	H304				

#### **SECTION 4: First aid measures**

General information

Contact physician if discomfort continues.

#### 4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention. Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention. Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance. Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control centre immediately. 4.2. Most important Defatting of the skin. symptoms and effects, both acute and delayed 4.3. Indication of any Treat symptomatically. immediate medical attention and special treatment needed

## **SECTION 5: Firefighting measures**

**General fire hazards** 

No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

5.1. Extinguishing media	
Suitable extinguishing media	Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
5.2. Special hazards arising from the substance or mixture	No unusual fire or explosion hazards noted.
5.3. Advice for firefighters Special protective equipment for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Special fire fighting procedures	Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

# **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.			
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.			
6.2. Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.			
6.3. Methods and material for containment and cleaning up	Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.			
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.			
	Never return spills in original containers for re-use.			
6.4. Reference to other sections	For personal protection, see section 8. For waste disposal, see section 13.			

# **SECTION 7: Handling and storage**

7.1. Precautions for safe handling	Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame.
7.3. Specific end use(s)	Not available.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## **Occupational exposure limits**

cupational exposure limits Belgium. Exposure Limit Values. Material	Туре	Value	Form
HyGold 41	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m3	Vapour.

Belgium. Exposure Limit Values Components	s. Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Bulgaria. OELs. Regulation No 1 Material	L3 on protection of workers a Type	against risks of exposure to Value	chemical agents at work
HyGold 41	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	300 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	
Czech Republic. OELs. Governm			_
Material	Туре	Value	Form
HyGold 41	Ceiling	10 mg/m3	Aerosol
<b>.</b> .	TWA	5 mg/m3	Aerosol
Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
Denmark. Exposure Limit Value Material	s Type	Value	Form
HyGold 41	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.
Finland. Workplace Exposure Li Components	mits Type	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	500 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Germany. DFG MAK List (adviso Compounds in the Work Area ( Components	DFG)	e Investigation of Health Ha Value	azards of Chemical Form
-	Туре		
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	5 mg/m3	Respirable aerosol fraction
		350 mg/m3	Vapour.
		50 ppm	Vapour.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Respirable fraction.

	Туре	Value	Form
HyGold 41	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light haphthenic (CAS 54742-53-6)	TWA	5 mg/m3	Mist.
lungary. OELs. Joint Decree on Material	Chemical Safety of Workplace Type	es Value	Form
HyGold 41	Ceiling	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light haphthenic (CAS 54742-53-6)	Ceiling	5 mg/m3	Mist.
Iceland. OELs. Regulation 154/ Material	1999 on occupational exposur Type	e limits Value	Form
lyGold 41	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6)	TWA	1 mg/m3	Mist.
reland. Occupational Exposure Components	Limits Type	Value	Form
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Italy Occupational Exposure L			Fa
	Туре	Value	Form
Components Distillates (petroleum), hydrotreated light haphthenic (CAS	TWA	5 mg/m3	
Italy. Occupational Exposure Li Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Latvia. OELs. Occupational expo Components	TWA	5 mg/m3	Inhalable fraction.
Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Latvia. OELs. Occupational expo	TWA	5 mg/m3 substances in work enviro	Inhalable fraction.
Components Distillates (petroleum), hydrotreated light haphthenic (CAS 54742-53-6) Latvia. OELs. Occupational expe Components Distillates (petroleum), hydrotreated light haphthenic (CAS	TWA osure limit values of chemical s Type TWA	5 mg/m3 substances in work enviro Value 5 mg/m3	Inhalable fraction.
Components Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Latvia. OELs. Occupational expe Components Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Lithuania. OELs. Limit Values for Material	TWA osure limit values of chemical s Type TWA or Chemical Substances, Gener	5 mg/m3 substances in work enviro Value 5 mg/m3 ral Requirements	Inhalable fraction.
Components Distillates (petroleum), apdrotreated light aphthenic (CAS 4742-53-6) Components Distillates (petroleum), apdrotreated light aphthenic (CAS 4742-53-6) Lithuania. OELs. Limit Values for faterial	TWA osure limit values of chemical s Type TWA or Chemical Substances, Gener Type	5 mg/m3 substances in work enviro Value 5 mg/m3 ral Requirements Value 3 mg/m3	Inhalable fraction. nment Form
Components Distillates (petroleum), hydrotreated light haphthenic (CAS 44742-53-6) <b>Latvia. OELs. Occupational expe</b> Components Distillates (petroleum), hydrotreated light haphthenic (CAS 44742-53-6) Lithuania. OELs. Limit Values for daterial	TWA osure limit values of chemical s Type TWA or Chemical Substances, Gener Type STEL TWA	5 mg/m3 substances in work enviro Value 5 mg/m3 ral Requirements Value	Inhalable fraction. nment Form Fume and mist.
Components Distillates (petroleum), hydrotreated light haphthenic (CAS h4742-53-6) components Distillates (petroleum), hydrotreated light haphthenic (CAS h4742-53-6) cithuania. OELs. Limit Values for haterial hyGold 41 Components Distillates (petroleum), hydrotreated light (CAS	TWA osure limit values of chemical s Type TWA or Chemical Substances, Gener Type STEL	5 mg/m3 substances in work enviro Value 5 mg/m3 ral Requirements Value 3 mg/m3 1 mg/m3	Inhalable fraction. nment Form Fume and mist. Fume and mist.
Components Distillates (petroleum), hydrotreated light haphthenic (CAS 54742-53-6) Latvia. OELs. Occupational expe Components Distillates (petroleum), hydrotreated light haphthenic (CAS 54742-53-6) Lithuania. OELs. Limit Values for	TWA Desure limit values of chemical s Type TWA TWA Dor Chemical Substances, Gener Type STEL TWA TWA Type	5 mg/m3 substances in work enviro Value 5 mg/m3 ral Requirements Value 3 mg/m3 1 mg/m3 Value	Inhalable fraction. nment Form Fume and mist. Fume and mist.
Components Distillates (petroleum), hydrotreated light haphthenic (CAS 54742-53-6) Latvia. OELs. Occupational expension Distillates (petroleum), hydrotreated light haphthenic (CAS 54742-53-6) Lithuania. OELs. Limit Values fe Material HyGold 41 Components Distillates (petroleum), hydrotreated light (CAS	TWA  Desure limit values of chemical a Type TWA  Description TWA  Description Type STEL TWA Type STEL STEL STEL STEL STEL STEL STEL STEL	5 mg/m3 substances in work enviro Value 5 mg/m3 ral Requirements Value 3 mg/m3 1 mg/m3 Value 500 mg/m3	Inhalable fraction. nment Form Fume and mist. Fume and mist.

# Netherlands. OELs (binding)

Material	Туре	Value	Form
HyGold 41	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms fo Material	or Contaminants in the Workplace Type	Value	Form
HyGold 41	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TLV	275 mg/m3	
		40 ppm	
Distillates (petroleum),	TLV	1 mg/m3	Mist.

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

# Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Material	Туре	Value	Form
HyGold 41	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	STEL	300 mg/m3	
	TWA	100 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.

# Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Material	Туре	Value	Form
HyGold 41	STEL	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	eated light enic (CAS		Inhalable fraction.

## Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Material	Туре	Value	
HyGold 41	STEL	10 mg/m3	
	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	
	TWA	5 mg/m3	

Components	n No. 300/2007 concerning protec Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
Spain. Occupational Expo Material	sure Limits Type	Value	Form
HyGold 41	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	200 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
,	TWA	5 mg/m3	Mist.
Sweden. OELs. Work Envi	ironment Authority (AV), Occupatio	nal Exposure Limit Values (	(AFS 2015:7)
Material	Туре	Value	Form
HyGold 41	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	STEL	500 mg/m3	
	TWA	350 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Switzerland. SUVA Grenz Components	werte am Arbeitsplatz Type	Value	Form
Distillates (petroleum), hydrotreated light (CAS	STEL	700 mg/m3	
64742-47-8)	TWA	350 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
ogical limit values	No biological exposure limits noted for	or the ingredient(s).	
ommended monitoring cedures	Not available.		
ived no effect levels IELs)	Not available.		
dicted no effect centrations (PNECs)	Not available.		
Exposure controls			
propriate engineering trols	Provide adequate ventilation, includin occupational exposure limit is not exp		to ensure that the defined
ividual protection measur General information	es, such as personal protective equ Not available.	ipment	
Eye/face protection	Goggles/face shield are recommende		

Material name: HyGold 41 - Ergon International

Skin protection	
- Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.
- Other	Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.
Respiratory protection	Under normal conditions, respirator is not normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN14387.
Thermal hazards	Not available.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental exposure controls	Not available.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance	Clear & bright
Physical state	Liquid.
Form	Liquid.
Colour	Not available.
Odour	Mild Petroleum Odor
Odour threshold	Not available.
рН	Not applicable.
Melting point/freezing point	-75 °C (-103 °F) ASTM D5950/ ISO 3016
Initial boiling point and boiling range	> 212,78 °C (> 415 °F) ASTM D2887/ ISO 3294
Flash point	121,0 °C (249,8 °F) Cleveland open cup ASTM D92 estimated 111,0 °C (231,8 °F) Pensky-Martens Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or e	xplosive limits
Flammability limit - lower (%)	0,7 % estimated
Flammability limit - upper (%)	5 % estimated
Vapour pressure	0,6 hPa estimated
Vapour density	Not available.
Relative density	0,87 (15,56 °C (60 °F) ASTM D4052)
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not established.
Auto-ignition temperature	> 315,56 °C (> 600 °F) ASTM E659
Decomposition temperature	Not available.
Viscosity	4,2 cSt @40°C (40 °C (104 °F) ASTM D445/ ISO 3104)
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information	No relevant additional information available.

# **SECTION 10: Stability and reactivity**

10.1. Reactivity	Strong oxidising agents.
10.2. Chemical stability	Stable.
10.3. Possibility of hazardous reactions	Hazardous polymerisation does not occur.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

# **SECTION 11: Toxicological information**

Skin contact Eye contact Ingestion	May be fatal if Frequent or pro May be irritatin May cause gas increase risk of	ng to eyes. trointestinal discomfort if swallowed. Do	skin, leading to discomfort and dermatitis
Inhalation Skin contact Eye contact Ingestion Symptoms 11.1. Information on toxicologi	May be fatal if Frequent or pro May be irritatin May cause gas increase risk of	olonged contact may defat and dry the ng to eyes. trointestinal discomfort if swallowed. Do	skin, leading to discomfort and dermatitis
Skin contact Eye contact Ingestion Symptoms 11.1. Information on toxicologi	Frequent or pro May be irritatin May cause gas increase risk of	olonged contact may defat and dry the ng to eyes. trointestinal discomfort if swallowed. Do	skin, leading to discomfort and dermatitis
Eye contact Ingestion Symptoms 11.1. Information on toxicologi	May be irritatir May cause gas increase risk of	ng to eyes. trointestinal discomfort if swallowed. Do	skin, leading to discomfort and dermatitis
Ingestion Symptoms 11.1. Information on toxicologi	May cause gas increase risk of	trointestinal discomfort if swallowed. Do	
Symptoms 11.1. Information on toxicologi	increase risk of		
11.1. Information on toxicologi	Defatting of th	i product aspiration. May be fatar il swa	o not induce vomiting. Vomiting may illowed and enters airways.
-		e skin. Coughing. Shortness of breath.	Discomfort in the chest
Acute toxicity	cal effects		
	Not applicable.		
-	Irritating to ski		
Serious eye damage/eye irritation	Not classified.	May cause minor irritation on eye conta	act.
Respiratory sensitisation	Not classified.		
Skin sensitisation	Not classified.		
Germ cell mutagenicity	No data availal mutagenic or g	ble to indicate product or any componen genotoxic.	nts present at greater than 0.1% are
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EL requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.		
at work (as amended) Not listed. Reproductive toxicity	Contains no ind	gredient listed as toxic to reproduction	
		nervous system effects.	
- single exposure		nervous system enects.	
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Mixture versus substance information	Not available.		
Other information	Risk of chemical pneumonia after aspiration.		
SECTION 12: Ecological in	nformation		
12.1. Toxicity	Not expected t	o be harmful to aquatic organisms.	
Product		Species	Test Results
HyGold 41			
Aquatic			
Fish L	C50	Fish	5,0435 mg/l, 96 hours estimated
Components		Species	Test Results
Distillates (petroleum), hydrotreated	d light (CAS 647	742-47-8)	
Aquatic			
Fish L	C50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2,9 mg/l, 96 hours

Not available. \* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability	Not inherently biodegradable.
12.3. Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
Partition coefficient n-octanol/water (log Kow)	Not established.
<b>Bioconcentration factor (BCF)</b>	Not available.
12.4. Mobility in soil	Not available.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.
EU waste code	Not applicable. Waste codes should be assigned by the user based on the application for which the product was used.
Disposal methods/information	Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
	information.

## **SECTION 14: Transport information**

#### ADR

14.1. - 14.6.: Not regulated as dangerous goods.

# RID

14.1. - 14.6.: Not regulated as dangerous goods.

#### ADN

14.1. - 14.6.: Not regulated as dangerous goods.

#### IATA

14.1. - 14.6.: Not regulated as dangerous goods.

#### IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

## **14.7. Transport in bulk** Not available.

according to Annex II of MARPOL 73/78 and the IBC Code

**General information** 

Not regulated as dangerous goods.

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

#### Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended** Not listed.

Not listed.		
Regulation (EC) No. 1907	/2006, REACH Article 59(10) Candidate List as currently publis	shed by ECHA
Not listed.		
uthorisations		
Regulation (EC) No. 1907, Not listed.	/2006, REACH Annex XIV Substances subject to authorization,	, as amended
estrictions on use		
Regulation (EC) No. 1907, amended	/2006, REACH Annex XVII Substances subject to restriction or	ו marketing and use as
Directive 2004/37/EC: on mutagens at work, as ame		o carcinogens and
	ydrotreated light naphthenic (CAS 64742-53-6)	
Other EU regulations		
Not listed.	major accident hazards involving dangerous substances, as ar	nended
ther regulations	The product is classified and labelled in accordance with EC directives or respective national laws This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006	
lational regulations	Germany: WGK 1	
5.2. Chemical safety ssessment	No Chemical Safety Assessment has been carried out.	
nternational Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Y
Canada	Domestic Substances List (DSL)	Y
Canada	Non-Domestic Substances List (NDSL)	1
China	Inventory of Existing Chemical Substances in China (IECSC)	Y
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Y
Europe	European List of Notified Chemical Substances (ELINCS)	٦
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Y
Korea	Existing Chemicals List (ECL)	Y
New Zealand	New Zealand Inventory	Y
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Y
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Y
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Y

SECTION 16: Other information

country(s).

List of abbreviations	Not available.
References	ACGIH IARC Monographs. Overall Evaluation of Carcinogenicity ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics ILO Safety Cards International Labour Organization International Maritime Organization Marine Pollutants List NFPA Hazardous Chemical Data Sheets NIOSH Pocket Guide Registry of Toxic Effects of Chemical Substances (RTECS) US DOT Hazardous Materials Regulations
Information on evaluation method leading to the classification of mixture	Not available.

Full text of any H-statements not written out in full under Sections 2 to 15	H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.
Revision information	Product and Company Identification: Alternate Trade Names SECTION 2: Hazards identification: Response SECTION 2: Hazards identification: Prevention SECTION 11: Toxicological information: Carcinogenicity
Training information	Not available.
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Further information	Local CHEMTREC Numbers: CHEMTREC China: 4001-204937 CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349