

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyGold L750

Identification number 649-465-00-7 (Index number)

Registration number 01-2119467170-45

Synonyms None.

24-February-2014 **Issue date**

Version number

Revision date 29-April-2021 Supersedes date 07-May-2019

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Metalworking Fluids, Industrial Lubricants, Grease Manufacturing, Hydraulic Oils, Gear Oils, Heavy

Duty Engine Oil, Bar & Chain, Carriers & Diluents, Engine Oil.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company: Ergon, Inc. Address: P.O. Box 1639

Jackson, MS 39215

E-mail: sds@ergon.com

Emergency Contacts

Customer service: 1-800-222-7122

Chemtrec: 1-800-424-9300 After Business Hours (North America Only)

1-703-527-3887 After Business Hours (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended

Hazard summary Not available.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.

Signal word Not applicable. **Hazard statements** Not applicable.

Precautionary statements

Prevention Not available. Response Not applicable. Storage Not applicable. Disposal Not applicable.

Supplemental label

information

None.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated heavy naphthenic	<=100	64742-52-5 265-155-0	01-2119467170-45	649-465-00-7	
Classification: -					L

Material name: HyGold L750 SDS EU 1 / 10

Note L - Not classified as a carcinogen. Meets EU requirement of less than 3% (w/w) DMSO extract

for total polycyclic aromatic compound (PAC) using IP 346.

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eve contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of Ingestion

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both acute and delayed

Defatting of the skin.

4.3. Indication of any

Treat symptomatically.

immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

5.1. Extinguishing media

Suitable extinguishing

media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or

No unusual fire or explosion hazards noted.

mixture

5.3. Advice for firefighters Special protective

equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

Material name: HyGold L750 SDS EU

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work.

Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Material	Туре	Value	Form	
HyGold L750	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work Material Type Value

	71"		
HyGold L750	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	

Denmark. Exposure Limit Values

Material	Туре	Value	Form	
HyGold L750	TLV	1 mg/m3	Mist.	
Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.	

Finland, Workplace Exposure Limits

64742-52-5)

Components	Туре	Value	Form	
Distillates (petroleum), hydrotreated heavy	TWA	5 mg/m3	Mist.	
naphthenic (CAS				

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Material	Туре	Value	Form
HyGold L750	TWA	5 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/ Material	1999, as amended) Type	Value	Form
HyGold L750	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.

Material name: HyGold L750 SDS EU

	Туре	Value	Form
HyGold L750	Ceiling	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	5 mg/m3	Mist.
Iceland. OELs. Regulation 154/1999 or Material	n occupational exposure limits Type	Value	Form
HyGold L750	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	1 mg/m3	Mist.
Ireland. Occupational Exposure Limits Material	Туре	Value	Form
HyGold L750	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Italy. Occupational Exposure Limits Material	Туре	Value	Form
HyGold L750	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
		F / 2	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
hydrotreated heavy naphthenic (CAS		J	Inhalable fraction. Form
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem	nical Substances, General Requir	rements	
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material	nical Substances, General Requir Type	ements Value	Form
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material	nical Substances, General Requir Type STEL	rements Value 3 mg/m3	Form Fume and mist.
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material HyGold L750	nical Substances, General Requir Type STEL TWA	rements Value 3 mg/m3 1 mg/m3	Form Fume and mist. Fume and mist.
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material HyGold L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	nical Substances, General Requir Type STEL TWA Type	rements Value 3 mg/m3 1 mg/m3 Value	Form Fume and mist. Fume and mist. Form
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material HyGold L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	nical Substances, General Requir Type STEL TWA Type STEL	rements Value 3 mg/m3 1 mg/m3 Value 3 mg/m3	Form Fume and mist. Fume and mist. Form Fume and mist.
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material HyGold L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Netherlands. OELs (binding) Material	nical Substances, General Requir Type STEL TWA Type STEL TWA Type STEL TWA	rements Value 3 mg/m3 1 mg/m3 Value 3 mg/m3 Value 1 mg/m3 Value	Form Fume and mist. Form Fume and mist. Fume and mist.
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material HyGold L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Netherlands. OELs (binding)	nical Substances, General Requir Type STEL TWA Type STEL TWA Type TWA Type TWA	rements Value 3 mg/m3 1 mg/m3 Value 3 mg/m3	Form Fume and mist. Form Fume and mist. Form Fume and mist. Fume and mist. Form
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material HyGold L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Netherlands. OELs (binding) Material HyGold L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS	nical Substances, General Requir Type STEL TWA Type STEL TWA Type STEL TWA	rements Value 3 mg/m3 1 mg/m3 Value 3 mg/m3 Value 5 mg/m3	Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Mist.
hydrotreated heavy naphthenic (CAS 64742-52-5) Lithuania. OELs. Limit Values for Chem Material HyGold L750 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Netherlands. OELs (binding) Material HyGold L750	nical Substances, General Requir Type STEL TWA Type STEL TWA Type TWA Type TWA Type TWA Type	rements Value 3 mg/m3 1 mg/m3 Value 3 mg/m3 Value 5 mg/m3 Value	Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Mist. Form

Material name: HyGold L750 5607 Version #: 06 Revision date: 29-April-2021 Issue date: 24-February-2014

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentration and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817 Material Type Value Form TWA 5 mg/m3 Inhalable fraction. Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Pormal Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Pormal Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Pormal Distillates (petroleum), Type Value Form Type Value Form Distillates (petroleum), Type Value Type Value Distillates (petroleum), Type Value Distillates (petroleum), Type Value Type Value Form TWA 5 mg/m3 Fume and mist. Type Value Form Distillates (petroleum), Form Fume and mist. Type Value Form Distillates (petroleum), Form Fume and mist. Type Value Form Distillates (petroleum), Form Fume and mist. Type Value Form Distillates (petroleum), Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist.				
hydrotreated heavy naphthenic (CAS 64742-52-5) Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentration and intensities of harmful health factors in the work environment, Journal of Laws 2014, Item 817 Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Ocmponents Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Portugal. VLEs. Norm on occupational exposure to chemical agents at the workplace Value Form Distillates (petroleum), TWA 5 mg/m3 Inhalable fraction. Portugal. VLEs. Norm on occupational exposure to chemical agents at the workplace Value Form Distillates (petroleum), Type Value Distillates (petroleum), Type Value Form Distillates (petroleum), STEL 10 mg/m3 Form of Material Type Value Form Portugal. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Material Type Value Form Promition of Hall in work with chemical agents Material Form Form TWA 5 mg/m3 Furne and mist. Type Value Form Promition of Material Type Value Form TWA 1 mg/m3 Furne and mist. Form TWA 3 mg/m3 Furne and mist. Form Prome and mist. Promocord Health in work with chemical agents Prome and mist. Prome and mi	Norway. Administrative Norm Components			Form
Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Components Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Type Value Form Inhalable fraction. Type Value Form Inhalable fraction. Type Value Form Inhalable fraction. Form Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Type Value Form Inhalable fraction. Type Value HyGold L750 TWA 5 mg/m3 Inhalable fraction. Type Value HyGold L750 STEL 10 mg/m3 TWA 5 mg/m3 Components Type Value Distillates (petroleum), Type Value Distillates (petroleum), Type Value Inhalable fraction. Type Value Form TWA 5 mg/m3 Furne and mist. Type Value Form TWA 5 mg/m3 Furne and mist. Inhalable fraction. Type Value Form TWA 5 mg/m3 Furne and mist. Inhalable fraction. Type Value Form TWA 5 mg/m3 Furne and mist. Inhalable fraction. Type Value Form TWA 5 mg/m3 Furne and mist. Inhalable fraction.	Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Components Type Value Form Distiliates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Inhalable fraction. Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Value Form Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Inhalable fraction. Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Material Type Value Value Value HyGold L750 STEL 10 mg/m3 TWA 5 mg/m3 TWA Components Type Value Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Furne and mist. HyGold L750 STEL 3 mg/m3 Furne and mist. HyGold L750 STEL				
Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Components Type Value Form TWA 5 mg/m3 Inhalable fraction. Form Form Type Value Form TWA 5 mg/m3 Inhalable fraction. Form Type Value Form TWA 5 mg/m3 Inhalable fraction. Form Type Value Form TWA 5 mg/m3 Inhalable fraction. Form TWA 5 mg/m3 Furne and mist. In mg/m3 Furne and mist. Form TWA 1 mg/m3 Furne and mist. Form Distillates (petroleum), Type Value Form Distillates (petroleum), Type Value Form Distillates (petroleum), Type Value Form Form Form Furne and mist. Furne and mist. Form Furne and mist. Furne and mist.			-	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)	HyGold L750	TWA	5 mg/m3	Inhalable fraction.
hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796) Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Components Type Value Form Distillates (petroleum), hydrotreated heavy napathenic (CAS 64742-52-5) Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value HyGold L750 STEL 10 mg/m3 TWA 5 mg/m3 Components Type Value Distillates (petroleum), STEL 10 mg/m3 TWA 5 mg/m3 Components Type Value Distillates (petroleum), STEL 10 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Material Type HyGold L750 STEL 3 mg/m3 Fume and mist. Type Value Form TWA 1 mg/m3 Fume and mist. Type Value Form HyGold L750 STEL 3 mg/m3 Fume and mist. Type Value Form TWA 1 mg/m3 Fume and mist. TWA 1 mg/m3 Fume and mist. Sppm Fume and mist. Form Distillates (petroleum), Type Value Form Components Type Value Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist.	Components	Туре	Value	Form
Material Type Value Form HyGold L750 TWA 5 mg/m3 Inhalable fraction. Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Inhalable fraction. Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value Value Value HyGold L750 STEL 10 mg/m3 Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 SHOWAKIA. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Material Form HyGold L750 STEL 3 mg/m3 Fume and mist. HyGold L750 STEL 1 mg/m3 Fume and mist. HyGold L750 STEL 3 mg/m3 Fume and mist. TWA 1 mg/m3 Fume and mist. TWA 1 mg/m3 Fume and mist. Components Type Value Form Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 3 mg/m3 Fume and mist. Hydrotreated heavy naphthenic (CAS 64742-52-5) Type Value Form <td>Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)</td> <td>TWA</td> <td>5 mg/m3</td> <td>Inhalable fraction.</td>	Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value HyGold L750 STEL 10 mg/m3 TWA 5 mg/m3 Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 STEL 10 mg/m3 Form TWA 5 mg/m3 STEL 10 mg/m3 Form TWA 5 mg/m3 Form TWA 5 mg/m3 Form Form TWA 5 mg/m3 Fune and mist. 15 ppm Fune and mist. 15 ppm Fune and mist. 5 ppm Fune and mist. 64742-52-5) Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Form Form Form Form Fune and mist. Form Fine and mist. Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Fune and mist. Form Fune and mist. Fune and mis				Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value HyGold L750 STEL 10 mg/m3 TWA 5 mg/m3 Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Form HyGold L750 STEL 3 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Form HyGold L750 STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. TWA 1 mg/m3 Fume and mist. TWA 1 mg/m3 Fume and mist. TWA 1 mg/m3 Fume and mist. Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Type Value Form Distillates (petroleum), STEL 3 mg/m3 Fume and mist. Form Fume and mist.	HyGold L750	TWA	5 mg/m3	Inhalable fraction.
hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of workers from exposure to chemical agents at the workplace Value HyGold L750 STEL 10 mg/m3 TWA 5 mg/m3 Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Form HyGold L750 STEL 3 mg/m3 Fume and mist. TWA 1 mg/m3 Fume and mist. Type Value Form Distillates (petroleum), STEL 3 mg/m3 Fume and mist. Type Value Form Fume and mist. Type Value Form Distillates (petroleum), STEL 3 mg/m3 Fume and mist. Type Value Form Distillates (petroleum), STEL 3 mg/m3 Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist. Form Fume and mist.	Components	Туре	Value	Form
Material Type Value HyGold L750 STEL TWA 10 mg/m3 5 mg/m3 Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL TWA 10 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Type Form HyGold L750 STEL TWA 3 mg/m3 15 ppm Fume and mist. Fume and mist. TWA TWA 1 mg/m3 5 ppm Fume and mist. Fume and mist. Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 3 mg/m3 4 mg/m3 5 ppm Fume and mist. Fume and mist. Fume and mist.	hydrotreated heavy naphthenic (CAS	TWA	5 mg/m3	Inhalable fraction.
TWA 5 mg/m3 Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Form Type Value Form HyGold L750 STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 5 ppm Fume and				ace
Components Type Value Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA STEL TWA S mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Form HyGold L750 STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 15 ppm Fume and mist. 5 ppm Fume and mist. 6 ppm Fume and mist. 7 ppe Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist.	HyGold L750	STEL	10 mg/m3	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Type Value Form HyGold L750 STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. 15 ppm Fume and mist. 5 ppm Fume and mist. 6 ppm Fume and		TWA	5 mg/m3	
hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 5 mg/m3 Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Material Type Value Form HyGold L750 STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. 5 ppm Fume and mist. Type Value Form Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist.	Components	Туре	Value	
Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents Material HyGold L750 STEL 3 mg/m3 Fume and mist. 15 ppm Fume and mist. TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist. 15 ppm Fume and mist.	Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	
MaterialTypeValueFormHyGold L750STEL3 mg/m3Fume and mist.15 ppmFume and mist.TWA1 mg/m3Fume and mist.5 ppmFume and mist.ComponentsTypeValueFormDistillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)STEL3 mg/m3Fume and mist.15 ppmFume and mist.	,	TWA	5 mg/m3	
TWA 15 ppm Fume and mist. 15 ppm Fume and mist. 1 mg/m3 Fume and mist. 5 ppm Fume and mist. Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist.	_			_
TWA 15 ppm Fume and mist. 15 ppm Fume and mist. 1 mg/m3 Fume and mist. 5 ppm Fume and mist. Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist.	HyGold L750	STEL	3 mg/m3	Fume and mist.
TWA 1 mg/m3 Fume and mist. 5 ppm Fume and mist. Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist.			5.	Fume and mist.
Components Type Value Form Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist.		TWA	• •	Fume and mist.
Distillates (petroleum), STEL 3 mg/m3 Fume and mist. hydrotreated heavy naphthenic (CAS 64742-52-5) 15 ppm Fume and mist.			5 ppm	Fume and mist.
hydrotreated heavy naphthenic (CAS) 64742-52-5) 15 ppm Fume and mist.	_	Туре	Value	Form
	Components			
TWA 1 mg/m3 Fume and mist.	Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	3 mg/m3	Fume and mist.
	Distillates (petroleum), hydrotreated heavy naphthenic (CAS	STEL	-	

Material name: HyGold L750

Type

STEL TWA 5 ppm

Value

10 mg/m3

5 mg/m3

5607 Version #: 06 Revision date: 29-April-2021 Issue date: 24-February-2014

Spain. Occupational Exposure Limits

Material

HyGold L750

Fume and mist.

Form

Mist.

Mist.

Spain. Occupational Exposure Limits Form Components Value Type Distillates (petroleum), **STEL** 10 mg/m3 Mist. hydrotreated heavy naphthenic (CAS 64742-52-5) **TWA** 5 mg/m3 Mist. Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7) **Material Value Form** Type HyGold L750 **STEL** 3 mg/m3 Mist.

 HyGold L750
 STEL
 3 mg/m3
 Mist.

 TWA
 1 mg/m3
 Mist.

 Components
 Type
 Value
 Form

STEL

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

TWA 1 mg/m3 Mist.

3 mg/m3

Mist

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Form Material Value Type HyGold L750 **TWA** 5 mg/m3 Inhalable fraction. Components Form **Type** Value TWA Inhalable fraction. Distillates (petroleum), 5 mg/m3

hydrotreated heavy naphthenic (CAS 64742-52-5)

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Not available.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information Not available.

Skin protection
- Hand protection

Eye/face protection

Goggles/face shield are recommended.

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

gloves may be suitable.

- **Other** Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection Under normal conditions, respirator is not normally required. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Not available.

Hygiene measuresAlways observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear & bright Physical state Liquid.

Material name: HyGold L750

Form Liquid.
Colour Amber.

Odour Mild Petroleum Odor

Odour threshold Not available. **pH** Not available.

Melting point/freezing point -27 °C (-16,6 °F) ASTM D5949/ ISO 3016

Initial boiling point and

boiling range

320 °C (608 °F) ASTM D2887

Flash point 217,0 °C (422,6 °F) Pensky-Martens Closed Cup ASTM D93/ ISO 2592

228,0 °C (442,4 °F) Cleveland open cup ASTM D92/ ISO 2719

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

Not available.

upper (%)

Vapour pressure Not available.

Vapour density > 5

Relative density 0,92 (15,56 °C (60 °F) ASTM D4052/ ISO 12185)

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not established.

(n-octanol/water)

Auto-ignition temperature > 315,56 °C (> 600 °F) ASTM E659

Decomposition temperature Not available.

Viscosity 144 cSt (40 °C (104 °F) ASTM D445/ ISO 3014)

Explosive propertiesNot available. **Oxidising properties**Not available.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidising agents.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous

Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous

reactions

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

decomposition products weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available. **Information on likely routes of exposure**

Inhalation May be harmful if inhaled. However, this product does not currently meet the criteria for

classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration.

Symptoms Not available.

11.1. Information on toxicological effects

Acute toxicity Not classified.

Skin corrosion/irritation Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified.

Material name: HyGold L750 SDS EU

Respiratory sensitisationNot classified. **Skin sensitisation**Not classified.

Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EL

requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346. Note L -

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicityContains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

C-----

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard
Mixture versus substance

information

Not classified. Not available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Not expected to be harmful to aquatic organisms.

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative Bioaccumulati

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient

n-octanol/water (log Kow)

Not established.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

around.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

EU waste codeNot applicable. Waste codes should be assigned by the user based on the application for which the

product was used.

Disposal methods/information

No components are identified as hazardous wastes. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations,

and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

TMDG

14.1. - 14.6.: Not regulated as dangerous goods.

Material name: HyGold L750 SDS EU

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Not available.

Code

General information Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulationsThe product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006

National regulations Germany: WGK 1

15.2. Chemical safety No Chemical Safety Assessment has been carried out.

assessment

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

Material name: HyGold L750 SDS EU

Country(s) or regionInventory nameOn inventory (yes/no)*New ZealandNew Zealand InventoryYes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: Other information

List of abbreviations Not available.

References Chemical Abstracts Service Registry Handbook

CRC: Handbook of Chemistry and Physics

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

ACGIH

IARC Monographs. Overall Evaluation of Carcinogenicity

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under

Sections 2 to 15

None.

Revision information Composition / Information on Ingredients: Disclosure Overrides

SECTION 3: Composition/information on ingredients: Composition comments

Physical & Chemical Properties: Multiple Properties SECTION 11: Toxicological information: Carcinogenicity

Training information

Disclaimer

Not available.

The information provided in this Safety Data Sheet is correct to the best of our knowledge.

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Further information Local CHEMTREC Numbers:

CHEMTREC China: 4001-204937

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349

Material name: HyGold L750 SDS EU