ERGON E

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyPrene L1200

Identification number 649-465-00-7 (Index number)

Registration number 01-2119467170-45

Synonyms None.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Tire Oils, Rubber Compounding, Automotive & Industrial Hoses, Dedusting, Plasticizer, Titanium

Dioxide Wash, Compressor Wash Oils, Hydraulic Fracturing Oil, Adhesives, Carpet Backing, Feed Stock for White Oil, Refrigeration Oil, Diluents and Carriers, Carbon Black, Banbury Dust Stop,

Defoamers, Sealants, Belts & Hoses, Coatings, Leather Tanning, Agriculture Oils.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

CHEMTREC: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International),

+32-28083237 (Belgium) +33-975181407 (France) +49-69643508409 (Germany) +39-0245557031 (Italy) +34-931768545 (Spain)

E-mail: sds@ergon.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

This substance does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.

Signal word None.

Hazard statements The substance does not meet the criteria for classification.

Precautionary statements

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Supplemental label

information

None.

2.3. Other hazards This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

The substance is not considered to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. The substance is not included in the list established in accordance with REACH

Article 59(1) for having endocrine disrupting properties.

Material name: HyPrene L1200 - Ergon International
4725 Version #: 04 Revision date: 17-November-2022 Issue date: 18-June-2018

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated heavy naphthenic	<=100	64742-52-5 265-155-0	01-2119467170-45	649-465-00-7	
Classification:	-				L

Composition comments

Note L - Not classified as a carcinogen. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eve contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any immediate medical attention and special treatment

Treat symptomatically.

Defatting of the skin.

needed

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an

extinguisher, as this will spread the fire.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Special fire fighting procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves. rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot

be contained.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the

ground.

Material name: HyPrene L1200 - Ergon International 4725 Version #: 04 Revision date: 17-November-2022 Issue date: 18-June-2018

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS, For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame.

Observe industrial sector guidance on best practices. 7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values

Material	Туре	Value	Form
HyPrene L1200	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Bulgaria. OELs. Regulation No 13 Material	on protection of workers a Type	against risks of exposure to Value	chemical agents at work
HyPrene L1200	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	
Czech Republic. OELs. Governme	nt Decree 361		
Material	Туре	Value	
HyPrene L1200	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
Denmark. Exposure Limit Values			
Material	Туре	Value	Form
HyPrene L1200	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
Finland. Workplace Exposure Lim			
Material	Туре	Value	Form
HyPrene L1200	TWA	5 mg/m3	Mist.

Material name: HyPrene L1200 - Ergon International

4725 Version #: 04 Revision date: 17-November-2022 Issue date: 18-June-2018

Components	Limits Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Compounds in the Work Area	-	_	
Material	Туре	Value	Form
HyPrene L1200	TWA	5 mg/m3	Respirable fraction
Greece. OELs (Decree No. 90/ Material	1999, as amended) Type	Value	Form
HyPrene L1200	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree of Material	on Chemical Safety of Workpla Type	ces Value	
HyPrene L1200	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	
Iceland. OELs. Regulation 154 Material	1/1999 on occupational exposu Type	ıre limits Value	Form
HyPrene L1200	TWA	1 mg/m3	Mist.
	Туре	Value	Form
Components	.,,,,		
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	1 mg/m3	Mist.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Italy. Occupational Exposure	TWA	1 mg/m3 Value	Mist. Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Italy. Occupational Exposure Material	TWA	Value	
Distillates (petroleum), hydrotreated heavy naphthenic (CAS	TWA Limits Type		Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Italy. Occupational Exposure Material HyPrene L1200	TWA Limits Type TWA	Value 5 mg/m3	Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Italy. Occupational Exposure Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA Limits Type TWA Type	Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Italy. Occupational Exposure Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Latvia. OELs. Occupational ex	TWA Limits Type TWA Type TWA Type TWA Tope TWA Tope TWA	Value 5 mg/m3 Value 5 mg/m3	Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Italy. Occupational Exposure Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Latvia. OELs. Occupational ex Material	TWA Limits Type TWA Type TWA Type TWA Tope TWA Tope Tope Tope Tope Tope Type	Value 5 mg/m3 Value 5 mg/m3 I substances in work envir	Form Inhalable fraction. Form Inhalable fraction.

Material name: HyPrene L1200 - Ergon International

Material

HyPrene L1200

4725 Version #: 04 Revision date: 17-November-2022 Issue date: 18-June-2018 4

Type

STEL

TWA

Form

Fume and mist.

Fume and mist.

Value

3 mg/m3

1 mg/m3

Components	Туре	Value	Form
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 54742-52-5)	STEL	3 mg/m3	Fume and mist.
•	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding) Material	Туре	Value	Form
HyPrene L1200	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms fo Material	or Contaminants in the Workplace Type	Value	Form
HyPrene L1200	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TLV	1 mg/m3	Mist.
	r of Labour and Social Policy on 6 Jur f harmful health factors in the work e Type		
			-
hydrotreated heavy naphthenic (CAS	TWA	5 mg/m3	Inhalable fraction.
hydrotreated heavy naphthenic (CAS			Inhalable fraction. Inhalable fraction.
hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupat		5 mg/m3 0 ppm	
hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupat Material	TWA ional exposure to chemical agents (N	5 mg/m3 0 ppm IP 1796)	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupat Material HyPrene L1200 Components	TWA tional exposure to chemical agents (N Type	5 mg/m3 0 ppm IP 1796) Value	Inhalable fraction. Form
hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupat Material HyPrene L1200	TWA ional exposure to chemical agents (N Type TWA	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3	Inhalable fraction. Form Inhalable fraction.
Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo	TWA Tional exposure to chemical agents (N Type TWA Type	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), mydrotreated heavy maphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo Material	TWA tional exposure to chemical agents (Notational Type) TWA Type TWA TWA TWA TWA TWA	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), mydrotreated heavy maphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo Material	TWA Tional exposure to chemical agents (Note	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 nts at the workpl Value	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
hydrotreated heavy haphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy haphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo Material HyPrene L1200	TWA cional exposure to chemical agents (Notation Type) TWA Type TWA TWA Type TWA TWA TWA TYPE TWA TYPE STEL	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 nts at the workpl Value 10 mg/m3	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupat Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA tional exposure to chemical agents (Notational exposure to chemical agents) TWA Type TWA TWA TWA Type TWA TWA TYPE TWA TYPE TWA TYPE STEL TWA	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 nts at the workpl Value 10 mg/m3 5 mg/m3	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo Material HyPrene L1200 Components Distillates (petroleum), naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo Material HyPrene L1200 Components Distillates (petroleum), naphthenic (CAS 64742-62-62) Distillates (petroleum), naphthenic (CAS 64742-62-62)	TWA cional exposure to chemical agents (Notation Type) TWA Type TWA TWA Type TWA Type STEL TWA Type	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 nts at the workpl Value 10 mg/m3 5 mg/m3 Value	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupat Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA cional exposure to chemical agents (Notational exposure to chemical agents) TWA Type TWA TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 nts at the workpl Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 Value 10 mg/m3	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. ace
Anydrotreated heavy Anaphthenic (CAS A742-52-5) Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), Anydrotreated heavy Anaphthenic (CAS A742-52-5) Romania. OELs. Protection of wo Material HyPrene L1200 Components Distillates (petroleum), Anydrotreated heavy Anaphthenic (CAS A742-52-5) Slovakia. OELs. Regulation No. 36 Material	TWA ional exposure to chemical agents (Natype) TWA Type TWA Type TWA rkers from exposure to chemical age Type STEL TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 nts at the workpl Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 5 mg/m3 Value 10 mg/m3	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. ace chemical agents
Anydrotreated heavy Anaphthenic (CAS A742-52-5) Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), Anydrotreated heavy Anaphthenic (CAS A742-52-5) Romania. OELs. Protection of wo Material HyPrene L1200 Components Distillates (petroleum), Anydrotreated heavy Anaphthenic (CAS A742-52-5) Slovakia. OELs. Regulation No. 36 Material	TWA ional exposure to chemical agents (Notational exposure to chemical agents) Twa Type TWA Type TWA rkers from exposure to chemical age Type STEL TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 nts at the workpl Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 c mg/m3 alth in work with Value	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. ace chemical agents Form
hydrotreated heavy naphthenic (CAS 64742-52-5) Portugal. VLEs. Norm on occupate Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Romania. OELs. Protection of wo Material HyPrene L1200 Components Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) Slovakia. OELs. Regulation No. 36	TWA ional exposure to chemical agents (Notational exposure to chemical agents) Twa Type TWA Type TWA rkers from exposure to chemical age Type STEL TWA Type STEL TWA Type STEL TWA Type STEL TWA Type	5 mg/m3 0 ppm IP 1796) Value 5 mg/m3 Value 5 mg/m3 Ints at the workpl Value 10 mg/m3 5 mg/m3 Value 10 mg/m3 3 mg/m3 alth in work with Value 3 mg/m3	Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. ace chemical agents Form Fume and mist.

Components Distillator (natural aura)	Туре	2 / 2	Process and a 1-1
Distillates (petroleum), hydrotreated heavy	STEL	3 mg/m3	Fume and mist.
naphthenic (CAS			
64742-52-5)			
		15 ppm	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.
Spain. Occupational Expo			F
Material	Туре	Value	Form
HyPrene L1200	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy	STEL	10 mg/m3	Mist.
naphthenic (CAS			
64742-52-5)			
	TWA	5 mg/m3	Mist.
Sweden. OELs. Work Envi	ironment Authority (AV), Occupatio	onal Exposure Limit Values	
Material	Туре	Value	Form
HyPrene L1200	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum),	STEL	3 mg/m3	Mist.
hydrotreated heavy			
naphthenic (CAS 64742-52-5)			
017 12 32 3)	TWA	1 mg/m3	Mist.
Switzerland. SUVA Grenz		5, -	
Material	Type	Value	Form
HyPrene L1200	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
	TWA	5 mg/m3	Inhalable fraction.
Distillates (petroleum), hydrotreated heavy	TWA	5 Hig/ilis	Illialable Ilaction.
naphthenic (CAS			
64742-52-5)			
ogical limit values	No biological exposure limits noted for	• ,,	
ommended monitoring cedures	Follow standard monitoring procedur	res.	
ived no effect levels	Not available.		
ELs)	NOT available.		
dicted no effect	Not available.		
centrations (PNECs)			
Exposure controls			
ropriate engineering	Adequate ventilation should be provi		
trols	Provide adequate ventilation, includir occupational exposure limit is not ex-		to ensure that the defined
ividual protection measur	es, such as personal protective equ		
General information	Personal protection equipment shoul	d be chosen according to the C	EN standards and in discus
Fig. 16	with the supplier of the personal pro		alandard FN 466
Eye/face protection	Goggles/face shield are recommende	ea. Eye protection should meet	standard EN 166.
Skin protection	Ween quitable alone to the ENGS	1 Chamian wastatant store	woodanaa dada Teesaa ka
- Hand protection	Wear suitable gloves tested to EN374 forearms is likely wear gauntlet style Nitrile gloves may be suitable. (Breal	gloves. When prolonged or fre kthrough time of > 240 minute	equent repeated contact occ
	protection Neoprene, PVC gloves ma	y be suitable.	
Othor	Chamical/ail registant elething is rese		

Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Material name: HyPrene L1200 - Ergon International

- Other

SDS EU

Respiratory protection Under normal conditions, respirator is not normally required. No respiratory protection is ordinarily

required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)] meeting EN14387.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material and **Hygiene measures**

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liauid. **Form** Liquid. Colour **Amber**

Mild Petroleum Odor Odour

-24 °C (-11,2 °F) ASTM D5950/ ISO 3016 Melting point/freezing point Boiling point or initial boiling 330 °C (626 °F) ASTM D2887/ ISO 3294 point and boiling range

Flammability Will burn if involved in a fire.

Flash point 241,0 °C (465,8 °F) Cleveland open cup ASTM D92/ ISO 2719/ IP36

Auto-ignition temperature > 315,56 °C (> 600 °F) ASTM E659 **Decomposition temperature** The property has not been measured. The property has not been measured.

Kinematic viscosity $>=38,1 \text{ mm}^2/\text{s}$

Solubility

Solubility (water) Insoluble **Partition coefficient** Not established.

(n-octanol/water) (log value)

Vapour pressure The property has not been measured.

Density and/or relative density

0,92 (15,56 °C (60 °F) ASTM D4052/ ISO 12185) Relative density

Vapour density > 5

Particle characteristics

Particle size Not applicable, material is a liquid.

9.2. Other information

9.2.1. Information with

regard to physical hazard

classes

No relevant additional information available.

9.2.2. Other safety characteristics

Surface tension < 35 mN/m (25 °C (77 °F))

Viscosity 230 cSt (40 °C (104 °F) ASTM D445/ ISO 3014)

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidising agents.

10.2. Chemical stability

10.3. Possibility of hazardous

reactions

Hazardous polymerisation does not occur.

10.4. Conditions to avoid Avoid temperatures exceeding the flash point.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May be harmful if inhaled. However, this product does not currently meet the criteria for

classification.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration.

Symptoms Defatting of the skin. Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Not classified. **Acute toxicity**

Skin corrosion/irritation Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified.

Respiratory sensitisation Not classified. Skin sensitisation Not classified.

Germ cell mutagenicity Non-mutagenic based on Modified Ames Assay.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU

requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346. Note L -

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated heavy naphthenic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-52-5)

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard Not classified. Mixture versus substance

information

Not available.

11.2. Information on other hazards

Endocrine disrupting

properties

This substance does not have endocrine disrupting properties with respect to human health, as it does not meet the assessment criteria laid out in Regulations (EC) No 1907/2006, (EU) No

2017/2100 and (EU) 2018/605.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient Not established.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

This substance does not have endocrine disrupting properties with respect to the environment, as it 12.6. Endocrine disrupting properties does not meet the assessment criteria laid out in Regulations (EC) No 1907/2006, (EU) No

2017/2100 and (EU) 2018/605.

12.7. Other adverse effects Oil spills are generally hazardous to the environment.

Material name: HyPrene L1200 - Ergon International

SDS EU 4725 Version #: 04 Revision date: 17-November-2022 Issue date: 18-June-2018

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations, Avoid discharge into water courses or onto the

around.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

Not applicable. Waste codes should be assigned by the user based on the application for which the **EU** waste code

product was used.

Disposal recommendations are based on material as supplied. Disposal must be in accordance with Disposal

methods/information current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

ΤΔΤΔ

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Maritime transport in

bulk according to IMO instruments

General information Not regulated as dangerous goods.

Not available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Directive 2004/37/EC; on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Material name: HyPrene L1200 - Ergon International

4725 Version #: 04 Revision date: 17-November-2022 Issue date: 18-June-2018

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC)

No 1907/2006, as amended.

Directive 2012/18/EU on major accident hazards involving dangerous substances: Part 2 (Named dangerous substances) - 34. Petroleum products and alternative fuels.

National regulations Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

amended.

Germany: WGK 1

Inventory name

15.2. Chemical safety

assessment

Australia

No Chemical Safety Assessment has been carried out.

Australian Inventory of Industrial Chemicals (AICIS)

International Inventories

Country(s) or region

Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Taiwan Chemical Substance Inventory (TCSI)

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico Yes *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

SECTION 16: Other information

List of abbreviations Not available. References **ACGIH**

IARC Monographs. Overall Evaluation of Carcinogenicity

Chemical Abstracts Service Registry Handbook

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

EC Annex1 **ILO Safety Cards**

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not applicable.

Full text of any statements, which are not written out in full under sections 2 to 15

None.

Revision information Training information

This document has undergone significant changes and should be reviewed in its entirety.

Follow training instructions when handling this material.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material name: HyPrene L1200 - Ergon International

On inventory (yes/no)*

Yes

Yes