SAFETY DATA SHEET

ERGON 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyPrint 60

Identification number 649-466-00-2 (Index number)

Registration number 01-2119480375-34

Synonyms None.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pigments; Printing Inks

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

MANUFACTURER: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

Drève Richelle 161 Building C B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

CHEMTREC: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International),

+32-28083237 (Belgium) +33-975181407 (France) +49-69643508409 (Germany) +39-0245557031 (Italy) +34-931768545 (Spain)

E-mail: sds@ergon.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Aspiration hazard Category 1 H304 - May be fatal if swallowed

and enters airways.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Distillates (petroleum), hydrotreated light naphthenic

Hazard pictograms

Signal word Danger

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

Prevention

P260 Do not breathe gas/fumes/vapour/spray.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

P331 Do NOT induce vomiting.

Storage

Store locked up. P405

Disposal

See section 13 of this SDS for disposal instructions.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

information

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated light naphthenic	<=100	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	
Classification: Asp. Tox. 1;H304					

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eve contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control centre immediately.

4.2. Most important symptoms and effects, both

acute and delayed

Defatting of the skin.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as

an extinguisher, as this will spread the fire.

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure

Special fire fighting

procedures

demand breathing apparatus, protective clothing and face mask.

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurised air mask if product is involved in a fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Keep unnecessary personnel away. Do not touch or walk through spilled material. Wear appropriate personal protective equipment.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Material name: HyPrint 60 - Ergon International

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk, Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame.

7.3. Specific end use(s) Not available.

Belgium, Exposure Limit Values

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Material	Туре	Value	Form
HyPrint 60	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
	13 on protection of workers a		chemical agents at work
Material	Туре	Value	
HyPrint 60	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	
Czech Republic. OELs. Govern	ment Decree 361		
Material	Туре	Value	
HyPrint 60	Ceiling	1000 mg/m3	
	TWA	200 mg/m3	
Denmark. Exposure Limit Valu	ies		
Material .	Туре	Value	Form
HyPrint 60	TLV	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	1 mg/m3	Mist.

Material name: HyPrint 60 - Ergon International

SDS FU 4711 Version #: 06 Revision date: 09-January-2023 Issue date: 18-July-2018

Finland. Workplace Exposure Limit Material	Туре	Value	Form
HyPrint 60	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA	5 mg/m3	Mist.
Germany. DFG MAK List (advisory C Compounds in the Work Area (DFG		Investigation of Health H	
Material	Туре	Value	Form
HyPrint 60	TWA	5 mg/m3	Respirable fraction.
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated light naphthenic (CAS 54742-53-6)	TWA	5 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/1999 Material	, as amended) Type	Value	Form
HyPrint 60	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Hungary. OELs. Joint Decree on Ch Material	emical Safety of Workplac Type	es Value	
HyPrint 60	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), nydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	
Iceland. OELs. Regulation 154/199 Material	9 on occupational exposu Type	re limits Value	Form
HyPrint 60	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	1 mg/m3	Mist.
Ireland. Occupational Exposure Lin Components	nits Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Italy. Occupational Exposure Limits Material	s Type	Value	Form
HyPrint 60	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
•			

Material name: HyPrint 60 - Ergon International

SDS EU 4 / 12

4711 Version #: 06 Revision date: 09-January-2023 Issue date: 18-July-2018

Material	Туре	Value	
HyPrint 60	TWA	5 mg/m3	
Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	
Lithuania. OELs. Limit Values for (Material	Chemical Substances, Gen Type	eral Requirements Value	Form
HyPrint 60	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding) Material	Туре	Value	Form
HyPrint 60	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms for Material	Contaminants in the Wor Type	kplace Value	Form
HyPrint 60	TLV	1 mg/m3	Mist.
•	TLV Type	1 mg/m3 Value	Mist. Form
Components Distillates (petroleum), hydrotreated light naphthenic (CAS		_	
Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of h	Type TLV of Labour and Social Police	Value 1 mg/m3 y on 6 June 2014 on the ma	Form Mist.
Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of h Components Distillates (petroleum), hydrotreated light naphthenic (CAS	Type TLV of Labour and Social Police armful health factors in t	Value 1 mg/m3 y on 6 June 2014 on the make work environment, Journ Value 5 mg/m3	Form Mist. Eximum permissible nal of Laws 2014, item 8 Form Inhalable fraction.
Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of h Components Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occupation	Type TLV of Labour and Social Police armful health factors in to Type TWA	Value 1 mg/m3 Ty on 6 June 2014 on the make work environment, Jour Value 5 mg/m3	Form Mist. aximum permissible nal of Laws 2014, item 8
Components Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of h Components Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occupation	Type TLV of Labour and Social Police armful health factors in to Type TWA nal exposure to chemical Type	Value 1 mg/m3 y on 6 June 2014 on the make work environment, Jour Value 5 mg/m3 0 ppm agents (NP 1796) Value	Form Mist. Aximum permissible anal of Laws 2014, item 8 Form Inhalable fraction. Inhalable fraction. Form
Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of h Components Distillates (petroleum), hydrotreated light haphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occupation Material	Type TLV of Labour and Social Police armful health factors in to the type TWA nal exposure to chemical Type TWA	Value 1 mg/m3 y on 6 June 2014 on the make work environment, Jour Value 5 mg/m3 0 ppm agents (NP 1796) Value 5 mg/m3	Form Mist. Eximum permissible nal of Laws 2014, item 8 Form Inhalable fraction. Inhalable fraction.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of h Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occupation Material HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS	Type TLV of Labour and Social Police armful health factors in to Type TWA nal exposure to chemical Type	Value 1 mg/m3 y on 6 June 2014 on the make work environment, Jour Value 5 mg/m3 0 ppm agents (NP 1796) Value	Form Mist. Aximum permissible anal of Laws 2014, item 8 Form Inhalable fraction. Form Inhalable fraction.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of h Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occupation Material HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Romania. OELs. Protection of work	Type TLV of Labour and Social Police armful health factors in to Type TWA nal exposure to chemical Type TWA Type TWA Type TWA Type	Value 1 mg/m3 y on 6 June 2014 on the make work environment, Jour Value 5 mg/m3 0 ppm agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3	Form Mist. Aximum permissible and of Laws 2014, item 8 Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.
Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Poland. Ordinance of the Minister concentrations and intensities of head of the Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Portugal. VLEs. Norm on occupation Material HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Romania. OELs. Protection of work Material HyPrint 60 Romania. OELs. Protection of work Material HyPrint 60	Type TLV of Labour and Social Police armful health factors in to Type TWA nal exposure to chemical Type TWA Type TWA Type TWA Type TWA Type	Value 1 mg/m3 y on 6 June 2014 on the make work environment, Jour Value 5 mg/m3 0 ppm agents (NP 1796) Value 5 mg/m3 Value 5 mg/m3 value 5 mg/m3	Form Mist. Aximum permissible and of Laws 2014, item 8 Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction. Form Inhalable fraction.

Romania. OELs. Protection of workers Components	Туре	Value	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	
	TWA	5 mg/m3	
Slovakia. OELs. Regulation No. 300/20 Material	007 concerning protection of Type	of health in work with Value	chemical agents Form
HyPrint 60	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
	TWA	1 mg/m3 -	Fume and mist.
		5 ppm	Fume and mist.
Spain. Occupational Exposure Limits Material	Туре	Value	Form
HyPrint 60	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Sweden. OELs. Work Environment Aut Material	thority (AV), Occupational E Type	Exposure Limit Values Value	(AFS 2015:7) Form
HyPrint 60	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Components	Туре	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.
Switzerland. SUVA Grenzwerte am Ar Material	beitsplatz Type	Value	Form
HyPrint 60	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
Distillates (petroleum),	TWA	5 mg/m3	Inhalable fraction.
naphthenic (CAS			
naphthenic (CAS 64742-53-6)	al exposure limits noted for th	e ingredient(s).	
naphthenic (CAS 64742-53-6) ogical limit values No biologic ommended monitoring Not availab	•	e ingredient(s).	
naphthenic (CAS 64742-53-6) ogical limit values No biologic ommended monitoring Not availab cedures ved no effect levels (DNELs)	•	e ingredient(s).	
ommended monitoring Not available cedures (DNELs) General Population	ole.		
naphthenic (CAS 64742-53-6) ogical limit values No biologic ommended monitoring Not available cedures ived no effect levels (DNELs) General Population Components	value	e ingredient(s). Assessment factor	Notes
naphthenic (CAS 64742-53-6) ogical limit values No biologic ommended monitoring Not availab cedures ved no effect levels (DNELs) General Population	value		Notes Repeated dose toxicity

Workers Components	Value	Assessment factor	r Notes
Distillates (petroleum), hydrotr			
Long-term, Local, Inhalation			Repeated dose toxicity
Long-term, Systemic, Derr			Repeated dose toxicity
Long-term, Systemic, Inha	lation 2,73 mg/m	3 45	Repeated dose toxicity
dicted no effect concentration	ons (PNECs)		
Components	Value	Assessment factor	Notes
Distillates (petroleum), hydrotr	eated light naphthenic (CAS	64742-53-6)	
Secondary poisoning	9,33 mg/kg	I	Oral
osure guidelines			
Austria MAK: Skin designat	ion		
Distillates (petroleum), hyd (CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
Belgium OELs: Skin designa	ation		
Distillates (petroleum), hyd (CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
Croatia ELVs: Skin designat	tion		
(CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
Czech Republic PELs: Skin	designation		
(CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
Estonia OELs: Skin designat			
(CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
EU. OELs from Annex III, Pa		=	
(CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
Iceland OELs: Skin designa			
(CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
Ireland Exposure Limit Value	=		
(CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
Lithuania OELs: Skin design			
(CAS 64742-53-6) Netherlands OELs (binding)	drotreated light naphthenic	Can be absorbed through the skin	
Distillates (petroleum), hyd	drotreated light naphthenic	Can be absorbed through the skin	
(CAS 64742-53-6) Slovakia OELs for Carcinoge	ens and Mutagens: Skin d	lesignation	
_	drotreated light naphthenic	Can be absorbed through the skin	
	of workers from exposure	to carcinogen and mutagen agen	ts (ULRS 101/2005, as
•	drotreated light naphthenic	Can be absorbed through the skin	
Sweden Threshold Limit Va	lues: Skin designation		
Distillates (petroleum), hyd (CAS 64742-53-6)	drotreated light naphthenic	Can be absorbed through the skin	
. Exposure controls			
oropriate engineering strols	Provide adequate ventilatio occupational exposure limit	n, including appropriate local extraction is not exceeded.	n, to ensure that the define
lividual protection measures General information	·		
Eye/face protection	Goggles/face shield are rec	rommended	
Skin protection	asygnes, race similar are rec	ociidedi	
	Chambre 1 1 1 1 1 1	1 1 76 1 11 6	. 19 1

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Material name: HyPrint 60 - Ergon International

- Hand protection

- Other

gloves may be suitable.

Respiratory protection Under normal conditions, respirator is not normally required. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C

Thermal hazards Not available.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

(149 °F)] meeting EN14387.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid. **Form** Liquid.

Colour Colorless to slight yellow tint

Odour Mild Petroleum Odor

Melting point/freezing point Boiling point or initial boiling

point and boiling range

-63 °C (-81,4 °F) ASTM D5950/ISO 3016 284 °C (543,2 °F) ASTM D86/ ISO 3294

Flammability Not available.

153,0 °C (307,4 °F) Cleveland open cup ASTM D92/ ISO 2592 Flash point

143,0 °C (289,4 °F) Pensky-Martens Closed Cup ASTM D93/ ISO 2719

> 315,56 °C (> 600 °F) ASTM E659 **Auto-ignition temperature**

Decomposition temperature Not available. Not applicable pН Kinematic viscosity Not available.

Solubility

Solubility (water) Insoluble

Partition coefficient Not established.

(n-octanol/water) (log value)

Not available. Vapour pressure

Density and/or relative density

Relative density 0,885 (15,56 °C (60 °F) ASTM D4052/ ISO 12185)

Vapour density > 5

Particle characteristics Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard No relevant additional information available.

9.2.2. Other safety characteristics

9.34 (40 °C (104 °F) ASTM D445/ISO 3104) **Viscosity**

SECTION 10: Stability and reactivity

Strong oxidising agents. 10.1. Reactivity

10.2. Chemical stability Stable.

10.3. Possibility of hazardous

reactions

classes

Hazardous polymerisation does not occur.

10.4. Conditions to avoid Avoid temperatures exceeding the flash point.

10.5. Incompatible materials Strong oxidising agents.

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular 10.6. Hazardous

decomposition products weight hydrocarbons.

4711 Version #: 06 Revision date: 09-January-2023 Issue date: 18-July-2018

SECTION 11: Toxicological information

General information Not available.

Information on likely routes of exposure

Inhalation May be fatal if swallowed and enters airways.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. Skin contact

May be irritating to eyes. **Eve contact**

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration. May be fatal if swallowed and enters airways.

Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest. **Symptoms**

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not applicable.

Components **Species Test Results**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Acute

Dermal

LD50 Rat > 2000 mg/kg

Inhalation

LC50 Rat $> 5000 \text{ mg/m}^3$

Oral

LD50 Rat > 5000 mg/kg

Not available. * Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified. May cause minor irritation on eye contact.

Respiratory sensitisation Not classified.

Skin sensitisation Not classified. May cause defatting of the skin, but is not an irritant.

Germ cell mutagenicity Chilean Spanish went out in Job 18-0024189, French and German were reviewed under

17-0023466 and Hindi under 17-0023485

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU Carcinogenicity

requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at

work (as amended)

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Reproductive toxicity Contains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

May be fatal if swallowed and enters airways. **Aspiration hazard**

Mixture versus substance

information

Not available.

11.2. Information on other hazards

Endocrine disrupting

properties

Not available.

Other information Risk of chemical pneumonia after aspiration.

SECTION 12: Ecological information

12.1. Toxicity Not expected to be harmful to aquatic organisms.

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient

Not established.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil Not available.

12.5. Results of PBT and vPvB

assessment

Not a PBT or vPvB substance or mixture.

12.6. Endocrine disrupting

properties

Not available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation 12.7. Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

EU waste code Not applicable. Waste codes should be assigned by the user based on the application for which

the product was used.

Disposal recommendations are based on material as supplied. Disposal must be in accordance Disposal methods/information

with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Maritime transport in

bulk according to IMO instruments

Not available.

General information

Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulationsThe product is classified and labelled in accordance with EC directives or respective national laws.

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations Germany: WGK 1

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

SECTION 16: Other information

List of abbreviationsNot available. **References**ACGIH

IARC Monographs. Overall Evaluation of Carcinogenicity

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any statements, which are not written out in full under sections 2 to 15

H304 May be fatal if swallowed and enters airways.

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision information SECTION 2: Hazards identification: Disposal

SECTION 6: Accidental release measures: For emergency responders SECTION 6: Accidental release measures: For non-emergency personnel SECTION 7: Handling and storage: 7,1. Precautions for safe handling

Physical & Chemical Properties: Multiple Properties SECTION 9: Physical and chemical properties: Colour SECTION 11: Toxicological information: Reproductivity

Training information
Disclaimer

Not available.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.