ERGON E

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of the substance HyPrint 60

Identification number 649-466-00-2 (Index number)

Registration number 01-2119480375-34

Synonyms None.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pigments; Printing Inks

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Manufacturer: Ergon, Inc.

P.O. Box 1639

Jackson, MS 39181 USA

EU Contact: Ergon International, Inc.

Drève Richelle 161 Building C

B-1410 Waterloo, Belgium

Emergency Phone

Numbers:

US Customer Service: + 1-800-222-7122

Chemtrec: + 1-800-424-9300 After Business Hours (North America)

+ 1-703-527.-3887 (International),

+32-28083237 (Belgium) +33-975181407 (France) +49-69643508409 (Germany) +39-0245557031 (Italy) +34-931768545 (Spain)

E-mail: sds@ergon.com
Poison Centre (Centre +32022649636

Antipoisons - Belgium):

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Aspiration hazard Category 1 H304 - May be fatal if swallowed

and enters airways.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Distillates (petroleum), hydrotreated light naphthenic

Hazard pictograms

Signal word Danger

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

Prevention

P260 Do not breathe gas/fumes/vapor/spray.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331 Do NOT induce vomiting.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

information

None.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.1. Substances

General information

| Chemical name | % | CAS-No. / EC No. | REACH Registration No | o. Index No. | Notes |
|--|------------|-------------------------|-----------------------|--------------|-------|
| Distillates (petroleum), hydrotreated light naphthenic | <=100 | 64742-53-6 265-156-6 | 01-2119480375-34 | 649-466-00-2 | |
| Classification: | Carc. 1B;F | 1350 | | | |

SECTION 4: First aid measures

General information Contact physician if discomfort continues.

4.1. Description of first aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eve contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control center immediately.

4.2. Most important symptoms and effects, both

acute and delayed

Defatting of the skin. Irritating to mouth, throat, and stomach. Shortness of breath. Coughing.

4.3. Indication of any immediate medical attention and special treatment

Treat symptomatically.

needed

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

extinguisher, as this will spread the fire.

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special protective equipment for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an

Special fire fighting

procedures

Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurized air mask if product is involved in a fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Do not touch or walk through spilled material. Wear appropriate personal protective equipment.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS. Local authorities should be advised if significant spillages cannot be contained. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

SDS EU

Material name: HyPrint 60 - Ergon International

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

64742-53-6)

Occupational exposure limits

Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1

| - C | hemical | agents, | as | amended |
|-----|---------|---------|----|---------|
|-----|---------|---------|----|---------|

| Material | Туре | Value | Form | |
|--|------|----------|-------|--|
| HyPrint 60 | STEL | 10 mg/m3 | Mist. | |
| | TWA | 5 mg/m3 | Mist. | |
| Components | Туре | Value | Form | |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | STEL | 10 mg/m3 | Mist. | |
| | TWA | 5 mg/m3 | Mist. | |

Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended

| Material | Туре | Value | |
|---|------|---------|--|
| HyPrint 60 | TWA | 5 mg/m3 | |
| Components | Туре | Value | |
| Distillates (petroleum), hydrotreated light naphthenic (CAS | TWA | 5 mg/m3 | |

Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Appex 2, Part A & Appex 3, Part A, as amended)

| Material | Type | Value | | |
|------------------------------------|--|-------------------------------------|---------------|--|
| HyPrint 60 | Ceiling | 1000 mg/m3 | | |
| | TWA | 200 mg/m3 | | |
| Denmark. Work Environm Material | ent Authority. Exposure Limits for Type | Substances & Materials, An Value | nex 2 Form | |
| HyDrint 60 | TIV | 1 mg/m2 | Mict | |

| Denmark. Work Environment Authorit Material | y. Exposure Limits for Substances Type | s & Materials, Anno Value | ex 2 Form |
|--|---|------------------------------|--------------|
| HyPrint 60 | TLV | 1 mg/m3 | Mist. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | STEL | 2 mg/m3 | Mist. |

| | Туре | Value | NA' - I |
|---|--|---|--|
| | TLV | 1 mg/m3 | Mist. |
| Finland. HTP-arvot, App 3., Biı Material | nding Limit Values, Social Affairs Type | and Ministry of Health Value | Form |
| HyPrint 60 | TWA | 5 mg/m3 | Mist. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Mist. |
| Germany. DFG MAK List (advis Compounds in the Work Area | sory OELs). Commission for the I (DFG), as updated | nvestigation of Health H | azards of Chemical |
| Material | Туре | Value | Form |
| HyPrint 60 | TWA | 5 mg/m3 | Respirable fraction. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Respirable fraction. |
| Greece. OELs, Presidential De Material | cree No. 307/1986, as amended Type | Value | Form |
| HyPrint 60 | TWA | 5 mg/m3 | Mist. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Mist. |
| Hungary. OELs. Decree on pro amended | tection of workers exposed to ch | emical agents (5/2020. | (II.6)), Annex 1&2, as |
| | | | |
| Material | Туре | Value | |
| | Type TWA | Value 5 mg/m3 | |
| HyPrint 60 | | | |
| Material HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Iceland. OELs. Regulation 390 | TWA Type | 5 mg/m3 Value 5 mg/m3 | tion at the Workplace, |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Iceland. OELs. Regulation 390 amended | TWA Type TWA | 5 mg/m3 Value 5 mg/m3 | tion at the Workplace, Form |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Iceland. OELs. Regulation 390 amended Material | TWA Type TWA TWA O/2009 on Pollution Limits and Mo | 5 mg/m3 Value 5 mg/m3 easures to Reduce Pollu | |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Iceland. OELs. Regulation 390 amended Material HyPrint 60 | TWA Type TWA TWA TWA TYPE TYPE Type | 5 mg/m3 Value 5 mg/m3 easures to Reduce Pollu Value | Form |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA Type TWA 7/2009 on Pollution Limits and Mo Type TWA | 5 mg/m3 Value 5 mg/m3 easures to Reduce Pollu Value 1 mg/m3 | Form Mist. |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Iceland. OELs. Regulation 390 amended Material HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA Type TWA 7/2009 on Pollution Limits and Mo Type TWA Type TWA Type | 5 mg/m3 Value 5 mg/m3 Peasures to Reduce Pollu Value 1 mg/m3 Value 1 mg/m3 | Form Mist. Form Mist. |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Iceland. OELs. Regulation 390 amended Material HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Ireland. OELVs, Schedules 1 & | TWA Type TWA 7/2009 on Pollution Limits and Mo Type TWA Type TWA Type TWA Type TWA | 5 mg/m3 Value 5 mg/m3 Peasures to Reduce Pollu Value 1 mg/m3 Value 1 mg/m3 Agents and Carcinogen | Form Mist. Form Mist. s Regulations |
| HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Iceland. OELs. Regulation 390 amended Material HyPrint 60 Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Ireland. OELVs, Schedules 1 & Components Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA Type TWA 7/2009 on Pollution Limits and Mo Type TWA Type TWA Type TWA Type TWA Type TWA | 5 mg/m3 Value 5 mg/m3 Peasures to Reduce Pollu Value 1 mg/m3 Value 1 mg/m3 Value 5 mg/m3 | Form Mist. Form Mist. S Regulations Form |

| Value | Form |
|---------|---------------------|
| | |
| 5 mg/m3 | Inhalable fraction. |
| | 5 mg/m3 |

| Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, | , |
|--|---|
| Annex 1), as amended | |

| Material | Туре | Value | |
|---|------|---------|--|
| HyPrint 60 | TWA | 5 mg/m3 | |
| Components | Туре | Value | |
| Distillates (petroleum), hydrotreated light naphthenic (CAS | TWA | 5 mg/m3 | |

Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended

| Material | Туре | Value | Form |
|--|------|---------|----------------|
| HyPrint 60 | STEL | 3 mg/m3 | Fume and mist. |
| | TWA | 1 mg/m3 | Fume and mist. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | STEL | 3 mg/m3 | Fume and mist. |
| | TWA | 1 mg/m3 | Fume and mist. |

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

| Material | Туре | Value | Form | |
|--|------|---------|-------|--|
| HyPrint 60 | TWA | 5 mg/m3 | Mist. | |
| Components | Туре | Value | Form | |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Mist. | |

Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended

| Material | Туре | Value | Form | |
|--|------|---------|-------|--|
| HyPrint 60 | TLV | 1 mg/m3 | Mist. | |
| Components | Туре | Value | Form | |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TLV | 1 mg/m3 | Mist. | |

Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)

| Components | Туре | Value | Form |
|--|------|---------|---------------------|
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Inhalable fraction. |

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)

| Material | Туре | Value | Form |
|--|------|---------|---------------------|
| HyPrint 60 | TWA | 5 mg/m3 | Inhalable fraction. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Inhalable fraction. |

| Material | Туре | Value | |
|--|-------------------------------|-----------------------------|-----------------------|
| HyPrint 60 | STEL | 10 mg/m3 | |
| | TWA | 5 mg/m3 | |
| Components | Туре | Value | |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | STEL | 10 mg/m3 | |
| | TWA | 5 mg/m3 | |
| Slovakia. OELs. Maximum per | | nemical factors in workplac | e air (Regulation No |
| 355/2006, Annex 1, Table 1, a Material | s amended) Type | Value | Form |
| HyPrint 60 | STEL | 3 mg/m3 | Fume and mist. |
| | | 15 ppm | Fume and mist. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | STEL | 3 mg/m3 | Fume and mist. |
| | | 15 ppm | Fume and mist. |
| | TWA | 1 mg/m3 | Fume and mist. |
| | | 5 ppm | Fume and mist. |
| Spain. OELs. INSST, Límites de | e Exposición Profesional Para | Agentes Químicos, Table 1 | -Valores Límites |
| Ambientales (VLAs) Material | Туре | Value | Form |
| HyPrint 60 | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Components | Туре | Value | Form |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | STEL | 10 mg/m3 | Mist. |
| | TWA | 5 mg/m3 | Mist. |
| Sweden. OELs (Annex 1). Wor | k Environment Authority (AV) | , Occupational Exposure Li | mit Values (AFS 2018: |
| amended Material | Туре | Value | Form |
| HyPrint 60 | STEL | 3 mg/m3 | Mist. |
| , | T\//\ | 1 mg/m ² | Mict |

| Туре | Value | Form | |
|------|----------------------------|---|--|
| STEL | 3 mg/m3 | Mist. | |
| TWA | 1 mg/m3 | Mist. | |
| Туре | Value | Form | |
| STEL | 3 mg/m3 | Mist. | |
| | STEL TWA Type | STEL 3 mg/m3 TWA 1 mg/m3 Type Value | STEL 3 mg/m3 Mist. TWA 1 mg/m3 Mist. Type Value Form |

| TWA | 1 mg/m3 | Mist. |
|-----|---------|-------|
| | | |

| Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte | | | | |
|--|------|---------|---------------------|--|
| Material | Туре | Value | Form | |
| HyPrint 60 | TWA | 5 mg/m3 | Inhalable fraction. | |
| Components | Туре | Value | Form | |
| Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) | TWA | 5 mg/m3 | Inhalable fraction. | |

Biological limit valuesNo biological exposure limits noted for the ingredient(s). **Recommended monitoring**Not available.

procedures

Derived no effect levels (DNELs) General population Components Value Assessment factor Notes Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Long-term, Local, Inhalation 1.19 ma/m3 75 Repeated dose toxicity Long-term, Systemic, Oral 0,74 mg/kg 120 Repeated dose toxicity **Workers** Components Assessment factor Notes Value Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Long-term, Local, Inhalation 5,58 ma/m3 45 Repeated dose toxicity Long-term, Systemic, Dermal 0,97 mg/kg 72 Repeated dose toxicity Long-term, Systemic, Inhalation 2,73 mg/m3 45 Repeated dose toxicity Predicted no effect concentrations (PNECs) **Components** Value **Assessment factor Notes** Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Secondary poisoning 9,33 mg/kg Oral **Exposure guidelines** Austria MAK: Skin designation Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) **Belgium OELs: Skin designation** Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) Croatia ELVs: Skin designation Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) **Czech Republic PELs: Skin designation** Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) **Denmark GV: Skin designation** Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) **Estonia OELs: Skin designation** Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) EU. OELs from Annex III, Part A to Directive 2004/37/EC: Skin designation Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) France Mandatory OELs (VLEP): Skin designation Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) **Iceland OELs: Skin designation** Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) **Ireland Exposure Limit Values: Skin designation** Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) Lithuania OELs: Skin designation Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin. (CAS 64742-53-6) Netherlands OELs (binding): Skin designation

Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin.

(CAS 64742-53-6)

Romania OELs: Skin designation

Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin.

(CAS 64742-53-6)

Slovakia OELs for Carcinogens and Mutagens: Skin designation

Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin.

(CAS 64742-53-6)

Slovenia. CMR. Protection of workers from exposure to carcinogen and mutagen agents (ULRS 101/2005, as amended)

Distillates (petroleum), hydrotreated light naphthenic Can be absorbed through the skin.

(CAS 64742-53-6)

Sweden Threshold Limit Values: Skin designation

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering

controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

General information Not available.

Eye/face protection

Goggles/face shield are recommended.

Skin protection

- **Hand protection** Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC

gloves may be suitable.

- **Other** Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection Under normal conditions, respirator is not normally required. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >65 °C (149 °F)]

meeting EN14387.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Environmental exposure

controls

Not available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.FormLiquid.

Color Colorless to slight yellow tint

Odor Mild Petroleum Odor

Melting point/freezing point -81,4 °F (-63 °C) ASTM D5950/ISO 3016

Boiling point or initial boiling

point and boiling range

543,2 °F (284 °C) ASTM D86/ ISO 3294

Flammability Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Flash point 307,4 °F (153,0 °C) Cleveland Open Cup ASTM D92/ ISO 2592

289,4 °F (143,0 °C) Pensky-Martens Closed Cup ASTM D93/ ISO 2719

Auto-ignition temperature >600 °F (>315,56 °C) ASTM E659

Decomposition temperatureNot available.pHNot applicableKinematic viscosityNot available.

Solubility

Solubility (water) Insoluble

Partition coefficient Not established.

(n-octanol/water) (log value)Vapor pressureNot available.

Density and/or relative density

Relative density 0,885 (60 °F (15,56 °C) ASTM D4052/ ISO 12185)

Vapor density >5

Particle characteristics Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard

No relevant additional information available.

classes

9.2.2. Other safety characteristics

Viscosity 9,34 (104 °F (40 °C) ASTM D445/ISO 3104)

SECTION 10: Stability and reactivity

10.1. Reactivity Strong oxidizing agents.

10.2. Chemical stability Stable.

10.3. Possibility of hazardous

reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid Avoid temperatures exceeding the flash point. **10.5. Incompatible materials** Strong oxidizing agents.

TO.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

decomposition products weight hydrocarbons.

SECTION 11: Toxicological information

General information Not available.

Information on likely routes of exposure
Inhalation
May be fatal if swallowed and enters airways.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration. May be fatal if swallowed and enters airways.

Symptoms Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not applicable.

Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified. May cause minor irritation on eye contact.

Respiratory sensitization Not classified.

Skin sensitization Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU

requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

work (as amended)

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated light naphthenic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-53-6)

Reproductive toxicity Contains no ingredient listed as toxic to reproduction.

Specific target organ toxicity

single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard May

May be fatal if swallowed and enters airways.

Mixture versus substance

information

Not available.

11.2. Information on other hazards

Endocrine disrupting

Not available.

properties

Other information Risk of chemical pneumonia after aspiration.

SECTION 12: Ecological information

12.1. Toxicity Not expected to be harmful to aquatic organisms.

12.2. Persistence and

degradability

Not inherently biodegradable.

12.3. Bioaccumulative

potential

Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient

n-octanol/water (log Kow)

Not established.

Not available.

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Endocrine disrupting

properties

12.7. Other adverse effects No other adverse environmental effects (e.g., ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

Not applicable. Waste codes should be assigned by the user based on the application for which the **EU** waste code

product was used.

Disposal recommendations are based on material as supplied. Disposal must be in accordance with **Disposal** methods/information

current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

14.1. UN number Not regulated as dangerous goods.

14.2. UN proper shipping

Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary hazard

Hazard No. (ADR) Not assigned. **Tunnel restriction** Not assigned.

code

14.4. Packing group 14.5. Environmental No.

hazards

14.6. Special precautions Not assigned.

for user

RID

14.1. UN number Not regulated as dangerous goods. 14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary hazard 14.4. Packing group 14.5. Environmental No.

hazards

14.6. Special precautions Not assigned.

for user

ADN

Not regulated as dangerous goods. **14.1. UN number** 14.2. UN proper shipping Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary hazard 14.4. Packing group

14.5. Environmental No.

hazards

14.6. Special precautions Not assigned.

for user

IATA

14.1. UN numberNot regulated as dangerous goods. **14.2. UN proper shipping**Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary hazard 14.4. Packing group 14.5. Environmental No.

hazards

14.6. Special precautions Not assigned.

for user

IMDG

14.1. UN number Not regulated as dangerous goods. **14.2. UN proper shipping** Not regulated as dangerous goods.

name

14.3. Transport hazard class(es)

Class Not assigned.

Subsidiary hazard 14.4. Packing group 14.5. Environmental hazards
Marine pollutant No.

EmS Not assigned.

14.6. Special precautions Not assigned.
for user

14.7. Maritime transport in

bulk according to IMO

instruments

General information Not regulated as dangerous goods.

Not available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorizations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended

Not listed.

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EU)

2020/878.

Germany: WGK 1 **National regulations**

France regulations

France INRS Table of Occupational Diseases

Distillates (petroleum), hydrotreated light naphthenic Affections provoquées par les huiles et graisses d'origine minérale

(CAS 64742-53-6) ou de synthèse 36

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

Inventory status

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Industrial Chemicals (AICIS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

SECTION 16: Other information

List of abbreviations Not available. References **ACGIH**

IARC Monographs. Overall Evaluation of Carcinogenicity

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any statements, which are not written out in full under sections 2 to 15

H350 May cause cancer.

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision information Product and Company Identification: Product and Company Identification

Hazards Identification: US Hazard Categories

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties

Regulatory Information: United States

HazReg Data: North America

GHS: Classification

REACH: Registration Substance

Training information Disclaimer

Not available.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.