

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name or designation of the mixture** HyVolt III

**Registration number** -

**UFI:** EU: C500-C029-G00D-DQUF

**Synonyms** None.

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Transformer Oil

**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

**MANUFACTURER:** Ergon, Inc.  
P.O. Box 1639  
Jackson, MS 39181 USA

**EU Contact:** Ergon International, Inc.  
Drève Richelle 161 Building C  
B-1410 Waterloo, Belgium

### Emergency Phone Numbers:

**US Customer Service:** + 1-800-222-7122

**CHEMTREC:** + 1-800-424-9300 After Business Hours (North America)  
+ 1-703-527-3887 (International),  
+32-28083237 (Belgium)  
+33-975181407 (France)  
+49-69643508409 (Germany)  
+39-0245557031 (Italy)  
+34-931768545 (Spain)

**E-mail:** sds@ergon.com

**Poison Centre (Centre Antipoisons - Belgium):** +32022649636

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

#### Health hazards

Aspiration hazard Category 1 H304 - May be fatal if swallowed and enters airways.

#### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard Category 3 H412 - Harmful to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**UFI:** EU: C500-C029-G00D-DQUF

**Contains:** Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based

#### Hazard pictograms



**Signal word** Danger

**Hazard statements**

H304 May be fatal if swallowed and enters airways.  
H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements****Prevention**

P260 Do not breathe gas/mist/vapours/spray.  
P273 Avoid release to the environment.

**Response**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor.  
P331 Do NOT induce vomiting.

**Storage**

P405 Store locked up.

**Disposal**

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental label information**

None.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Distillates (petroleum), hydrotreated light naphthenic	30 - 99,6	64742-53-6 265-156-6	01-2119480375-34	649-466-00-2	
<b>Classification:</b> -					L
Distillates (petroleum), hydrotreated light paraffinic	0 - 50	64742-55-8 265-158-7	01-2119487077-29	649-468-00-3	
<b>Classification:</b> -					L
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based	0 - 50	72623-86-0 276-737-9	01-2119474878-16	649-482-00-X	
<b>Classification:</b> -					L
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED	0 - 45	72623-87-1 276-738-4	01-2119474889-13	649-483-00-5	
<b>Classification:</b> Asp. Tox. 1;H304					L
2,6-DI-TERT-BUTYL-P-CRESOL	< 0,4	128-37-0 204-881-4	01-2119565113-46	-	
<b>Classification:</b> Aquatic Chronic 1;H410					

**Composition comments**

The full text for all H-statements is displayed in section 16. Note L: The classification as a carcinogen does not apply as it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

**SECTION 4: First aid measures****General information**

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Keep victim under observation. Contact physician if discomfort continues.

**4.1. Description of first aid measures****Inhalation**

Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or poison control centre immediately.

**Skin contact**

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. Get medical attention if irritation develops and persists.

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion**

Rinse mouth thoroughly. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Never give liquid to an unconscious person. Call a poison control centre immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Aspiration may cause pulmonary oedema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhoea. Defatting of the skin. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**4.3. Indication of any immediate medical attention and special treatment needed**

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**SECTION 5: Firefighting measures**

**General fire hazards** No unusual fire or explosion hazards noted.

**5.1. Extinguishing media**

**Suitable extinguishing media** Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire. Powder. Dry chemicals. Carbon dioxide (CO2). Halon.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** No unusual fire or explosion hazards noted.

**5.3. Advice for firefighters**

**Special protective equipment for firefighters** Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

**Special fire fighting procedures** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Cool containers exposed to flames with water until well after the fire is out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material. Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained.

**For emergency responders** Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Prevent entry into waterways, sewer, basements or confined areas. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment.

**6.3. Methods and material for containment and cleaning up** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Absorb in vermiculite, dry sand or earth and place into containers. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

**6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling** Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Do not get this material on clothing. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

**7.2. Conditions for safe storage, including any incompatibilities** Keep away from heat and sources of ignition. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Store locked up. Store in a well-ventilated place.

**7.3. Specific end use(s)** Observe industrial sector guidance on best practices.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits****Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001, as amended**

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	MAK	10 mg/m3

**Belgium. OEL. Exposure Limit Values to Chemical Substances at Work, Code of Well-being at work, Book VI, Title 1 - Chemical agents, as amended**

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	2 mg/m3	Vapour and aerosol.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**Bulgaria. OELs. Ordinance No 13 on protection of workers against risks of exposure to chemical agents at work, as amended**

Material	Type	Value
HyVolt III	TWA	5 mg/m3
Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	50 mg/m3
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	10 mg/m3
	TWA	5 mg/m3

**Croatia. OELs (GVI). Regulation on Protection of Workers against Exposure to Dangerous Chemicals at Work, OELs and Biological Limit Values, Annex I (NN 91/2018), as amended**

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	MAC	10 mg/m3

**Czech Republic. Occupational exposure limit values of chemicals at work (Decree on protection of health at work, 361/2007, Annex 2, Part A & Annex 3, Part A, as amended)**

Material	Type	Value
HyVolt III	Ceiling	1000 mg/m3
	TWA	200 mg/m3

**Denmark. Work Environment Authority. Exposure Limits for Substances & Materials, Annex 2**

Material	Type	Value	Form
HyVolt III	TLV	1 mg/m3	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	20 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TLV	10 mg/m3	
	STEL	2 mg/m3	Mist.
	TLV	1 mg/m3	Mist.

**Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health**

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m3	Mist.

**Finland. HTP-arvot, App 3., Binding Limit Values, Social Affairs and Ministry of Health**

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	20 mg/m3	
	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	VME	10 mg/m3

**Regulatory status:** Indicative limit (VL)

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG), as updated**

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3	Vapor and aerosol, inhalable fraction.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Respirable fraction.
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Respirable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m3	Respirable fraction.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	AGW	10 mg/m3	Inhalable fraction.

**Greece. OELs, Presidential Decree No. 307/1986, as amended**

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m3	Mist.

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.

**Hungary. OELs. Decree on protection of workers exposed to chemical agents (5/2020. (II.6)), Annex 1&2, as amended**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Material	Type	Value	Form
HyVolt III	Ceiling	5 mg/m3	Mist.

**Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended**

Material	Type	Value	Form
HyVolt III	TWA	1 mg/m3	Mist.

**Iceland. OELs. Regulation 390/2009 on Pollution Limits and Measures to Reduce Pollution at the Workplace, as amended**

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	1 mg/m3	Mist.

**Ireland. OELs, Schedules 1 & 2, Code of Practice for Chemical Agents and Carcinogens Regulations**

Material	Type	Value	Form
HyVolt III	TWA	0,2 mg/m3	Inhalable fraction.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	2 mg/m3	
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

**Italy. OELs (Legislative Decree n.81, 9 April 2008), as amended**

Material	Type	Value	Form
HyVolt III	TWA	5 mg/m3	Inhalable fraction.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapour.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

**Latvia. OELs. Occupational Exposure Limits of Chemical Substances at Workplace (Reg. No. 325/ 2007, L.V. 80, Annex 1), as amended**

Components	Type	Value
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3

**Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended**

Material	Type	Value	Form
HyVolt III	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.

**Lithuania. OELs. Occupational Exposure Limit Values for Chemical Substances (Hygiene Norm HN 23:2011; Order No. V-824/A1-389), as amended**

<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m <sup>3</sup>	Fume and mist.
	TWA	1 mg/m <sup>3</sup>	Fume and mist.

**Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt III	TWA	5 mg/m <sup>3</sup>	Mist.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m <sup>3</sup>	Mist.

**Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt III	TLV	1 mg/m <sup>3</sup>	Mist.

**Poland. Maximum permissible concentrations and intensities of harmful factors in the work environment (Dz.U.Poz. 1286/2018, Annex 1)**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt III	STEL	10 mg/m <sup>3</sup>	Aerosol
	TWA	5 mg/m <sup>3</sup>	Aerosol
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796-2014)**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
HyVolt III	STEL	10 mg/m <sup>3</sup>	Aerosol
	TWA	5 mg/m <sup>3</sup>	Aerosol
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	2 mg/m <sup>3</sup>	Inhalable fraction and vapour.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m <sup>3</sup>	Inhalable fraction.

**Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)**

<b>Material</b>	<b>Type</b>	<b>Value</b>
HyVolt III	STEL	10 mg/m <sup>3</sup>
	TWA	5 mg/m <sup>3</sup>

**Romania. OELs. Limit Values of Chemical Agents at Workplace (Regulation 1.218/2006, M.O 845, Annex 1, 3&4, as amended)**

Components	Type	Value
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	10 mg/m3
	TWA	5 mg/m3

**Slovakia. OELs. Maximum permissible exposure limits for chemical factors in workplace air (Regulation No 355/2006, Annex 1, Table 1, as amended)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Fume and mist.
	TWA	15 ppm 1 mg/m3	Fume and mist. Fume and mist.
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)	STEL	5 ppm 3 mg/m3	Fume and mist. Fume and mist.
	TWA	15 ppm 1 mg/m3 5 ppm	Fume and mist. Fume and mist. Fume and mist.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	STEL	3 mg/m3	Fume and mist.
	TWA	15 ppm 1 mg/m3 5 ppm	Fume and mist. Fume and mist. Fume and mist.

**Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Ann. I 100/2001), as amended**

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	KTV	40 mg/m3	Inhalable fraction.

**Slovenia. OELs. Occupational Exposure Limits of Chemicals at Workplace (Reg. on Protection of Workers from Risks due to Exp. to Chemicals at Work, Annex I), as amended**

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3	Inhalable fraction.

**Spain. OELs. INSST, Límites de Exposición Profesional Para Agentes Químicos, Table 1-Valores Límites Ambientales (VLAs)**

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3	
	STEL	10 mg/m3	Mist.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Mist.

**Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended**

Material	Type	Value	Form
HyVolt III	STEL	3 mg/m3	Mist.



**Sweden. OELs (Annex 1). Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2018:1), as amended**

Material	Type	Value	Form
	TWA	1 mg/m3	Mist.
Components	Type	Value	Form
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	STEL	3 mg/m3	Mist.
	TWA	1 mg/m3	Mist.

**Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte**

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	STEL	40 mg/m3	Vapor and aerosol, inhalable.
	TWA	10 mg/m3	Vapor and aerosol, inhalable.
Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m3	Inhalable fraction.

**UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1**

Components	Type	Value
2,6-DI-TERT-BUTYL-P-CRES OL (CAS 128-37-0)	TWA	10 mg/m3

**Biological limit values** No biological exposure limits noted for the ingredient(s).**Recommended monitoring procedures** Follow standard monitoring procedures.**Derived no effect levels (DNELs)** Not available.**Predicted no effect concentrations (PNECs)** Not available.**Exposure guidelines****Austria MAK: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Can be absorbed through the skin.

**Belgium OELs: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Can be absorbed through the skin.

**Croatia ELVs: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Can be absorbed through the skin.

**Czech Republic PELs: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Can be absorbed through the skin.

**Denmark GV: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Can be absorbed through the skin.

**Estonia OELs: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Can be absorbed through the skin.

**EU. OELs from Annex III, Part A to Directive 2004/37/EC: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) Can be absorbed through the skin.

**France Mandatory OELs (VLEP): Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Iceland OELs: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Ireland Exposure Limit Values: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Lithuania OELs: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Netherlands OELs (binding): Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Romania OELs: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Slovakia OELs for Carcinogens and Mutagens: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Slovenia. CMR. Protection of workers from exposure to carcinogen and mutagen agents (ULRS 101/2005, as amended)**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**Sweden Threshold Limit Values: Skin designation**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)	Can be absorbed through the skin.
--	-----------------------------------

**8.2. Exposure controls**

<b>Appropriate engineering controls</b>	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
---	---

**Individual protection measures, such as personal protective equipment**

<b>General information</b>	Wear suitable protective equipment. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
----------------------------	---

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
----------------------------	---

**Skin protection**

<b>- Hand protection</b>	Wear suitable gloves tested to EN374. Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.
--------------------------	--

<b>- Other</b>	Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.
----------------	---

<b>Respiratory protection</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
-------------------------------	---

<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
------------------------	---

<b>Hygiene measures</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
-------------------------	---

<b>Environmental exposure controls</b>	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.
--	--

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Colour</b>	L0.5
<b>Odour</b>	Mild Petroleum Odor
<b>Melting point/freezing point</b>	-63 °C (-81,4 °F) ASTM D5950/ISO 3016
<b>Boiling point or initial boiling point and boiling range</b>	287 °C (548,6 °F) ASTM D2887/ ISO 3294
<b>Flammability</b>	Will burn if involved in a fire.

## Upper/lower flammability or explosive limits

**Explosive limit - lower ( %)** Not available.

**Explosive limit – upper ( %)** Not available.

**Flash point** 156,0 °C (312,8 °F)

**Auto-ignition temperature** ≥315 °C (≥599 °F) ASTM E659

**Decomposition temperature** Not determined.

**pH** Not determined.

**Kinematic viscosity** 9,4 mm<sup>2</sup>/s ISO 3104 (40 °C (104 °F))

## Solubility

**Solubility (water)** Insoluble

**Partition coefficient** Not established.

**(n-octanol/water) (log value)** Not applicable.

**Vapour pressure** Not determined.

## Density and/or relative density

**Relative density** 0,88 (20 °C (68 °F) ASTM D4052/ ISO 12185)

**Vapour density** Not determined.

**Particle characteristics** Not available.

## 9.2. Other information

**9.2.1. Information with regard to physical hazard classes** No relevant additional information available.

**9.2.2. Other safety characteristics** No relevant additional information available.

## SECTION 10: Stability and reactivity

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** Stable.

**10.3. Possibility of hazardous reactions** Hazardous polymerisation does not occur.

**10.4. Conditions to avoid** Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**10.5. Incompatible materials** Strong oxidising agents.

**10.6. Hazardous decomposition products** Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

**Inhalation** May be fatal if swallowed and enters airways.

**Skin contact** May cause an allergic skin reaction. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration.

**Symptoms** Aspiration may cause pulmonary oedema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhoea. Coughing. Discomfort in the chest. Shortness of breath. Defatting of the skin.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Components	Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
	Rat	> 2000 mg/kg

Components	Species	Test Results
<b>Oral</b> LD50	Rat	> 6000 mg/kg > 2930 mg/kg
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)		
<b>Acute Dermal</b> LD50	Rat	> 2000 mg/kg
<b>Oral</b> LD50	Rat	> 5000 mg/kg
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)		
<b>Acute Dermal</b> LD50	Rabbit	> 2000 mg/kg
<b>Oral</b> LD50	Rat	> 5000 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Serious eye damage/eye irritation</b>	Due to partial or complete lack of data the classification is not possible. Prolonged exposure may cause irritation to eyes.	
<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Skin sensitisation</b>	Based on available data, the classification criteria are not met. May cause defatting of the skin, but is not an irritant.	
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.	
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Note L - Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.	

**Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)  
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6) 3 Not classifiable as to carcinogenicity to humans.  
Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0) 3 Not classifiable as to carcinogenicity to humans.

<b>Reproductive toxicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - single exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - repeated exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Mixture versus substance information</b>	No information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties** This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

**Other information** May cause allergic respiratory and skin reactions. Risk of chemical pneumonia after aspiration.

**SECTION 12: Ecological information**

**12.1. Toxicity** Harmful to aquatic life with long lasting effects.

Product	Species	Test Results
HyVolt III		
<b>Aquatic</b>		
Crustacea	EC50	Daphnia
Fish	LC50	Fish
		28,1551 mg/l, 48 hours estimated
		67,5721 mg/l, 96 hours estimated

Product	Species	Test Results
<i>Acute</i>		
Crustacea	EC50	Daphnia 19,3983 mg/l, 48 hours estimated
Fish	LC50	Fish 15,016 mg/l, 4 days estimated
Components	Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)		
<b>Aquatic</b>		
<i>Acute</i>		
Algae	EC10	Freshwater algae 0,24 mg/l, 72 hours
Crustacea	EC50	Daphnia magna 0,48 mg/l, 48 hours
Fish	LC50	Fish 0,199 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	NOEC	Daphnia magna 0,069 mg/l, 21 days
Fish	NOEC	Fish 0,053 mg/l, 30 days

Not available. \* Estimates for product may be based on additional component data not shown.

<b>12.2. Persistence and degradability</b>	Expected to be inherently biodegradable.
<b>12.3. Bioaccumulative potential</b>	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.
<b>Partition coefficient n-octanol/water (log Kow)</b>	Not established.
2,6-DI-TERT-BUTYL-P-CRESOL	5,1
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	Expected to be slightly to moderately mobile in soil.
<b>12.5. Results of PBT and vPvB assessment</b>	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
<b>12.6. Endocrine disrupting properties</b>	This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
<b>12.7. Other adverse effects</b>	Oil spills are generally hazardous to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. Waste codes should be assigned by the user based on the application for which the product was used.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. Do not contaminate ponds, waterways or ditches with chemical or used container.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	Not regulated as dangerous goods.
<b>14.2. UN proper shipping name</b>	Not regulated as dangerous goods.
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	Not assigned.
<b>Subsidiary hazard</b>	-
<b>Hazard No. (ADR)</b>	Not assigned.
<b>Tunnel restriction code</b>	Not assigned.
<b>14.4. Packing group</b>	-

**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Not assigned.

#### RID

**14.1. UN number** Not regulated as dangerous goods.  
**14.2. UN proper shipping name** Not regulated as dangerous goods.  
**14.3. Transport hazard class(es)**  
**Class** Not assigned.  
**Subsidiary hazard** -  
**14.4. Packing group** -  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Not assigned.

#### ADN

**14.1. UN number** Not regulated as dangerous goods.  
**14.2. UN proper shipping name** Not regulated as dangerous goods.  
**14.3. Transport hazard class(es)**  
**Class** Not assigned.  
**Subsidiary hazard** -  
**14.4. Packing group** -  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Not assigned.

#### IATA

**14.1. UN number** Not regulated as dangerous goods.  
**14.2. UN proper shipping name** Not regulated as dangerous goods.  
**14.3. Transport hazard class(es)**  
**Class** Not assigned.  
**Subsidiary hazard** -  
**14.4. Packing group** -  
**14.5. Environmental hazards** No.  
**14.6. Special precautions for user** Not assigned.

#### IMDG

**14.1. UN number** Not regulated as dangerous goods.  
**14.2. UN proper shipping name** Not regulated as dangerous goods.  
**14.3. Transport hazard class(es)**  
**Class** Not assigned.  
**Subsidiary hazard** -  
**14.4. Packing group** -  
**14.5. Environmental hazards**  
**Marine pollutant** No.  
**EmS** Not assigned.  
**14.6. Special precautions for user** Not assigned.

**14.7. Maritime transport in bulk according to IMO instruments** This product is a liquid. Therefore, bulk transport is governed by MARPOL 73/78, Annex I.

**General information** Not regulated as dangerous goods.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**  
Not listed.

**Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**  
Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**UFI:**

EU: C500-C029-G00D-DQUF

**Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

**Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended**

Not listed.

**Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended**

Not listed.

**Other EU regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EU) 2020/878.

**Other regulations**

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

**National regulations**

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.  
Germany: WGK 1

**France regulations**

**France INRS Table of Occupational Diseases**

Distillates (petroleum), hydrotreated light naphthenic (CAS 64742-53-6)

Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse 36

Lubricating Oils (petroleum), C15-30, Hydrotreated Neutral Oil-based (CAS 72623-86-0)

Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse 36

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)

Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse 36

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out. The chemical safety assessment has been carried out for the components of the mixture listed in section 3 of the SDS. Exposure scenarios relevant for these substances are annexed to this eSDS.

**Inventory status**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## SECTION 16: Other information

### List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization (Comité Européen de Normalisation).

CEN: European Committee for Standardization.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

vPvB: very Persistent, very Bioaccumulative.

PBT: Persistent, bioaccumulative, toxic.

STEL: Short-term Exposure Limit.

### References

ACGIH

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical safety report. IARC Monographs. Overall Evaluation of Carcinogenicity

Korea. Dangerous Substances Threshold Quantity (Presidential Decree of Dangerous Substances Safety Management Act No. 18406, Schedule 1)

Korea. Regulated volatile organic compounds (VOCs) (MOE Notice No. 2001-36, March 8, 2001, as amended)

Chemical Abstracts Service Registry Handbook

CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

### Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

### Full text of any statements, which are not written out in full under sections 2 to 15

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

### Revision information

Composition / Information on Ingredients: Undisclosed Ingredient Statement

SECTION 8: Exposure controls/personal protection: Appropriate engineering controls

Transport Information: Material Transportation Information

GHS: Classification

### Training information

Follow training instructions when handling this material.



**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon International cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.