ERGON:

SAFETY DATA SHEET

1. Identification

Product identifier HyVolt C50A

Other means of identification None.

Recommended use Transformer Oil **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company: Ergon, Inc.

Address: P.O. Box 1639

Jackson, MS 39215

E-mail: sds@ergon.com

Emergency Contacts

Customer Service: 1-800-222-7122

Chemtrec: 1-800-424-9300 After Business Hours (North America Only)

1-703-527-3887 After Business Hours (International)

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazardsAspiration hazardCategory 1Environmental hazardsHazardous to the aquatic environment,Category 3

long-term hazard

Label elements



Signal word Danger

Hazard statement Harmful to aquatic life with long lasting effects. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Do not breathe gas/mist/vapors/spray. Avoid release to the environment.

Response IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce

vomiting.

Storage Store locked up.

Disposal Dispose of contents/container to an appropriate treatment and disposal facility in accordance with

applicable laws and regulations, and product characteristics at time of disposal. See section 13 of

this SDS for disposal instructions.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
OIL, MINERAL		64742-53-6	65 - 85
C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS — DISTILLATES		848301-69-9	0 - 40

Material name: HyVolt C50A SDS CANADA

Chemical name	Common name and synonyms	CAS number	%
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED		72623-86-0	0 - 40
OIL, MINERAL		64742-55-8	0 - 35
SOLVENT NAPHTHA (PETROLEUM) HEAVY AROM.	,	64742-94-5	< 1
BUTYLATED HYDROXYTOLUENE (BHT)		128-37-0	< 0.4

Composition comments

Not classified as a carcinogen. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

4. First-aid measures

Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Skin contact

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact

Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion

Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

aspiration. Call a poison control center immediately.

Most important

symptoms/effects, acute and

delayed

Defatting of the skin.

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Contact physician if discomfort continues.

5. Fire-fighting measures

Suitable extinguishing media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an

extinguisher, as this will spread the fire.

Unsuitable extinguishing

media

Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from

the chemical

No unusual fire or explosion hazards noted.

Special protective equipment and precautions for

firefiahters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting equipment/instructions Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurized air mask if product is involved in a

General fire hazards

No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Methods and materials for containment and cleaning up Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS.

Material name: HyVolt C50A SDS CANADA

Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
OIL, MINERAL (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	TWA	10 mg/m3	
C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS – DISTILLATES (CAS 848301-69-9)	TWA	1590 mg/m3	
		400 ppm	
OIL, MINERAL (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS 64742-94-5)	TWA	200 mg/m3	Vapor.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

builty Regulation 250/57/as amenaca)					
Components	Туре	Value	Form		
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	TWA	2 mg/m3	Vapor and aerosol, inhalable.		

Material name: HyVolt C50A SDS CANADA

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form	
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-86-0)	TWA	1 mg/m3	Mist.	
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Material	Туре	Value	Form
HyVolt C50A	TWA	5 mg/m3	Inhalable fraction.
Components	Туре	Value	Form
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
OIL, MINERAL (CAS 64742-53-6)	TWA	5 mg/m3	Inhalable fraction.
OIL, MINERAL (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Material	Туре	Value	Form	
HyVolt C50A	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	
Components	Туре	Value	Form	
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	TWA	10 mg/m3		
C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS – DISTILLATES (CAS 848301-69-9)	TWA	1590 mg/m3		
		400 ppm		
OIL, MINERAL (CAS 64742-55-8)	STEL	10 mg/m3	Mist.	

Material name: HyVolt C50A SDS CANADA

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)				
Components	Туре	Value	Form	
OIL, MINERAL (CAS 64742-53-6)	STEL	10 mg/m3	Mist.	
OIL, MINERAL (CAS 64742-55-8)	TWA	5 mg/m3	Mist.	
OIL, MINERAL (CAS 64742-53-6)	TWA	5 mg/m3	Mist.	

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21))

Components	Туре	Value	Form
BUTYLATED HYDROXYTOLUENE (BHT) (CAS 128-37-0)	15 minute	4 mg/m3	Inhalable fraction and vapor.
	8 hour	2 mg/m3	Inhalable fraction and vapor.
C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS – DISTILLATES (CAS 848301-69-9)	15 minute	500 ppm	
	8 hour	400 ppm	
OIL, MINERAL (CAS 64742-55-8)	15 minute	10 mg/m3	
OIL, MINERAL (CAS 64742-53-6)	15 minute	10 mg/m3	
	8 hour	5 mg/m3	
OIL, MINERAL (CAS 64742-55-8)	8 hour	5 mg/m3	
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS 64742-94-5)	15 minute	250 mg/m3	Vapor.
	8 hour	200 mg/m3	Vapor.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - Alberta OELs: Skin designation

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS Can be absorbed through the skin. 64742-94-5)

Canada - British Columbia OELs: Skin designation

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS Can be absorbed through the skin. 64742-94-5)

Canada - Manitoba OELs: Skin designation

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS Can be absorbed through the skin. 64742-94-5)

Canada - Ontario OELs: Skin designation

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS Can be absorbed through the skin. 64742-94-5)

Canada - Saskatchewan OELs: Skin designation

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS Can be absorbed through the skin. 64742-94-5)

US ACGIH Threshold Limit Values: Skin designation

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS Can be absorbed through the skin. 64742-94-5)

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Goggles/face shield are recommended.

Material name: HyVolt C50A SDS CANADA

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Other Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Respiratory protection Under normal conditions, respirator is not normally required. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Not available.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance Clear & bright

Physical state Liquid. **Form** Liauid.

Color Water White to Pale Odor Mild Petroleum Odor

Odor threshold Not available. Ηq Not applicable

Melting point/freezing point -85 °F (-65 °C) ASTM D5950

Initial boiling point and

boiling range

545 °F (285 °C) ASTM D2887/ ISO 3294

Flash point 289.4 °F (143 °C) Pensky-Martens Closed Cup ASTM D93/ ISO 2719

311 °F (155 °C) Cleveland Open Cup ASTM D92/ ISO 2592

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Vapor pressure Not available. Vapor density Not available.

Relative density 0.89 (59 °F (15 °C) ASTM D4052/ ISO 12185)

Solubility(ies)

Solubility (water) Insoluble

Not established. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature

> 599 °F (> 315 °C) ASTM E659

Decomposition temperature Not available.

9.5 cSt (104 °F (40 °C) ASTM D445) **Viscosity**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Strong oxidizing agents.

Material name: HyVolt C50A SDS CANADA **Hazardous decomposition**

products

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular

weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation May be fatal if swallowed and enters airways.

Skin contact Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest.

Information on toxicological effects

Acute toxicity Not applicable.

Components Species Test Results

C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS - DISTILLATES (CAS 848301-69-9)

Acute Inhalation

LC50 Rat 61 mg/l, 4 Hours

Not available. * Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

irritation

Not classified. May cause minor irritation on eye contact.

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Not classified

Reproductive toxicityContains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity

- repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects

Further information Risk of chemical pneumonia after aspiration.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product		Species	Test Results
HyVolt C50A			
Aquatic			
Crustacea	EC50	Daphnia	24.429 mg/l, 48 hours estimated
Fish	LC50	Fish	60.1604 mg/l, 96 hours estimated
Components		Species	Test Results
BUTYLATED HYDROX	YTOLUENE (BHT) (CAS 128-37-0)	
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	1.44 mg/l, 48 hours

Material name: HyVolt C50A SDS CANADA

Components Species Test Results

C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS - DISTILLATES (CAS 848301-69-9)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours

Fish LC50 Rainbow trout, donaldson trout 8.8 mg/l, 96 hours

(Oncorhynchus mykiss)

8.8 mg/l, 96 hours

Not available. * Estimates for product may be based on additional component data not shown.

Persistence and degradability Not inherently biodegradable.

Bioaccumulative potentialBioaccumulation is unlikely to be significant because of the low water solubility of this product.

Mobility in soil Not available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material

characteristics at time of disposal.

Hazardous waste code Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

General information Not regulated as dangerous goods.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the SDS

contains all the information required by the CPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations The product is classified and labelled in accordance with EC directives or respective national laws

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

Stockholm Convention

Not applicable.

Material name: HyVolt C50A SDS CANADA

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

International Inventories

Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information

 Issue date
 09-23-2019

 Revision date
 02-08-2022

Version # 04

Further information Local CHEMTREC Numbers:

CHEMTREC China: 4001-204937

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Indonesia: 001-803-017-9114 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Mexico: 1-800-681-9531 CHEMTREC Singapore: +(65)-31581349

References ACGIH

EPA: AQUIRE database

Inventory name

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Material name: HyVolt C50A SDS CANADA

On inventory (yes/no)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Hazard identification: Response

Composition / Information on Ingredients: Ingredients

Material name: HyVolt C50A SDS CANADA