ERGONE

SAFETY DATA SHEET

1. Identification

Product identifier HyVolt C50A

Other means of identification None.

Recommended use Transformer Oil **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company: Ergon, Inc.

Address: P.O. Box 1639

Jackson, MS 39215

E-mail: sds@ergon.com

Emergency Contacts

Customer Service: 1-800-222-7122

Chemtrec: 1-800-424-9300 After Business Hours (North America Only)

1-703-527-3887 After Business Hours (International)

2. Hazard(s) identification

Physical hazardsNot classified.Health hazardsAspiration hazard

Environmental hazards Not classified. **OSHA defined hazards** Not classified.

Label elements



Signal word Danger

Hazard statement Harmful to aquatic life with long lasting effects. May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Do not breathe gas/mist/vapors/spray. Avoid release to the environment.

Response IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce

vomiting.

Storage Store locked up.

Disposal Dispose of contents/container to an appropriate treatment and disposal facility in accordance with

applicable laws and regulations, and product characteristics at time of disposal. See section 13 of

Category 1

this SDS for disposal instructions.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC		64742-53-6	65 - 85
C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS – DISTILLATES		848301-69-9	0 - 40

Material name: HyVolt C50A SDS US

Chemical name	Common name and synonyms	CAS number	%
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED		72623-86-0	0 - 40
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC		64742-55-8	0 - 35
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.		64742-94-5	< 1
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)]		128-37-0	< 0.4

Composition comments

Not classified as a carcinogen. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical

advice/attention.

Defatting of the skin.

Skin contact Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated

clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of

Do not use a solid water stream as it may scatter and spread fire.

aspiration. Call a poison control center immediately.

Most important

symptoms/effects, acute and delayed

Indication of immediate Treat symptomatically.

medical attention and special treatment needed

General information

Contact physician if discomfort continues.

5. Fire-fighting measures

Suitable extinguishing media

Halon. Dry chemicals. Foam. Carbon dioxide (CO2). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefiahters

No unusual fire or explosion hazards noted.

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Fire fighting equipment/instructions Cool containers exposed to flames with water until well after the fire is out. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Use pressurized air mask if product is involved in a

General fire hazards No unusual fire or explosion hazards noted. Flammability Class: Combustible IIIB

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Material name: HyVolt C50A SDS US

Methods and materials for containment and cleaning up

Large Spills: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

7. Handling and storage

Precautions for safe handling

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Use care in handling/storage.

8. Exposure controls/personal protection

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Occupational exposure limits

Components	Туре	Value	Form
C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS – DISTILLATES (CAS 848301-69-9)	PEL	400 mg/m3	
		100 ppm	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limit Value		Value	Form
Components	Туре	Value	FOIII
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.

Material name: HyVolt C50A SDS US

6871 Version #: 03 Revision date: 02-08-2022 Issue date: 02-19-2020

US. ACGIH Threshold Limit Values Form Value Components **Type SOLVENT NAPHTHA TWA** 200 mg/m3 Non-aerosol. (PETROLEUM), HEAVY AROM. (CAS 64742-94-5) **US. NIOSH: Pocket Guide to Chemical Hazards Material Value Form** Type HyVolt C50A 10 mg/m3 STEL Mist. **TWA** 5 mg/m3 Mist. **Form Components Value Type** 2,6-DI-TERT-BUTYL-P-CRES **TWA** 10 mg/m3 OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0) C18-C50 BRANCHED, **TWA** 400 mg/m3 CYCLIC AND LINEAR **HYDROCARBONS** -DISTILLATES (CAS 848301-69-9) 100 ppm **DISTILLATES** Ceiling 1800 mg/m3 (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6) **STEL** 10 mg/m3 Mist. **DISTILLATES STEL** Mist. 10 mg/m3 (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8) **TWA** 5 mg/m3 Mist. 100 mg/m3 **SOLVENT NAPHTHA TWA** (PETROLEUM), HEAVY

Biological limit values

AROM. (CAS 64742-94-5)

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS Can be absorbed through the skin. 64742-94-5)

Appropriate engineering

occupational exposure limit is not exceeded.

controls

Individual protection measures, such as personal protective equipment

Eye/face protection

Goggles/face shield are recommended.

Skin protection

Other

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Respiratory protection

Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined

Under normal conditions, respirator is not normally required. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal hazards Not available.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants.

Discard contaminated footwear that cannot be cleaned.

Material name: HyVolt C50A sps us

9. Physical and chemical properties

Appearance Clear & bright

Physical state Liquid. **Form** Liquid.

Color Water White to Pale Odor Mild Petroleum Odor

Odor threshold Not available. Not applicable pН

-85 °F (-65 °C) ASTM D5950 Melting point/freezing point

Initial boiling point and

boiling range

545 °F (285 °C) ASTM D2887/ ISO 3294

Flash point 289.4 °F (143 °C) Pensky-Martens Closed Cup ASTM D93/ ISO 2719

311 °F (155 °C) Cleveland Open Cup ASTM D92/ ISO 2592

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Explosive limit - lower

(%)

Not available.

Explosive limit - upper

(%)

Not available.

Not available. Vapor pressure Vapor density Not available.

Relative density 0.89 (59 °F (15 °C) ASTM D4052/ ISO 12185)

Solubility(ies)

Insoluble Solubility (water)

Partition coefficient Not established.

(n-octanol/water)

Auto-ignition temperature > 599 °F (> 315 °C) ASTM E659

Decomposition temperature Not available.

9.5 cSt (104 °F (40 °C) ASTM D445) **Viscosity**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

Chemical stability Stable.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular products weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation May be fatal if swallowed and enters airways.

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis Skin contact

Eye contact May be irritating to eyes.

Ingestion May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may

increase risk of product aspiration. May be fatal if swallowed and enters airways.

Material name: HyVolt C50A SDS US Symptoms related to the physical, chemical and toxicological characteristics

Defatting of the skin. Coughing. Shortness of breath. Discomfort in the chest.

Information on toxicological effects

Acute toxicity Not applicable.

Components Species Test Results

C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS - DISTILLATES (CAS 848301-69-9)

Acute Inhalation

LC50 Rat 61 mg/l, 4 Hours

Not available. * Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye

Not classified. May cause minor irritation on eye contact.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitizationNot classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer. **Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EL

requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC)

using IP 346.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityContains no ingredient listed as toxic to reproduction

Specific target organ toxicity

- single exposure

Not classified.

Specific target organ toxicity Not classified.

- repeated exposure

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects

Further information Risk of chemical pneumonia after aspiration.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product		Species	Test Results	
HyVolt C50A				
Aquatic				
Crustacea	EC50	Daphnia	24.429 mg/l, 48 hours estimated	
Fish	LC50	Fish	60.1604 mg/l, 96 hours estimated	
Components		Species	Test Results	

2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 1.44 mg/l, 48 hours

C18-C50 BRANCHED, CYCLIC AND LINEAR HYDROCARBONS - DISTILLATES (CAS 848301-69-9)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours

Material name: HyVolt C50A sps us

ComponentsSpeciesTest ResultsFishLC50Rainbow trout,donaldson trout (Oncorhynchus mykiss)8.8 mg/l, 96 hours8.8 mg/l, 96 hours

Not available. * Estimates for product may be based on additional component data not shown.

Persistence and degradability Not inherently biodegradable.

Bioaccumulative potentialBioaccumulation is unlikely to be significant because of the low water solubility of this product.

Mobility in soil Not available.

Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions When this product as supplied is to be discarded as waste, it does not meet the definition of a

RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material

characteristics at time of disposal.

Hazardous waste code Not applicable.

Waste from residues / unused products

Dispose of in accordance with local regulations. Avoid discharge into water courses or onto the

ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78

and the IBC Code

General information Not regulated as dangerous goods.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard

29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw

materials with no additives or recycled oils that might introduce PCB contamination.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Material name: HyVolt C50A sps us

SARA 311/312 Yes

Hazardous chemical

Classified hazard Aspiration hazard

categories

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

⁽PICCS)

Taiwan Chemical Substance Inventory (TCSI) **Taiwan** Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

Issue date 02-19-2020 **Revision date** 02-08-2022

Version # 03

Further information Local CHEMTREC Numbers:

> CHEMTREC Mexico: 1-800-681-9531 CHEMTREC China: 4001-204937 CHEMTREC Indonesia: 001-803-017-9114

CHEMTREC EU (Brussels): +(32)-28083237 CHEMTREC Malaysia: +(60)-327884561 CHEMTREC Singapore: +(65)-31581349

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Material name: HyVolt C50A SDS US

6871 Version #: 03 Revision date: 02-08-2022 Issue date: 02-19-2020

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

References ACGIH

EPA: AQUIRE database

NLM: Hazardous Substances Data Base

US. IARC Monographs on Occupational Exposures to Chemical Agents

IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Chemical Abstracts Service Registry Handbook CRC: Handbook of Chemistry and Physics

ILO Safety Cards

International Labour Organization

International Maritime Organization Marine Pollutants List

NFPA Hazardous Chemical Data Sheets

NIOSH Pocket Guide

Registry of Toxic Effects of Chemical Substances (RTECS)

US DOT Hazardous Materials Regulations

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Hazard(s) identification: Prevention

Hazard(s) identification: Hazard statement

Composition / Information on Ingredients: Ingredients

Regulatory information: US state regulations

GHS: Classification

Material name: HyVolt C50A SDS US