# ERGON E

## **SAFETY DATA SHEET**

## 1. Identification

Product identifier	HyVolt I US
Other means of identification	None.
Recommended use	Dielectric Fluid.
<b>Recommended restrictions</b>	None known.
Manufacturer/Importer/Suppl	ier/Distributor information
Company:	Ergon, Inc.
Address:	P.O. Box 1639
	Jackson, MS 39215
E-mail:	sds@ergon.com
Emergency Contacts	
Customer Service:	1-800-222-7122
Chemtrec:	1-800-424-9300 After Business Hours (North America Only)
	1-703-527-3887 After Business Hours (International)

## 2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
	▲	



Signal word	Danger
Hazard statement	May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Do not breathe gas/mist/vapors/spray.
Response	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

## 3. Composition/information on ingredients

lixtures			
Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC		64742-53-6	30.0 - 99.9
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED		72623-86-0	0 - 50

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC		64742-55-8	0 - 45
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC		64742-56-9	0 - 10
2,6-DI-TERT-BUTYL-P-CRESOL [BUTYLATED HYDROXYTOLUE (BHT)]		128-37-0	< 0.08
Composition comments	Not classified as a carcinogen. Meets EU requi polycyclic aromatic compound (PAC) using IP		) DMSO extract for total
4. First-aid measures			
Inhalation	Move to fresh air. Oxygen or artificial respirati advice/attention.	on if needed. IF exposed or co	oncerned: Get medical
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.		
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Flush thoroughly with water. If irritation occurs, get medical assistance.		
Ingestion	Rinse mouth. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a physician or poison control center immediately.		
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash. Defatting of the skin. Prolonged exposure may cause chronic effects.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and trea Symptoms may be delayed.	t symptomatically. Keep victin	n under observation.
General information	Ensure that medical personnel are aware of the protect themselves. Contact physician if discond doctor in attendance.		
5. Fire-fighting measure	S		
Suitable extinguishing media	Water spray or fog. Foam. Do not use water jo chemicals. Carbon dioxide (CO2). Halon.	et as an extinguisher, as this v	will spread the fire. Dry
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as th	is will spread the fire.	
Specific hazards arising from the chemical	No unusual fire or explosion hazards noted.		
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet breathing apparatus, protective clothing and f		ure or pressure demand
Fire fighting equipment/instructions	Firefighters must use standard protective equi face shield, gloves, rubber boots, and in enclo with water until well after the fire is out. Use	sed spaces, SCBA. Cool conta	iners exposed to flames
Specific methods	Use standard firefighting procedures and cons	ider the hazards of other invo	lved materials.

**General fire hazards** No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions,	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear
protective equipment and	appropriate protective equipment and clothing during clean-up. Do not touch damaged containers
emergency procedures	or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.
	Local authorities should be advised if significant spillages cannot be contained. For personal
	protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Prevent entry into waterways, sewer, basements or confined areas. Avoid discharge to the aquatic environment. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.
7. Handling and storage	
Precautions for safe handling	DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Wash hands after handling and before eating. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. All handling to take place in well-ventilated area. Shower after work. Remove and wash contaminated clothing promptly.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit At this time, the other constituents have no known exposure limits.

Components	Contaminants (29 CFR 19: Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	PEL	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	PEL	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)	PEL	5 mg/m3	Mist.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	2 mg/m3	Inhalable fraction and vapor.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	TWA	5 mg/m3	Inhalable fraction.

#### blo 7-1 Limite fo Air Co nir (20.0) ..... ....

US. ACGIH Threshold Limi Components	t Values Type	Value	Form
LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-86-0)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide Material	to Chemical Hazards Type	Value	Form
HyVolt I US	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Components	Туре	Value	Form
2,6-DI-TERT-BUTYL-P-CRES OL [BUTYLATED HYDROXYTOLUENE (BHT)] (CAS 128-37-0)	TWA	10 mg/m3	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC (CAS 64742-56-9)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
logical limit values propriate engineering trols	No biological exposure limits noted f Provide adequate ventilation, includi occupational exposure limit is not ex	ng appropriate local extraction,	to ensure that the defined
Eye/face protection	es, such as personal protective equ Goggles/face shield are recommende	-	
Skin protection Hand protection	Chemical resistant gloves are recom gloves.	mended. If contact with forearn	ns is likely wear gauntlet sty
Other	Chemical/oil resistant clothing is rec	ommended. Launder contamina	ted clothing before reuse.
Respiratory protection	Under normal conditions, respirator concentrations above the exposure I		
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
neral hygiene Isiderations	Always observe good personal hygie before eating, drinking, and/or smok Discard contaminated footwear that	king. Routinely wash work cloth	
Physical and chemical	properties		
pearance	Clear & bright		
Physical state	Liquid.		
-			

Odo	r	

Form

Color

Material name: HyVolt I US

Liquid.

Water White to Pale

Mild Petroleum Odor

Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	-85 °F (-65 °C) ASTM D5950
Initial boiling point and boiling range	545 °F (285 °C) ASTM D2887/ ISO 3924
Flash point	289.4 °F (143 °C) Pensky-Martens Closed Cup ASTM D93/ ISO 2719 311 °F (155 °C) Cleveland Open Cup ASTM D92/ ISO 2592
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or e	xplosive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.89 (59 °F (15 °C) ASTM D4052/ ISO 12185)
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not established.
Auto-ignition temperature	> 599 °F (> 315 °C) ASTM E659
Decomposition temperature	Not available.
Viscosity	9.5 cSt (104 °F (40 °C) ASTM D445)

## 10. Stability and reactivity

Reactivity Chemical stability Possibility of hazardous reactions	The product is stable and non-reactive under normal conditions of use, storage and transport Stable. Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

## **11.** Toxicological information

#### Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis
Eye contact	May be irritating to eyes.
Ingestion	May be fatal if swallowed and enters airways. May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. Coughing. Discomfort in the chest. Shortness of breath. Defatting of the skin.
Information on toxicological e	ffects
Acute toxicity	Not applicable.
Skin corrosion/irritation	May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Serious eye damage/eye irritation	Not classified. May cause minor irritation on eye contact.		
Respiratory or skin sensitization	on		
Respiratory sensitization	Not classified.		
Skin sensitization	May cause defatting of the sk	in, but is neither an irritar	nt nor a sensitizer.
Germ cell mutagenicity	No data available to indicate p mutagenic or genotoxic.	product or any componen	ts present at greater than 0.1% are
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EL requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.		
IARC Monographs. Overall	Evaluation of Carcinogenic	ity	
2,6-DI-TERT-BUTYL-P-CR HYDROXYTOLUENE (BHT		3 Not classifiable as to	carcinogenicity to humans.
LUBRICATING OILS (PET			carcinogenicity to humans.
OSHA Specifically Regulate	ed Substances (29 CFR 1910	).1001-1052)	
Not regulated. US. National Toxicology Pr	ogram (NTP) Report on Car	cinogens	
DISTILLATES (PETROLEU PARAFFINIC (CAS 64742-	M), HYDROTREATED LIGHT 55-8)	Known To Be Human C	arcinogen.
Reproductive toxicity	Contains no ingredient listed a	as toxic to reproduction	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	May be fatal if swallowed and enters airways.		
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects		
Further information	Risk of chemical pneumonia after aspiration.		
12. Ecological information	n		
Ecotoxicity	Not expected to be harmful to	aquatic organisms.	
Product	Species		Test Results
HyVolt I US			
Aquatic			
Crustacea	EC50 Daphnia		800 mg/l, 48 hours estimated
Components	Species		Test Results
2,6-DI-TERT-BUTYL-P-CRESO	L [BUTYLATED HYDROXYTOLUE	ENE (BHT)] (CAS 128-37-	0)
Aquatic			
Crustacea	EC50 Water flea (Da	iphnia pulex)	1.44 mg/l, 48 hours
	product may be based on addit	ional component data not	shown.
Persistence and degradability	Not inherently biodegradable.		
Bioaccumulative potential	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	ons		
Disposal instructions	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.		

Local disposal regulationsDispose in accordance with all applicable regulations.Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste<br/>disposal company.

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.
14. Transport information	on
DOT	
Not regulated as dangerous	goods.
ΙΑΤΑ	

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

## Annex II of MARPOL 73/78

#### and the IBC Code

**General information** 

Not regulated as dangerous goods.

#### 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Yes Hazardous chemical **Classified hazard** Aspiration hazard

## categories

#### SARA 313 (TRI reporting) Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

#### (SDWA)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
laterial name: HvVolt I US		SDS US

Material name: HyVolt I US

Country(s) or region	Inventory name On inventor	ory (yes/no)*	
Canada	Non-Domestic Substances List (NDSL)	No	
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes	
Europe	European List of Notified Chemical Substances (ELINCS)	No	
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes	
Korea	Existing Chemicals List (ECL)	Yes	
New Zealand	New Zealand Inventory	Yes	
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes	
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes	
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes	

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	04-07-2021
Revision date	03-01-2022
Version #	02
Further information	Local CHEMTREC Numbers: CHEMTREC Mexico: 1-800-681-9531
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Refining, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
Revision information	Composition/information on ingredients: Composition comments Composition/information on ingredients: Component information First-aid measures: Most important symptoms/effects, acute and delayed Fire-fighting measures: General fire hazards Other information, including date of preparation or last revision: References