

1. Identification

Product identifier	HyVolt III
Other means of identification	None.
Recommended use	Transformer Oil
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Company:	Ergon, Inc.
Address:	P.O. Box 1639 Jackson, MS 39215
E-mail:	sds@ergon.com
Emergency Contacts	
Customer Service:	1-800-222-7122
Chemtrec:	1-800-424-9300 After Business Hours (North America Only) 1-703-527-3887 After Business Hours (International)

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Aspiration hazard Category 1
Environmental hazards	Not classified.
OSHA defined hazards	Not classified.

Label elements



Signal word	Danger
Hazard statement	May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Do not breathe gas/mist/vapors/spray.
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC		64742-53-6	30 - 99.6
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT		64742-47-8	0 - 55
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC		64742-55-8	0 - 50
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED		72623-87-1	0 - 20

Chemical name	Common name and synonyms	CAS number	%
2,6-DI-TERT-BUTYL-P-CRESOL		128-37-0	< 0.4
Other components below reportable levels			15.37

4. First-aid measures

Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician or poison control center immediately.
Skin contact	Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Do NOT induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Never give liquid to an unconscious person. Call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhea. Defatting of the skin. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Keep victim under observation. Contact physician if discomfort continues.

5. Fire-fighting measures

Suitable extinguishing media	Halon. Dry chemicals. Foam. Carbon dioxide (CO ₂). Water spray or fog. Do not use water jet as an extinguisher, as this will spread the fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	No unusual fire or explosion hazards noted.
Special protective equipment and precautions for firefighters	Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.
Fire fighting equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Cool containers exposed to flames with water until well after the fire is out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Absorb in vermiculite, dry sand or earth or absorbent material then place into containers. The product is immiscible with water and will spread on the water surface. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Prevent entry into waterways, sewer, basements or confined areas. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Precautions for safe handling DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Wash hands after handling and before eating. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get this material in contact with eyes. Do not get this material on clothing. Avoid contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Shower after work. Remove and wash contaminated clothing promptly.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat and sources of ignition. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	PEL	5 mg/m ³	Mist.
		2000 mg/m ³	
		500 ppm	

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)	TWA	2 mg/m ³	Inhalable fraction and vapor.
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	TWA	5 mg/m ³	Inhalable fraction.
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)	TWA	5 mg/m ³	Inhalable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	IDLH	2500 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Material	Type	Value	Form
HyVolt III	STEL	10 mg/m ³	Mist.
	TWA	5 mg/m ³	Mist.
Components	Type	Value	Form
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)	TWA	10 mg/m ³	
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)	TWA	100 mg/m ³	

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6)	Ceiling	1800 mg/m ³	
	STEL	10 mg/m ³	Mist.

Biological limit values	No biological exposure limits noted for the ingredient(s).
Appropriate engineering controls	Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.
Other	Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Clear & bright
Physical state	Liquid.
Form	Liquid.
Color	L0.5
Odor	Mild Petroleum Odor
Odor threshold	Not available.
pH	Not determined.
Melting point/freezing point	-81.4 °F (-63 °C) ASTM D5950/ISO 3016
Initial boiling point and boiling range	548.6 °F (287 °C) ASTM D2887/ ISO 3294
Flash point	312.8 °F (156.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Will burn if involved in a fire.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not determined.
Vapor density	Not determined.
Relative density	0.88 (68 °F (20 °C) ASTM D4052/ ISO 12185)
Solubility(ies)	
Solubility (water)	Insoluble
Partition coefficient (n-octanol/water)	Not established. Not applicable.
Auto-ignition temperature	≥599 °F (≥315 °C) ASTM E659
Decomposition temperature	Not determined.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.

Kinematic viscosity	9.4 mm ² /s ISO 3104 (104 °F (40 °C))
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong oxidizing agents.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May be fatal if swallowed and enters airways.
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause gastrointestinal discomfort if swallowed. Do not induce vomiting. Vomiting may increase risk of product aspiration.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Dizziness. Nausea, vomiting. Diarrhea. Coughing. Discomfort in the chest. Shortness of breath. Defatting of the skin.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
	Rat	> 2000 mg/kg
Oral		
LD50	Rat	> 6000 mg/kg
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5200 mg/m ³ , 4 Hours
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS 72623-87-1)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Prolonged exposure may cause irritation to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization Not classified. May cause defatting of the skin, but is neither an irritant nor a sensitizer.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346.

IARC Monographs. Overall Evaluation of Carcinogenicity

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (CAS 64742-53-6) 3 Not classifiable as to carcinogenicity to humans.

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC (CAS 64742-55-8) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Further information Risk of chemical pneumonia after aspiration.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Product		Species	Test Results
HyVolt III			
Aquatic			
Crustacea	EC50	Daphnia	24.3982 mg/l, 48 hours estimated
Fish	LC50	Fish	58.5556 mg/l, 96 hours estimated
<i>Acute</i>			
Crustacea	EC50	Daphnia	16.8277 mg/l, 48 hours estimated
Fish	LC50	Fish	13.0178 mg/l, 4 days estimated

Components		Species	Test Results
2,6-DI-TERT-BUTYL-P-CRESOL (CAS 128-37-0)			
Aquatic			
<i>Acute</i>			
Algae	EC10	Freshwater algae	0.24 mg/l, 72 hours
Crustacea	EC50	Daphnia magna	0.48 mg/l, 48 hours
Fish	LC50	Fish	0.199 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Daphnia magna	0.069 mg/l, 21 days
Fish	NOEC	Fish	0.053 mg/l, 30 days

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (CAS 64742-47-8)

Aquatic			
<i>Acute</i>			
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	2.2 mg/l, 4 days

Not available. * Estimates for product may be based on additional component data not shown.

Persistence and degradability Expected to be inherently biodegradable.

Bioaccumulative potential Bioaccumulation is unlikely to be significant because of the low water solubility of this product.

Partition coefficient n-octanol / water (log Kow)

2,6-DI-TERT-BUTYL-P-CRESOL 5.1

Mobility in soil Expected to be slightly to moderately mobile in soil.

Other adverse effects Oil spills are generally hazardous to the environment. The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. Do not contaminate ponds, waterways or ditches with chemical or used container.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Avoid discharge into water courses or onto the ground.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This product is a liquid. Therefore, bulk transport is governed by MARPOL 73/78, Annex I.

General information Not regulated as dangerous goods.

15. Regulatory information

US federal regulations All components are on the U.S. EPA TSCA Inventory List.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

HyVolt oils are certified to be PCB-free. HyVolt oils are processed from naturally occurring raw materials with no additives or recycled oils that might introduce PCB contamination.

Toxic Substances Control Act (TSCA) One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT Listed.
(CAS 64742-47-8)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Aspiration hazard

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-07-2014
Revision date	07-26-2024
Version #	21
Further information	CHEMTREC Korea: 003-0813-2549 Local CHEMTREC Numbers: CHEMTREC Mexico: 1-800-681-9531
NFPA ratings	Health: 1 Flammability: 1 Instability: 0
List of abbreviations	CEN: European Committee for Standardization (Comité Européen de Normalisation). TLV: Threshold Limit Value. TWA: Time Weighted Average. vPvB: very Persistent, very Bioaccumulative. PBT: Persistent, bioaccumulative, toxic. STEL: Short-term Exposure Limit.

References

ACGIH
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
Chemical safety report. EPA: AQUIRE database
IARC Monographs. Overall Evaluation of Carcinogenicity
Korea. Dangerous Substances Threshold Quantity (Presidential Decree of Dangerous Substances Safety Management Act No. 18406, Schedule 1)
Korea. Regulated volatile organic compounds (VOCs) (MOE Notice No. 2001-36, March 8, 2001, as amended)
National Toxicology Program (NTP) Report on Carcinogens
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
Chemical Abstracts Service Registry Handbook
CRC: Handbook of Chemistry and Physics
ILO Safety Cards
International Labour Organization
International Maritime Organization Marine Pollutants List
NFPA Hazardous Chemical Data Sheets
NIOSH Pocket Guide
Registry of Toxic Effects of Chemical Substances (RTECS)
US DOT Hazardous Materials Regulations

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Ergon Refining, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.