

**1. Identification**

<b>Product identifier</b>	HyGold Denali L500
<b>Other means of identification</b>	
<b>CAS number</b>	64742-52-5
<b>Recommended use</b>	Metalworking Fluids, Industrial Lubricants, Grease Manufacturing, Hydraulic Oils, Gear Oils, Heavy Duty Engine Oil, Bar & Chain, Carriers & Diluents, Engine Oil.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Company:</b>	Ergon, Inc.
<b>Address:</b>	P.O. Box 1639 Jackson, MS 39215
<b>E-mail:</b>	sds@ergon.com
<b>Emergency Contacts</b>	
<b>Customer Service:</b>	1-800-222-7122
<b>Chemtrec:</b>	1-800-424-9300 After Business Hours (North America Only) 1-703-527-3887 After Business Hours (International)

**2. Hazard(s) identification****Hazards for the product as sold**

<b>Physical hazards</b>	Not classified.
<b>Health hazards</b>	Not classified.
<b>Environmental hazards</b>	Not classified.
<b>OSHA defined hazards</b>	Not classified.

**Label elements**

<b>Hazard symbol</b>	None.
<b>Signal word</b>	None.
<b>Hazard statement</b>	The substance does not meet the criteria for classification.
<b>Precautionary statement</b>	
<b>Prevention</b>	Not assigned.
<b>Response</b>	Not assigned.
<b>Storage</b>	Not assigned.
<b>Disposal</b>	Not assigned.

<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
--	-------------

<b>Supplemental information</b>	None.
---------------------------------	-------

**3. Composition/information on ingredients****Substances**

<b>Chemical name</b>	<b>Common name and synonyms</b>	<b>CAS No./Unique ID</b>	<b>%</b>
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	≤100
<b>Composition comments</b>	Not classified as a carcinogen. Meets EU requirement of less than 3% (w/w) DMSO extract for total polycyclic aromatic compound (PAC) using IP 346. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.		

## 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Direct contact with eyes may cause temporary irritation. Defatting of the skin.
<b>Indication of immediate medical attention and special treatment needed</b>	Treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted. NFPA 30 Class: Combustible Liquid Class IIIB

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). The product is immiscible with water and will spread on the water surface.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
<b>Environmental precautions</b>	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. The product is insoluble in water.
	Avoid discharge into drains, water courses or onto the ground. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid prolonged exposure. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Keep away from heat, sparks and open flame. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)**

Additional components	Type	Value	Form
Oil mist, mineral	PEL	5 mg/m3	Mist.
<b>US. ACGIH Threshold Limit Values (TLV)</b>			
Additional components	Type	Value	Form
Oil mist, mineral	TWA	5 mg/m3	Inhalable fraction.
<b>NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended</b>			
Additional components	Type	Value	
Oil mist, mineral	IDLH	2500 mg/m3	
<b>US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)</b>			
Additional components	Type	Value	Form
Oil mist, mineral	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).		
<b>Appropriate engineering controls</b>	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
<b>Individual protection measures, such as personal protective equipment</b>			
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).		
<b>Skin protection</b>			
<b>Hand protection</b>	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves.		
<b>Other</b>	Wear suitable protective clothing.		
<b>Respiratory protection</b>	In case of insufficient ventilation, wear suitable respiratory equipment.		
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.		
<b>General hygiene considerations</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

**9. Physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Light Amber to Golden
<b>Odor</b>	Mild Petroleum Odor
<b>Melting point/freezing point</b>	-23.8 °F (-31 °C) ASTM D5950/ISO 3016
<b>Boiling point or initial boiling point and boiling range</b>	613.4 °F (323 °C) ASTM D2887/ ISO 3294
<b>Flammability</b>	Will burn if involved in a fire.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	Not determined.
<b>Explosive limit - upper (%)</b>	Not determined.
<b>Flash point</b>	>392.0 °F (>200.0 °C) Cleveland Open Cup ASTM D92/ ISO 2592
<b>Auto-ignition temperature</b>	>600 °F (>315.56 °C) ASTM E659
<b>Decomposition temperature</b>	Not determined.
<b>pH</b>	Not applicable.
<b>Kinematic viscosity</b>	101 cSt ASTM D445 (104 °F (40 °C))
<b>Solubility</b>	
<b>Solubility (water)</b>	Insoluble in water.

<b>Partition coefficient (n-octanol/water)</b>	Not applicable.
<b>Vapor pressure</b>	Not determined.
<b>Density and/or relative density</b>	
<b>Relative density</b>	0.92 (60 °F (15.56 °C) ASTM D4052/ ISO 12185)
<b>Vapor density</b>	>5
<b>Particle characteristics</b>	
<b>Particle size</b>	Not applicable, material is a liquid.
<b>Other information</b>	
<b>Evaporation rate</b>	Not determined.

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Contact with incompatible materials. Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Defatting of the skin. Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

#### Acute toxicity

Product	Species	Test Results
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation. May cause defatting of the skin, but is neither an irritant nor a sensitizer.	
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
<b>Carcinogenicity</b>	Not classifiable as to carcinogenicity to humans.	

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Highly refined mineral oil (CAS -)	3 Not classifiable as to carcinogenicity to humans.
------------------------------------	---

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

## US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Persistence and degradability** Expected to be inherently biodegradable.

**Bioaccumulative potential** No data available.

**Mobility in soil** No data available.

**Other adverse effects** Oil spills are generally hazardous to the environment.

## 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to** Not established.

### IMO instruments

## 15. Regulatory information

**US federal regulations** This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.  
This SDS complies with the OSHA Hazard Communication Standard (29 CFR § 1910.1200), as amended in the final rule published May 20, 2024.

**Toxic Substances Control Act (TSCA)** This substance is on the TSCA 8(b) inventory and is designated "active".

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

**SARA 304 Emergency release notification**

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

### SARA 311/312 Hazardous chemical

### SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

### Safe Drinking Water Act (SDWA)

Not regulated.

## US state regulations

### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 02-11-2020

Revision date 01-06-2026

Version # 04

NFPA ratings  
Health: 0  
Flammability: 1  
Instability: 0

Disclaimer Ergon Refining, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.